

APPENDIX 1

CME 850XR

Specifications

Power

Cummins QSB 6.7 (409 cubic inch) turbocharged and charge air cooled 6 cylinder Tier-4f diesel engine

Rated horsepower (driving).....195 hp @ 2,300 rpm

Rated horsepower (drilling).....117 hp @ 2,300 rpm

Carrier

Track width.....27.5 in. (69.85 cm)

Tractive force (max).....44,525 lbs. (20,196 kg)

Average ground bearing pressure.....3.9 psi (.274 kgf/cm)

Inside turning radius.....zero turn

Drive:.....hydrostatic closed-loop transmissions

Hydraulic front winch.....20,000 lb. (9,072 kg)

Speed (max)

Low range.....2.4 mph (3.86 kph)

High range.....5 mph (8.04 kph)

Gradeability

Straight-ahead climb.....60% grade

Side-hill traverse.....40% grade

Rotary Drive

Transmission.....5 speed fwd., 1 speed rev.

Rotary torque.....15,410 ft. lbs. max (20,893 Nm)

Rotary speed.....670 rpm max

Hollow spindle I.D. 2 3/4 in. (7 cm) (3 3/4 in. (10 cm) avail.)

Hydraulic Feed System

Retract force.....28,275 lbs. (12,825 kg)

Pulldown force.....18,650 lbs. (8,460 kg)

Retract rate (max).....90 ft.(27 m)/min.

Feed rate (max).....55 ft.(17 m)/min.

Stroke.....72 in. (183 cm)

Leveling System

Three jacks, inverted design with chrome-plated piston rods enclosed at all times

Stroke.....36 in. (91 cm)

Approximate Weight

(less drilling tools).....31,250 lbs. (14,175 kg)

