

PURCHASE
OF
15K MODULAR APPROACH SHORING KITS
AT
YOKOTA AIR BASE, JAPAN
730TH AIR FREIGHT TERMINAL
BUILDING 71

DATE: 30 APRIL 2026

1. GENERAL SCOPE OF PRODUCT TO BE PURCHASED

- a. 730TH AMS require ten (10) each MilAirX 15K DOMOPS Modular Approach Shoring Kits (DAMAS).

SHORING KIT REQUIREMENTS:

- a. Type: 4-Leg 2up2down configuration 448" Assembled
- b. EACH KIT WILL INCLUDE:
 1. Eight (8) each 24" x 94" 15K Ramp Section
 2. Two (2) each 24" x 54" 15K Lead Up
 3. Two (2) each 24"x18" 15K Wedge
 4. Four (4) each 4" tall 15k Ramp Pad
 5. Four (4) each 15K Stand Adjustable Height 13" – 15"
 6. Two (2) each 15K Stand adjustable Height 20" – 24"
 7. One (1) each 96" x 42" x 40" Top-Open Side-Access Container

2. CERTIFICATION REQUIREMENTS

- a. Approach shoring must be air transportability test loading activity (ATTLA) certified for C-5, C-17 & C-130 Aircraft.

3. TOP-OPEN SIDE-ACCESS CONTAINER REQUIREMENTS

- a. Container must have the capability to be tied down to aircraft floor/pallet with D-rings
- b. Container must be forklift-capable, with integrated forklift tine access points.

4. TRAINING REQUIREMENTS

- a. Contractor will provide training manuals in English language covering the assembly, disassembly and container packing procedures

Documentation to be provided includes:

- a. Installation manuals
- b. Illustrated parts breakdown

Note: These documents may be supplied electronically (CD/DVD acceptable)

5. TECHNICAL SUPPORT

- a. Contractor must provide either phone or email technical support, including assistance with parts ordering.

6. SPARE PARTS SUPPORT

- a. Contractor must have the capability of providing spare parts for the approach shoring system
- b. Must be able to support OCONUS shipping or shipment through a DLA distribution center (e.g., Travis Air Force Base, California).

7. WARRANTY

A 1-year warranty on all parts is required.