

Combi Oven – Double Stack

Manufactory:

Convotherm

Model No.

C4ET-6.20-ES-MXP-DI or equal

Description:

1 each

Equipment Construction: may not allow the migration of deleterious substances or impart colors, odors, or tastes to FOOD and under normal use conditions shall be—

- (A) Safe;
- (B) Durable, CORROSION-RESISTANT, and nonabsorbent;
- (C) Sufficient in weight and thickness to withstand repeated WAREWASHING;
- (D) Finished to have a SMOOTH, EASILY CLEANABLE surface; and
- (E) Resistant to pitting, chipping, crazing, scratching, scoring, distortion, and decomposition.

Design and Construction Features:

Disappearing door are important to get more space and greater safety at work.

The ovens have to stacked for space saving.

Stacking kit for electric combi ovens, allows stacking on top of combi oven,
Feet 300mm

Color touch screen with a minimum of 10" touch screen and format 16:9 Robust, wear-free, capacitive touch screen protected behind non-reflective, hardened safety glass with smooth surfaces for easy cleaning, durable LED background lighting.

Display screen cleaning mode – deactivates the display for a minimum of 20 seconds.
Natural User Interface – natural intuitive operation: Activate, animate and slide the controls using touch, scroll and movement gesture.

This enables precise setting without an additional adjustment dial. Graphic user guidance with self-explanatory image representations, graphics and symbols.
Language-dependent text display (English must be an option) – language display can be directly adjusted.

Display setting must include the minimum setting modes:

Soft Steaming: 30°C up to 99°C (+/-10°C)

Steaming: (30°C up to 130°C)

Convection: 30°C up to 250°C (+/-10°C)

Combi Steaming: 30°C up to 250°C (+/-10°C)

Perfection: 30°C up to 180°C (+/-10°C)

Low temperature cooking / Cook & Hold: 30°C up to 120°C (+/-10°C)

Cook & Hold – cook and hold in one process

Eco Cooking – energy-save function

Service diagnostics programs: automatic self-test for all relevant appliance functions such as climate function and cleaning function, results must be shown in display.

High-speed steam generation technology with heat recovery.

Steam Exhaust System.

Condensation of the steam in the cooking chamber.

Hot steam will not escape when the door is opened at the end of the cooking programs.

Climate control Individual setting of the cooking chamber climate control with humidity and temperature measurement as well as active humidification and dehumidification.

Allows humidity adjustment from 0 up to 100% (in 10%) Hygienic cooking chamber

door with insulated triple glazing Saves energy due to low heat loss, high level of work

safety due to low outside temperature, perfect hygiene and very easy to clean due to

flat seamless inner surface. Safety glass and right-hand hinged door, one-hand

operation with door-damping function. Door lock with end stop, non-contact door

switch, insert able door seal – replaceable by the client. Hygiene condensate collecting

tray on the door and appliance with direct drain. Hinged operation panel for easy

maintenance access.

Capacities:

Standard configuration:

6+1 Shelves GN 2/1 crosswise insertion or 12 GN-2/1 wire racks to fit US sheet pans

18 x 26"

Test mark / Safety:

Steam Exhaust System

Condensation of the steam in the cooking chamber. Hot steam will not escape when the door is opened at the end of the cooking programs.

increased protection against sprayed water with safety temperature thermostat

operation display, warning and fault indication.

Cleaning:

Hand sprayer standard

Cleaning Program - automatic cleaning hygienic concept

5x Combi-Oven Cleaner liquid for automatic cleaning system

Exterior Dimension:

2x Oven Exterior with right-hinged door wxdxh: 1246 x 992 x 786 mm (+/-10mm)

Installation:

Disconnect existing equipment and connect new equipment to preinstalled/existing supply line.

Water Filter System needs to be installed to preinstalled/existing supply line.

Equipment has to be delivered including Power Cord and Plug or installation.

Ready for Operation.

Work performed during regular working hours Mon – Fri 0800-1500.

Access must be via dock, level floor or elevator.

Electric Specs:

Energy Source: 400V, Triple Phase, 50Hz
Plug: 2x 400V, 32Am
Power: 2x 19.5KW
Cable: minimum of 4m
Equipment must be CE-Certified

Delivery Address:
405TH LRC Bavaria
Dragoon-In Warrior Restaurant
Building 612
92249 Vilseck
Germany.