



Model Number Descriptions

Unit Model Number

Digit 1, 2, 3, 4 — Unit Model

CGAM = Air-Cooled Scroll Packaged Chiller

Digit 5, 6, 7 — Nominal Tonnage

020 = 20 Tons
026 = 26 Tons
030 = 30 Tons
035 = 35 Tons
040 = 40 Tons
052 = 52 Tons
060 = 60 Tons
070 = 70 Tons
080 = 80 Tons
090 = 90 Tons
100 = 100 Tons
110 = 110 Tons
120 = 120 Tons
130 = 130 Tons

Digit 8 — Unit Voltage

A = 200V/60Hz/3 phase
B = 230V/60Hz/3 phase
D = 380V/60Hz/3 phase
F = 460V/60Hz/3 phase
G = 575V/60Hz/3 phase

Digit 9 — Manufacturing Location

2 = Trane Commercial Systems, Pueblo, CO USA

Digits 10, 11 — Design Sequence

****** = Factory assigned

Digit 12 — Unit Type

2 = High Efficiency
3 = Extra Efficiency

Digit 13 — Agency Listing

X = No Agency Listing
A = Special ASME/Canadian Pressure Vessel Code
E = ETL Listed/Certified to CSA/Conforms to UL

Digit 14 — Pressure Vessel Code

X = BPHE — exempt from ASME
1 = Special ASME/Canadian Pressure Vessel Code

Digit 15 — Unit Application

B = High Ambient (32-125°F/0-52°C)
D = Wide Ambient (0-125°F/-18-52°C)
J = Extreme Low Ambient — down to -20°F (-28.9°C)

Digit 16 — Refrigerant Isolation Valves

2 = Refrigerant isolation valve(discharge valve)s

Digit 17 — Structural Options

A = Standard Unit Structure

Digit 18 — Freeze Protection (Factor-Installed Only)

X = Without Freeze Protection
1 = With Freeze Protection (External T-Stat control)

Digit 19 — Insulation

A = Factory Insulation - All Cold Parts
B = Insulation for High Humidity/Low Evap Temp

Digit 20 — Factory Charge

3 = Full Factory Refrigerant Charge R-454B
4 = Nitrogen Charge — R-454B Field Supplied

Digit 21 — Evaporator Application

A = Standard Cooling (40 to 65°F/4.4 to 18°C)
B = Low Temperature Process (10 to 40°F/-12.2 to 4.4°C)
C = Ice-Making - Hardwired Interface (20 to 65°F/-7 to 18°C)
D = Low leaving water (below 10°F/-12.2°C)

Digit 22 — Water Connections

1 = Grooved Pipe Connection

Digit 23 — Condenser Fin Material

A = Lanced Aluminum Fins
D = Lanced Aluminum Fins with CompleteCoat™

Digit 24 — Condenser Heat Recovery

X = No Heat Recovery

Digit 25 — Not Used

X

Digit 26 — Starter Type

A = Across the Line Starter/Direct On Line

Digit 27 — Incoming Power Line Connection

1 = Single Point Power Connect

Digit 28 — Power Line Connection Type

A = Terminal Block
C = Circuit Breaker Standard Fault
D = Circuit Breaker with High Fault Rated Control Panel
E = Circuit Breaker with High Fault Rated Control Panel with Energy Meter

Digit 29 — Enclosure Type

2 = Enclosure type UL 60335 Rated for Outdoor Applications

Digit 30 — Unit Operator Interface

B = Tracer® AdaptiView™ TD7

Digit 31 — Remote Interface (Digital Comm)

X = No Remote Digital Communication
2 = LonTalk®/Tracer® Summit Interface
4 = BACNet® Interface

Digit 32 — External Chilled/Hot Water and Current Demand Limit Setpoint

X = No External Chilled Water Setpoint
A = External Chilled Water and Demand Limit Setpoint 4-20 mA
B = External Chilled Water and Demand Limit Setpoint 2-10 Vdc

Digit 33 — Percent Capacity

X = Without Percent Capacity
1 = With Percent Capacity

Digit 34 — Programmable Relays

X = No Programmable Relays
A = With Programmable Relays

Digit 35 — Pump Type

X = No Pumps and No Contactors
8 = Dual High Head Pump



Model Number Descriptions

Digit 36 — Pump Flow Control

X = No Pump Control
B = Pump Flow Controlled by the Variable Speed Drive

Digit 37 — Buffer Tank

X = No Buffer Tank
1 = Buffer Tank

Digit 38 — Short Circuit Rating

X = No Short Circuit Rating
A = Default A Short Circuit Rating
B = High A Short Circuit Rating

Digit 39 — Installation Accessories

X = No Installation Accessories
1 = Elastomeric Isolators
5 = Elastomeric Pads

Digit 40 — Water Strainer

A = With Water Strainer Factory Installed

Digit 41 — Sound Attenuator Package

3 = Super Quiet
5 = Comprehensive Acoustic Package

Digit 42 — Appearance Options

X = No Appearance Options
A = Architectural Louvered Panels
B = Half Louvers

Digit 43 — Exterior Finish

1 = Standard Paint

Digit 44 — Label, Literature Language

B = Spanish and English
D = English
E = French and English

Digit 45 — Phase Reversal Protection

1 = Phase Reversal Protection
2 = Convenience Outlet and Phase Reversal Protection

Digit 46 — Shipping Package

X = No Skid (Standard)
A = Unit Containerization Package
B = Shipped with tarp Covering Full Unit
C = Unit Containerization Package and Tarp

Digit 47 — Performance Test Options

X = No Performance Test
1 = Customer Inspection
2 = One-Point Test with Report
3 = Witness One-Point Test with Report
4 = Operational Test with Water

Digit 48 — Flow Switch Setpoint

C = Flow Switch Setpoint 15
F = Flow Switch Setpoint 35
H = Flow Switch Setpoint 45
L = Flow Switch Setpoint 60

Digit 49 — Wireless Connectivity Options

X = None
A = Wi-Fi®
B = LTE Modem
C = Air-Fi™
D = Wi-Fi and LTE Modem
E = Wi-Fi and Air-Fi
F = LTE Modem and Air-Fi
G = Wi-Fi, LTE Modem and Air-Fi

Digit 50 — Specials

X = None
S = Special

Note: If a digit is not defined, it may be held for future use.