

PACKAGING REQUIREMENTS																			
PURCHASE INSTRUMENT NUMBER: FD20202600529-00											VERSION: 1								
MIL-STD 129 REVISION: R											MIL-STD 2073-1 REVISION: E								
THE FOLLOWING STATEMENT IS IN COMPLIANCE WITH THE UNITED NATIONS-IMPLEMENTED RESTRICTIONS ON WOOD PACKAGING MATERIAL (WPM). THIS REQUIREMENT IS SPECIFICALLY CONCERNED WITH INVASIVE SPECIES SUCH AS THE PINEWOOD NEMATODE. WPM IS DEFINED AS WOOD PALLETS, SKIDS, LOAD BOARDS, PALLET COLLARS, WOODEN BOXES, REELS, DUNNAGE, CRATES, FRAMES, AND CLEATS. THE STATEMENT BELOW CITES THE REQUIREMENTS IN DETAIL AND COVERS LUMBER FOR BUILDING CONTAINERS AND PALLETS USED FOR DELIVERIES RESULTING IN SHIPMENTS WORLDWIDE (DIRECT, OR THROUGH AIR LOGISTICS CENTERS (ALC), CONTAINER CONSOLIDATION POINTS (CCP), OR OTHER BASES). WOODEN LUMBER, WOODEN PALLET AND PACKAGING/CONTAINER STATEMENT: ALL WOODEN LUMBER, WOODEN PALLET'S, AND WOODEN CONTAINERS PRODUCED ENTIRELY OR IN PART OF WOOD PACKING MATERIAL (WPM) SHALL BE CONSTRUCTED FROM DEBARKED WOOD IN ADDITION TO THE APPLICATION OF HEAT-TREATED (HT) MATERIAL (HT TO 56 DEGREES CENTIGRADE OR 133 DEGREES FAHRENHEIT FOR 30 MINUTES). CERTIFICATION/MARKING IS REQUIRED BY AN ACCREDITED AGENCY RECOGNIZED BY THE AMERICAN LUMBER STANDARDS COMMITTEE (ALSC). FOR REFERENCE DOCUMENTATION, SEE LATEST REVISION OF "INTERNATIONAL STANDARDS FOR PHYTOSANITARY MEASURES" (ISPM)NO.15), "REGULATION OF WOOD PACKAGING MATERIAL IN INTERNATIONAL TRADE."																			
PACRN:		PACKAGING REQUIREMENT:						PRESERVATION LEVEL:		PACKAGING LEVEL:		SPI:		SPI REV:		SPI DATE:			
AAA		Specification Commercial Packaging (ASTM-D-3951)						COM											
ITEM(S): 1680ND101681GXM																			
CODED DATA:																			
QUP		ICQ	PRES METH	CD	PRES MTL	WRAP MTL	CUSH DUNN	CT	UNIT CONT	INT CONT	UCL	SPEC MKG	UNIT PACK WEIGHT	UNIT PACK LENGTH	UNIT PACK WIDTH	UNIT PACK DEPTH	UNIT PACK CUBE	OPI	
ADDITIONAL PACKAGING AND CONTAINER MARKING REQUIREMENTS:																			
SUPPLEMENTAL PACKAGING INSTRUCTION TEXT:																			
VENDOR PACKAGING INSTRUCTIONS: Shipping Container Marking Shipping containers shall be marked meeting the following criteria: (a) MIL-STD-129, Standard Practice for Military Marking. (b) Additional marking and/or bar coding requirements exceeding those of MIL-STD-129 (e.g., unit serial numbers, original equipment manufacturers (OEM) name, or OEM model number, as specified on the AFMC Form 158. Specification Commercial Packaging (ASTM D3951) (a) Items shall be packaged in accordance with American Society for Testing and Materials (ASTM) Specification D3951-98, Standard Practice for Commercial Packaging. Individual shipments exceeding 150 pounds, 108 inches in length, or 130 inches in girth plus length shall be packaged on skidded crates or palletized to allow handling by forklift. (b) The exterior container shall be marked (readable from 24 inches): "ASTM D3951 - NOT FOR OUTSIDE STORAGE."																			
ORGANIZATION / OFFICE SYMBOL:				PACKAGING SPECIALIST:				PHONE NUMBER:				SIGNATURE:				DATE:			
406 SCMS / GULAA				Monson, Wendy L				801-777-1457 / 777-1457				//SIGNED//Monson, Wendy L				26071 - 12 MAR 2026			