

Statement of Need
Vehicle Upfit Requirements
Office of Force Protection (SLP)

The Office of Force Protection currently has a requirement to outfit their police vehicles with emergency equipment. The Office of Force Protection has three primary divisions, which include: Canine, Tactical Response, and Operations. Each division's police vehicles have a unique upfit requirement, to enable them to sustain their daily mission and training requirements.

Below is a list of requirements for each specialized vehicle. The products mentioned below are not name brand specific. Any name brand mentioned is for reference purposes only. Similar items are acceptable. If alternate items are suggested they must meet or exceed the manufactured standards of reliability and functionality of the item mentioned in the solicitation. Alternate items must be approved before installation and be selected in the best interest of the United States Government and the National Geospatial Intelligence Agency.

East Operations Vehicles

- Headlight taillight flasher (Will need integrated lights in the headlight and taillights). Installed with plug-in connectors, single flash pattern, high beam override, built in shutdown protection against loss of ground, short circuit and under voltage, durable and non-corrosive **ABS** plastic housing.
- Two outliner perimeter red and blue lights mounted under driver side and passenger side doors Mounted above side steps. Allows installation as a running board light, push bumper light, tailgate, and distributes a bright output to increase vehicle visibility, aluminum housing and sealed light, heads that prevent corrosion and water ingress. Available in Amber, blue, red and white, split

and solid cover combinations. 10 flash patterns, including dim and steady burn override, powder coat aluminum frame, IP67 rated for dust and water resistant, phase 1 and phase 2 syncing capabilities, 12VDC, temperature range -40 degrees Fahrenheit to 170 degrees Fahrenheit, 55" cable enclosed in a jacket, RoHS IP67 rated, 5-year warranty.

- Speaker Kit. Compact, low profile design that works with all Code 3 sirens, designed to fit easily behind front grill, high efficiency (2) 50W speakers, two 180 AWG wire connection, aluminum housing
- Excel siren with microphone
- Wide body console
- Dual cup holder
- Upper arm rest structure
- Faceplate for Harris radio
- Installation of customer supplied Police radio equipment.
- Black Rubber Floor Mats
- Rifle Rack for AR-15 and Shotgun Fits between the seats. Low profile design, powder coated steel, mounts to floor board 34"H 9"Wx8"D; 18 lbs
- Supervisor flex 2 piece multi-color 6 modules order is RW/BW/RW- BW/RW/BW
- Half Cage for Prisoner Transport
- Install price including parts: wire, loom, heat shrink, fuses, connectors, all auxiliary wiring to be protected through a power fuse module located under the hood. Fuse bus is energized with a solenoid that is energized with "KEY ON". All wire, switches, relays, and power fuse modules must be properly secured and mounted as per industry standards. AH leads from this main power point are to be fused using ATO/ATC bus 12 circuit's 30A/100A Max fuse block with screw terminals for securing wires. All ring terminals and other circuit connections to be mechanically crimped using a

ratcheting crimper to ensure proper tension and 3:1 adhesive lined black heat shrink to cover crimp to insure added protection to connections. All circuits must have proper wiring gauge and circuit protection as recommended by equipment manufacturer.

- Reflective agency naming stripping to identify vehicle as a Police vehicle.
- Mount for LED Spotlight on Driver A Frame. With black spotlight housing.

Tactical Response Team Vehicle

Headlight taillight flasher (Will need integrated lights in the headlights and taillights) Installed with plug-in connectors. single flash pattern, high beam override, built in shutdown protection against loss of ground, short circuit and under voltage, durable and noncorrosive ABS plastic housing.

- Front window Supervisor flex 2 piece multi-color, blue/blue
- Series 25" side window blue lights, blue/blue
- Exterior lighting system under rear spoiler {preferred} or if it is not available for vehicle, rear window multi-function light bar, minimum 30 flash patterns, minimum 39 in. in length, blue/blue
- Two outliner perimeter under driver side and passenger side doors. Mounted above side steps for driver side and passenger side. Allows installation as a running board light, push bumper light, tailgate, distributes a bright output to increase vehicle visibility, aluminum housing and sealed light heads that prevent corrosion and water ingress, available in amber, blue, red and white, split and solid cover combinations, 10 flash patterns, including dim and steady burn override, powder coat aluminum frame, IP67 rated for dust and water resistant. phase 1 and phase 2 syncing capabilities, 12VDC, temperature range -40 degrees Fahrenheit to 170 degrees Fahrenheit, 55" cable enclosed in a jacket, RoHS IP67 rated, minimum 60 inches, blue/blue
- 2 Rear tailgate lights (on both sides of license plate) mega thin series surface mount 4.8" dual

color, blue/blue

- 2 Vibrant hide-a-blast LED, 16 flash pattern, to be mounted under rearview mirrors (driver/passenger door)
 - Speaker Kit. Compact, low profile design that works with all Code 3 sirens, designed to fit easily behind front grill, high efficiency (2) 50W speakers, two 180 AWG wire connection, aluminum housing
 - Excel siren with mic with toggle switch to allow activation of lights and siren
 - Jotto Wide body console
 - Dual cup holder
 - Jotto Upper arm rest structure
 - Faceplate for Harris radio
 - Push bumpers LED lights (front and side) PB-450-L Grill Guard. blue/blue
 - Black Rubber Floor Mats
 - Tint driver and passenger windows to match rear
-
- Rifle Racks for AR-15. Mount at single point that attaches to lower receiver, restricting access to takedown pins, trigger group, and magazine release. Fits between the seats. Low profile design, powder coated steel, mounts to floor board, electronic push button release\ back up cuff key override.
 - Truck vault to fit rear of vehicle (full length), 2 drawer, 10 1/8" height, push button Kaba simplex combo lock with key override, black exterior carpet, gray interior carpet, interior lighting, black composite drawer fronts, removable dividers.
 - 10,000 lb winch with synthetic rope. When transporting our principle there are small back roads through the woods. In the event a tree or object is blocking the road we need a way to remove the obstacle. also in inclement weather if the vehicle goes off the road the winch allows us to return to the road and get the principle to their destination.
 - Roof racks for TRT officers to hold onto during building assaults and vehicle take downs. Round. Maximum crossbar dimensions 3-1'4" wide x

1-1/4" tall, Crossbar Spread (center to center) without extender 26-i '4" - 37 1/2", weight capacity without extender 130 lbs. Inside dimensions without extender 48" long x 37 - 1/2 inch wide x 5" deep, Carrier weight without extender 54 1/2" long x 40 -1/2 wide x 5" deep

- Strong running boards to stand on. Black powder coated, minimum 4" wide cab length and wheel to wheel length, slip resistant U.V. step pad area, flat to allow the user to stand at any point on the running board.

K9

- Remove 2nd and 3rd row of seats for K9 cage and rear storage.
- E/Z Rider K9 Platform System Includes Rubber Mat, Powder Coat and Interior Cage light.
- Full K9 Police Vehicle Cage Insert in 2nd row.
 - o Front exit door to be mounted on steel roller bearings, hinged window screens on sides, top with dome light & vent holes, insert to be all aluminum construction with Rhino lining applied on the floor of insert. and heavy duty, nonslip rubber floor mat.
- K9 transport system, Hot-n-Pop pro horn, siren and light bar and horn activation, dual window drop down, and remote door opener
 - o Includes S.O.S. Horn Feature. Engine Stall Monitor Feature, Safety Pop Stopper Feature, Fast Pop Feature (door pop/unlock timing sequence), Siren Activation, Light Bar Activation, Long Range Remote Pager Module, K9 Temperature Sensors, Dual Remote Sensors with 15' cables adjustable temperature alarm, Full alphanumeric LCD display, compact transmitter with nylon rugged case, external antenna kit, gas spring to fully extend and hold door open for safe canine release, No Dog Left Behind feature.
- 12" fan, 350 CFM activation module, manual switch and materials.
- Long range remote pager with dual band antenna and adapters
- Remote Heat Alarm Pager/Beeper with 11" tan mast antenna

- Remote Siren with Integrated Microphone
 - o Full featured 100-watt remote siren with PA light control.
Integrated microphone and switch controls in handset,
Progressive push button control mimics siide switch action,
Eight 10-amp light and auxiliary relay positions
- Exterior composite speaker w/mounting bracket
- LED Spotlight. Mounted on Driver A Frame. With black spotlight housing
- Mount for LED Spotlight on Driver A Frame
- Limousine Metalized Window Tint for 2020 Ford Expedition
 - o Level of darkness; 20% darkness on front driver and
passenger windows, and 5% darkness on rear passenger
windows
- Extended truck bed extender (with black powder coat finish, heavy duty
locking drawers, welded steel frame. and rubber mat liner).
 - o Dimensions: 12"H X 48"W X 38"D
 - o Top and bottom trays slide out entire length of tray
 - o Mounting on upper tray for tying down items on upper tray
 - o Locked drawers accessible with both code and key locks
 - o Small compartment lighting within each drawer, activated when drawer is opened
 - o Right drawer partitioned with no-lock cradle for AR-15
 - o Lighting on interior of lift gate for illumination of cargo area
- Lockable storage in center console.
 - o Police radio, light and siren relays, and hot n' pop equipment stored within
 - o Police radio mic, light and siren controls, and hot n' pop
display mounted on the outside of storage compartment
 - o Partition separating control modules from rest of storage area
 - o Police radio speaker mounted behind driver's seat
- Front Facing Red and Blue lights
 - Tri-color (R/B/W) light bar with 18 LED lights mounted inside front windshield
 - 111 Dimensions: 20"L X 1"H X 7.5"D
 - 2 Tricolor (R/Bffl) light heads with 18 LED lights mounted on left and right side
of grille

- Dimensions: 4"L X 1"H X 1"D

West Requirements

Operations Vehicles

- Headlight taillight flasher (Will need integrated lights in the headlights and taillights). Installed with plug-in connectors, single flash pattern, high beam override, built in shutdown protection against loss of ground, short circuit and under voltage, durable and non-corrosive ABS plastic housing.
- 2 Vibrant hide-a-blast LED, 16 flash patterns, to be mounted under or on rearview mirrors (driver/passenger mirrors)
- 2 Tricolor (R/B/W) light heads with 18 LED lights mounted inside left and right side of grille
 - Dimensions: 4"L x 1"H x 1"D
- Multi-function light bar, 30 flash patterns, mounted lengthwise inside of rear cargo window, the length of the window (red/blue)
- LED emergency lights (red/blue) mounted on interior of the rear hatch to allow illumination of the cargo area and under the rear hatch when the tailgate is open.
- Two outliner perimeter red and blue lights mounted under driver side and passenger side doors Mounted above side steps. Allows installation as a running board light, push bumper light, tailgate and distributes a bright output to increase vehicle visibility, aluminum housing and sealed light, heads that prevent corrosion and water ingress. Available in amber, blue, red, and white, split and solid cover combinations. 10 flash

patterns including dim and steady burn override, powder coat aluminum frame, IP67 rated for dust and water resistant, phase 1 and phase 2 syncing capabilities, 12VDC, temperature range -40 degrees Fahrenheit to 170 degrees Fahrenheit, 55” cable enclosed in a jacket, RoHS IP67 rated, 5-year warranty

- Speaker Kit. Compact, low profile design that works with all Code 3 sirens, designed to fit easily behind front grill, high efficiency (2) SOW speakers, two 180 AWG Wire connection, aluminum housing
- Excel siren with microphone
- Wide body console
- Dual cup holder
- Upper arm rest structure
- Faceplate for Harris radio
- Installation of customer supplied Police radio equipment.
- External hand operated spotlight on driver’s side.
- Black Rubber Floor Mats
- Rifle rack for two AR-15 that fits between the seats. Low profile design, powder coated steel, mounts to floor board 34”H x 9”W x 8”D; 18 lbs
- Supervisor flex 2-piece multi-color 6 modules order is RW/BW/RW - BW/RW/BW – mounted in the rear window.
- 15% Metalized Window Tint driver and passenger windows to match rear.
- Install price including parts: wire, loom, heat shrink, fuses, connectors, all auxiliary wiring to be protected through a power fuse module located

under the hood. Fuse bus is energized with a solenoid that is energized with “KEY ON”. All wire, switches, relays, and power fuse modules must be properly secured and mounted as per industry standards. All leads from this main power point are to be fused using ATO/ATC bus 12 circuit’s 30A/100A Max fuse block with screw terminals for securing wires. All ring terminals and other circuit connections to be mechanically crimped using a ratcheting crimper to ensure proper tension and 3:1 adhesive lined black heat shrink to cover crimp to ensure added protection to connections. All circuits must have proper wiring gauge and circuit protection as recommended by equipment manufacturer.

- Harris XL 200M. Dimensions: HxWxD 2.0 x 6.9 x 9.7 in.

Canine Vehicles

- 12" fan, 350 CFM activation module, manual switch and materials
- Long range remote pager with dual band antenna and adapters
- Remote Heat Alarm Pager/Beeper with 11" tall mast antenna
- Remote Siren with Integrated Microphone
 - Full featured 100-watt remote siren with PA light control, Integrated microphone and switch controls in handset, Progressive push button control mimics slide switch action, Eight 10-amp light and auxiliary relay positions
- Exterior composite speaker w/mounting bracket
- Limousine Metalized Window Tint for vehicles
 - 15% Metalized Window Tint driver and passenger windows to

- match rear, as well as, 35% tint for the entire front windshield
- Lockable storage in center console.
 - Police radio, light and siren relays, and hot n' pop equipment stored within
 - Police radio mic, light and siren controls, and hot n' pop display mounted on the outside of storage compartment
 - Partition separating control modules from rest of storage area
 - Police radio speaker mounted behind driver's seat
 - Front Facing Red and Blue lights
 - Tri-color (R/B/W) light bar with 18 LED lights mounted inside front windshield
 - Dimensions: 20"L x 1"H x 7.5"D
 - 2 Tricolor (R/B/W) light heads with 18 LED lights mounted on left and right side of grille
 - Dimensions: 4"L x 1"H x 1"D
 - 2 Tricolor (R/B/W) light heads with 18 LED lights mounted on lower bumper, recessed within fog lamp molding
 - Dimensions: 4"L x 1"H x 1"D
 - Existing high beams programmed to strobe when emergency equipment is activated
 - Side Facing Red and Blue lights
 - Tricolor (R/B/W) light bar mounted in between doors and running boards on both sides with 72 LED bulbs with scene lighting

- Dimensions: 38.75"L x 1.5"H x 1.5"D
 - Red and Blue light heads mounted lengthwise on upper inside of each rear cargo window
- Dimensions: 13.25"L x 1.5"H x 1.5" D
- Rear Facing Red and Blue lights
 - 2 mounts for separate sets of rear facing lights
 - 3 light heads on each side
 - Each light head alternates red and blue light
 - Dimensions for each side: 18"L x 3"H x 10"D
 - Red and Blue strobes mounted into reverse lights
 - Dimensions: 107mm diameter, 33mm height
- Existing rear brake lights programmed to flash when emergency equipment is activated
- Multi-function light bar, 30 flash patterns, mounted lengthwise inside of rear cargo window, the length of the window (red/blue)
- Harris XL 200M. Dimensions: HxWxD 2.0 x 6.9 x 9.7 in.

Tactical Response Team Vehicle

- Headlight, taillight, fog light flasher (Will need integrated lights in the headlights, taillights and fog lights). Installed with plug-in connectors, single flash pattern, high beam override, built in shutdown protection against loss of ground, short circuit and under voltage, durable and

noncorrosive ABS plastic housing.

- Red/blue strobes mounted into reverse lights
- Front window Supervisor flex 2-piece multi-flash pattern, red/blue
- Multi-function light bar, 30 flash patterns, mounted lengthwise inside of each (Driver and Passenger) rear cargo window, the length of the windows, red/blue
- Exterior lighting system under rear spoiler red/blue, as well as, a light bar at the bottom of the rear window the length of window red/blue, minimum 30 flash pattern.
- Outer perimeter light bars the length of running boards under driver side and passenger side doors. Mounted above side steps for driver side and passenger side. Allows installation as a running board light, distributes a bright output to increase vehicle visibility, 10 flash patterns powder coat aluminum frame, IP67 rated for dust and water resistant, phase 1 and phase 2 syncing capabilities, 12VDC, temperature range -40 degrees Fahrenheit to 170 degrees Fahrenheit, 55" cable enclosed in a jacket, RoHS IP67 rated, blue/blue, 2 Rear tailgate lights (on both sides of license plate) multi flash pattern, mega thin series surface mount 4.8" dual color, blue/blue
- 2 Vibrant hide-a-blast LED, 16 flash pattern, to be mounted under or on rearview mirrors (driver/passenger door) red/blue
- Speaker Kit. Compact, low profile design that works with all Code 3 sirens, designed to fit easily behind front grill, high efficiency (2) SOW speakers, two 180 AWG wire connection, aluminum housing
- Excel siren with mic with toggle switch to allow activation of lights and siren. Toggle switch position 1 off, 2 rear/side lights only 3 all lights, 4

all lights with siren, in addition siren cut off when vehicle is in park.

- Jotto Wide body console
- Dual cup holder
- Jotto Upper arm rest structure
- Faceplate for Harris radio
- Installation of customer supplied Police radio equipment
- Push bumper with LED lights, multi pattern (4 front and 2 each side)
PB-450-L Grill Guard, blue/blue
- Black Rubber Floor Mats
- 15% Metalized Window Tint driver and passenger windows to match rear, as well as, 35% tint for the entire front windshield
- Rifle Racks that holds two AR-15's. Mount at single point that attached to lower receiver, restricting access to takedown pins, trigger group, and magazine release. Fits between the seats. Low profile design, powder coated steel, mounts to floor board, electronic push button release with back-up cuff key override.
- Truck vault to fit rear of vehicle (full length), 2 drawer, 10 1/8" height, push button Kaba simplex combo lock with key override, black exterior carpet, gray interior carpet, interior lighting, black composite drawer fronts, removable dividers.
- Strong running boards to stand on. Black powder coated, minimum 4" wide cab length and wheel to wheel length, slip resistant UV pad step pad area, flat to allow the user to stand at any point on the running board.

LED lights mounted on interior of the rear hatch to allow illumination of the

UNCLASSIFIED

cargo area and under the rear hatch when the tailgate is open

- Harris XL 200M. Dimensions: HxWxD 2.0 x 6.9 x 9.7 in.

UNCLASSIFIED