

Specification Sheet

The Government requires commercially available equipment meeting the specifications provided below.

Pressure Transducer

Quantity: 54

Specification	Value
Media	Hydrogen
Pressure Range	25-2200 psi
Operational Mode	Absolute, Sealed Gage
Over Pressure	2x Rated Pressure
Burst Pressure	5x Rated Pressure to 15,000 psi Maximum
Rated Electrical Excitation	8 to 32 VDC
Maximum Current	25 mA (Maximum)
Insulation Resistance	100 Megohms @ 50 VDC
Output Impedance	750 Megohm Max
Full Scale Output (Net)	4.0 VDC +/- .25 VDC
Total Error Band (Excluding End Points)	+/- .25% FSO Max. (Combined Non-Linearity, Hysteresis, Repeatability, and All Thermal Effects Included)
Resolution	Infinitesimal
Operating Temperature Range	-40 deg F to +265 deg F (-40 deg C to +130 deg C)
Compensated Temperature Range	-40 deg F to +250 deg F (-40 deg C to +120 deg C)
Linear Vibration	20g Peak, Sine 10 to 2000 Hz
Humidity	100% Relative Humidity
Mechanical Shock	20g half Sine Wave 11 msec. Duration
Electrical Connection	PTIH-10-6P Connector or Equivalent

Weight	110 Grams
Pressure Sensing Principle	Fully Active Four Arm Wheatstone Bridge Dielectrically Isolated Silicon on Silicon
Mounting Torque	100 Inch-Pounds (Max.)
Pressure Port Connection	7/16-20UNJF-3A MS33656E-4

NOTE: The requirement can be met by manufacturer Kulite, part number BME-76-1100, or an “or equal” commercially available product.