

STATEMENT OF WORK

1. Objective/Requirements

This requirement is for the acquisition of the M+P Vibration Controller for NASA Kennedy Space Center (KSC). The information listed below is required to complete this purchase.

2. Characteristics, Scope, and Specs

QTY	PART #	DESCRIPTION
1	n/a	KSC on-site Calibration
-	-	40 Channel Controller:
1	VCbase-16CH	Basic License
3	VC-8ch+	Software Licence Extension for 8 additional Input Channels
1	VC-SIN-16CH	Sine Sweep and Stationary Control
1	VC-SRD-16CH	Sine Resonance Search, Track and Dwell
1	VC-RAN-16CH	Broadband Random Control
1	VC-NOL-16CH	Notch/Force Limiting Sine & Random, Sine Force, Displacement and Velocity Control
1	VC-VNO-16CH	Vector Notching Sine & Random
1	VC-CLS-16CH	Classical Shock Control
1	VC-SRS-16CH	Shock Response Spectrum with Shock Synthesis
1	VC-ROR-16CH	Random-on-Random
1	VC-SOR-16CH	Sine-on-Random incl. Multi-Sine w/wo Random
1	VC-RLD-16CH	Roadload and Time Domain Replication
1	VC-EXP-16CH	External pulse with Roadload Editor
1	VC-TRP-16CH	Throughput Time Domain Data Recording for all Excitation Modes
1	VC-MSCRN-16CH	Multi-Screen Support
1	DNGL-VC	License Dongle m+p VibControl
2	VRB	Base Module 3 Slots
1	VRT2S2	Analog Output/ Tacho Input Module 2 Channels each
5	VRAI820	Analog to Digital Converter Module, 8 Input Channels, 24 bit, 204.8 kHz
1	MPI-RWS	Rack Workstation - (Specifications provided on request)
1	MPI-MON27	27in Desktop Monitor
1	SW105	Netgear Pro Safe GS105E 5 Port Gigabit Ethernet Switch incl. power supply

1	ESTOP	Emergency Stop Button
-	-	Training:
1	HF-INST	Comissioning and User Training 5 days On-Site

3. Place of Performance

NASA/ Kennedy Space Center (KSC)
BOSS Receiving - M6-0744
ATTN: Mark Hamilton
Kennedy Space Center, FL 32899

4. Period of Performance

60 days ARO
Need by: 07/31/2026