



NOTES:

1. APPLICABLE STANDARDS/SPECIFICATIONS:
 - A. ASME Y14.5-2009
 - B. ASMEY14.100-2017
 - C. MIL-A-2550
 - D. MIL-DTL-2156
2. LOAD WITH CHARGE COMPOSITION B, GRADE A OR B, MINIMUM 10 LB. SPEC MIL-C-401. (NOTE 6 & NOTE 10).
3. AFTER PRESSING IN CLOSING CAP ASSEMBLY, DETONATOR WELL SHALL RECEIVE A GAGE .25 MIN DIA AND 2.86 MIN LENGTH. A THIN FILM OF PAINT ON THREADS PERMITTED, PROVIDED THREAD GAGE ENTERS FREELY (NOTE 7).
4. REPLACE PROTECTOR TAPE AFTER GAGING.
5. INSERT PADS AS REQUIRED TO ASSURE TIGHT ASSEMBLY.
6. SPEC APPLIES EXCEPT THAT COMP B SHALL CONTAIN 0.5% CALCIUM SILICATE, SPEC MIL-C-51077 (NOTE 12).
7. BEFORE PRESSING IN CLOSING CAP, APPLY ADHESIVE CLASS I OR 2, MMM-A-189, UTILIZING A NON-SPRAY APPLICATION METHOD 360° (IN CIRCUMFERENCE) ON INSIDE OF SURFACE OF DETONATOR WELL. CLOSING CAP ENSURING ADHESIVE IS NOT APPLIED TO SURFACES OF THE CAP TO BE IN CONTACT WITH EXPLOSIVE MATERIAL ONCE PRESSED INTO THE BODY ASSEMBLY.
8. MARK AS SHOWN WITH ITEM NOMENCLATURE, EXPLOSIVE FILL AND LOT NO. USING INK, STENCIL, TYPE I, II, OR IV, SPEC A-A-208, YELLOW COLOR, NUMBER 33538 OF SAE AMS-STD-595.
9. BODY ASSEMBLY DRAWING 8861569 TO BE LOADED AT AMBIENT TEMP OF NOT LOWER THAN 15°C (59°F).
10. RECOVERED COMPOSITION B MAY BE USED PROVIDED IT MEETS ALL OF THE REQUIREMENTS OF MIL-C-401.
11. AFTER REAMING COMP B MUST NOT INTERFERE WITH INSTALLATION OF CLOSING CAP.
12. ALTERNATE 0.12% AMORPHOUS SILICA, 4 MICRON DIAMETER, W.R. GRACE CO., SYLOID 68.



REVISIONS				
DRAWING	REV	DESCRIPTION	DATE\YEAR-MO-DAI	APPROVED
M	NOR R06B2001	060807	2006-10-04	FET
N	NOR R06B5006	061012	2006-10-17	FET
P	NOR R06B5009	070117	2007-01-29	BMG
R	NOR R09B2005	090409	2009-04-17	JTD
T	NOR R09B2004	090409	2009-04-21	JTD
U	NOR R11B2006	110906	2011-10-06	BMG
V	REDRAWN WITH CHANGE R24B2006 / 2024-08-26		2024-09-18	RLV

8	I	19203	8861578	RING REINFORCING
7	I	19203	8861570	CONTAINER, CONE
6	I	19203	8861567	SLEEVE STAND-OFF
5	I	19203	8858393	BOOSTER
4	I	19203	8858392	SPACER, WOOD
3	I	19203	8858391	PAD
2	I	19200	8861572	CONE ASSEMBLY
1	I	19200	8861568	CLOSING CAP ASSEMBLY
INDEX	QTY	CAGE CODE	PART NO. OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION

DISTRIBUTION STATEMENT A. APPROVED FOR PUBLIC RELEASE. DISTRIBUTION IS UNLIMITED.

PMIC					DO NOT SCALE DRAWING		CONTRACT NUMBER		DESIGN ACTIVITY	
					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		CONTRACTOR		US ARMY PICATINNY ARSENAL DOVER, NEW JERSEY	
MECHANICAL PROPERTIES					TOLERANCES ON ANGLES ± ° 2 PLACE DECIMALS ± 3 PLACE DECIMALS ±		DRAWN BY J. CARMONA-CACERES		DATE/YEAR-MO-DAI 1962-01-25	
YP					THIRD ANGLE PROJECTION 		CHECKER B. PETERS		ENGINEER O. FERMIN	
TS							ENGINEER		QUALITY ENGINEER	
EL2							DRAWING APPROVAL O. FERMIN		2024-08-26	
RA		13025692	M2A4						SIZE D	DAI 19203
BH		NEXT ASSY		USED ON	MATL ENGR	MODELED BY J. CARMONA-CACERES	DESIGN APPROVAL S. PATEL		DWG NO. 8861565	
RH		APPLICATION					2024-08-26		SCALE 0.500	UNIT WT. 0.000
									SHEET 1 OF 1	