

MARKING INSTRUCTIONS, BOX, WOOD

- M1 - THE BOX SHALL BE MARKED IN ACCORDANCE WITH DWG 8796522.
M2 - THE PROPER SHIPPING NAME AND IDENTIFICATION NUMBER SHALL BE CHARGES, DEMOLITION UN 0048
M3 - THE DESCRIPTIVE NOMENCLATURE SHALL BE; CHARGE, DEMOLITION: SHAPED, 15LB. M2A4.
M4 - THE NSN AND DODIC SHALL BE: 1375-01-023-7994-M420.
M5 - THE UN POP MARKING (SEE NOTE 5) SHALL BE:

u 4C1/Y*/S/**
n USA/DOD/AYD

THE LETTERS "u" AND "n" SHALL BE IN LOWER CASE AND ENCLOSED IN A CIRCLE. PRIOR TO SHIPMENT, THE MANUFACTURER SHALL MAKE SURE THE CONTAINER HAS BEEN TESTED BY A GOVERNMENT APPROVED POP TEST LABORATORY FOR COMPLIANCE WITH TITLE 49 CODE OF THE FEDERAL REGULATIONS. AT * ENTER THE LAST TWO DIGITS OF THE YEAR PACKED. THE POP TESTED BOX WEIGHT MUST BE GREATER THAN OR EQUAL TO THE WEIGHT OF THE PACKED OUT BOXES IAW 49 CFR.

NOTES:

- 2 - MATERIAL: FILLER, SHEET FORM MIL-PRF-50449.
3 - QUANTITY: AS REQUIRED.
4 - MATERIAL: TAPE, GUMMED, PAPER, TYPE II, GRADE B, ASTM D5749.
5 - MATERIAL: INK, STENCIL, BLACK 37038, TYPE II, III, OR IV, SPEC A-A-208.
6 - FOR REQUIRED MARKING SEE APPLICABLE PART DRAWING.
7 - MATERIAL: BAG, RE-SEALABLE, POLYETHYLENE, CLEAR, 2 MIL MIN THICK, PRESS SEAL CLOSURE, COMMERCIAL.

REFERENCE DATA:
COA1 DWG: 13025692

FIBERBOARD BOX PACK INCLUDES:

- 1 - CHARGE, DEMOLITION: SHAPED, 15LB. M2A4: 8861565-1
1 - SLEEVE, STAND OFF: 8861567-1
2 - ADAPTER, PRIMING MIA5: 13021902

DISTRIBUTION STATEMENT A
APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION IS UNLIMITED.

PACKING INSTRUCTION

- P1 - ALL MATERIAL SHALL BE DRY AT THE TIME OF PACKING. PAPER PRODUCT SHOULD NOT HAVE MORE THAN 9% MOISTURE CONTENT.
P2 - SECURE BOTTOM FLAPS OF FIBERBOARD BOX WITH TAPE, APPLIED OVER FULL LENGTH OF CENTER AND END SEAMS WITH MINIMUM 2 INCH EXTENSION ON TO END PANELS AND AROUND CORNERS OF THE BOX.
P3 - INSERT BASE RING SUPPORT - 9281171-3 (REF) ON THE BOTTOM OF THE CHARGE. INSERT THE CHARGE INTO THE FIBERBOARD BOX.
P4 - PLACE A STAND SEPARATOR 9281171-2 (REF) OVER THE NOSE OF THE CHARGE.
P5 - INSERT THE CHARGE STAND OVER THE CHARGE AND SEPARATOR.
P6 - PLACE A TOP RING SUPPORT 9281171-1 (REF) ON TOP OF THE CHARGE WITH THE NOSE OF THE CHARGE SECURELY INSERTED INTO THE CENTER CAVITY OF THE SUPPORT.
P7 - PACK 2 ADAPTER, PRIMING MIA5 13021902 INTO RE-SEALABLE BAG, REMOVE EXCESS AIR, AND PRESS SEAL. PLACE BAGGED ADAPTERS IN HOLE CUT THRU TOP FILLER.
P8 - CLOSE THE FIBERBOARD BOX FLAPS AND SECURE THE FLAPS AS INSTRUCTED IN P2. FORCE MAY NEED TO BE APPLIED TO COMPRESS POLYETHYLENE COMPONENTS TO ENSURE PROPER CLOSING.
P9 - BLUNT ALL CORNERS OF THE BOX AND INSERT THE BOX INTO A BARRIER BAG.
P10 - EXHAUST ALL EXCESS AIR FROM THE BARRIER BAG AND CLOSE THE BAG OPENING BY MEANS OF HEAT SEALING. SEAL SHALL MEET HEAT SEAL TEST OF MIL-STD-2073.
P11 - PACK FOUR (4) CHARGES PACKAGED AS DESCRIBED (P1 THROUGH P10) INTO A WOODEN BOX.
P12 - ADD FILLER AT SIDES, ENDS AND ON TOP OF THE BOX CONTENT. ADD ADDITIONAL FILLERS AS REQUIRED FOR A TIGHT PACK.
P13 - CLOSE THE BOX AND APPLY STRAPPING AND METALLIC SEAL AS SPECIFIED IN THE INSTRUCTIONS CONTAINED IN THE APPENDIX OF THE BOX SPECIFICATION.

BAG, BARRIER - 9281173
NOTE 6

BOX, FIBERBOARD - 9281172
NOTE 6

BOX, WOOD - 9281174

COMPONENTS, POLYETHYLENE - 9281171

FILLER, END - 9281170-2
18. X 13.
NOTES 2, 3

FILLER, SIDE - 9281170-1
18. X 13.
NOTES 2, 3

FILLER, TOP - 9281170-3
18. X 18.
NOTES 2, 3

MARKING - 8796522
NOTE 6

TAPE - 9281170-4
2 INCH WIDTH
NOTE 4


BAG, RE-SEALABLE -9281170-5
3 (OPEN FACE) MIN X 4 MIN
NOTE 7

REVISIONS			
DRAW REV	DESCRIPTION	DATE(YEAR-MO-DA)	APPROVED
C	NOR R0B2013 / 2000-05-10	2000-06-27	BAC
D	NOR R06B2001 / 2006-08-07	2006-10-04	FET
E	NOR R09B2001 / 2009-03-30	2009-04-21	GJC
F	NOR R11B2008 / 2011-12-21	2012-01-06	GJC
G	REDRAWN WITH CHANGES NOR R24B2007 / 2024-08-26	2024-10-09	RLV

THIS DRAWING WAS GENERATED FROM A SOLID MODEL AND IS CAD MAINTAINED. CHANGES SHALL BE INCORPORATED BY THE DESIGN ACTIVITY.

CURRENT DESIGN ACTIVITY CAGE CODE 19200
US ARMY
COMBAT CAPABILITIES DEVELOPMENT COMMAND ARMAMENTS CENTER
PICATINNY ARSENAL, NEW JERSEY 07806-5000

PART NO. 9281170

PMIC				DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON ANGLES ± ° 2 PLACE DECIMALS ± 3 PLACE DECIMALS ±		CONTRACT NUMBER CONTRACTOR DRAWN BY T. TRAN DATE(YEAR-MO-DA) 1973-07-13 CHECKER J. GRANUZZO ENGINEER O. FERMIN QUALITY ENGINEER DRAWING APPROVAL O. FERMIN 2024-08-26 DESIGN APPROVAL S. PATEL 2024-08-26		DESIGN ACTIVITY U.S. ARMY MUNITIONS COMMAND PICATINNY ARSENAL, DOVER, NEW JERSEY 07801 PACKING AND MARKING FOR CHARGE, DEMOLITION: SHAPED, 15LB, M2A4			
MECHANICAL PROPERTIES				THIRD ANGLE PROJECTION 				SIZE C DAI 19203 DWG NO. 9281170			
YP											
TS											
EL2				13025692 M2A4		NEXT ASSY USED ON		SCALE 1.000 UNIT WT. 0.000 SHEET 1 OF 1			
RA											
BH											
RH		APPLICATION									