

DESCRIPTION: MAGNETIC SHIELDING, TUNGSTEN IMPREGNATED POLYMER, PC 1 OF DWG 2370.2-7445

ORDERING DATA:

- A. Fabricated using materials and instructions listed below.
- B. Materials: see Tables 1 and 2.
- C. Color and Marking Requirements: Shielding products must not contain yellow or magenta color. Label "RF-7445" and the weight on each piece using a contrasting color (not yellow or magenta).
- D. QUANTITY: 65 Each

TABLE 1 MATERIAL DESCRIPTION		
ITEM No.	DESCRIPTION	SPEC
1	Tungsten shielding homogenous matrix of tungsten powder and silicone rubber. Approximately 95 percent tungsten by weight.	See Table 2
2	Magnetic layer is strong enough to hold a minimum of double the weight of each individual shielding piece.	See Table 2

TABLE 2 TUNGSTEN SHIELDING ATTRIBUTES		
ATTRIBUTE		VALUE
(1)	THICKNESS	PER PC 1 OF DWG 2370.2-7445
(2)	HEIGHT	PER PC 1 OF DWG 2370.2-7445
(3)	DENSITY	7 G/CC MINIMUM
(4)	TVL – TENTH VALUE THICKNESS	EQUAL TO 2.00" OR BETTER
(5)	SHAPE	PCs MUST BE ABLE TO FIT UP FLUSH AROUND A 8" SCH 40 PIPE WITH NO GAPS

- E. Testing for detrimental materials is required. Quantitative test reports shall be provided as evidence that all materials used have been tested in accordance with Appendix A, Section A.6 of MIL-STD-2041 Rev E, Notice 1 Control of Detrimental Materials, and that the materials do not exceed the following limits:

BROMIDES	250 PPM (LEACHABLE)*
CHLORIDES	250 PPM (LEACHABLE)*
FLUORIDES	250 PPM (LEACHABLE)*
SULFUR	250 PPM (LEACHABLE)*
MERCURY	SHALL NOT EXCEED 10 PPM

*At the option of the vendor, total levels of each halogen and sulfur may be determined in lieu of water-leachable levels per MIL-STD-2041 Rev E, Notice 1.

If the materials have been satisfactorily tested within the last four years, a copy of those test reports and a statement by the manufacturer that there has been no changes in the formulation or manufacturing process shall be submitted and is acceptable in lieu of performing additional detrimental material analyses.

- F. Shielding shall be clean, well finished and free from foreign matter, cracks, holes, or other defects that may affect appearance or serviceability.
- G. Shielding shall be appropriately palletized and packaged to provide adequate protection for shipping and storing. Each shipping pallet shall have a maximum loaded weight of not more than 3000 pounds. The loaded pallet shall comply with all D.O.T. Safety regulations. Partial shipments are acceptable.
- H. Vendor shall provide Certified Test Reports that provide quantitative data to verify that the materials provided meet the requirements of Table (2), Attributes (1) through (3). Test Reports shall be signed and dated by the vendor's Quality Assurance rep. and shall be traceable to the purchase contract under which the material is provided.