

1. General Specifications

- Product: Mobile vehicle lift system
- Type: RG 6,5 HD-VG
- Quantity: 1 complete set of 4 vehicle lifts.
- Application: Designed for lifting buses and commercial vehicles safely at the tires in an inside workshop environment.

2. Performance Characteristics

- Lifting Capacity: min 6,500 kg per vehicle lift.
- Lifting Stroke: min 1,800 mm (effective).
- Lifting Speed: min 500 mm/min.
- Manual adjustable wheel receiver that accommodates a wide range of tire sizes with desired adjustable positions:
 - V1: 390 mm (for tire diameters 550 - 620 mm)
 - V2: 420 mm (for tire diameters 620 - 690 mm)
 - V3: 450 mm (for tire diameters 690 - 810 mm)
 - V4: 470 mm (for tire diameters 810 - 940 mm)
 - V5: 570 mm (for tire diameters 940 - 1140 mm)
- Minimum Tire Rim Diameter: 320 mm.

3. Mechanical and Construction

- Drive System: Electromechanical drive via a geared brake motor unit with an integrated holding brake.
- Construction: Robust, welded steel construction from shot-blasted profiles and plates. A beveled base frame allows for easy maneuvering.
- Steering: Hydraulic steering and pump drawbar, functionally equivalent to a pallet truck.
- Coating:
 - Surface Treatment: 1K hydro primer and a 2K PUR structural topcoat.

- Finish: Durable, high-quality polyurethane topcoat resistant to water, hydraulic oil, grease, coolants, and common solvents.

4. Electrical and Control

- Power: min 2.2 kW per vehicle lift.
- Motor Protection: min IP55.
- Power Supply Connection: 5-pin male 32A CEE-socket.
- Operating Voltage: 3-phase 400V, 50 Hz (L1, L2, L3, N, PE), right-hand motion.
- Control System:
 - A central control box with a 10m power supply cable and a 5-pin CEE plug.
 - Indicator light for each vehicle lift.
 - Main switch with an EMERGENCY-STOP function.
 - Illuminated "Control ON" pushbutton.
 - Selector switches for "Normal Remote Control (HSK) or Special Pushbutton" and "Single Control | 1+2 | 3+4 | set of 4".
 - "RAISE | LOWER" pushbuttons.
 - 15m remote control (HSK) with "RAISE | LOWER | EMERGENCY-STOP" buttons (Hold-to-Run).
- Minimum Cable Set Lengths:
 - Lift 1: 0.5 meters
 - Lift 2: 10 meters
 - Lift 3: 10 meters
 - Lift 4: 15 meters

5. Safety and Standards

- Safety Devices:
 - Self-locking spindle system with support nut and safety nut.
 - Safety relay for emergency stop and contactor monitoring.
 - Electrically monitored support nut and steering drawbar chassis.

- Standards Compliance:
 - Vehicle lift standard EN 1493:2010.
 - Machinery Directive 2006/42/EC.
 - The system is delivered with CE marking and a Declaration of Conformity.
- Quality System:
 - Welding certified according to EN 1090-2 (EXCL2), inspected by TÜV.
 - Certified according to DIN ISO 9001:2015 by DGUV.

6. Documentation

The following documentation must be provided:

- Original inspection book.
- Operating and maintenance instructions.
- Overview drawing.
- Spare parts list.
- Wiring scheme with an electrical spare parts list (located inside the control box).