

1.0 General Information

This document provides the minimum technical and performance requirements for the solicited equipment. To be considered technically acceptable, any offered product must meet or exceed all of the characteristics listed for each line item below.

Offerors must provide sufficient technical documentation (e.g., product literature, specification sheets) with their quote to allow the Government to conduct a technical evaluation and verify compliance. The Government is not responsible for locating or seeking out information to determine technical acceptability. Quotes that fail to provide adequate documentation to demonstrate compliance with all stated requirements may be deemed technically unacceptable and may not be considered for award.

2.0 Equipment Requirements

CLIN 0001: Combination Oven, Double-Stack

- **Configuration:** Must be a double-stacked electric oven unit.
- **Capacity (per unit):** Must accommodate a minimum of twenty (20) 18" x 26" sheet pans OR forty (40) 12" x 20" steam pans.
- **Operating Modes:** Must include modes for steaming, convection, and combination cooking.
- **Temperature Range:** Must be capable of operating in a range from 85°F to 572°F.
- **Controls:** Must feature a 10.1" TFT color display with a capacitive touch screen.
- **Core Probe:** Must include a six (6) point temperature core probe.
- **Electrical:** Must operate on a 208/240 V, 60 Hz, 3 Phase power supply.
- **Water Connection:** Must have a 3/4" GHT water inlet and a 2" drain outlet.
- **Certifications:** Must be NSF and UL certified.

CLIN 0002: Refrigerator, Reach-In, Two-Door

- **Configuration:** Must be a two (2) door, reach-in refrigerator.
- **Construction:** Must have a stainless steel front and doors, with anodized aluminum sides and interior.
- **Capacity:** Must have a minimum capacity of 46.01 cubic feet.
- **Temperature Control:** Must feature a microprocessor control system with an LED temperature display.
- **Shelving:** Must include a minimum of three (3) epoxy-coated shelves per section, for a total of six (6) shelves.
- **Hinging:** Doors must be hinged on the left and right respectively.
- **Electrical:** Must operate on a 115 V, 60 Hz, 1 Phase power supply and include a NEMA 5-15P plug.
- **Refrigerant:** Must use R-450A refrigerant.
- **Certifications:** Must be ENERGY STAR qualified, UL, and NSF listed.

CLIN 0003: Food Warmer and Proofer Cabinet

- **Configuration:** Must be a single-door, mobile cabinet.
- **Functionality:** Must be capable of functioning as both a heated holding cabinet and a proofer.
- **Construction:** Must have a stainless steel exterior and interior.
- **Controls:** Must have a simple control with an adjustable thermostat.
- **Temperature Range:**
 - Holding temperature range must be from 80°F to 200°F.
 - Proofing function must achieve 95% humidity in a temperature range from 80°F to 120°F.
- **Capacity:** Must hold a minimum of sixteen (16) 18" x 26" x 1" sheet pans OR thirty-two (32) 12" x 20" x 2-1/2" hotel pans.
- **Electrical:** Must operate on a 120 V, 60 Hz, 1 Phase, 16 Amp power supply and include a NEMA 5-20P plug.
- **Casters:** Must be equipped with four (4) 5-inch casters, of which two are rigid and two are swivel with brakes.
- **Certifications:** Must be EcoSmart, UL, and NSF listed.