

RFQ	REFERENCE NO. OF DOCUMENT BEING CONTINUED N00173-26-Q-1301346868	PAGES 1 OF 2
-----	---	-----------------

NAME OF OFFEROR OR CONTRACTOR

ITEM NO.	SUPPLIES/SERVICES	QUANTITY	UNIT	UNIT PRICE	AMOUNT
1	WR10CCD-B Compact DownConverter Module Estimated Specifications: RF: 75-110 GHz, Flange: WR10 UG-387/U L0: 18.75-27.5 GHz, Flange: 2.9mm(f), N=4 IF: up to 15 GHz, 2.9mm(f), includes IF Amplifier (~12dB Gain) L0 Power: 0-6 dBm typical, 9dBm damage Typical Performance: Lmix: 10 dB typ. (SSB) RF Input Power (~P1dB): +5dBm typical				
2	WR10CCU-B Compact UpConverter Module Estimated Specifications: RF: 75-110 GHz, Flange: WR10 UG-387/U L0: 18.75-27.5 GHz, Flange: 2.9mm(f), N=4 IF: 10MHz-15GHz, 2.9mm(f) L0 Power: 0-6 dBm typical, 9dBm damage Typical Performance: Lmix: 10 dB typ. (SSB) IF Input Power (~P1dB): +5dBm typical VDI Compact Converter (CCU CCD) Technical Notes: VDI Compact Converters are designed for high performance up and downconversion for wide band modulated mmWave signals. These devices operate in double side band mode, so RF side band filters are generally recommended and are available from VDI. External RF amplifiers are also available from VDI to boost the RF signal. VDI CCs include a single-volt Power Supply. Conversion loss is measured at IF~1GHz, loss increases at a rate of about 1.5dB/10GHz up to the specified maximum IF. CCD modules include an IF amplifier with ~12dB gain.				
3	WR10PSG - Portable Signal Generator Extension Module (75-110GHz) Performance: +6dBm (typ.) RF Flange: WR-10 UG-387/U-M Input Drive Frequency: 12.5-18.33GHz (N=6)				