

Mobile Breathing Air Compressor Trailer

Purpose of Use

The mobile breathing air compressor trailer is designed to support fire and emergency operations by providing a safe, reliable source of clean breathing air. Its primary purpose is to refill Self-Contained Breathing Apparatus (SCBA) cylinders used by firefighters during emergencies, training, extended incidents, and special operations. The trailer allows air refilling to occur on scene or at remote locations without reliance on fixed facilities, improving response readiness, operational efficiency, and firefighter safety.

General Description

The system is a self-contained, trailer-mounted unit that produces, stores, and dispenses high-pressure breathing air. It includes an air compressor, storage cylinders, monitoring equipment, and power systems, all integrated onto a towable trailer. The unit is designed for mobile use and can operate independently or connect to shore power when available.

Unit Specifications (Silent Characteristics)

- › Manufactured in compliance with the National Trailer Manufacturers Association (NATM) guidelines
- › NFPA 1901 2016 edition compliant 2 position containment fill station accommodates SCBA or SCUBA cylinders up to 31" overall length
- › Diesel/electric dual drive system incorporating exclusive automatic belt tensioning system. Must meet the following diesel/electric motor requirements.
 - Diesel: 27 Horsepower (HP)
 - Diesel: 20 (kW)
 - Electric: 20 (HP)
 - Electric: 15(kW)
- › High gloss powder coat paint for a hard durable finish
- › Hydraulic surge brakes with breakaway actuator
- › Bulk fill pneumatic logic
- › Two (2) ASME air storage cylinders with bulk fill pneumatic logic
- › Formed structural steel frame designed and built by BAUER
- › Unit must come with all required connections to connect to wall electrical outlet for shore power

- › Chlorosulfonated polyethylene (CSPE), a synthetic rubber known for its exceptional durability and resistance to harsh environments. type cover protection for the operations panel and fill station
- › Telescoping light mast with four 500 watt fixtures, snorkel tube for compressor air inlet integrated with light mast and 7500 watt auxiliary generator
- › 7.5 kW belt driven generator
- › Electronic moisture-monitoring system used on SCBA compressor purification towers. Its must continuously monitor the condition of the purification cartridges (drying media) and alert operators when the filter is nearing saturation. Compressor must produce clean, dry, breathable air that meets NFPA and OSHA standards.
- › Must be able to deliver completed unit to Travis Air Force Fire Department between 90 – 120 days
- › Spare tire and wheel chocks with fender well storage
- › Must weigh 5500 pounds or less
- › Dimensions must be no more than 183"L, 95" W, 105" H

Mobility: Towable by approved department vehicles

-SYSTEM START-UP AND ORIENTATION FOR FIRE PERSONNEL BY FACTORY CERTIFIED TECHNICIAN

FREIGHT TO CUSTOMERS FACILITY AT TRAVIS AIR FORCE BASE FIRE DEPARTMENT