

NOTE: OFFEROR TO COMPLETE BLOCKS 12, 17, 23, 24, AND 30.				1. REQUISITION NUMBER A023026		PAGE 1 OF 37							
2. CONTRACT NUMBER		3. AWARD/EFFECTIVE DATE		4. ORDER NUMBER		5. SOLICITATION NUMBER N0010426QN051		6. SOLICITATION ISSUE DATE					
7. FOR SOLICITATION INFORMATION CALL:		a. NAME Brittany Langletzt				b. TELEPHONE NUMBER (No collect calls) 7712293917		8. OFFER DUE DATE/ LOCAL TIME 15 Mar 2026 04:00 PM					
9. ISSUED BY NAVSUP WEAPON SYSTEMS SUPPORT MECH P O BOX 2020, 5450 CARLISLE PIKE MECHANICSBURG, PA 17050-0788 UNITED STATES Brittany Langletzt, Email: brittany.a.langletzt.civ@us.navy.mil Telephone: 7712293917				CODE N00104		10. THIS ACQUISITION IS ☒ UNRESTRICTED OR ☐ SET ASIDE: _____ % FOR: ☐ SMALL BUSINESS ☐ WOMEN-OWNED SMALL BUSINESS (WOSB) ☐ NORTH AMERICAN INDUSTRY CLASSIFICATION STANDARD (NAICS): 333924 ☐ HUBZONE SMALL BUSINESS ☐ ECONOMICALLY DISADVANTAGED WOMEN-OWNED SMALL BUSINESS (EDWOSB) ☐ 8(A) ☐ SIZE STANDARD: 900 ☐ SERVICE-DISABLED ☐ VETERAN-OWNED SMALL BUSINESS (SDVOSB)							
11. DELIVERY FOR FREE ON BOARD (FOB) DESTINATION UNLESS BLOCK IS MARKED ☒ SEE SCHEDULE		12. DISCOUNT TERMS		13a. THIS CONTRACT IS A ☒ RATED ORDER UNDER THE DEFENSE PRIORITIES AND ALLOCATIONS SYSTEM - DPAS (15 CFR 700)		13b. RATING DO-A3 14. METHOD OF SOLICITATION ☒ REQUEST FOR QUOTE (RFQ) ☐ INVITATION FOR BID (IFB) ☐ REQUEST FOR PROPOSAL (RFP)							
15. DELIVER TO See Continuation				CODE		16. ADMINISTERED BY CODE							
17a. CONTRACTOR/ OFFEROR TELEPHONE NUMBER ☐ 17b. CHECK IF REMITTANCE IS DIFFERENT AND PUT SUCH ADDRESS IN OFFER		CODE		FACILITY CODE		18a. PAYMENT WILL BE MADE BY CODE							
19. ITEM NUMBER		20. SCHEDULE OF SUPPLIES/SERVICES See Continuation (Use Reverse and/or Attach Additional Sheets as Necessary)				21. QUANTITY		22. UNIT		23. UNIT PRICE		24. AMOUNT	
25. ACCOUNTING AND APPROPRIATION DATA See Continuation						26. TOTAL AWARD AMOUNT (For Government Use Only)							
☒ 27a. SOLICITATION INCORPORATES BY REFERENCE (FEDERAL ACQUISITION REGULATION) FAR 52.212-1, 52.212-4. FAR 52.212-3 AND 52.212-5 ARE ATTACHED. ADDENDA ☐ ARE ☒ ARE NOT ATTACHED						☐ 27b. CONTRACT/PURCHASE ORDER INCORPORATES BY REFERENCE FAR 52.212-4. FAR 52.212-5 IS ATTACHED. ADDENDA ☐ ARE ☐ ARE NOT ATTACHED							
☐ 28. CONTRACTOR IS REQUIRED TO SIGN THIS DOCUMENT AND RETURN COPIES TO ISSUING OFFICE. CONTRACTOR AGREES TO FURNISH AND DELIVER ALL ITEMS SET FORTH OR OTHERWISE IDENTIFIED ABOVE AND ON ANY ADDITIONAL SHEETS SUBJECT TO THE TERMS AND CONDITIONS SPECIFIED						☐ 29. AWARD OF CONTRACT: REFERENCE _____ OFFER DATED _____. YOUR OFFER ON SOLICITATION (BLOCK 5), INCLUDING ANY ADDITIONS OR CHANGES WHICH ARE SET FORTH HEREIN, IS ACCEPTED AS TO ITEMS: See Continuat							
30a. SIGNATURE OF OFFEROR/CONTRACTOR						31a. UNITED STATES OF AMERICA (SIGNATURE OF CONTRACTING OFFICER)							
30b. NAME AND TITLE OF SIGNER (Type or print)				30c. DATE SIGNED		31b. NAME OF CONTRACTING OFFICER (Type or print)				31c. DATE SIGNED			

Solicitation/Contract Form Continuation

Material Handling Equipment NAVSUP WSS DDG 136/136/137 6K MPJ 42” (ECC:1900)

Continuation of Supplies or Services and Prices/Costs

Additional Information/Notes

SOLICITATION REMARKS:

1. The resultant award of this solicitation will be issued bilaterally, requiring the contractor's written acceptance prior to execution.
2. All contractual documents (i.e. contracts, purchase orders, task orders, delivery orders, and modifications) related to the instant procurement are considered to be "issued" by the Government when copies are either deposited in the mail, transmitted by facsimile, or sent by other electronic commerce methods such as email. The Government's acceptance of the contractor's proposal constitutes bilateral agreement to "issue" contractual documents as detailed herein.
3. Any contract awarded as a result of this solicitation will be certified for national defense under the Defense Priorities and Allocations System (DPAS). Provision 52.211-14, Notice of Priority Rating for National Defense, Emergency Preparedness, and Energy Program Use, shall be inserted in solicitations when the contract to be awarded shall be a rated order.
4. The option provision is included in the event the Government has an additional requirement 365 DAYS after issuance of the award. This will authorize the Government to add the additional quantity, up to the percentage cited, to the order, via modification without having to re-solicit
5. Faxed, NECO, or postal mail quotes will NOT be accepted. Electronically submit quotes to the Contract Specialist at brittany.a.langletz.civ@us.navy.mil.
6. Since the Government intends to award without discussion, all quotes must be submitted in accordance with Section L 52.212-1, Instructions to Offerors-Commercial Products and Commercial Services, and any questions about the requirement should be raised up to 30 days prior to the hour and date for receipt of quotes.

Item	Supplies/Service	Quantity	Unit	Unit Price	Amount
0001	PNICN LLCQB0122 FFP Item Nomenclature: 6K, 42 inch Manual Pallet Jack Pricing Arrangement: Firm Fixed Price				
Option Line Item 0001AA	PNICN LLCQB0122 FFP Item Nomenclature: 6K, 42 inch Manual Pallet Jack East coast (Norfolk) shipping costs should be included in unit price. Model#/P/N* _____ *To be completed by vendor Delivery: 365 Days from receipt of contract Inspect at Source Accept at Source NOTE: The requirements in DFARS 252.211-7003, Item Identification and Valuation, are applicable for this line item. The contractor shall provide DoD unique identification or a DoD recognized unique identification equivalent.	2	Each		
	PNICN LLCQB0122 FFP Item Nomenclature: 6K, 42 inch Manual Pallet Jack East coast (Norfolk) shipping costs should be included in unit price. Model#/P/N* _____ *To be completed by vendor Delivery: 365 Days from receipt of contract				

Option Line Item 0001AB	Inspect at Source Accept at Source NOTE: The requirements in DFARS 252.211-7003, Item Identification and Valuation, are applicable for this line item. The contractor shall provide DoD unique identification or a DoD recognized unique identification equivalent.	2	Each		
Option Line Item 0001AC	PNICN LLCQB0122 FFP Item Nomenclature: 6K, 42 inch Manual Pallet Jack East coast (Norfolk) shipping costs should be included in unit price. Model#/P/N*_____ *To be completed by vendor Delivery: 365 Days from receipt of contract Inspect at Source Accept at Source NOTE: The requirements in DFARS 252.211-7003, Item Identification and Valuation, are applicable for this line item. The contractor shall provide DoD unique identification or a DoD recognized unique identification equivalent.	2	Each		
0002	CDRLs Not Separately Priced See Exhibit A: DD1423 CDRLs for more information Pricing Arrangement: Firm Fixed Price		Set		

Continuation of Description

Requirements

DDG 134/136/137 Material Handling Equipment

NAVSUP WSS PR No./ERP No. 6K MPJ 42 (ECC:1900)

Continuation of Packaging and Marking

Continuation of Inspection and Acceptance

Continuation of Deliveries or Performance

Line Item	Delivery Schedule	Quantity	Address and POC	Special Handling/Notes
0001				FoB Details Contractor Destination
0002				FoB Details Contractor Destination

Continuation of Accounting and Appropriation Data

Contract Clauses

FAR Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
52.204-10	Reporting Executive Compensation and First-Tier Subcontract Awards. (Deviation)	Feb 2026		
52.222-54	Employment Eligibility Verification. (Deviation)	Feb 2026		
52.222-19	Child Labor-Cooperation with Authorities and Remedies. (Deviation)	Feb 2026		
52.222-35	Equal Opportunity for Veterans. (Deviation)	Feb 2026		
52.222-36	Equal Opportunity for Workers with Disabilities. (Deviation)	Feb 2026		
52.222-37	Employment Reports on Veterans. (Deviation)	Feb 2026		
52.232-33	Payment by Electronic Funds Transfer-System for Award Management.	Oct 2018		
52.203-19	Prohibition on Requiring Certain Internal Confidentiality Agreements or Statements.	Jan 2017		
52.226-8	Encouraging Contractor Policies to Ban Text Messaging While Driving.	May 2024		
52.232-40	Providing Accelerated Payments to Small Business Subcontractors.	Mar 2023		
52.233-3	Protest after Award.	Aug 1996		
52.233-4	Applicable Law for Breach of Contract Claim. (Deviation)	Feb 2026		
52.209-6	Protecting the Government's Interest When Subcontracting With Contractors Debarred, Suspended, Proposed for Debarment, or Voluntarily Excluded. (Deviation)	Feb 2026		
52.204-13	System for Award Management-Maintenance. (Deviation)	Feb 2026		
52.203-6	Restrictions on Subcontractor Sales to the Government.	Jun 2020		

DFARS Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
252.203-7000	Requirements Relating to Compensation of Former DoD Officials.	Sep 2011		
252.203-7002	Requirement to Inform Employees of Whistleblower Rights.	Dec 2022		
252.204-7018	Prohibition on the Acquisition of Covered Defense Telecommunications Equipment or Services.	Jan 2023		
252.225-7056	Prohibition Regarding Business Operations with the Maduro Regime.	Jan 2023		
252.225-7060	Prohibition on Certain Procurements from the Xinjiang Uyghur Autonomous Region.	Jun 2023		
252.232-7003	Electronic Submission of Payment Requests and Receiving Reports.	Dec 2018		
252.232-7010	Levies on Contract Payments.	Dec 2006		
252.247-7023	Transportation of Supplies by Sea.	Oct 2024		
252.204-7015	Notice of Authorized Disclosure of Information for Litigation Support.	Jan 2023		
252.223-7008	Prohibition of Hexavalent Chromium.	Jan 2023		
252.246-7003	Notification of Potential Safety Issues.	Jan 2023		
252.246-7008	Sources of Electronic Parts.	Jan 2023		

FAR Clauses Incorporated by Full Text

52.212-4 Terms and Conditions-Commercial Products and Commercial Services. (Deviation) (Feb 2026)

TERMS AND CONDITIONS-COMMERCIAL PRODUCTS AND COMMERCIAL SERVICES (FEB 2026) (DEVIATION)

(a) *Definitions.* The clause at Federal Acquisition Regulation (FAR) 52.202-1, Definitions, is incorporated by reference.

(b) *Inspection/Acceptance.* The Contractor shall only tender for acceptance those items that conform to the requirements of this contract. The Government reserves the right to inspect or test any supplies or services that have been tendered for acceptance. The Government may require repair or replacement of nonconforming supplies or reperformance of nonconforming services at no increase in contract price. If repair/replacement or reperformance will not correct the defects or is not possible, the Government may seek an equitable price reduction or adequate consideration for acceptance of nonconforming supplies or services. The Government must exercise its post acceptance rights-

(1) Within a reasonable time after the defect was discovered or should have been discovered; and

(2) Before any substantial change occurs in the condition of the item, unless the change is due to the defect in the item.

(c) *Assignment.* The Contractor or its assignee may assign its rights to receive payment due as a result of performance of this contract to a bank, trust company, or other financing institution, including any Federal lending agency in accordance with the Assignment of Claims Act (31 U.S.C. 3727). However, when a third party makes payment (e.g., use of the Governmentwide commercial purchase card), the Contractor may not assign its rights to receive payment under this contract.

(d) *Changes.* Changes in the terms and conditions of this contract may be made only by written agreement of the parties.

(e) *Disputes.* This contract is subject to 41 U.S.C. chapter 71, Contract Disputes. Failure of the parties to this contract to reach agreement on any request for equitable adjustment, claim, appeal, or action arising under or relating to this contract shall be a dispute to be resolved in accordance with

the clause FAR 52.233-1, Disputes, which is incorporated in this contract by reference. The Contractor shall proceed diligently with performance of this contract, pending final resolution of any dispute arising under the contract.

(f) *Excusable delays.* The Contractor shall be liable for default unless nonperformance is caused by an occurrence beyond the reasonable control of the Contractor and without its fault or negligence. Examples of occurrences include acts of God or the public enemy, acts of the Government in either its sovereign or contractual capacity, fires, floods, epidemics, quarantine restrictions, strikes, unusually severe weather, and delays of common carriers. When an excusable delay occurs, the Contractor shall-

- (1) Notify the Contracting Officer in writing as soon as possible;
- (2) Remedy the delay as quickly as possible; and
- (3) Notify the Contracting Officer when the occurrence is over.

(g) *Invoice.* The Government will handle invoices according to the Prompt Payment Act (31 U.S.C. 3903) and 5 CFR part 1315. The Contractor shall submit invoices to the address designated in the contract to receive invoices. An invoice must include the information required by 5 CFR part 1315.9(b).

(h) *Patent indemnity.* The Contractor shall indemnify the Government and its officers, employees, and agents against liability, including costs, for actual or alleged direct or contributory infringement of, or inducement to infringe, any United States or foreign patent, trademark, or copyright, arising out of the performance of this contract, provided the Contractor is reasonably notified of such claims and proceedings.

(i) *Payment-*

(1) *Items accepted.* Payment shall be made for items accepted by the Government that have been delivered to the delivery destinations set forth in this contract.

(2) *Prompt payment.* The Government will make payment in accordance with the Prompt Payment Act (31 U.S.C. 3903) and prompt payment regulations at 5 CFR part 1315.

(3) *Discount.* In connection with any discount offered for early payment, time shall be computed from the date of the invoice. For the purpose of computing the discount earned, payment shall be considered to have been made on the date that appears on the payment check or the specified payment date if an electronic funds transfer payment is made.

(4) *Overpayments.* If the Contractor becomes aware of a duplicate contract financing or invoice payment or that the Government has otherwise overpaid on a contract financing or invoice payment, the Contractor shall-

- (i) Remit the overpayment amount to the payment office cited in the contract along with a description of the overpayment including the-
 - (A) Circumstances of the overpayment (e.g., duplicate payment, erroneous payment, liquidation errors, date(s) of overpayment);
 - (B) Affected contract number and delivery order number, if applicable;
 - (C) Affected line item or subline item, if applicable;
 - (D) Contractor point of contact; and

(ii) Provide a copy of the remittance and supporting documentation to the Contracting Officer.

(5) *Interest.*

(i) All amounts that become payable by the Contractor to the Government under this contract shall bear simple interest from the date due until paid unless paid within 30 days of becoming due. The interest rate shall be the interest rate established by the Secretary of the Treasury as provided in 41 U.S.C. 7109, which is applicable to the period in which the amount becomes due, as provided in (i)(6)(v) of this clause, and then at the rate applicable for each six-month period as fixed by the Secretary until the amount is paid.

(ii) The Government may issue a demand for payment to the Contractor upon finding a debt is due under the contract.

(iii) *Final decisions.* The Contracting Officer will issue a final decision as required by FAR part 33 if-

- (A) The Contracting Officer and the Contractor are unable to reach agreement on the existence or amount of a debt within 30 days;
- (B) The Contractor fails to liquidate a debt previously demanded by the Contracting Officer within the timeline specified in the demand for payment unless the amounts were not repaid because the Contractor has requested an installment payment agreement; or
- (C) The Contractor requests a deferment of collection on a debt previously demanded by the Contracting Officer (see FAR part 32).

(iv) If a demand for payment was previously issued for the debt, the demand for payment included in the final decision shall identify the same due date as the original demand for payment.

(v) Amounts shall be due at the earliest of the following dates:

(A) The date fixed under this contract.

(B) The date of the first written demand for payment, including any demand for payment resulting from a termination for cause.

(vi) The interest charge shall be computed for the actual number of calendar days involved beginning on the due date and ending on-

(A) The date on which the designated office receives payment from the Contractor;

(B) The date of issuance of a Government check to the Contractor from which an amount otherwise payable has been withheld as a credit against the contract debt; or

(C) The date on which an amount withheld and applied to the contract debt would otherwise have become payable to the Contractor.

(vii) The interest charge made under this clause may be reduced under the procedures for interest credits prescribed in FAR part 32 in effect on the date of this contract.

(j) *Risk of loss.* Unless the contract specifically provides otherwise, risk of loss or damage to the supplies provided under this contract shall remain with the Contractor until, and shall pass to the Government upon-

(1) Delivery of the supplies to a carrier, if transportation is f.o.b. origin; or

(2) Delivery of the supplies to the Government at the destination specified in the contract, if transportation is f.o.b. destination.

(k) *Taxes.* The contract price includes all applicable Federal, State, and local taxes and duties.

(l) *Termination for the Government's convenience.* The Government reserves the right to terminate this contract, or any part hereof, for its sole convenience. In the event of such termination, the Contractor shall immediately stop all work and shall immediately cause any and all of its suppliers and subcontractors to cease work. Subject to the terms of this contract, the Contractor shall be paid a percentage of the contract price reflecting the percentage of the work performed prior to the notice of termination, plus reasonable charges the Contractor can demonstrate to the satisfaction of the Government using its standard record keeping system, have resulted from the termination. The Contractor shall not be required to comply with the cost accounting standards or contract cost principles for this purpose. This paragraph does not give the Government any right to audit the Contractor's records. The Contractor shall not be paid for any work performed or costs incurred which reasonably could have been avoided.

(m) *Termination for cause.* The Government may terminate this contract, or any part hereof, for cause in the event of any default by the Contractor, or if the Contractor fails to comply with any contract terms and conditions, or fails to provide the Government, upon request, with adequate assurances of future performance. The Government will send a cure notice to the Contractor, unless the reason for the termination is late delivery. In the event of termination for cause, the Government shall not be liable to the Contractor for any amount for supplies or services not accepted, and the Contractor shall be liable to the Government for any and all rights and remedies provided by law. If it is determined that the Government improperly terminated this contract for default, such termination shall be deemed a termination for convenience.

(n) *Title.* Unless specified elsewhere in this contract, title to items furnished under this contract shall pass to the Government upon acceptance, regardless of when or where the Government takes physical possession.

(o) *Warranty.* The Contractor warrants and implies that the items delivered under this contract are merchantable and fit for use for the particular purpose described in this contract.

(p) *Limitation of liability.* Except as otherwise provided by an express warranty, the Contractor will not be liable to the Government for consequential damages resulting from any defect or deficiencies in accepted items.

(q) *Compliance with laws unique to Government contracts.* The Contractor agrees to comply with 31 U.S.C. 1352 relating to limitations on the use of appropriated funds to influence certain Federal contracts; 40 U.S.C. chapter 37, Contract Work Hours and Safety Standards; 41 U.S.C. chapter 87, Kickbacks; 49 U.S.C. 40118, Government-financed air transportation; and 41 U.S.C. chapter 21 relating to procurement integrity.

(r) *Order of precedence.* Any inconsistencies in this solicitation or contract shall be resolved by giving precedence in the following order:

(1) The schedule of supplies/services;

(2) The Disputes, Payments, Invoice, Compliance with Laws Unique to Government Contracts, and Unauthorized Obligations paragraphs of this clause;

(3) Other contract clauses incorporated in the solicitation or contract;

(4) Addenda to this solicitation or contract;

(5) Solicitation provisions incorporated in the solicitation;

(6) Other paragraphs of this clause;

(7) Other documents, exhibits, and attachments; and

(8) The specification.

(s) *Unauthorized obligations.*

(1) Except as stated in paragraph (s)(2) of this clause, when any supply or service acquired under this contract is subject to any End User License Agreement (EULA), Terms of Service (TOS), or similar legal instrument or agreement, that includes any clause requiring the Government to indemnify the Contractor or any person or entity for damages, costs, fees, or any other loss or liability that would create an Anti-Deficiency Act violation (31 U.S.C. 1341), the following shall govern:

(i) Any such clause is unenforceable against the Government.

(ii) Neither the Government nor any Government-authorized end user shall be deemed to have agreed to such clause by virtue of it appearing in the EULA, TOS, or similar legal instrument or agreement. If the EULA, TOS, or similar legal instrument or agreement is invoked through an "I agree" click box or other comparable mechanism (e.g., "click-wrap" or "browse-wrap" agreements), execution does not bind the Government or any Government authorized end user to such clause.

(iii) Any such clause is deemed to be stricken from the EULA, TOS, or similar legal instrument or agreement.

(2) Paragraph (s)(1) of this clause does not apply to indemnification by the Government that is expressly authorized by statute and specifically authorized under applicable agency regulations and procedures.

(t) *Comptroller General examination of record.* This paragraph applies if this contract was awarded using other than sealed bid procedures and is in excess of the simplified acquisition threshold on the date of award of this contract.

(1) The Comptroller General of the United States, or an authorized representative of the Comptroller General, shall have access to and right to examine any of the Contractor's directly pertinent records involving transactions related to this contract.

(2) The Contractor shall make available at its offices, at all reasonable times, the records, materials, and other evidence for examination, audit, or reproduction, until 3 years after final payment under this contract or for any shorter period specified in FAR part 4, longer period required by statute, or periods specified in other clauses of this contract. If this contract is completely or partially terminated, the records relating to the work terminated shall be made available for 3 years after any resulting final termination settlement. Records relating to appeals under the disputes clause or to litigation or the settlement of claims arising under or relating to this contract shall be made available until such appeals, litigation, or claims are finally resolved.

(3) As used in this clause, records include books, documents, accounting procedures and practices, and other data, regardless of type and regardless of form. This clause does not require the Contractor to create or maintain any record that the Contractor does not maintain in the ordinary course of business or pursuant to a provision of law.

(u) *Incorporation by reference.* The Contractor's representations and certifications, including those completed electronically via the System for Award Management (SAM), are incorporated by reference into the contract.

(End of clause)

DFARS Clauses Incorporated by Full Text

252.211-7003 Item Unique Identification and Valuation.

(Jan 2023)

ITEM UNIQUE IDENTIFICATION AND VALUATION (JAN 2023)

(a) *Definitions.* As used in this clause-

"Automatic identification device" means a device, such as a reader or interrogator, used to retrieve data encoded on machine-readable media.

"Concatenated unique item identifier" means-

(1) For items that are serialized within the enterprise identifier, the linking together of the unique identifier data elements in order of the issuing agency code, enterprise identifier, and unique serial number within the enterprise identifier; or

(2) For items that are serialized within the original part, lot, or batch number, the linking together of the unique identifier data elements in order of the issuing agency code; enterprise identifier; original part, lot, or batch number; and serial number within the original part, lot, or batch number.

"Data matrix" means a two-dimensional matrix symbology, which is made up of square or, in some cases, round modules arranged within a perimeter finder pattern and uses the Error Checking and Correction 200 (ECC200) specification found within International Standards Organization (ISO)/International Electrotechnical Commission (IEC) 16022.

"Data qualifier" means a specified character (or string of characters) that immediately precedes a data field that defines the general category or intended use of the data that follows.

"DoD recognized unique identification equivalent" means a unique identification method that is in commercial use and has been recognized by DoD. All DoD recognized unique identification equivalents are listed at <https://www.acq.osd.mil/asda/dpc/ce/ds/unique-id.html>.

"DoD item unique identification" means a system of marking items delivered to DoD with unique item identifiers that have machine-readable data elements to distinguish an item from all other like and unlike items. For items that are serialized within the enterprise identifier, the unique item identifier shall include the data elements of the enterprise identifier and a unique serial number. For items that are serialized within the part, lot, or batch number within the enterprise identifier, the unique item identifier shall include the data elements of the enterprise identifier; the original part, lot, or batch number; and the serial number.

"Enterprise" means the entity (e.g., a manufacturer or vendor) responsible for assigning unique item identifiers to items.

"Enterprise identifier" means a code that is uniquely assigned to an enterprise by an issuing agency.

"Government's unit acquisition cost" means-

(1) For fixed-price type line, subline, or exhibit line items, the unit price identified in the contract at the time of delivery;

(2) For cost-type or undefinitized line, subline, or exhibit line items, the Contractor's estimated fully burdened unit cost to the Government at the time of delivery; and

(3) For items produced under a time-and-materials contract, the Contractor's estimated fully burdened unit cost to the Government at the time of delivery.

"Issuing agency" means an organization responsible for assigning a globally unique identifier to an enterprise, as indicated in the Register of Issuing Agency Codes for ISO/IEC 15459, located at http://www.aimglobal.org/?Reg_Authority15459.

"Issuing agency code" means a code that designates the registration (or controlling) authority for the enterprise identifier.

"Item" means a single hardware article or a single unit formed by a grouping of subassemblies, components, or constituent parts.

"Lot or batch number" means an identifying number assigned by the enterprise to a designated group of items, usually referred to as either a lot or a batch, all of which were manufactured under identical conditions.

"Machine-readable" means an automatic identification technology media, such as bar codes, contact memory buttons, radio frequency identification, or optical memory cards.

"Original part number" means a combination of numbers or letters assigned by the enterprise at item creation to a class of items with the same form, fit, function, and interface.

"Parent item" means the item assembly, intermediate component, or subassembly that has an embedded item with a unique item identifier or DoD recognized unique identification equivalent.

"Serial number within the enterprise identifier" means a combination of numbers, letters, or symbols assigned by the enterprise to an item that provides for the differentiation of that item from any other like and unlike item and is never used again within the enterprise.

"Serial number within the part, lot, or batch number" means a combination of numbers or letters assigned by the enterprise to an item that provides for the differentiation of that item from any other like item within a part, lot, or batch number assignment.

"Serialization within the enterprise identifier" means each item produced is assigned a serial number that is unique among all the tangible items produced by the enterprise and is never used again. The enterprise is responsible for ensuring unique serialization within the enterprise identifier.

"Serialization within the part, lot, or batch number" means each item of a particular part, lot, or batch number is assigned a unique serial number within that part, lot, or batch number assignment. The enterprise is responsible for ensuring unique serialization within the part, lot, or batch number within the enterprise identifier.

"Type designation" means a combination of letters and numerals assigned by the Government to a major end item, assembly or subassembly, as appropriate, to provide a convenient means of differentiating between items having the same basic name and to indicate modifications and changes thereto.

"Unique item identifier" means a set of data elements marked on items that is globally unique and unambiguous. The term includes a concatenated unique item identifier or a DoD recognized unique identification equivalent.

"Unique item identifier type" means a designator to indicate which method of uniquely identifying a part has been used. The current list of accepted unique item identifier types is maintained at <https://www.acq.osd.mil/asda/dpc/ce/ds/unique-id.html>.

(b) The Contractor shall deliver all items under a contract line, subline, or exhibit line item.

(c) *Unique item identifier.*

(1) The Contractor shall provide a unique item identifier for the following:

(i) Delivered items for which the Government's unit acquisition cost is \$5,000 or more, except for the following line items:

Contract Line, Subline, or

Exhibit Line Item Number	Item Description
_____	_____
_____	_____
_____	_____

(ii) Items for which the Government's unit acquisition cost is less than \$5,000 that are identified in the Schedule or the following table:

Contract Line, Subline, or

Exhibit Line Item Number	Item Description
_____	_____
_____	_____
_____	_____

(If items are identified in the Schedule, insert "See Schedule in this table.")

(iii) Subassemblies, components, and parts embedded within delivered items, items with warranty requirements, DoD serially managed repairables and DoD serially managed nonrepairables as specified in Attachment Number ____.

(iv) Any item of special tooling or special test equipment as defined in FAR 2.101 that have been designated for preservation and storage for a Major Defense Acquisition Program as specified in Attachment Number ____.

(v) Any item not included in (i), (ii), (iii), or (iv) for which the contractor creates and marks a unique item identifier for traceability.

(2) The unique item identifier assignment and its component data element combination shall not be duplicated on any other item marked or registered in the DoD Item Unique Identification Registry by the contractor.

(3) The unique item identifier component data elements shall be marked on an item using two dimensional data matrix symbology that complies with ISO/IEC International Standard 16022, Information technology - International symbology specification - Data matrix; ECC200 data matrix specification.

(4) *Data syntax and semantics of unique item identifiers.* The Contractor shall ensure that-

(i) The data elements (except issuing agency code) of the unique item identifier are encoded within the data matrix symbol that is marked on the item using one of the following three types of data qualifiers, as determined by the Contractor:

(A) Application Identifiers (AIs) (Format Indicator 05 of ISO/IEC International Standard 15434), in accordance with ISO/IEC International Standard 15418, Information Technology - EAN/UCC Application Identifiers and Fact Data Identifiers and Maintenance and ANSI MH 10.8.2 Data Identifier and Application Identifier Standard.

(B) Data Identifiers (DIs) (Format Indicator 06 of ISO/IEC International Standard 15434), in accordance with ISO/IEC International Standard 15418, Information Technology - EAN/UCC Application Identifiers and Fact Data Identifiers and Maintenance and ANSI MH 10.8.2 Data Identifier and Application Identifier Standard.

(C) Text Element Identifiers (TEIs) (Format Indicator 12 of ISO/IEC International Standard 15434), in accordance with the Air Transport Association Common Support Data Dictionary; and

(ii) The encoded data elements of the unique item identifier conform to the transfer structure, syntax, and coding of messages and data formats specified for Format Indicators 05, 06, and 12 in ISO/IEC International Standard 15434, Information Technology - Transfer Syntax for High Capacity Automatic Data Capture Media.

(5) *Unique item identifier.*

(i) The Contractor shall-

(A) Determine whether to-

(1) Serialize within the enterprise identifier;

(2) Serialize within the part, lot, or batch number; or

(3) Use a DoD recognized unique identification equivalent (e.g. Vehicle Identification Number); and

(B) Place the data elements of the unique item identifier (enterprise identifier; serial number; DoD recognized unique identification equivalent; and for serialization within the part, lot, or batch number only: original part, lot, or batch number) on items requiring marking by paragraph (c)(1) of this clause, based on the criteria provided in MIL-STD-130, Identification Marking of U.S. Military Property, latest version;

(C) Label shipments, storage containers and packages that contain uniquely identified items in accordance with the requirements of MIL-STD-129, Military Marking for Shipment and Storage, latest version; and

(D) Verify that the marks on items and labels on shipments, storage containers, and packages are machine readable and conform to the applicable standards. The contractor shall use an automatic identification technology device for this verification that has been programmed to the requirements of Appendix A, MIL-STD-130, latest version.

(ii) The issuing agency code-

(A) Shall not be placed on the item; and

(B) Shall be derived from the data qualifier for the enterprise identifier.

(d) For each item that requires item unique identification under paragraph (c)(1)(i), (ii), or (iv) of this clause or when item unique identification is provided under paragraph (c)(1)(v), in addition to the information provided as part of the Material Inspection and Receiving Report specified elsewhere in this contract, the Contractor shall report at the time of delivery, as part of the Material Inspection and Receiving Report, the following information:

- (1) Unique item identifier.
- (2) Unique item identifier type.
- (3) Issuing agency code (if concatenated unique item identifier is used).
- (4) Enterprise identifier (if concatenated unique item identifier is used).
- (5) Original part number (if there is serialization within the original part number).
- (6) Lot or batch number (if there is serialization within the lot or batch number).
- (7) Current part number (optional and only if not the same as the original part number).
- (8) Current part number effective date (optional and only if current part number is used).
- (9) Serial number (if concatenated unique item identifier is used).
- (10) Government's unit acquisition cost.
- (11) Unit of measure.
- (12) Type designation of the item as specified in the contract schedule, if any.
- (13) Whether the item is an item of Special Tooling or Special Test Equipment.
- (14) Whether the item is covered by a warranty.

(e) For embedded subassemblies, components, and parts that require DoD item unique identification under paragraph (c)(1)(iii) of this clause or when item unique identification is provided under paragraph (c)(1)(v), the Contractor shall report as part of the Material Inspection and Receiving Report specified elsewhere in this contract, the following information:

- (1) Unique item identifier of the parent item under paragraph (c)(1) of this clause that contains the embedded subassembly, component, or part.
- (2) Unique item identifier of the embedded subassembly, component, or part.
- (3) Unique item identifier type.**
- (4) Issuing agency code (if concatenated unique item identifier is used).**
- (5) Enterprise identifier (if concatenated unique item identifier is used).**
- (6) Original part number (if there is serialization within the original part number).**

- (7) Lot or batch number (if there is serialization within the lot or batch number).**
- (8) Current part number (optional and only if not the same as the original part number).**
- (9) Current part number effective date (optional and only if current part number is used).**
- (10) Serial number (if concatenated unique item identifier is used).**
- (11) Description.

** Once per item.

(f) The Contractor shall submit the information required by paragraphs (d) and (e) of this clause as follows:

(1) End items shall be reported using the receiving report capability in Wide Area WorkFlow (WAWF) in accordance with the clause at 252.232-7003. If WAWF is not required by this contract, and the contractor is not using WAWF, follow the procedures at <http://dodprocurementtoolbox.com/site/uidregistry/>.

(2) Embedded items shall be reported by one of the following methods-

(i) Use of the embedded items capability in WAWF;

(ii) Direct data submission to the IUID Registry following the procedures and formats at <http://dodprocurementtoolbox.com/site/uidregistry/>; or

(iii) Via WAWF as a deliverable attachment for exhibit line item number (fill in) ____, Unique Item Identifier Report for Embedded Items, Contract Data Requirements List, DD Form 1423.

(g) *Subcontracts*. If the Contractor acquires by subcontract, any item(s) for which item unique identification is required in accordance with paragraph (c)(1) of this clause, the Contractor shall include this clause, including this paragraph (g), in the applicable subcontract(s), including subcontracts for commercial products or commercial services.

(End of clause)

252.232-7006 Wide Area WorkFlow Payment Instructions.

(Jan 2023)

WIDE AREA WORKFLOW PAYMENT INSTRUCTIONS (JAN 2023)

(a) *Definitions*. As used in this clause-

"Department of Defense Activity Address Code (DoDAAC)" is a six position code that uniquely identifies a unit, activity, or organization.

"Document type" means the type of payment request or receiving report available for creation in Wide Area WorkFlow (WAWF).

"Local processing office (LPO)" is the office responsible for payment certification when payment certification is done external to the entitlement system.

"Payment request" and "receiving report" are defined in the clause at 252.232-7003, Electronic Submission of Payment Requests and Receiving Reports.

(b) *Electronic invoicing*. The WAWF system provides the method to electronically process vendor payment requests and receiving reports, as authorized by Defense Federal Acquisition Regulation Supplement (DFARS) 252.232-7003, Electronic Submission of Payment Requests and Receiving Reports.

(c) *WAWF access*. To access WAWF, the Contractor shall-

(1) Have a designated electronic business point of contact in the System for Award Management at <https://www.sam.gov>; and

(2) Be registered to use WAWF at <https://wawf.eb.mil/> following the step-by-step procedures for self-registration available at this web site.

(d) *WAWF training*. The Contractor should follow the training instructions of the WAWF Web-Based Training Course and use the Practice Training Site before submitting payment requests through WAWF. Both can be accessed by selecting the "Web Based Training" link on the WAWF home page at <https://wawf.eb.mil/>

(e) *WAWF methods of document submission*. Document submissions may be via web entry, Electronic Data Interchange, or File Transfer Protocol.

(f) *WAWF payment instructions*. The Contractor shall use the following information when submitting payment requests and receiving reports in WAWF for this contract or task or delivery order:

(1) *Document type.* The Contractor shall submit payment requests using the following document type(s):

- (i) For cost-type line items, including labor-hour or time-and-materials, submit a cost voucher.
- (ii) For fixed price line items-

(A) That require shipment of a deliverable, submit the invoice and receiving report specified by the Contracting Officer.

Stand-Alone Receiving Report - Certifications; COMBO - Receiving Report & Invoice - Material

(Contracting Officer: Insert applicable invoice and receiving report document type(s) for fixed price line items that require shipment of a deliverable.)

(B) For services that do not require shipment of a deliverable, submit either the Invoice 2in1, which meets the requirements for the invoice and receiving report, or the applicable invoice and receiving report, as specified by the Contracting Officer.

(Contracting Officer: Insert either "Invoice 2in1" or the applicable invoice and receiving report document type(s) for fixed price line items for services.)

(iii) For customary progress payments based on costs incurred, submit a progress payment request.

(iv) For performance based payments, submit a performance based payment request.

(v) For commercial financing, submit a commercial financing request.

(2)) Fast Pay requests are only permitted when Federal Acquisition Regulation (FAR) 52.213-1 is included in the contract.

[Note: The Contractor may use a WAWF "combo" document type to create some combinations of invoice and receiving report in one step.]

(3) *Document routing.* The Contractor shall use the information in the Routing Data Table below only to fill in applicable fields in WAWF when creating payment requests and receiving reports in the system.

Routing Data Table*

<i>Field Name in WAWF</i>	<i>Data to be entered in WAWF</i>
Pay Official DoDAAC	<u>To Be Determined (TBD)</u>
Issue By DoDAAC	<u>N00104</u>
Admin DoDAAC	<u>TBD</u>
Inspect By DoDAAC	<u>TBD</u>
Ship To Code	N33543 - Norfolk
Ship From Code	<u>TBD</u>

Mark For Code	<u>TBD</u>
Service Approver (DoDAAC)	<u>N/A</u>
Service Acceptor (DoDAAC)	<u>N/A</u>
Accept at Other DoDAAC	<u>N/A</u>
LPO DoDAAC	<u>N/A</u>
DCAA Auditor DoDAAC	<u>N/A</u>
Other DoDAAC(s)	<u>N/A</u>

(*Contracting Officer: Insert applicable DoDAAC information. If multiple ship to/acceptance locations apply, insert "See Schedule" or "Not applicable.")

(**Contracting Officer: If the contract provides for progress payments or performance-based payments, insert the DoDAAC for the contract administration office assigned the functions under FAR 42.302(a)(13).)

(4) *Payment request.* The Contractor shall ensure a payment request includes documentation appropriate to the type of payment request in accordance with the payment clause, contract financing clause, or Federal Acquisition Regulation 52.216-7, Allowable Cost and Payment, as applicable.

(5) *Receiving report.* The Contractor shall ensure a receiving report meets the requirements of DFARS Appendix F.

(g) *WAWF point of contact.*

(1) The Contractor may obtain clarification regarding invoicing in WAWF from the following contracting activity's WAWF point of contact.

(Contracting Officer: Insert applicable information or "Not applicable.")

(2) Contact the WAWF helpdesk at 866-618-5988, if assistance is needed.

(End of clause)

Addendum to 52.212-4, Contract Terms and Conditions - Commercial Products and Commercial Services

Contract Terms and Conditions Required To Implement Statutes or Executive Orders — Commercial Products and Commercial Services

Addendum to Contract Clauses

Contract Clauses

FAR Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
52.222-3	Convict Labor. (Deviation)	Feb 2026		
52.232-25	Prompt Payment.	Jan 2017		
52.211-15	Defense Priority and Allocation Requirements.	Apr 2008		
52.204-9	Personal Identity Verification of Contractor Personnel.	Jan 2011		
52.232-23	Assignment of Claims.	May 2014		
52.244-6	Subcontracts for Commercial Products and Commercial Services. (Deviation)	Feb 2026		
52.240-91	Security Prohibitions and Exclusions. (Deviation)	Feb 2026		
52.209-10	Prohibition on Contracting With Inverted Domestic Corporations. (Deviation)	Feb 2026		
52.202-1	Definitions.	Jun 2020		
52.240-93	Basic Safeguarding of Covered Contractor Information Systems. (Deviation)	Feb 2026		
52.204-91	Contractor Identification. (Deviation)	Feb 2026		
52.233-3	Protest after Award. (Deviation) (Alternate I)	Feb 2026	Alternate I	Feb 2026

DFARS Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
252.204-7003	Control of Government Personnel Work Product.	Apr 1992		
252.225-7012	Preference for Certain Domestic Commodities.	Apr 2022		
252.211-7008	Use of Government-Assigned Serial Numbers.	Sep 2010		
252.225-7001	Buy American and Balance of Payments Program.	Feb 2024		
252.225-7002	Qualifying Country Sources as Subcontractors.	Mar 2022		
252.225-7013	Duty-Free Entry.	Aug 2025		
252.225-7016	Restriction on Acquisition of Ball and Roller Bearings.	Jan 2023		
252.225-7021	Trade Agreements.	Feb 2024		
252.225-7036	Buy American-Free Trade Agreements--Balance of Payments Program.	Feb 2024		
252.225-7048	Export-Controlled Items.	Jun 2013		
252.246-7007	Contractor Counterfeit Electronic Part Detection and Avoidance System.	Jan 2023		
252.204-7012	Safeguarding Covered Defense Information and Cyber Incident Reporting. (DEVIATION 2024-O0013 REVISION 1)	May 2024	Deviation 2024-O0013	May 2024

FAR Clauses Incorporated by Full Text

52.222-35 Equal Opportunity for Veterans. (Alternate I) (Feb 2026) Alternate I (Jul 2014)

Alternate I (JUL 2014). As prescribed in 22.1310 (a)(2), add the following as a preamble to the clause:

Notice: The following term(s) of this clause are waived for this contract: _____[List term(s)].

52.222-36 Equal Opportunity for Workers with Disabilities. (Alternate I) (Feb 2026) Alternate I (Jul 2014)

Alternate I (JUL 2014). As prescribed in 22.1408 (b), add the following as a preamble to the clause:

Notice: The following term(s) of this clause are waived for this contract: _____[List term(s)].

52.217-6 Option for Increased Quantity. (Mar 1989)

Option for Increased Quantity (Mar 1989)

The Government may increase the quantity of supplies called for in the Schedule at the unit price specified. The Contracting Officer may exercise the option by written notice to the Contractor within 365 days [insert in the clause the period of time in which the Contracting Officer has to exercise the option]. Delivery of the added items shall continue at the same rate as the like items called for under the contract, unless the parties otherwise agree.

(End of clause)

DFARS Clauses Incorporated by Full Text

252.223-7001 Hazard Warning Labels.

(Dec 1991)

HAZARD WARNING LABELS (DEC 1991)

(a) "Hazardous material," as used in this clause, is defined in the Hazardous Material Identification and Material Safety Data clause of this contract.

(b) The Contractor shall label the item package (unit container) of any hazardous material to be delivered under this contract in accordance with the Hazard Communication Standard (29 CFR 1910.1200 et seq). The Standard requires that the hazard warning label conform to the requirements of the standard unless the material is otherwise subject to the labelling requirements of one of the following statutes:

- (1) Federal Insecticide, Fungicide and Rodenticide Act;
- (2) Federal Food, Drug and Cosmetics Act;
- (3) Consumer Product Safety Act;
- (4) Federal Hazardous Substances Act; or
- (5) Federal Alcohol Administration Act.

(c) The Offeror shall list which hazardous material listed in the Hazardous Material Identification and Material Safety Data clause of this contract will be labelled in accordance with one of the Acts in paragraphs (b)(1) through (5) of this clause instead of the Hazard Communication Standard. Any hazardous material not listed will be interpreted to mean that a label is required in accordance with the Hazard Communication Standard.

MATERIAL (If None, Insert "None.")	ACT

(d) The apparently successful Offeror agrees to submit, before award, a copy of the hazard warning label for all hazardous materials not listed in paragraph (c) of this clause. The Offeror shall submit the label with the Material Safety Data Sheet being furnished under the Hazardous Material Identification and Material Safety Data clause of this contract.

(e) The Contractor shall also comply with MIL-STD-129, Marking for Shipment and Storage (including revisions adopted during the term of this contract).

(End of clause)

252.208-7000 Intent to Furnish Precious Metals as Government-Furnished Material

(Dec 1991)

INTENT TO FURNISH PRECIOUS METALS AS GOVERNMENT-FURNISHED MATERIAL (DEC 1991)

(a) The Government intends to furnish precious metals required in the manufacture of items to be delivered under the contract if the Contracting Officer determines it to be in the Government's best interest. The use of Government-furnished silver is mandatory when the quantity required is one hundred troy ounces or more. The precious metal(s) will be furnished pursuant to the Government Furnished Property clause of the contract.

(b) The Offeror shall cite the type (silver, gold, platinum, palladium, iridium, rhodium, and ruthenium) and quantity in whole troy ounces of precious metals required in the performance of this contract (including precious metals required for any first article or production sample), and shall specify the national stock number (NSN) and nomenclature, if known, of the deliverable item requiring precious metals.

<u>Precious Metal*</u>	<u>Quantity</u>	<u>Deliverable Item</u> <u>(NSN and Nomenclature)</u>
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—

*If platinum or palladium, specify whether sponge or granules are required.

(c) Offerors shall submit two prices for each deliverable item which contains precious metals—one based on the Government furnishing precious metals, and one based on the Contractor furnishing precious metals. Award will be made on the basis which is in the best interest of the Government.

(d) The Contractor agrees to insert this clause, including this paragraph (d), in solicitations for subcontracts and purchase orders issued in performance of this contract, unless the Contractor knows that the item being purchased contains no precious metals.

(End of clause)

List of Contract Documents, Exhibits, or Attachments

Attachments:

Number	Attachment Name	Attachment Description	Reference Identifier	Date
01	1.04_MPJ_SOW TE_A023026	Statement of Work		13 Feb 2026

Solicitation Provisions

FAR Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
52.212-1	Instructions to Offerors-Commercial Products and Commercial Services. (Deviation)	Feb 2026		

DFARS Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
252.203-7005	Representation Relating to Compensation of Former DoD Officials.	Sep 2022		
252.204-7008	Compliance with Safeguarding Covered Defense Information Controls.	Oct 2016		
252.204-7019	Notice of NIST SP 800-171 DoD Assessment Requirements.	Nov 2023		
252.204-7024	Notice on the Use of the Supplier Performance Risk System.	Mar 2023		
252.225-7055	Representation Regarding Business Operations with the Maduro Regime.	May 2022		
252.225-7059	Prohibition on Certain Procurements from the Xinjiang Uyghur Autonomous Region-Representation.	Jun 2023		

DFARS Clauses Incorporated by Full Text

252.204-7017 Prohibition on the Acquisition of Covered Defense Telecommunications Equipment or Services-Representation. (May 2021)

PROHIBITION ON THE ACQUISITION OF COVERED DEFENSE TELECOMMUNICATIONS EQUIPMENT OR SERVICES-REPRESENTATION (MAY 2021)

The Offeror is not required to complete the representation in this provision if the Offeror has represented in the provision at 252.204-7016, Covered Defense Telecommunications Equipment or Services-Representation, that it "does not provide covered defense telecommunications equipment or services as a part of its offered products or services to the Government in the performance of any contract, subcontract, or other contractual instrument."

(a) *Definitions.* "Covered defense telecommunications equipment or services," "covered mission," "critical technology," and "substantial or essential component," as used in this provision, have the meanings given in the 252.204-7018 clause, Prohibition on the Acquisition of Covered Defense Telecommunications Equipment or Services, of this solicitation.

(b) *Prohibition.* Section 1656 of the National Defense Authorization Act for Fiscal Year 2018 (Pub. L. 115-91) prohibits agencies from procuring or obtaining, or extending or renewing a contract to procure or obtain, any equipment, system, or service to carry out covered missions that uses covered defense telecommunications equipment or services as a substantial or essential component of any system, or as critical technology as part of any system.

(c) *Procedures.* The Offeror shall review the list of excluded parties in the System for Award Management (SAM) at <https://www.sam.gov> for entities that are excluded when providing any equipment, system, or service to carry out covered missions that uses covered defense telecommunications equipment or services as a substantial or essential component of any system, or as critical technology as part of any system, unless a waiver is granted.

(d) *Representation.* If in its annual representations and certifications in SAM the Offeror has represented in paragraph (c) of the provision at 252.204-7016, Covered Defense Telecommunications Equipment or Services-Representation, that it "does" provide covered defense telecommunications equipment or services as a part of its offered products or services to the Government in the performance of any contract, subcontract, or other contractual instrument, then the Offeror shall complete the following additional representation:

The Offeror represents that it ☐ will ☐ will not provide covered defense telecommunications equipment or services as a part of its offered products or services to DoD in the performance of any award resulting from this solicitation.

(e) *Disclosures.* If the Offeror has represented in paragraph (d) of this provision that it "will provide covered defense telecommunications equipment or services," the Offeror shall provide the following information as part of the offer:

(1) A description of all covered defense telecommunications equipment and services offered (include brand or manufacturer; product, such as model number, original equipment manufacturer (OEM) number, manufacturer part number, or wholesaler number; and item description, as applicable).

(2) An explanation of the proposed use of covered defense telecommunications equipment and services and any factors relevant to determining if such use would be permissible under the prohibition referenced in paragraph (b) of this provision.

(3) For services, the entity providing the covered defense telecommunications services (include entity name, unique entity identifier, and Commercial and Government Entity (CAGE) code, if known).

(4) For equipment, the entity that produced or provided the covered defense telecommunications equipment (include entity name, unique entity identifier, CAGE code, and whether the entity was the OEM or a distributor, if known).

(End of provision)

252.204-7016 Covered Defense Telecommunications Equipment or Services-Representation.

(Dec 2019)

COVERED DEFENSE TELECOMMUNICATIONS EQUIPMENT OR SERVICES-REPRESENTATION (DEC 2019)

(a) *Definitions.* As used in this provision, "covered defense telecommunications equipment or services" has the meaning provided in the clause 252.204-7018, Prohibition on the Acquisition of Covered Defense Telecommunications Equipment or Services.

(b) *Procedures.* The Offeror shall review the list of excluded parties in the System for Award Management (SAM) (<https://www.sam.gov>) for entities excluded from receiving federal awards for "covered defense telecommunications equipment or services".

(c) *Representation.* The Offeror represents that it ☐ does, ☐ does not provide covered defense telecommunications equipment or services as a part of its offered products or services to the Government in the performance of any contract, subcontract, or other contractual instrument.

(End of provision)

Addendum to 52.212-1, Instructions to Offerors - Commercial Products and Commercial Services

Evaluation - Commercial Products and Commercial Services

FAR Clauses Incorporated by Full Text

52.212-2 Evaluation-Commercial Products and Commercial Services. (Deviation)

(Feb 2026)

EVALUATION-COMMERCIAL PRODUCTS AND COMMERCIAL SERVICES (FEB 2026) (DEVIATION)

(a) Evaluation factors. The Government will award a contract resulting from this solicitation to the responsible Offeror whose offer conforming to the solicitation will be most advantageous to the Government, price and other factors considered. The following factors will be used to evaluate offers:

[Insert evaluation factors in the relative order of importance. For requests for proposals, state: Evaluation factors other than price when combined are [significantly more important than price/approximately equal to price/significantly less important] than price. For invitations for bids, list only price and price-related factors.]

—

—

—

—

(b) *Options (if applicable)*. The Government will evaluate offers for award purposes by adding the total price for all options to the total price for the basic requirement. The Government may determine that an offer is unacceptable if the option prices are significantly unbalanced. The evaluation of options does not obligate the Government to exercise the option(s).

(c) *Notice of award*. A written notice of award or acceptance of an offer furnished to the successful Offeror within the time for acceptance specified in the offer, shall result in a binding contract without further action by either party. Before the offer's specified expiration time, the Government may accept an offer (or part of an offer), whether or not there are negotiations after its receipt, unless a written notice of withdrawal is received before award.

(End of provision)

Addendum to Evaluation - Commercial Product and Commercial Services

Offeror Representations and Certifications - Commercial Products and Commercial Services

Addendum to Solicitation Provisions

FAR Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
52.222-50	Combating Trafficking in Persons.	Oct 2025		
52.203-18	Prohibition on Contracting with Entities that Require Certain Internal Confidentiality Agreements or Statements-Representation.	Jan 2017		
52.204-7	System for Award Management-Registration. (Deviation)	Feb 2026		
52.223-23	Sustainable Products. (Deviation)	Feb 2026		
52.240-90	Security Prohibitions and Exclusions Representations and Certifications. (Deviation)	Feb 2026		
52.217-5	Evaluation of Options. (Deviation)	Feb 2026		
52.217-4	Evaluation of Options Exercised at Time of Contract Award. (Deviation)	Feb 2026		
52.204-7	System for Award Management-Registration. (Deviation) (Alternate I)	Feb 2026	Alternate I	Feb 2026

DFARS Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
252.215-7013	Supplies and Services Provided by Nontraditional Defense Contractors.	Jan 2023		

FAR Clauses Incorporated by Full Text

52.222-50 Combating Trafficking in Persons. (Deviation) (Alternate I) (Feb 2026) Alternate I (Feb 2026)

Alternate I (FEB 2026) (DEVIATION). As prescribed in 22.1703-2(a)(2), substitute the following paragraph in place of paragraph (c)(1)(i) of the basic clause:

(c)(1)(i)(A) The United States Government's policy prohibiting trafficking in persons described in paragraph (b) of this clause; and

(B) The following directive(s) or notice(s) applicable to employees performing work at the contract place(s) of performance as indicated below:

Document Title	Document may be obtained from:	Applies to performance in/at:
—	—	—
—	—	—

[Contracting Officer must insert title of directive/notice; indicate the document is attached or provide source (such as website link) for obtaining document; and, indicate the contract performance location outside the United States to which the document applies.]

52.211-14 Notice of Priority Rating for National Defense, Emergency Preparedness, and Energy Program Use. (Apr 2008)

Notice of Priority Rating for National Defense, Emergency Preparedness, and Energy Program Use (Apr 2008)

Any contract awarded as a result of this solicitation will be [] DX rated order; < X >DO rated order certified for national defense, emergency preparedness, and energy program use under the Defense Priorities and Allocations System (DPAS) (15 CFR700), and the Contractor will be required to follow all of the requirements of this regulation. [Contracting Officer check appropriate box.]

(End of provision)

52.225-18 Place of Manufacture.

(Aug 2018)

PLACE OF MANUFACTURE (AUG 2018)

(a) *Definitions.* As used in this provision-

Manufactured end product means any end product in product and service codes (PSCs) 1000-9999, except-

- (1) FPSC 5510, Lumber and Related Basic Wood Materials;
- (2) Product or Service Group (PSG) 87, Agricultural Supplies;
- (3) PSG 88, Live Animals;
- (4) PSG 89, Subsistence;
- (5) PSC 9410, Crude Grades of Plant Materials;
- (6) PSC 9430, Miscellaneous Crude Animal Products, Inedible;
- (7) PSC 9440, Miscellaneous Crude Agricultural and Forestry Products;
- (8) PSC 9610, Ores;
- (9) PSC 9620, Minerals, Natural and Synthetic; and
- (10) PSC 9630, Additive Metal Materials.

Place of manufacture means the place where an end product is assembled out of components, or otherwise made or processed from raw materials into the finished product that is to be provided to the Government. If a product is disassembled and reassembled, the place of reassembly is not the place of manufacture.

(b) For statistical purposes only, the offeror shall indicate whether the place of manufacture of the end products it expects to provide in response to this solicitation is predominantly-

- (1) ☐ In the United States (Check this box if the total anticipated price of offered end products manufactured in the United States exceeds the total anticipated price of offered end products manufactured outside the United States); or
- (2) ☐ Outside the United States.

(End of provision)

52.209-11 Representation by Corporations Regarding Delinquent Tax Liability or a Felony Conviction under any Federal Law. (Deviation)

(Feb 2026)

REPRESENTATION BY CORPORATIONS REGARDING DELINQUENT TAX LIABILITY OR A FELONY CONVICTION UNDER ANY
FEDERAL LAW (FEB 2026) (DEVIATION)

(a) The Government will not enter into a contract with any corporation that-

(1) Has any unpaid Federal tax liability that has been assessed, for which all judicial and administrative remedies have been exhausted or have lapsed, and that is not being paid in a timely manner pursuant to an agreement with the authority responsible for collecting the tax liability, where the awarding agency is aware of the unpaid tax liability, unless an agency has considered suspension or debarment of the corporation and made a determination that suspension or debarment is not necessary to protect the interests of the Government; or

(2) Was convicted of a felony criminal violation under any Federal law within the preceding 24 months, where the awarding agency is aware of the conviction, unless an agency has considered suspension or debarment of the corporation and made a determination that this action is not necessary to protect the interests of the Government.

(b) The Offeror represents that-

(1) It is ☐ is not ☐ a corporation that has any unpaid Federal tax liability that has been assessed, for which all judicial and administrative remedies have been exhausted or have lapsed, and that is not being paid in a timely manner pursuant to an agreement with the authority responsible for collecting the tax liability; and

(2) It is ☐ is not ☐ a corporation that was convicted of a felony criminal violation under a Federal law within the preceding 24 months.

(End of provision)

52.222-18 Certification Regarding Knowledge of Child Labor for Listed End Products. (Feb 2021)

CERTIFICATION REGARDING KNOWLEDGE OF CHILD LABOR FOR LISTED END PRODUCTS (FEB 2021)

(a) *Definition.*

Forced or indentured child labor means all work or service-

(1) Exacted from any person under the age of 18 under the menace of any penalty for its nonperformance and for which the worker does not offer himself voluntarily; or

(2) Performed by any person under the age of 18 pursuant to a contract the enforcement of which can be accomplished by process or penalties.

(b) *Listed end products.* The following end product(s) being acquired under this solicitation is (are) included in the List of Products Requiring Contractor Certification as to Forced or Indentured Child Labor, identified by their country of origin. There is a reasonable basis to believe that listed end products from the listed countries of origin may have been mined, produced, or manufactured by forced or indentured child labor.

Listed End Product	Listed Countries of Origin
_____	_____
_____	_____

(c) *Certification.* The Government will not make award to an offeror unless the offeror, by checking the appropriate block, certifies to either paragraph (c)(1) or paragraph (c)(2) of this provision.

(1) ☐ The offeror will not supply any end product listed in paragraph (b) of this provision that was mined, produced, or manufactured in a corresponding country as listed for that end product.

(2) ☐ The offeror may supply an end product listed in paragraph (b) of this provision that was mined, produced, or manufactured in the corresponding country as listed for that product. The offeror certifies that it has made a good faith effort to determine whether forced or indentured child labor was used to mine, produce, or manufacture such end product. On the basis of those efforts, the offeror certifies that it is not aware of any such use of child labor.

(End of provision)

52.204-90 Offeror Identification. (Deviation) (Feb 2026)

OFFEROR IDENTIFICATION (FEB 2026) (DEVIATION)

If the Offeror will not have an active Federal Government contracts registration in the System for Award Management (<https://www.sam.gov>) when submitting its offer, it shall complete paragraphs (c) and (d) of this provision and include its responses with its offer.

(a) *Definitions.* As used in this provision-

Commercial and Government Entity (CAGE) code has the meaning provided in the clause at FAR 52.204-91, Contractor Identification, of this solicitation.

Common parent means that corporate entity that owns or controls an affiliated group of corporations that files its Federal income tax returns on a consolidated basis, and of which the offeror is a member.

Electronic Funds Transfer (EFT) indicator means a bank account identifier to establish additional System for Award Management records for identifying alternative EFT accounts (see part 32) for the same entity.

Highest-level owner means the entity that owns or controls an immediate owner of the offeror, or that owns or controls one or more entities that control an immediate owner of the offeror. No entity owns or exercises control of the highest-level owner.

Immediate owner means an entity, other than the offeror, that has direct control of the offeror. Indicators of control include, but are not limited to, one or more of the following: ownership or interlocking management, identity of interests among family members, shared facilities and equipment, and the common use of employees. There may be more than one immediate owner (e.g., joint ventures).

Predecessor means an entity whose assets were acquired by the offeror or another entity (most often through merger or acquisition) and whose affairs are now carried out by the offeror or the other entity under a new name.

Taxpayer Identification Number means the number required by the Internal Revenue Service (IRS) to be used by the offeror to report income tax and other returns. It may be either a Social Security Number or an Employer Identification Number.

Unique entity identifier (UEI) has the meaning provided in the clause at FAR 52.204-91, Contractor Identification, of this solicitation.

(b) *Unique entity identifier (UEI)*.

(1) The Offeror shall enter, in the block with its name and address on the cover page of its offer, the annotation "Unique Entity Identifier" followed by the UEI that identifies the Offeror's name and address exactly as stated in the offer. The Offeror shall also enter its EFT indicator, if applicable.

(2) If the Offeror does not have a UEI, it shall go to <https://www.sam.gov> to obtain one. The Government will independently validate the existence and uniqueness of the Offeror before assigning a UEI.

(c) *Taxpayer identification*. The Offeror shall provide with its offer the following information that is necessary to comply with debt collection requirements of 31 U.S.C. 7701(c) and 3325(d); reporting requirements of 26 U.S.C. 6041, 6041A, and 6050M; and the implementing IRS regulations:

(1) Taxpayer identification number (TIN)

☐ TIN: ____;

☐ TIN has been applied for; or

☐ TIN is not required because:

☐ Offeror is a nonresident alien, foreign corporation, or foreign partnership that does not have income effectively connected with the conduct of a trade or business in the United States and does not have an office or place of business or a fiscal paying agent in the United States;

☐ Offeror is an agency or instrumentality of a foreign government; or

☐ Offeror is an agency or instrumentality of the Federal Government.

(2) *Type of organization*.

☐ Sole proprietorship;

☐ Partnership;

☐ Corporate entity (not tax-exempt);

☐ Corporate entity (tax-exempt);

☐ Government entity (Federal, State, or local);

☐ Foreign government;

☐ International organization per 26 CFR 1.6049-4; or

☐ Other.

(3) *Common parent.*

☐ Offeror is not owned or controlled by a common parent as defined in paragraph (a) of this provision; or

☐ Name and TIN of common parent:

Name: _____

TIN: _____

(4) The TIN provided in paragraph (c)(1) of this provision may be matched with IRS records to verify the accuracy of the Offeror's TIN. The Government may use the TIN to collect and report on any delinquent amounts arising out of the Offeror's relationship with the Government (31 U.S.C. 7701(c)(3)).

(d) Commercial and Government Entity (CAGE) code.

(1) The Offeror shall provide its CAGE code with its offer with its name and location address or otherwise include it prominently in its offer. The CAGE code shall be for that name and location address. Insert the word "CAGE" before the code. The Offeror may obtain a CAGE code as indicated in the following table.

If the Offeror is...	Then...
Located in the United States or its outlying areas	Submit a request to the DLA CAGE Branch via https://cage.dla.mil
Located outside the United States and its outlying areas and its country is a member of the North Atlantic Treaty Organization (NATO) or a sponsored nation	Contact the appropriate National Codification Bureau (https://www.nato.int/structur/ac/135/about/contacts)
Located outside the United States and its outlying areas and its country is not a member of NATO or a sponsored nation	Contact the NATO Support and Procurement Agency (NSPA) (https://eportal.nspa.nato.int/AC135Public/scage/CageList.aspx)

(2) The Offeror shall provide the CAGE code and legal business name (Do not use a "doing business as" name) for-

(i) Its immediate owner(s), if any;

(ii) Its highest-level owner, if any; and

(iii) Any predecessor(s), or predecessor of an Offeror's predecessor, that held a Federal contract or grant within the last three years.

Owner Type	CAGE Code	Legal Business Name
Immediate owner	_____	_____

Highest-level owner	_____	_____
Predecessor*	_____	_____

* Predecessor CAGE code may be marked "Unknown."

(3) If the Offeror has more than one immediate owner (such as a joint venture), give the information for each owner (or joint venture participant). If the Offeror has more than one predecessor, provide information for each predecessor in reverse chronological order.

(End of provision)

DFARS Clauses Incorporated by Full Text

252.209-7002 Disclosure of Ownership or Control by a Foreign Government.

(Dec 2022)

DISCLOSURE OF OWNERSHIP OR CONTROL BY A FOREIGN GOVERNMENT

(DEC 2022)

(a) *Definitions.* As used in this provision-

(1) "Effectively owned or controlled" means that a foreign government or any entity controlled by a foreign government has the power, either directly or indirectly, whether exercised or exercisable, to control the election, appointment, or tenure of the Offeror's officers or a majority of the Offeror's board of directors by any means, e.g., ownership, contract, or operation of law (or equivalent power for unincorporated organizations).

(2) "Entity controlled by a foreign government"-

(i) Means-

- (A) Any domestic or foreign organization or corporation that is effectively owned or controlled by a foreign government; or
- (B) Any individual acting on behalf of a foreign government.

(ii) Does not include an organization or corporation that is owned, but is not controlled, either directly or indirectly, by a foreign government if the ownership of that organization or corporation by that foreign government was effective before October 23, 1992.

(3) "Foreign government" includes the state and the government of any country (other than the United States and its outlying areas) as well as any political subdivision, agency, or instrumentality thereof.

(4) "Proscribed information" means-

- (i) Top Secret information;
- (ii) Communications security (COMSEC) material, excluding controlled cryptographic items when unkeyed or utilized with unclassified keys;
- (iii) Restricted Data as defined in the U.S. Atomic Energy Act of 1954, as amended;
- (iv) Special Access Program (SAP) information; or
- (v) Sensitive Compartmented Information (SCI).

(b) *Prohibition on award.* No contract under a national security program may be awarded to an entity controlled by a foreign government if that entity requires access to proscribed information to perform the contract, unless the Secretary of Defense or a designee has waived application of 10 U.S.C. 4874.

(c) *Disclosure.* The Offeror shall disclose any interest a foreign government has in the Offeror when that interest constitutes control by a foreign government as defined in this provision. If the Offeror is a subsidiary, it shall also disclose any reportable interest a foreign government has in any entity that owns or controls the subsidiary, including reportable interest concerning the Offeror's immediate parent, intermediate parents, and the ultimate parent. Use separate paper as needed, and provide the information in the following format:

--

Offeror's Point of Contact for Questions about Disclosure (Name and Phone Number with Country Code, City Code and Area Code, as applicable)	

Name and Address of Offeror	

Name and Address of Entity Controlled by a Foreign Government	Description of Interest, Ownership Percentage, and Identification of Foreign Government
_____	_____
(End of provision)	

252.225-7000 Buy American--Balance of Payments Program Certificate.

(Feb 2024)

BUY AMERICAN-BALANCE OF PAYMENTS PROGRAM CERTIFICATE-BASIC (FEB 2024)

(a) *Definitions.* "Commercially available off-the-shelf (COTS) item," "component," "critical component," "critical item," "domestic end product," "foreign end product," "qualifying country," "qualifying country end product," and "United States," as used in this provision, have the meanings given in the 252.225-7001, Buy American and Balance of Payments Program-Basic clause of this solicitation.

(b) *Evaluation.* The Government-

(1) Will evaluate offers in accordance with the policies and procedures of Part 225 of the Defense Federal Acquisition Regulation Supplement; and

(2) Will evaluate offers of qualifying country end products without regard to the restrictions of the Buy American statute or the Balance of Payments Program.

(c) *Certifications and identification of country of origin.*

(1) For all line items subject to the Buy American and Balance of Payments Program-Basic clause of this solicitation, the Offeror certifies that-

(i) Each end product, except those listed in paragraphs (c)(2) or (3) of this provision, is a domestic end product and that each domestic end product listed in paragraph (c)(4) of this provision contains a critical component or a critical item; and

(ii) For end products other than COTS items, components of unknown origin are considered to have been mined, produced, or manufactured outside the United States or a qualifying country. For those end products that do not consist wholly or predominantly of iron or steel or a combination of both, the Offeror shall also indicate whether these foreign end products exceed 55 percent domestic content, except for those that are COTS items. If the percentage of the domestic content is unknown, select "no".

(2) The Offeror certifies that the following end products are qualifying country end products:

Line Item Number	Country of Origin
_____	_____
_____	_____
_____	_____

(3) The following end products are other foreign end products, including end products manufactured in the United States that do not qualify as domestic end products. For those foreign end products that do not consist wholly or predominantly of iron or steel or a combination of both, the Offeror shall also indicate whether these foreign end products exceed 55 percent domestic content, except for those that are COTS items. If the percentage of the domestic content is unknown, select "no".

_____	_____	_____
-------	-------	-------

Line Item Number	Country of Origin (If known)	Exceeds 55% Domestic Content (yes/no)
_____	_____	_____
_____	_____	_____
_____	_____	_____

(4) The Offeror shall separately list the line item numbers of domestic end products that contain a critical component or a critical item (see Federal Acquisition Regulation 25.105).

Domestic end products containing a critical component or a critical item:

Line Item Number _____

[List as necessary]

(End of provision)

252.225-7020 Trade Agreements Certificate.

(Nov 2014)

TRADE AGREEMENTS CERTIFICATE-BASIC (NOV 2014)

(a) *Definitions.* "Designated country end product," "nondesignated country end product," "qualifying country end product," and "U.S.-made end product" as used in this provision have the meanings given in the Trade Agreements-Basic clause of this solicitation.

(b) *Evaluation.* The Government-

(1) Will evaluate offers in accordance with the policies and procedures of Part 225 of the Defense Federal Acquisition Regulation Supplement; and

(2) Will consider only offers of end products that are U.S.-made, qualifying country, or designated country end products unless-

(i) There are no offers of such end products;

(ii) The offers of such end products are insufficient to fulfill the Government's requirements; or

(iii) A national interest waiver has been granted.

(c) *Certification and identification of country of origin.*

(1) For all line items subject to the Trade Agreements-Basic clause of this solicitation, the offeror certifies that each end product to be delivered under this contract, except those listed in paragraph (c)(2) of this provision, is a U.S.-made, qualifying country, or designated country end product.

(2) The following supplies are other nondesignated country end products:

(Line Item Number)		(Country of Origin)
_____		_____
_____		_____
_____		_____

(End of provision)

252.225-7035 Buy American--Free Trade Agreements--Balance of Payments Program Certificate.

(Feb 2024)

BUY AMERICAN-FREE TRADE AGREEMENTS-BALANCE OF PAYMENTS PROGRAM CERTIFICATE-BASIC (FEB 2024)

(a) *Definitions.* "Bahraini end product," "commercially available off-the-shelf (COTS) item," "component," "critical component," "critical item," "domestic end product," "Free Trade Agreement country," "Free Trade Agreement country end product," "foreign end product," "Moroccan end product," "Panamanian end product," "Peruvian end product," "qualifying country end product," and "United States," as used in this provision, have the meanings given in the 252.225-7036, Buy American-Free Trade Agreements-Balance of Payments Program-Basic clause of this solicitation.

(b) *Evaluation.* The Government-

(1) Will evaluate offers in accordance with the policies and procedures of part 225 of the Defense Federal Acquisition Regulation Supplement; and

(2) For line items subject to the Buy American-Free Trade Agreements-Balance of Payments Program-Basic clause of this solicitation, will evaluate offers of qualifying country end products or Free Trade Agreement country end products other than Bahraini end products, Moroccan end products, Panamanian end products, or Peruvian end products without regard to the restrictions of the Buy American or the Balance of Payments Program.

(c) *Certifications and identification of country of origin.*

(1) For all line items subject to the Buy American-Free Trade Agreements-Balance of Payments Program-Basic clause of this solicitation, the Offeror certifies that-

(i) Each end product, except the end products listed in paragraph (c)(2) of this provision, is a domestic end product;

(ii) Each domestic end product listed in paragraph (c)(3) of this provision contains a critical component or a critical item; and

(iii) Components of unknown origin are considered to have been mined, produced, or manufactured outside the United States or a qualifying country.

(2) The Offeror shall identify all end products that are not domestic end products.

(i) The Offeror certifies that the following supplies are qualifying country (except Australian) end products:

____ (Line Item Number) ____ (Country of Origin)

(ii) The Offeror certifies that the following supplies are Free Trade Agreement country end products other than Bahraini end products, Moroccan end products, Panamanian end products, or Peruvian end products:

____ (Line Item Number) ____ (Country of Origin)

(iii) The following supplies are other foreign end products, including end products manufactured in the United States that do not qualify as domestic end products. For those foreign end products that do not consist wholly or predominantly of iron or steel or a combination of both, the Offeror shall also indicate whether these foreign end products exceed 55 percent domestic content, except those that are COTS items. If the percentage of the domestic content is unknown, select "no".

Line Item Number	Country of Origin (If known)	Exceeds 55% Domestic Content (yes/no)

(3) The Offeror shall list the line item numbers of domestic end products that contain a critical component or a critical item (see section 25.105 of the Federal Acquisition Regulation).

Line Item Number: /List as necessary

(End of provision)

252.204-7998 **Alternate A, Annual Representations and Certifications. (DEVIATION 2026-O0043)** (Feb 2026) **Alternate A Deviation 2026-O0043** (Feb 2026)

Alternate A, Annual Representations and Certifications (DEVIATION 2026-O0043)(FEB 2026)

Include the following paragraphs (e), (f), and (g) in the provision at FAR 52.204-7:

(e)(1) If the provision at FAR 52.204-7, System for Award Management - Registration, is included in this solicitation, paragraph (g) of this provision applies.

(2) If the provision at FAR 52.204-7, System for Award Management - Registration, is not included in this solicitation, and the Offeror has an active registration in the System for Award Management (SAM), the Offeror may choose to use paragraph (g) of this provision instead of completing the corresponding individual representations and certifications in the solicitation. The Offeror shall indicate which option applies by checking one of the following boxes:

☐ (i) Paragraph (g) applies.

☐ (ii) Paragraph (g) does not apply and the Offeror has completed the individual representations and certifications in the solicitation.

(f)(1) The following representations or certifications in the SAM database are applicable to this solicitation as indicated:

(i) 252.204-7016, Covered Defense Telecommunications Equipment or Services--Representation. Applies to all solicitations.

(ii) 252.216-7008, Economic Price Adjustment--Wage Rates or Material Prices Controlled by a Foreign Government. Applies to solicitations for fixed-price supply and service contracts when the contract is to be performed wholly or in part in a foreign country, and a foreign government controls wage rates or material prices and may during contract performance impose a mandatory change in wages or prices of materials.

(iii) 252.225-7042, Authorization to Perform. Applies to all solicitations when performance will be wholly or in part in a foreign country.

(iv) 252.225-7049, Prohibition on Acquisition of Certain Foreign Commercial Satellite Services--Representations. Applies to solicitations for the acquisition of commercial satellite services.

(v) 252.225-7050, Disclosure of Ownership or Control by the Government of a Country that is a State Sponsor of Terrorism. Applies to all solicitations expected to result in contracts of \$150,000 or more.

(vi) 252.229-7012, Tax Exemptions (Italy)--Representation. Applies to solicitations when contract performance will be in Italy.

(vii) 252.229-7013, Tax Exemptions (Spain)--Representation. Applies to solicitations when contract performance will be in Spain.

(2) The following representations or certifications in SAM are applicable to this solicitation as indicated by the Contracting Officer: [
Contracting Officer check as appropriate.]

☐ (i) 252.209-7002, Disclosure of Ownership or Control by a Foreign Government.

☐ (ii) 252.225-7000, Buy American--Balance of Payments Program Certificate.

☐ (iii) 252.225-7020, Trade Agreements Certificate.

☐ Use with Alternate I.

☐ (iv) 252.225-7031, Secondary Arab Boycott of Israel.

☐ (v) 252.225-7035, Buy American--Free Trade Agreements--Balance of Payments Program Certificate.

☐ Use with Alternate I.

☐ Use with Alternate II.

☐ Use with Alternate III.

☐ Use with Alternate IV.

☐ Use with Alternate V.

☐ (vi) 252.226-7002, Representation for Demonstration Project for Contractors Employing Persons with Disabilities.

☐ (vii) 252.232-7015, Performance-Based Payments--Representation.

(g) The Offeror has completed the annual representations and certifications electronically via the SAM website at <https://www.sam.gov> After reviewing the SAM database information, the Offeror verifies by submission of the offer that the representations and certifications currently posted electronically that apply to this solicitation as indicated in FAR 52.204-7 and paragraph (f) of this provision have been entered or updated within the last 12 months, are current, accurate, complete, and applicable to this solicitation (including the business size standard applicable to the NAICS code

referenced for this solicitation), as of the date of this offer, and are incorporated in this offer by reference (see FAR 4.203-1); except for the changes identified below [*Offeror to insert changes, identifying change by provision number, title, date*]. These amended representation(s) and/or certification(s) are also incorporated in this offer and are current, accurate, and complete as of the date of this offer.

FAR/DFARS provision No.	Title	Date	Change
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

Any changes provided by the Offeror are applicable to this solicitation only, and do not result in an update to the representations and certifications located in the SAM database.

(End of provision)

Additional Regulation or Supplemental Clauses Incorporated by Full Text

WSSTERMEZ03 HIGHER-LEVEL CONTRACT QUALITY REQUIREMENT

(Dec 2014)

(a)

NOTE: When the "OTHER" block is selected, please identify the industry, military, or international Quality Management System that you intend to use. Your proposed system will be reviewed and assessed for suitability and equivalency.

(b) Measuring and Test Equipment

NOTE: When the "OTHER" block is selected, please identify the industry, military, or international Calibration Standard that you intend to use. Your proposed standard will be reviewed and assessed for suitability and equivalency.

(c) The contractor shall use and be compliant with the revision of the applicable Quality Management System and Calibration Standard in effect at time of the offeror's latest proposal submission.

Enclosure (1)

WSSTERMHZ17 MANDATORY USE OF WORKFLOW PRO (WFP) MOD ASSIST MODULE

(Mar 2026)

The use of Workflow Pro (WFP) Mod Assist is required under this purchase order/contract.

Mod Assist is the mandatory means of submitting an official request for modification of this contract. Unless otherwise authorized, in writing, by a warranted Contracting Officer, no other means for submitting a request for modification to a

contract, or a request for any action that would require a modification to the contract to execute will be accepted by the Government.

Submission of a request for modification of terms and conditions to this contract is not a guarantee that the terms or conditions will be modified.

The Mod Assist module should not be used by contractors to request signatures of End Use Certificates, Non-transfer Certificates.

Should the Contractor experience concerns with the use of Mod Assist, the Contractor must contact . The Government will not be responsible for any contract delay or disruption or any increased costs of performance of the Contractor due to the required use or any failure by the Contractor to use the Mod Assist module.

PROCEDURES FOR CONTRACTORS TO REQUEST ACCESS TO WORKFLOW PRO (WFP) MOD ASSIST

Click on the link [https://public.navsup.navy.mil/public/ops\\$workflow_pro_public.LOGIN](https://public.navsup.navy.mil/public/ops$workflow_pro_public.LOGIN) to open the NAVSUP WSS Workflow Pro (WFP) Mod Assist Vendor page.

To request an account, navigate to the bottom of the page and click "Request Account".

Fill in the information to create the user profile, you must select a Point of Contact from the drop-down menu.

Select "Privacy Act Agreement"; after reading the statement, click "Agree".

When all data has been entered on the form, click the blue "Submit" button.

Notification will be sent when the account is established.

WSSTERMEZ07 INSPECTION/ACCEPTANCE POINT

(Nov 2002)

1. Inspection of Supplies:

Name/Address/Location where supplies are to be inspected: Contractor's facility

2. Inspection of Packaging (if different from Inspection of Supplies):

Name/Address/Location where Packaging will be Performed and Inspected (if different from Name/Address/Location where supplies are to be inspected):

3. Final Acceptance: Contractor's facility

Name/Address/Location where final acceptance is to take place:

WSSTERMFZ06 GENERAL INFORMATION-FOB-DESTINATION

(Jun 2002)

TRANSPORTATION: Quotations are requested with transportation costs prepaid to destination. Unless otherwise specified, award will be made on an FOB Destination basis.

INSPECTION/ACCEPTANCE shall occur at: Contractor's Facility

If different than address on page one please cite location:

NOTE: If Inspection & Acceptance is at Destination charges must be included in offered price.

DELIVERY: 365 Days

(Offeror Insert)

INFORMATION TO BE FURNISHED BY OFFEROR:

Company is:

() large

- ☐ small
- ☐ woman owned enterprise
- ☐ Mfr
- ☐ minority business enterprise
- ☐ 8(a) enterprise
- ☐ Dealer

To assist the Contracting Officer in analyzing each proposed price in order to determine the fairness and reasonableness of that proposed price, it is requested you provide with your quotation the appropriate information listed:

A. Catalog Price

1. Is the item a standard commercial product sold in substantial quantities to the General Public? If yes, request furnish a copy of the price sheet with your quotation.

YES ☐ NO ☐

2. Is the item, while not the exact catalog item, sufficiently similar so as to be compared with the catalog item? If yes, request provide a copy of catalog price and briefly explain the difference.

YES ☐ NO ☐

B. Contractor's Pricing System

(In development of the current price, were the following generally accepted estimating procedures utilized:)

1. Were cost estimates reviewed and approved by responsible company official(s)?

YES ☐ NO ☐

2. Were specific procedures used in estimating direct/indirect costs?

YES ☐ NO ☐

3. Were the source data used in development of cost elements current, accurate and complete?

YES ☐ NO ☐

4. Were recently audited and approved rates and/or forward pricing rates negotiated and approved by the Administrative Contracting Officer utilized?

YES ☐ NO ☐

Naval Supply Systems Command Weapons System Support
(NAVSUP WSS)
Material Handling Program Office, N964

Procurement Documents

Statement of Work No.: NAVSUP WSS SOW-MPJ
Test and Evaluation Requirements No.: NAVSUP WSS TE-MPJ

MPJ

Manual Pallet Jack (MPJ), Shipboard

6,000 lb. Rated Capacity
42" and 48" Fork Lengths

Table of Contents

STATEMENT OF WORK	1
1.0 SCOPE	2
1.1 Acceptance Criteria.....	2
1.2 Background.....	2
2.0 APPLICABLE DOCUMENTS	2
MIL-DTL-15011	3
2.1 Definitions.....	3
2.1.1 Vehicle Orientation.....	3
2.1.2 Ambient Operating Temperature.	3
3.0 REQUIREMENTS	3
3.1 Classification.....	3
3.2 Salient Characteristics.....	3
Table SOW-1	4
3.3 First Article Testing (FAT).	4
3.4 Safety.....	4
3.4.1 Static Dissipative Devices.	4
3.4.2 Wheels and Tires.....	4
3.5 Rolling force.....	5
3.6 Ergonomics of Controls.....	5
3.6.1 Raising and Lowering Controls.	5
3.6.2 Brake Lever.....	5
3.6.3 Steering Force.	5
3.7 Hydraulic System.	5
3.7.1 Hydraulic Drift.....	5
3.8 Maintainability & Serviceability.....	5
3.8.1 Hydraulic Reservoir.	6
3.8.2 Lubricants and Hydraulic Fluids.....	6
3.9 Braking Mechanism.....	6
3.10 Braking Performance.....	6
3.10.1 Brake Hardware.....	6

3.10.2	Pre-Test Conditioning.....	6
3.11	Forks.....	6
3.12	Raising and Lowering Mechanism.....	7
3.12.1	Rear wheels.....	7
3.13	Pallet Compatibility.....	7
3.14	Wheel and Tires.....	7
3.14.1	Deck Loading.....	7
3.14.2	Tire Material.....	7
3.14.3	Load Wheels.....	7
3.14.4	Steer Wheels and Tires.....	7
3.15	Steering.....	8
3.15.1	Steer Handle/Tiller Bar.....	8
3.16	Structural Strength.....	8
3.17	Lifting and Tiedown Points.....	8
3.18	Gradeability and Slope Ascension.....	8
3.19	Resistance to Saline Atmosphere (Salt Fog).....	8
3.20	Stepped Surface Test.....	8
3.21	Drop Test.....	9
3.22	High Impact (HI) Shock Testing.....	9
3.22.1	Tiedown Assemblies for HI-Shock.....	9
3.22.2	Tiedown Deck Fitting Pattern.....	9
3.23	Reliability.....	9
3.24	Paint and Coatings.....	10
3.24.1	Primer and Topcoat Paint Systems.....	10
3.24.2	Powder Coat System.....	10
3.24.3	Pre-treatments and Additional Topcoats.....	10
3.24.4	Coverage and Color.....	10
3.24.5	Cadmium Plating.....	10
3.25	Information Plates.....	10
3.25.1	Identification Plate.....	11
3.25.2	Shipping Data Plate.....	11
3.25.3	Instruction, Warning and Caution Plates.....	11
3.25.4	Wheel Loading Plate.....	11

3.25.5	Lubrication Plate.	11
3.26	Vehicle Marking.	11
3.26.1	U.S. Navy (USN) Registration (Serial) Number.	11
3.26.2	Safe Working Load.	12
3.26.3	Lifting and Tiedown.	12
3.26.4	Naval Type Designation.	12
3.26.5	Shipboard use.	12
3.27	Special tools and equipment.	12
4.0	REGULATORY REQUIREMENTS	12
4.1	Recovered materials.	12
4.2	Hazardous Materials.	12
5.0	DOCUMENTATION	12
5.1	Technical Manuals.	12
5.1.1	Technical Manual Verification Review.	13
5.2	Provisioning.	13
5.2.1	Critical Spares and Allowance Parts Lists.	13
5.2.2	Engineering Data for Provisioning (EDFP).	14
5.2.3	Non-NSN Items.	14
5.2.4	Commercial and Government Entity (CAGE) Code.	15
5.3	MIP/MRC.	15
5.3.1	Recommended MIP/MRC developers.	15
6.0	PROGRAM MANAGEMENT	16
6.1	Contractor Responsibility.	16
6.2	Conference Meetings.	16
6.2.1	Post-award Guidance Conference.	16
6.2.2	Test Readiness Review.	17
7.0	QUALITY ASSURANCE PROVISIONS	17
7.1	Contractor Certification.	17
7.1.1	Equipment conformance.	17
7.1.2	Quality Assurance Program Plan.	17
7.1.3	Warranty.	18
7.1.4	Interchangeability.	18
8.0	PREPARATION FOR DELIVERY	18

8.1	Packaging & Shipment.....	18
8.1.1	Packaging.	18
8.1.2	Freight on Board.	18
8.1.3	Transportation.....	18
8.1.4	Spray-on Protective Coatings.....	18
TEST & EVALUATION REQUIREMENTS		20
1.0	First Article Testing (FAT).	20
1.1	Units Under Test (UUT).....	20
1.2	Test Facilities, Equipment and Personnel.	20
2.0	Production quality conformance testing.....	20
3.0	Test terms and conditions.....	20
3.1	Environmental conditions.	20
3.2	Surface conditions.	20
3.3	Authorized maintenance.....	20
3.4	Test Priority Recommendations.	21
3.4.1	Required Dimensions.	21
3.4.2	Rated load and Pallet Entry and withdrawal Tests.....	21
3.4.3	Lift and Tiedown Testing.	21
3.4.4	Paint Inspection.....	21
3.4.5	Reliability Demonstration Test.....	21
3.5	Test Loads.....	21
3.6	Tests, Inspections and Demonstrations.	21
4.0	First Article Testing (FAT)	21
4.1	General Requirements.	21
4.1.1	FAT Scheduling.....	21
4.1.2	FAT Test Plan.	22
4.1.3	FAT Report Summary.	22
4.2	Pre-test Inspections.	23
4.2.1	Wheel Inspection.....	23
4.2.2	Inspection of MPJ and Component Dimensions.....	24
4.2.3	Tiedown and lifting point inspection.....	24
4.2.4	Lubricants and Fluids.....	24
4.2.5	Serviceability.....	24

4.2.6	Markings and Information Plates.....	24
4.2.7	Ergonomics of Controls.	24
4.3	Reliability.....	25
4.3.1	Failures and Discrepancies During Reliability Test.....	25
4.4	Steering Test and Inspection.	25
4.4.1	Minimum Outside Turning Radius.....	25
4.4.2	Handle Durability.....	26
4.5	Brakes.....	26
4.5.1	Brake Pre-Test.....	26
4.5.2	FAT Brake Test Procedure.	26
4.6	Rolling Force.....	26
	Table TE-1	27
4.7	Raising and Lowering Mechanism.....	28
4.8	Hydraulic Reservoir Capacity Inspection.....	28
4.9	Hydraulic Drift.....	28
4.10	Pallet Compatibility.....	28
4.11	Slope Ascension.....	29
4.12	Stepped Surface Test.	29
4.13	Resistance to Saline Atmosphere.....	29
4.13.1	Details.....	29
4.13.2	Additional Guidelines:	29
4.14	Drop Test.	30
4.15	Heavyweight High-Impact (HI) Shock Test.....	30
4.15.1	Instrumentation.	30
4.15.2	HI-Shock Test Plan.	30
4.15.3	HI-Shock Final Test Report.	31
4.16	Lifting and Tiedown Points.....	31
4.17	Deck Loading.	31
4.18	Characteristics Inspection.	31
4.19	Maintainability and Serviceability Inspection.	31
4.20	Lubricants and Fluids Inspection.....	32
4.20.1	Brand/Type.....	32
4.21	Paint & Coatings Inspection.	32

4.21.1	Paint Inspection of UUT.....	32
4.22	Information Plates and Vehicle Markings Inspection.....	32
4.23	Structural Test.....	32
5.0	Production Quality Conformance Testing.	33
5.1	General Information	33
5.1.1	Production Readiness.	33
5.2	Production Quality Conformance (QC) Inspection and Testing.	33
5.2.1	Production Quality Conformance.	33
5.2.2	Incremental Production Inspections and Testing.	34
5.2.3	Inspection.	34
5.2.4	Testing.....	34
5.2.5	Documentation.	34
5.3	Brake Testing.....	34
5.3.1	Operational Weight Test.	34
5.3.2	Brake Test.	35
5.4	Paint Inspection of Production MPJs.	35
5.5	Inspection of Identification Plates and Markings on Production MPJs.	35
	Figure TE-1.....	36
	Table TE-2	38
	Table TE-3	39
	TEST METHOD NO. 1 – RELIABILITY DEMONSTRATION TEST	40
1.0	Test Course:.....	40
1.1	Pre-test MPJ Inspection:.....	40
2.0	Test Procedure:	40
	Figure TM-1.1. Hourly Time Record Sheet	41

STATEMENT OF WORK

Manual Pallet Jack (MPJ)

**6,000 LB RATED CAPACITY
42" AND 48" FORK LENGTHS**

1.0 **SCOPE**

This Statement of Work (SOW) covers the requirements for 6,000 lb. capacity, manually operated, hand lift, pallet trucks for use on Navy ships. The manual pallet jacks, herein referred to as MPJs, shall comply with Navy requirements for handling weapons and ammunition aboard ship. Shipboard use includes operations in a marine/salt air environment, as well as maneuvering in tight confines of shipboard magazines, storerooms and cargo holds.

1.1 **Acceptance Criteria.**

Truck must meet all the requirements within this SOW and pass all tests, inspections and demonstrations called out in NAVSUP WSS TE-MPJ.

1.2 **Background.**

The 6,000 lb. MPJ trucks will replace similar manual pallet jacks currently in use on the following Navy ship classes:

- CVN - Aircraft Carrier
- LSD - Landing Ship Dock
- LHD - Landing Helicopter Dock Amphibious Assault Ship
- ESB - Expeditionary Sea Base
- DDG - Guided Missile Destroyer
- LCS - Littoral Combat Ship

2.0 **APPLICABLE DOCUMENTS**

The following documents of the issue in effect on the date of the request for proposal, unless otherwise specified, form a part of this SOW to the extent specified herein. When documents conflict, this SOW shall govern.

NAVSUP WSS TE-MPJ	Testing Requirements for Shipboard, Manual, Pallet, Truck
NAVSEA SW023-AH-WHM-010	Handling Ammunition and Explosives with Industrial Material Handling Equipment
MIL-STD-130	Department of Defense Standard Practice: Identification Marking of U.S. Military Property
MIL-STD-209	Interface Standard for Lifting and Tiedown Provisions
MIL-HDBK 267	Guide for Selection of Lubricants and Hydraulic Fluids for use in Shipboard Equipment
NAS 411-1	Hazardous Materials Target List
NAVSUP Publication 538	Management of Materials Handling Equipment (MHE) and Shipboard Mobile Support Equipment (SMSE)
SAE AMS-STD-595	Colors Used in Government Procurement
MIL-STD-810	Environmental Engineering Considerations and Laboratory Tests
MIL-DTL-901	Shock Tests, HI (High Impact) Shipboard Machinery, Equipment, and Systems, Requirements For
MIL-STD-3034	Department of Defense Standard Practice: Reliability-Centered Maintenance (RCM) Process
DOD 4100.39-M VOL 1	Federal Logistics Information System (FLIS) Procedures Manual

DOD 5010.12	Acquisition Management Systems and Data Requirements Control List (AMSDL)
ISO 9001	Quality Management
NAVICP PD-21861	Purchase Description, Manual, Technical, Material Handling Equipment
MIL-P-24534	Planned Maintenance System: Development of Maintenance Requirement Cards, Maintenance Index Pages and Associated Documentation
MIL-DTL-15011	Pallets, Material Handling, Wood Post Construction, 4-Way Entry
MIL-DTL-23312	Pallets, Material Handling, Metal (For Ordnance Items) Mk 3 Mod 0, Mk 12, Mod 0 and Mod 1
MIL-STD-31000	Technical Data Package (TDP)

2.1 **Definitions.**

The following definitions apply to the requirements in this SOW.

2.1.1 **Vehicle Orientation.**

Within this statement of work and related documents, the forward end of the pallet truck shall be defined as the end that contains the steering control.

2.1.2 **Ambient Operating Temperature.**

The pallet truck shall be capable of operation within ambient temperatures ranging from 0 to 120 degrees Fahrenheit.

3.0 **REQUIREMENTS**

All MPJs shall meet the requirements as noted below.

3.1 **Classification.**

MPJs configurations described by this SOW are:

- Model 42: 6,000 pound capacity, NAVSUP Type HS, with solid, non-sparking wheels and 42 in. fork length
- Model 48: 6,000 pound capacity, NAVSUP Type HS, with solid, non-sparking wheels and 48 in. fork length

3.2 **Salient Characteristics.**

The truck must meet the salient characteristics listed in [Table SOW-1](#), as well as the additional requirements stated within this SOW.

Table SOW-1 Salient Characteristics

CHARACTERISTIC	Model 42	Model 48
Capacity to Full Lift Height	6,000 Lb.	6,000 Lb.
Fork Length	42 In.	48 In.
Maximum Overall Length (Handle raised)	60 In.	72 In.
Maximum Lowered Height (Top of Forks)	3.25 In.	
Minimum Raised Height (Top of Forks)	7.25 In.	
Maximum Width Across Forks (Outside Edges)	27 In.	
Minimum Distance Between Forks	8.75 In.	
Minimum Under Clearance w/ Forks Lowered (except at load wheel mounting)	Not less than 1 In.	
Maximum Truck Weight (Unloaded)	500 Lb.	
Handle Height (Maximum)	50 In.	
Grade/Slope Transition (Forward and Reverse Directions)	6 Percent (3.4 DEG)	

3.3 **First Article Testing (FAT).**

To validate the proposed truck meets the Navy's requirements, in this SOW, testing of pre-production truck(s) is required. The specific FAT requirements and methods are detailed in document: NAVSUP WSS TE-MPJ (refer to page [20](#)). A truck used for FAT shall be production ready (fabricated and configured to the same standards as the planned production trucks). Similarly, the configuration of the truck that successfully completes FAT represents the Navy approved configuration. During FAT, no changes influencing the configuration of the FAT units (or production units) shall be incorporated without NAVSUP approval.

3.4 **Safety.**

The truck shall conform to the applicable requirements of NAVSUP Publication 538 and NAVSEA SW023-AH-WHM-010.

3.4.1 **Static Dissipative Devices.**

Grounding straps are not required.

3.4.2 **Wheels and Tires.**

Non-sparking tires are required per SOW paragraph [3.14.2](#).

3.5 **Rolling force.**

The maximum force required to move the truck on a smooth, level surface at a constant speed of 2 mph shall not be greater than 195 lbs.

3.6 **Ergonomics of Controls.**

MPJ controls shall be designed to enhance safe and effective vehicle operation by Navy personnel suitably clothed for weather conditions within the ambient temperature range cited in paragraph 2.1.2.

3.6.1 **Raising and Lowering Controls.**

The lifting mechanism shall be controlled and operated by either the handle of the truck, a lever separate and independent of the handle, or by a foot pedal. Lowering shall be accomplished by means of a pressure-release device that is independent of the lifting mechanism. The mechanism shall be located in a position so that the operator is not endangered when lowering the load, with the steer handle positioned 60 degrees up from horizontal and through a steering arc of 45 degrees on either side of longitudinal axes through the centerline of the truck. The number of strokes of the steering handle required to lift a rated load to 4.0 inches above the fully lowered position shall be not more than 17. All hand-release devices shall withstand a force of 100 pounds (45 kg). All foot pedal devices shall withstand a force of 250 pounds (113 kg) without damage or malfunction.

3.6.2 **Brake Lever.**

Handles or levers shall allow the use of a mittened glove, gloved and ungloved hands. Maximum handle reach shall not exceed 3.5 inches. The maximum sustained (holding position with brake off) holding distance shall be 1.5 to 2.0 inches. Handle and lever radius shall be 1 inch or greater. The handle force required to release the brakes shall not exceed 25 pounds. The sustained (holding) force shall not exceed 6 pounds. When brakes are fully disengaged, no additional force will be transferred to the brake mechanism during load transport.

3.6.3 **Steering Force.**

The truck with a rated load and the handle in the towing position shall not require a force in excess of 35 pounds to turn the steering assembly.

3.7 **Hydraulic System.**

3.7.1 **Hydraulic Drift.**

When holding a rated load at maximum lift height for a period of one-hour, downward drift shall not exceed 0.13 inches.

3.8 **Maintainability & Serviceability.**

Periodic lubrication points and grease fittings shall be easily accessible for servicing.

3.8.1 Hydraulic Reservoir.

The hydraulic reservoir shall be provided with an accessible filler plug for filling and checking the fluid level, and shall have sufficient capacity to fill the hydraulic system plus 30 percent reserve fluid.

3.8.2 Lubricants and Hydraulic Fluids.

The contractor shall review maintenance requirements and determine when lubricants and hydraulic fluids specified in MIL-HDBK-267 are acceptable alternatives. When applicable, operation and maintenance manuals shall incorporate the fluids military designation as cited in MIL-HDBK-267 rather than the equivalent commercial part number, name or trademark. Refer to paragraph 5.1 for additional technical manual requirements.

3.9 Braking Mechanism.

The trucks shall have an adjustable braking system for the steer wheels designed on the deadman principle so that the brake must be manually held off by the truck operator to move the truck with loaded or empty forks. The brake shall be automatically applied when the brake handle is released. The deadman braking system shall provide positive braking action as required below.

3.10 Braking Performance.

With the truck carrying the rated load and traveling at a speed of 2 miles per hour (mph), the truck brakes shall be capable of stopping the truck in a distance of 12 inches. On a 6-degree slope, with the wheels at any attitude, with the truck carrying the rated load on a pallet and with the forks raised to maximum height, the brakes shall be able to be applied, shall be able to hold and shall be able to be released. The brakes shall also be capable of holding the truck on a thoroughly wetted surface on a 15-degree slope. The truck shall be positioned on this slope with the forks facing uphill, while carrying the rated load on forks raised to maximum lift height.

3.10.1 Brake Hardware.

Brake actuating components and hardware shall be corrosion resistant and fully protected from damage from carried materials or incidental contact during use. Brake components extending beyond the wheel diameter shall be protected by guards. Brake mechanisms shall have provisions for component adjustment to compensate for wear. Brake mechanisms shall have provisions for lubrication without disassembly of parts or assemblies.

3.10.2 Pre-Test Conditioning.

Prior to initiating the FAT brake test, the brakes shall be engaged and disengaged for 1000 cycles.

3.11 Forks.

Forks shall be sized and spaced in accordance with [Table SOW-1](#). At all elevations, forks shall be horizontal within a tolerance of + 0.06 inches and -0.13 inches at the ends. Additionally, forks shall be end tapered on the underside and sides to facilitate entry and withdrawal from standard military pallets conforming to and MIL-P-23312 and also the standard 48 inches by 40 inches, four-way entry, post construction, wooden pallets conforming to MIL-DTL-15011.

3.12 Raising and Lowering Mechanism.

When interfacing with a standard 48 in. by 40 in., four-way entry, post construction wooden pallet conforming to MIL-DTL-15011, the raising and lowering mechanism shall be capable of the following:

3.12.1 Rear wheels.

With the truck fully inserted into a standard 48 in. by 40 in., four-way entry, post construction wooden pallet perpendicular to the bottom boards of the pallet, the raising and lowering mechanism shall permit the rear wheels to be lowered and raised in the bottom boards opening with a minimum clearance of 0.25 inches (6 mm).

3.13 Pallet Compatibility.

The forks of the pallet truck shall completely enter and withdraw from an empty, double-faced pallet conforming to MIL-DTL-23312 without moving the pallet more than 6 inches in the forward or backward direction. There shall be no contact from fully lowered position to maximum lift height between parts of the pallet and the lifting mechanism under the forks including the load wheels of the pallet truck. During the test, there shall be no physical contact between the top surface of the load wheels and the under surface of the pallet deck, and the surfaces of the load wheels shall not come in contact with the forks.

3.14 Wheel and Tires.

Wheels and tires shall meet the following requirements:

3.14.1 Deck Loading.

Wheels shall be sized that a truck shall not exert a force on the operating surface in excess of 500 psi per wheel.

3.14.1.1 Configuration.

Truck shall be carrying a rated load for all deck loading calculations and testing.

3.14.2 Tire Material

Tire material used on all wheels shall be a non-sparking, solid polyurethane.

3.14.3 Load Wheels.

Truck shall be provided with dual load wheels in each fork. Load wheels may be tandem mounted. Each wheel shall be 3 inches (76 mm) in diameter minimum by 3.75 inches (95 mm) in width minimum. Assembled to the underside of the forks, the load wheels shall be unobstructed when functioning both with and without a load

3.14.4 Steer Wheels and Tires.

Each wheel of dual steer wheels shall be not less than 8 inches (203 mm) in diameter and not less than 2.50 inches (64 mm) wide. The tires shall conform to sizes and loadings listed within the most current Tire and Rim Association (T&RA) Handbook for pressed-on or molded-on solid industrial tires

3.15 Steering.

The trucks shall be steered through the dual steer wheels by a steering handle. The steering handle shall turn the steering assembly a minimum of 80 degrees to the left and 80 degrees to the right of dead center position.

3.15.1 Steer Handle/Tiller Bar.

The steering handle shall have a maximum vertical height (from the ground to top of the handle) of not more than 50 inches. With the steer handle in the parked/upright position, the handle shall be of sufficient strength to withstand a force of 300 pounds applied horizontally in the direction towards the forks.

3.16 Structural Strength

The truck frame, forks, and related structures shall be capable of withstanding 200 percent of rated load (12,000 lbs.), with forks elevated to maximum lift height for one hour, with no evidence of permanent deformation greater than 0.063 in or downward drift not exceeding 0.13 in.

3.17 Lifting and Tiedown Points.

Permanently affixed lifting and tiedown points shall be provided that enables the truck in its stowed configuration to be lifted or restrained. Lifting and tiedown points shall conform to MIL-STD-209, for Type I equipment, excluding helicopter sling lift (HSL) and air transport requirements. Tiedown point shall be sized to allow for use of tiedown chain hooks as specified for the tiedown assembly in paragraph 3.22.1. Tiedown points shall also withstand HI-Shock, Grade A, testing as specified in paragraph 3.22.

3.18 Gradeability and Slope Ascension.

Truck shall be capable of transitioning from a smooth horizontal surface and ascending or descending a grade of 6 percent (3.4 DEG), as specified in Table SOW-1. The truck shall be aligned perpendicularly to the ramp and configured with forks fully lowered without a load. No part of the truck (other than the tires) shall contact the ground or ramp during approach, departure or cresting of the ramp.

3.19 Resistance to Saline Atmosphere (Salt Fog).

The truck shall be designed and fabricated to minimize and eliminate the corrosive effect of marine/salt air operations aboard Navy ships at sea. The truck shall be prepared and tested in accordance with MIL-STD-810, Method 509.8, Salt Fog.

3.20 Stepped Surface Test.

While carrying a rated load and traveling at a normal walking pace, the pallet truck shall traverse a 1-inch vertical drop between two horizontal operating surfaces. The path of the truck shall be perpendicular to the step. Travel speed shall be maintained while traversing the elevation change. Width of the step shall be greater than the width of the pallet truck so that both sets of load wheels traverse the drop at the same time. This test shall be repeated ten (10) consecutive times. Underclearance shall be sufficient that no part of the truck shall strike either surface

during this test and the truck shall suffer no permanent deformation, component failure, leaks or change in lifted height of the load.

3.21 Drop Test.

The MPJ, without a load, shall withstand a 3-foot drop onto its wheels to a concrete surface without failure of components, permanent deformation, or effect to its operational readiness.

3.22 High Impact (HI) Shock Testing.

The truck shall withstand heavyweight HI shock in accordance with MIL-DTL-901. The truck shall meet the requirements of Grade A, Class I, Type A, Deck mounted, base mounting plane and vertical axis restricted orientation. Truck shall be tested in its normal stowed configuration with forks lowered, parking brake "on" and steer bar/tiller in the vertical position.

3.22.1 Tiedown Assemblies for HI-Shock.

The tiedown assemblies used during HI-shock testing shall be Peck & Hale (CAGE 94658), Part Number 15MTC-1529 or equivalent as identified under NSN 2040-01-323-0772. The 14,400 lb. minimum breaking strength (MBS) of the designated tiedown assembly shall be used in determining the number of tiedowns required for shock testing. Test facility shall determine the number of tiedowns required for testing. If these tiedowns are not available at the testing facility, the contractor is obligated to purchase these tiedowns and assure they are available for the scheduled test.

3.22.2 Tiedown Deck Fitting Pattern.

The tiedown deck fittings on the test platform shall be positioned to allow the MPJ tiedown chains to be installed from the MPJ tiedown points at an angle as close to 45 degrees as possible (45 degrees is optimum). Manufacturer shall determine tiedown pattern and the number of tiedown assemblies recommended to safely restrain the unit during HI-Shock testing. The "minimum breaking strength" of the tiedown assembly (14,400 lb. MBS) shall be used in determining the number of required tiedown assemblies. Tiedown chain assemblies shall be crisscrossed such that a front left tiedown is secured to the deck near the rear left side of the MHE, and a rear left tiedown is secured to the deck near the front left side of the MHE. This configuration is the same for the right side tiedown assemblies. At a minimum, two tiedown assemblies shall be installed at each MPJ tiedown point to provide sufficient holding force in all directions.

3.23 Reliability.

The MPJ, carrying a rated load, at a speed of 1.5 to 2.0 mph, shall complete 6 hours of testing around a circular endurance course as specified in test and evaluation procedure TE-MPJ, para 4.3. Upon completion, the MPJ shall have incurred no failures and shall be fully operational.

NOTE

Plastic body filler compounds shall not be used to cosmetically improve the exterior surface of the MPJ before applying paint or corrosion preventative coating.

3.24 Paint and Coatings.

All surfaces that are not corrosion resistant shall undergo surface treatment, pre-treatment and top coating to provide adequate corrosion protection for use within a marine/salt air environment. Bare and untreated surfaces containing minor smoothness imperfections are acceptable as long as such imperfections do not compromise the integrity and durability of the corrosion protective coating system applied over that area. In their proposal, the contractor shall describe in detail their coating materials and process from surface prep of bare metals to acceptance inspection of the finish-coated components.

3.24.1 Primer and Topcoat Paint Systems.

Corrosion protective paint coatings shall consist of a minimum two-step process, primer and topcoat system, and shall utilize lead and chromate free products that are specifically formulated for continuous exposure in a marine, salt air environment. It is recommended that the primer coat be a corrosion inhibiting catalyzed epoxy. Similarly, top or finish coat shall be compatible with the base/primer coating and is recommended to be an impact and abrasion resistant, high-performance, gloss urethane-based paint. Both primer and topcoat shall be applied uniformly to a total thickness of not less than six (6) mils.

3.24.2 Powder Coat System.

Powder coating is an acceptable alternative to conventional spray painting. Powder coat shall consist of a primer and topcoat to obtain the necessary durability. Film build of each layer shall be two (2) to three (3) mils.

3.24.3 Pre-treatments and Additional Topcoats.

The contractor may use additional pretreatments or topcoats to maximize corrosion resistance. Detailed information identifying the type, name, manufacture and characteristic/benefits of the additional coatings shall be included in the contractor's proposal. Total paint thickness requirement shall be adjusted to account for each additional layer.

3.24.4 Coverage and Color.

The finish color shall be 13538 in accordance with SAE AMS-STD-595. Tires, hydraulic cylinder rods, rollers, plastics, etc. shall not be painted. Paint must also be kept off working surfaces where the coating may interfere with working parts or would affect the function/performance of the MPJ. Surface prep and paint application shall follow industry standards for the specific type of coating.

3.24.5 Cadmium Plating.

The use of cadmium plating is prohibited.

3.25 Information Plates.

The MPJ shall be equipped with the following information plates conforming to MIL-STD-130. Plates shall be furnished and installed by the contractor.

3.25.1 Identification Plate.

The MPJ shall be equipped with an identification plate that shall be in accordance with ANSI/ITSDF B56.1. In addition to the following MPJ nomenclature such as, "TRUCK, PALLET, MANUAL, SHIPBOARD ", contract number, lifting capacity, lift height, USN registration number, shipping weight, cube dimension, technical manual stock number, warranty expiration date and manufacturer's name and address.

3.25.2 Shipping Data Plate.

The MPJ shall be equipped with a shipping data plate that shows the silhouette of the MPJ in its transport position indicating the center of gravity, the location and capacity of the lifting and tiedown points along with the recommended lifting sling and related rigging hardware.

3.25.3 Instruction, Warning and Caution Plates.

The MPJ shall be equipped with instruction plates including warnings, cautions and diagrams describing special or important procedures to be followed in assembling, operating or servicing the MPJ. If available, decals used on the contractor's similar, commercially available MPJs may be substituted for these instruction plates.

3.25.4 Wheel Loading Plate.

The MPJ shall be equipped with a wheel loading plate to show wheel loading on each wheel (steering and load wheels) with and without rated load. Deck loading values shall be values determined during FAT, in accordance with paragraph 4.17 of NAVSUP WSS TE-MPJ.

3.25.5 Lubrication Plate.

The MPJ shall be equipped with a lubricant/fluid placard installed in a visible location that indicates all recommended lubricants and their specific application points. The lubricants shall be listed by both their commercial designation and their military equivalent, if applicable.

3.26 Vehicle Marking.

The MPJ shall have the following marking in black block letters. Markings shall be either painted/stenciled or adhesive backed vinyl labels unless otherwise stated:

3.26.1 U.S. Navy (USN) Registration (Serial) Number.

In each delivery order, NAVSUP WSS will provide a series of USN numbers to be used, one number per MPJ.

3.26.1.1 Exterior USN Marking.

The assigned USN registration number shall be marked in block numbers on each side of the truck (Example: 1610-12345). Height of characters shall be between 1.0 to 3.0 inches and sized based on space available for USN to be printed in a single line.

3.26.1.2 Metal Stamped Body Marking.

The MPJ shall have the USN number indelibly stamped into a fixed, non-removable plate in a location that can be easily viewed on the fully assembled MPJ and provides protection from damage during routine use. Removal of existing cover panels is

acceptable for gaining access to the stamped USN number. The USN shall 0.25 in high block characters.

3.26.2 Safe Working Load.

The MPJ shall be marked with the letters "SWL" followed by the MPJ's rated lifting capacity on each side of the MPJ in 2.0 inch-high characters. (Example: SWL 6000)

3.26.3 Lifting and Tiedown.

Lifting points shall be marked with the terms "LIFT" or "LIFT HERE" dependent on space available. Tiedown points shall be marked with the term "TIEDOWN". Both markings shall be in 0.75 inch-high letters.

3.26.4 Naval Type Designation.

The MPJ shall be marked with naval type designation "HS" in 1.5 inch-high letters on each side.

3.26.5 Shipboard use.

The MPJ shall be marked with the words "SHIPBOARD USE APPROVED" in not less than 0.75 inch-high letters on each side of the MPJ.

3.27 Special tools and equipment.

The pallet MPJ shall require no special tools or equipment for the Navy to diagnose deficiencies and perform routine maintenance and repairs.

4.0 REGULATORY REQUIREMENTS

4.1 Recovered materials.

The contractor is encouraged to use recovered materials to the maximum extent practicable in accordance with subpart 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the MPJ.

4.2 Hazardous Materials.

In fabricating, manufacturing, testing, operating, maintaining all forms of pollution shall be prevented or reduced whenever feasible. A Hazardous Material (HM) is a material that due to its chemical, physical, or biological nature causes safety, public health, or environmental concerns. Aerospace Industries Association National Aerospace Standard (AIA-NAS) 411-1 Hazardous Materials Target List shall be used as guidance in identifying Prohibited, Targeted and Tracked Chemicals.

5.0 DOCUMENTATION

5.1 Technical Manuals.

The technical manual shall be created based on Purchase Description NAVSUP WSS PD-21861, Technical Manual, Material Handling Equipment.

5.1.1 Technical Manual Verification Review.

Technical manual verification review (See CDRL A001 titled: Technical Manual Verification Review) will be conducted by the government (MHE ISEA) to validate that the MPJ's preliminary technical manual representing a near 100% complete document accurately reflects the MPJ configuration, general information, operating instructions, safety rating, preventative maintenance, repair and overhaul, illustrated parts breakdown and parts list index. Although reviews of preliminary copies of the tech manual may be conducted as often as necessary, the final government manual verification review shall be scheduled after successful completion of first article testing. A MPJ representing as close to production configuration as possible shall be available for this review which shall last for a period of no more than fourteen consecutive calendar days. This government review will be conducted at the manufacturer's facility. The MPJ will be operated only to the extent required to ensure that each section of the manual is accurate. No repair or overhaul operations will be conducted, but this documentation will be reviewed for clarity. The illustrated parts breakdown and parts list index will be reviewed to the extent possible without major disassembly of the MPJ. The contractor shall compile a written summary of all discrepancies identified during this review that shall be included in the technical manual verification review minute to be provided within 14 days after the end of the review meeting.

5.2 Provisioning.

NOTE

The description provided in paragraph [5.2.1](#) is to assist the contractor in estimating the scope of documentation required under Engineering Data for Provisioning in para [5.2.2](#).

5.2.1 Critical Spares and Allowance Parts Lists.

An allowance parts list (APL) is the Navy's primary document identifying what parts have been provisioned and are available within the National Stock System. The APL is based off a list of parts identified by the Navy as critical spares or those forecasted as necessary to resolve anticipated maintenance and common repairs to the MPJ. The critical parts list does not include common sized hardware (nuts, bolts, screws, washer, etc.) but will include routine wear items (brake pads, wheels, tires, seals, etc.) as well as sub-assemblies and components with a historical demand that can impact the readiness and availability of the MPJ. All components on the APL will require engineering data documentation per para [5.2.2](#). The critical parts list and APL will be developed by the Navy's MHE ISEA and Navy logistic specialists based on the parts breakdown information in the final/approved technical manual (see para [5.1.1](#)). The critical parts list that will identify what EDFP is required will be provided to the contractor within 60 days following acceptance of the completed technical manual. The contractor may review the critical parts list and provide to the MHE ISEA recommendations on additional critical parts.

5.2.2 Engineering Data for Provisioning (EDFP).

Approved EDFP is required for all systems or equipment that are acquired for Navy use and for which Provisioning Technical Documentation (PTD) is being acquired (See CDRL A002 titled: Engineering Data for Provisioning). This includes components replaced during scheduled maintenance, common wear items, and parts identified by the Navy as critical spares. EDFP is the technical data that provides definitive identification of dimensional, material, mechanical, electrical, or other characteristics adequate for provisioning of the support items of the end article(s) on contract. EDFP consists of but is not limited to data such as specifications, standards, drawings, photographs, sketches and descriptions, and the necessary assembly and general arrangement drawings, schematics, drawings, schematic diagrams, wiring and cable diagrams, etc., or what is sometimes referred to as form, fit and function. This data is necessary for the assignment of Source, Maintenance, and Recoverability (SMR) codes, for assignment of Item Management Codes, prevention of proliferation of identical items in the Government inventory, maintenance decisions, and item identification necessary in the assignment of a National Stock Number (NSN). EDFP format and content must be prepared in accordance with the latest industry standards and must be reproducible, as outlined below. Approved EDFP shall contain all appropriate annotations, i.e., proper Distribution Statements, Military Critical Technology markings, etc. Each item listed on the EDFP will identify the actual OEM in accordance with DOD 4100.39-M, Volume 1, paragraph 1.1.7 (f) (3).

5.2.3 Non-NSN Items.

For items without an NSN, recognized industry standard or government specification or standard, the following order of precedence is required for EDFP provided by the contractor:

- a) Technical Data equivalent to approved Product Engineering Drawings as defined in MIL-STD-31000
- b) Commercial drawings
- c) Commercial manuals, catalogs or catalog descriptions
- d) Sketches or photographs with a brief description of dimensional, material, mechanical, electrical or other characteristics.

5.2.3.1 Drawings.

Drawings required to support provisioning shall be assembly drawings with complete bill of material identifying all parts. If subassemblies are listed on a drawing and not broken down, then drawings for the subassemblies are required as part of the drawing package. All assemblies and subassemblies shall have drawings that fully identify all parts that are encompassed within a component, sub-system, and system.

5.2.3.1.1 Supplemental Provisioning Technical Documentation (SPTD).

If the actual OEM is not identified in the bill of material, SPTD in the form of catalog sheets, correspondence from the OEM (OEM letterhead), email, etc. shall be submitted to identify the OEM.

5.2.3.1.2 Proprietary Rights.

A company's declaration of Proprietary Rights for their equipment does not negate the requirements of EDPF. All drawings are stored in a secure repository. A Proprietary Rights Statement shall be clearly included within the field of the drawing. Military critical or proprietary drawings are coded as such and access is restricted in a manner prohibiting contractors from being able to access, view, print, or obtain these proprietary drawings. Shall contractor access be required it is limited to contractors working for DOD that have been vested and with current active Non-Disclosure letters on file.

5.2.4 Commercial and Government Entity (CAGE) Code.

CAGE code reference numbers and units of measure/units of measure price (UI/UM PRICE) are required in order to generate national stock numbers (NSNs).

5.3 MIP/MRC.

The contractor shall develop and deliver Maintenance Index Pages (MIPs) and Maintenance Requirement Cards (MRCs) in accordance with MIL-STD-3034 and MIL-P-24534 (See CDRLs A003 and A004 titled: Planned Maintenance System Maintenance Index Pages and Planned Maintenance System Maintenance Requirement Card). Delivery for approval shall be in electronic format [New PMS Editor (NPE)] to the ISEA address listed below. Developers for the MIPs/MRCs are to be (minimum) Level 2 certified. MIP/MRC must be acquired under separate contract line item in the contract.

ISEA:
Director
Naval Surface Warfare Center
Indian Head Division Detachment Picatinny
Building 458, Whittemore Ave.
Picatinny Arsenal, New Jersey 07806-5000
Attn: Andrew Heinrichs
Email: andrew.h.heinrichs.civ@us.navy.mil

5.3.1 Recommended MIP/MRC developers.

The following are recommended developers that may be contacted for assistance in delivery of required MIPs/MRCs.

TMMG
600 Independence Parkway, Suite 105
Chesapeake, VA 23320
Allison Schweitzer
(757) 410-1815
aschweitzer@tmmg.us.com

Asystek Solutions Group
3477 Corporate Parkway, Suite 100

Center Valley, PA 18034
(888) 659-6499
info@asysteksg.com

QED Systems, Inc.
4646 N. Witchduck Rd.
(757) 490-5000
info@qedsysinc.com

6.0 PROGRAM MANAGEMENT

6.1 Contractor Responsibility.

The Contractor is responsible for maintaining their Systems Engineering and Program Management policies and procedures to accomplish the tasks identified herein. The Contractor is responsible for planning, organizing, and managing the effort throughout the life of this contract. The Contractor is responsible for maintaining program costs, performance, and schedule to ensure requirements are being met, and to provide early detection of problems to resolve and reduce risk.

6.2 Conference Meetings.

Contractor shall arrange meetings (See CDRL A005 titled: Conferences/Meetings Agenda and Minutes) and provide Agenda, Minutes, and Action Items List. The following meetings are required at a minimum:

6.2.1 Post-award Guidance Conference.

Post-award guidance conference will occur not later than 30 days after award (See CDRL A005 titled: Conferences/Meetings Agenda and Minutes). This meeting shall be held via teleconference. Contractor will present:

6.2.1.1 Overview.

Overview of the specifications and performance of the MPJ as listed in their proposal. Explaining how each paragraph in the Statement of Work will be met.

6.2.1.2 Schedule.

Present a schedule of key events from contract award to the delivery of technical manuals following the completion of first article testing (FAT). This schedule shall include, but is not limited to: Pre-FAT testing performed by the contractor, estimated completion of build of FAT test unit(s), a basic schedule of FAT events, their order of occurrence and locations and the planned delivery of all contract deliverables during this time period.

6.2.1.3 Updates.

Present updates to the proposed MPJ that may be realized since proposal acceptance/contract award.

6.2.1.4 Risk Potential.

Identify where in the program risks are involved that may negatively impact the schedule.

6.2.2 Test Readiness Review.

Test readiness meeting (See CDRL A005 titled: Conferences/Meetings Agenda and Minutes) provides a detailed review of the contractor's readiness to enter test with a high confidence that the equipment will successfully complete the testing. This meeting shall be scheduled not less than 30 days prior to the start of FAT and will be held at the manufacturer's facility. The contractor shall:

6.2.2.1 Test Schedule.

Present a detailed test schedule referencing all test events required by this SOW and NAVSUP WSS TE-MPJ.

6.2.2.2 Updates.

Present design or performance changes incorporated since the post-award briefing.

6.2.2.3 Status/Demonstration.

Provide a functional and operational demonstration of the MPJ or display current progress of manufacturing of the FAT unit(s).

6.2.2.4 FAT Risk Review.

Identify and risks during FAT and how they can be mitigated to prevent or minimize the effect on the testing and production schedules.

6.2.2.5 Logistics Updates.

Present the current state of development of the technical manual and MIPS/MRC.

7.0 QUALITY ASSURANCE PROVISIONS**7.1 Contractor Certification.****7.1.1 Equipment conformance.**

The contractor shall certify and maintain substantiating evidence that the product offered meets the characteristics of this Purchase Description and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. In addition, the item delivered is substantially the same product offered for sale in the commercial marketplace or is the same product that has been delivered to the government on a previous contract or purchase order. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

7.1.2 Quality Assurance Program Plan.

The contractor shall establish, implement, document and maintain a quality system that ensures conformance to contractual requirements. The contractor shall implement the requirements of ANSI/ASQC Q9001, ISO 9001 or an equivalent quality system model: no third-party certification is required. The contractor shall make their quality assurance program plan or quality manual (development of a Government unique document is not required) available for Government review at their facility as required. The contractor shall officially

notify the Government when they update their plan or manual throughout the contract period of performance.

7.1.3 Warranty.

Unless otherwise specified in the contract or purchase order, the manufacturer's standard commercial warranty shall apply.

7.1.4 Interchangeability.

Upon successful completion of testing and Navy concurrence all FAT requirements have been met, the production configuration of the MPJ is considered to be frozen. All hardware, material, components and assemblies incorporated in the MPJ shall be identical for every production MPJ under this contract. Shall the contractor determine a configuration change is necessary during production, that change shall require prior government approval before production units can be altered. The contractor shall provide information and formally request the Navy's approval by submitting an Engineering Change Proposals (ECP). The ECP shall include all related changes to technical manuals (see paragraph 5.1), MIPs/MRCs (see paragraph 5.3) and provisioning data (see paragraph 5.2).

7.1.4.1 Engineering Change Proposals (ECP).

ECPs are prepared and submitted to the Contracting Officer in accordance with the configuration management requirements of associated Contract Data Requirements List (CDRL), DD Form 1423. (See CDRL A006 titled: Engineering Change Proposal during production).

8.0 PREPARATION FOR DELIVERY

8.1 Packaging & Shipment.

8.1.1 Packaging.

Preservation, packaging, packing and marking for shipment shall be in accordance with the manufacturer's standard commercial practice.

8.1.2 Freight on Board.

Destination.

8.1.3 Transportation.

The MPJ shall be shipped in enclosed type motor vehicles or trailer. If transportation terminals (way stations) are used, the MPJ shall be stored inside.

8.1.4 Spray-on Protective Coatings.

Sprayed-on coatings, applied to the fully assembled MPJ and used as additional and temporary protection during shipment, shall not be used.

Intentionally Left Blank

TEST & EVALUATION REQUIREMENTS TRUCK, PALLET, MANUAL, SHIPBOARD

1.0 First Article Testing (FAT).

FAT shall be performed on operational, complete and production ready MPJ(s) hereafter referred to as the “Unit Under Test” (UUT). This document shall be used in conjunction with Statement of work, NAVSUP WSS SOW MPJ for all inspections (I), demonstrations (D) and tests (T) identified in [Table TE-1](#).

1.1 Units Under Test (UUT).

To successfully complete FAT in the allotted time, the manufacturer shall decide the number of trucks to construct for uses during testing. The FAT test plan (see paragraph [4.1.2](#)) shall clearly state the number of UUTs, and shall identify the test(s) that each UUT will undergo.

1.1.1 Disposition of UUT

Upon completion of FAT, the UUT(s) shall not be reconditioned and/or used for deliverable line items (production units). The contractor shall determine and carry-out the method for disposal of the UUT(s) unless otherwise instructed in the contract.

1.2 Test Facilities, Equipment and Personnel.

Unless specifically stated otherwise in this document or NAVSUP WSS SOW MPJ, the contractor is responsible for determining and arranging the facilities, equipment and personnel that are necessary to conduct the testing required here in.

2.0 Production quality conformance testing.

All production MPJs, prior to submittal for acceptance by the Navy, shall be subjected to the production performance tests marked “T”, “I”, or “D” as specified in the Production Quality Conformance column (column 2) of [Table TE-1](#). Also, refer to paragraph [5.0](#) for additional production requirements.

3.0 Test terms and conditions.

Test conditions and schedule shall be as follows:

3.1 Environmental conditions.

Unless otherwise specified, tests shall be conducted at ambient temperature and climatic conditions existing at the place of test. Ambient conditions shall be recorded prior to each test.

3.2 Surface conditions.

The test surface, unless specified within the test procedures, shall be smooth, dry and level (within 1 degree) concrete surface. The surface shall be swept prior to testing so as to be free of debris, sand, gravel, etc. that may influence some testing results.

3.3 Authorized maintenance.

Only maintenance established by the contractor as the established routine scheduled maintenance and submitted prior to commencement of testing shall be performed during FAT and Production Quality Conformance tests.

3.4 Test Priority Recommendations.

Tests shall be in accordance with Table I and may be conducted in an order or combination as desired by the contractor. The following recommendations are provided to assist the contractor in scheduling FAT events:

3.4.1 Required Dimensions.

It is recommended that dimensional inspections of the UTT and related components as required to confirm conformance to data in [Table SOW-1](#), be conducted before testing of performance capabilities.

3.4.2 Rated load and Pallet Entry and withdrawal Tests.

The Navy recommends that the UUT be tested for the ability to lift and lower a rated load and also the ability to enter and withdrawal from a pallet prior to performing performance testing.

3.4.3 Lift and Tiedown Testing.

Recommends that lift and tiedown testing shall be successfully completed prior to conducting HI-Shock testing.

3.4.4 Paint Inspection.

Inspection of paint for compliance to requirements, para [4.21](#), shall be conducted before environmental tests (rain, temperature, and saline resistance) and before performance testing so as to avoid damage caused during testing and related paint repairs/repainting.

3.4.5 Reliability Demonstration Test.

Reliability shall be the last FAT initiated and completed. All modifications identified as required to pass the previously completed test in the FAT program, shall be incorporated into the UTT used for reliability testing.

3.5 Test Loads.

A rated load necessary to perform the testing required by this document shall be an unrestrained cube with overall dimensions of twice the load center dimension and whose center of gravity is located at the geometric center of the cube. The tolerance for weight of the test load shall be +2 percent, -0 percent.

3.6 Tests, Inspections and Demonstrations.

The UUT(s) used during FAT shall be subjected to testing, inspections and/or demonstrations as indicated by either a "T", "I" or "D", respectively, in Column 1 of [Table TE-1](#). Successful completion of FAT does not influence the tests requirements for production units as noted in column 2 of [Table TE-1](#).

4.0 First Article Testing (FAT)

4.1 General Requirements.

4.1.1 FAT Scheduling.

FAT tests shall be initiated not later than 240 days after contract award. Test/Inspection Report) shall be submitted for Navy review within 240 days from the initiation of FAT testing. Fourteen days prior to the start of each first article test described herein, the contractor shall

notify the Navy of the date, time, and location of the planned test. In response NAVSUP WSS shall confirm whether a Navy MHE Program Office representative will attend. (See CDRL A008 titled: Notification of First Article Test).

4.1.2 FAT Test Plan.

Prior to initiating the testing, inspections or demonstrations described in this document, the contractor shall submit a comprehensive overall test plan for the UTT (See CDRL A007 entitled: Test Plan for First Article Testing). This plan shall be a compilation of the test procedures describing in detail the procedures to be followed for each test, demonstration and inspection identified in [Table TE-1](#), column 1. Accompanying the test plan shall be a comprehensive test schedule detailing the anticipated start and completion dates for all tests. This test plan shall be submitted for Navy review not later than 14 days prior to the date of the test readiness review meeting (refer to paragraph [6.2.2](#) in the statement of work). Details within the test procedures shall include (but are not limited to).

- Number of MPJs used for FAT and on which test each MPJ will be used,
- Identification of all applicable documents,
- Test equipment and facility requirements,
- Definition of test failure,
- Detailed step-by-step description of testing,
- Pre-test set-up and preparations of the MPJ undergoing test,
- Pre and post-test inspections and evaluation methods.

During FAT, changes to test procedures or schedule shall be documented in a revision to the FAT test plan and a copy provided to the Navy.

4.1.2.1 Navy's Technical Warrant Holder (TWH) Review.

MIL-STD-901 High Impact (HI) Shock test requires an individual test plan that must be reviewed separately by the Navy's technical warrant holder (TWH) at Naval Surface Warfare Center Philadelphia Detachment. Within 30 days from receipt of the test plan by the Navy, the TWHs will reply with comments, corrections and recommendations. As necessary, the contractor shall incorporate these corrections into the test plan and resubmit a revised test plan for final approval. Only once the test plan is approved by the Navy can HI-Shock testing be initiated. Contractor shall submit all test plans to NAVSUP WSS who will coordinate the appropriate Navy reviews and approvals.

4.1.3 FAT Report Summary.

Upon completion of all testing the contractor shall compile the FAT results and related information into a comprehensive final report summary (See CDRL A009 titled: Test/Inspection Report). The FAT final report summary shall include:

- The most updated test plan and schedule
- Any approved contract variances/deviations/waivers that impact FAT (See CDRL A014: Request for Variance/Deviation/Waiver pre-production)
- Details descriptions, investigation results, and corrective action taken on all failures, discrepancies, non-conformances
- Description of all equipment modifications developed and incorporated
- Listing of personnel who witnessed each testing

This test report summary shall be submitted for government approval within 30 days after completion of FAT.

4.1.3.1 Navy's TWH Review of Findings.

HI Shock FAT results must be reviewed and approved by the appropriate Navy TWH. The TWHs will require 45 days in order to perform their review, and provide approval. Should a HI-Shock test event result in the UTT failure to meet test requirements, the contractor is responsible for all related redesign, incorporation of equipment changes, retesting and submission of an updated FAT test report. Only after the test results and test summary report are approved by the Navy is this test considered completed. Submit the final test summary report to NAVSUP WSS who will coordinate all review and approval efforts with the Navy THWs.

NOTE

During testing requiring the UUT to be operating, systems shall be monitored to verify that critical values (oil pressure, oil temperature, hydraulic temperature, coolant temp, voltage, etc.) remain within their designated normal operational range. How systems will be monitored and recorded during the test shall be explained within the contractor's test plan (para 4.1.2 above). Deviations of these reading from expected norms shall be noted and explained in the test results. Should critical parameter stray outside of the expected normal range sufficiently to trigger a fault code, warning or failure light, automatic shutdown or reduction of performance it shall be considered as a test failure and the test shall be immediately ended.

4.2 Pre-test Inspections.

Prior to the start of FAT, the following inspections shall be performed:

4.2.1 Wheel Inspection.

All wheels shall be inspected to confirm compliance with the requirements in the SOW, paragraph 3.14. As needed the contractor shall provide information to confirm material specification. Tires shall be measured to verify they fall within the size requirements. Failure to meet material and/or size requirements constitutes a failure of this inspection.

4.2.2 Inspection of MPJ and Component Dimensions.

All dimensions specified in [Table SOW-1](#) shall be measured and verified to be in compliance. Dimensions that do not comply shall be documented and reported to NAVSUP. FAT cannot proceed until all dimensional discrepancies are resolved.

4.2.3 Tiedown and lifting point inspection.

Tiedown and lifting points shall accommodate the hook used on tiedown assemblies identified in the SOW, para [3.22.1](#).

4.2.4 Lubricants and Fluids.

Contractor shall provide documentation to verify all lubricants and fluid used on the UUT are in compliance to para [3.8.2](#) in the SOW. Discrepancies shall be corrected before the UUT can proceed with FAT.

4.2.5 Serviceability.

UUT shall be inspected to confirm all fluid reservoirs and lubrication points are easily accessible and reservoirs recommended fluid levels are clearly marked as required in paragraphs [3.8.1](#) and [3.8](#) in the SOW. Discrepancies shall be corrected before the MPJ can proceed with FAT.

4.2.6 Markings and Information Plates.

The MPJ shall be inspected to verify all required markings and information plates are included as required by the SOW, paragraphs [3.25](#) and [3.26](#). Missing markings shall be documented. Testing may be performed with marking/plate added as soon as possible.

4.2.7 Ergonomics of Controls.

Controls shall be demonstrated and tested to meet the following requirements:

- A) The maximum force applied by the operator to the steering handle to perform the lifting of a rated load shall be 65 lbs.
- B) The number of strokes of the steering handle required to lift a rated load to 4.0 inches above the fully lowered position shall be not more than 17.
- C) Lowering is controlled by a pressure relief that is independent of the lifting mechanism. The lowering control shall be located in a position so that the operator is not endangered when lowering the load, with the steer handle positioned 60 degrees up from horizontal and through a steering arc of 45 degrees on either side of longitudinal axes through the centerline of the MPJ.
- D) Lowering/hydraulic pressure hand release lever shall withstand a maximum applied actuating force of 100 pounds without sustaining damage. All foot pedal devices shall withstand a force of 250 pounds (113 kg) without damage or malfunction.
- E) Actuating handles or levers shall allow for the use of a mitted glove, gloved and ungloved hands with a maximum handle reach not exceeding 3.5 inches.
- F) Maximum sustained holding distance of handles or levers shall be 1.5 to 2.0 inches and the sustained holding force shall not exceed 6 pounds.

G) The maximum force required to turn the steered wheels when the handle is in a towing position shall not exceed 35 pounds.

H) The handle force required to release the brakes shall not exceed 25 pounds.

Any of the above demonstrations/tests that do not meet the stated conditions shall constitute a failure to meet the Navy's requirements.

4.3 Reliability.

The MPJ shall be tested in accordance with [TEST METHOD NO. 1 – RELIABILITY DEMONSTRATION TEST](#).

4.3.1 Failures and Discrepancies During Reliability Test.

Test failures shall be reported to the contracting officer within 24 hours (See CDRL A013 titled: Failure Analysis and Corrective Action Report). Discrepancies that can be corrected with an adjustment or component replacement within 0.5 man-hour of repair time can be performed without prior Navy approval and the reliability demonstration testing continued from where it was stopped. Details of these failures and corrective action performed will be documented on daily logs and included in the FAT test report. Discrepancies that cannot be corrected within these limitations will cause a cessation of the reliability demonstration testing and the contractor shall initiate an investigation to determine the root cause of the problem. The contractor shall provide a report of their findings and recommended corrective action to the contracting officer within 5 days after identification of deficiency. Due to their severity, these discrepancies will require reliability demonstration testing to be re-initiated (starting over at zero test hours run). Examples of discrepancies requiring a failure analysis would include:

- Failure to commence operation, cessation of operation, or degradation of performance capabilities of the UUT.
- Issues that will cause serious damage to the UUT by continued operation.
- Discrepancies that affect safety of personnel or may create an environmental hazard.
- The repeat occurrence of a discrepancy initially categorized as minor.

4.4 Steering Test and Inspection.

Steering force required shall be measured with MPJ supporting a rated load and shall meet the requirements in paragraph [3.15](#) in the SOW. Steering systems ability to control the directional movement of the UUT as noted in paragraph [3.15](#) is demonstrated throughout FAT. The performance of the steering throughout FAT will be used to evaluate the general performance of the steering. Degradation or failure of the steering system to control the MPJ during FAT shall constitute a failure to meet the steering requirement.

4.4.1 Minimum Outside Turning Radius.

Measure the minimum outside turning radius of the UTT with a rated load. Failure to meet the requirement in [Table SOW-1](#) in the SOW shall constitute a failure of this test.

4.4.2 Handle Durability.

Place the MPJ on a level surface with the handle in the released upright position. Block and secure the MPJ to the floor. Apply a horizontal force of 300 pounds to the top of the handle and pull towards the load end of MPJ. Visible damage to the handle shall constitute a failure of this test.

4.5 Brakes.

Brake performance shall be tested as follows:

4.5.1 Brake Pre-Test.

Prior to initiating the FAT brake test, the UUT shall have the brake engaged and disengaged for 1000 cycles as required in paragraph 3.10.2 of the SOW. Brakes cycles shall be performed with the UTT stationary without a load. The brake shall be operated using the brake handle. Component damage or failure during cyclic testing shall constitute a failure of the brake pre-test. Following this pre-test there shall be no repairs, lubrication or adjustment of the brake system and the FAT brake test, paragraph 4.5.2 shall immediately follow.

4.5.2 FAT Brake Test Procedure.

Brake testing shall include a stationary and dynamic test of the brake system.

4.5.2.1 Dynamic Brake Testing.

With the UTT carrying a rated load and traveling at 2 mph, the brakes shall be applied. The MPJ shall come to a complete stop within a distance of 12 inches. Failure to meet the required stopping distance shall constitute a failure of this test. This same test shall be conducted on each production unit.

4.5.2.2 Static Brake Testing.

An adjustable tilting testing surface shall be used for this test that allows the UTT to be position on a surface with a 15-degree slope. The surface shall be coated with a non-skid compound, MIL-PRF-24667, type II, III or IV, or equivalent. The surface and MPJ shall be thoroughly wetted and then the MPJ, carrying the rated load, at maximum lift weight, and forks positioned downslope, parked with the brake applied. The surface shall be raised to 15 degrees. The UTT shall remain parked on the tilted surface for 2 minutes. There shall be no movement of the UTT or rotation of the braked wheels. Following this and while still angled at 15 degrees, the brakes shall be released and set four additional times waiting 2 minutes between each cycling of the brakes. This test procedure shall be repeated with the forks facing downslope. Failure of the engaged brakes to hold the UTT stationary shall constitute a failure of the test.

4.6 Rolling Force.

The MPJ shall be tested to determine the force required to maintain a speed of 2 mph. For this test the MPJ shall carry a rated load. Test shall be conducted on a level surface and be the average of two runs in opposite directions. An average rolling force greater than the requirement in the SOW, paragraph 3.5, shall constitute a failure of this test.

Table TE-1 Test, Inspection & Demonstration Requirements

First Article	Production Quality Conformance	Test	Test Para.	Requirements Paragraph*	Test No.
I		Pre-FAT Inspections	4.2	Various	
T		Reliability	4.3	3.23	1
T, I	D	Steering/Steering Handle	0	3.15	
T		Rolling Force	4.6	3.5	
T		Steer Handle Durability	4.4.2	3.15.1	
T		Brake Pre-Test	4.5.1	3.10.2	
T		Dynamic Brake Test	4.5.2.1	3.10	
T		Static (Slope) Brake Test	4.5.2.2	3.10	
T		Hydraulic System Drift	4.8	3.7.1	
T		Structural Test	4.23	3.16	
T		Slope Ascension	4.11	3.18	
T		Resistance to Saline atmosphere	4.13	3.19	
T		HI Shock	4.15	3.22	
T		Lifting and Tiedown Points	4.16	3.17	
T		Pallet Compatibility	4.10	3.13	
T		Raising and Lowering Mechanism	4.7	3.12	
T		Deck Loading	4.17	3.14.1	
T		Drop Test	4.14	3.21	
T		Stepped Surface Test	4.12	3.20	
T, D		Controls Ergonomics	4.2.7	3.6	
I		Characteristics – Forks, Dimensions and Underclearance	4.18	Table SOW-1 and 3.11	
I		Steering Angle	4.18	3.15	
I		Wheel/Tire Configuration, Size & Material	4.2.1	3.14.2 & 3.14.4	
I		Maintainability and Serviceability	4.19	3.8, 3.8.1 & 3.10.1	
I		Lubricants and Fluids	4.20	3.8.2	
* Requirement paragraphs and table are in NAVSUP WSS SOW MPJ.					

TABLE TE-1. TEST, INSPECTION & DEMONSTRATION REQUIREMENTS (Continued)					
First Article	Production Quality	<u>Test</u>	Test Para.	Requirements Paragraph*	Test No.
I	I (Coverage & Damage)	Paint & Coatings	4.21	3.24	
I	I	Information Plates & Vehicle Markings	4.22	3.25, 3.26	
I		Hydraulic Reservoir Capacity	4.8	3.8.1	
	T	Production QC Testing	5.0		
* Requirement paragraphs and table are in NAVSUP WSS SOW MPJ.					

4.7 Raising and Lowering Mechanism.

Utilizing a standard 48 in. by 40 in., four-way entry, post construction wooden pallet conforming to MIL-DTL-15011, the forks of the UUT shall fully inserted in the pallet perpendicular to the pallet's bottom boards. When lifted or lowered there shall be no interference between the load wheels and the pallet. Insufficient clearance allowing contact between the load wheels and the pallet shall constitute a failure of this test. Inspect that the controls for lifting and lowering conform to the requirements of paragraph 3.6.1 of the SOW. Performance or controls that do not meet these requirements shall constitute a failure of this test.

4.8 Hydraulic Reservoir Capacity Inspection.

The manufacturer shall provide proof through volumetric testing or by documentation of system capacity that the hydraulic reservoir has sufficient capacity, plus a 30% reserve. Should the hydraulic fluid capacity not meet this requirement it shall constitute a failure of this test.

4.9 Hydraulic Drift.

On a level surface the UUT shall be loaded with a rated load and the forks raised to their maximum lift height. Height to the top of the forks shall be measured and recorded. The UUT shall be left in this position for one hour after which the height to the top of the forks shall be measured again. The amount of drift of the forks shall not exceed 0.13 inches. Fork movement exceeding this requirement shall constitute a failure of this test.

4.10 Pallet Compatibility.

Empty, double-faced pallets conforming to MIL-DTL-15011 and MIL-DTL-23312 shall be placed with their front edges on a reference line marked in the test area. The forks of the UUT shall be fully engaged into the pallet (an end view of pallet). The distance from the reference line to same reference point on the pallet edge shall be measured. This test shall then be repeated 10 times with the MPJ fully engaged into the pallet. Forks shall be raised to maximum lift height and then lowered completely. The forks shall be withdrawn from the pallet. The distance from the reference line to the same reference point on the pallet edge shall be measured. The test shall be repeated 10 times for each pallet. The average distance through which the pallet moves either in a forward or backward direction shall not exceed 6 inches. Nonconformance shall constitute a failure of the test.

4.11 Slope Ascension.

The UUT shall be tested and capable of ascending a grade of 6% (3.4 DEG) per the SOW, [Table SOW-1](#) and paragraph [3.18](#). Contact between the surface and the UTT during this test shall constitute a failure of the test.

4.12 Stepped Surface Test.

The UTT, carrying a rated load at maximum lift height shall have the following height measurement recorded:

- A) Front end of frame.
- B) Front pivot point of raising and lowering mechanism.
- C) Top of forks at heel on both sides.
- D) Top of forks midway between front and rear pivot points of the raising and lowering mechanism on both sides.
- E) Rear pivot point of raising and lowering mechanism on both sides.

Test area shall be as defined in the SOW, paragraph [3.20](#). The UTT shall be rolled over the 1-inch elevation change from the higher surface to the lower at a speed of 2 mph. This shall be repeated for a total of 10 times. Following this, the above height measurements shall be retaken. Remove the rated load and examine the UUT for damage, including wheels for smooth operation. Contact between the UUT and either surface; a variation in the height measurements before and after this test, or damage to the UTT including binding or loss of smooth operation of the steering or wheels, shall constitute a failure of this test.

4.13 Resistance to Saline Atmosphere.

The UUT shall be tested fully assembled and in accordance with MIL-STD-810, Test Method 509.8, Salt Fog, Procedure I – Corrosion Screening. Upon completion of the testing a final test report shall be prepared and submitted (See CDRL A010 titled: Salt Fog Test Report). This report will be reviewed by NAVSUP, MHE Program Office engineering team. The results of this test can be subjective so discussions of test results, conclusions, and deficiency mitigation between the contractor and the Navy technical team (NAVSUP WSS and ISEA) are necessary and may result in revisions to the final report or some level of re-testing before NAVSUP WSS can provide concurrence and acceptance.

4.13.1 Details.

Pursuant to paragraph 3.1.1 of Method 509.8, the following test information is given:

4.13.1.1 Exposure.

Duration shall be alternating 24-hour periods of salt fog exposure and drying conditions for a minimum of four 24-hour periods (two wet and two dry). During testing the UUT shall not be washed or operated until all exposure and drying periods have been completed.

4.13.1.2 Salt Solution.

Salt concentration 5 percent.

4.13.2 Additional Guidelines:

4.13.2.1 Inspection.

Visual inspection after 48 hours and 96 hours exposure, but no washing or operation until after all exposure and drying periods are complete. Corrosion detected shall be documented and photographed so that the extent of corrosion damage and its location on the MPJ is clearly identified.

4.13.2.2 Navy Witness.

A representative of the Navy shall be invited to inspect the MPJ immediately following the completion of this test while the UTT is still at the test facility. Contractor shall provide the Navy, at a minimum, two weeks advance notification of this date for test completion and UTT inspection for travel arrangements to be made.

4.13.2.3 Evaluation.

Evaluation will be based on the guidelines of MIL-STD-810, Test Method 509.8, paragraph 5.

4.14 Drop Test.

The UTT shall be lifted by its designated lifting points and shall be dropped three (3) times from a height of 3 feet to a level concrete surface. The UUT shall be examined after each drop for obvious damage. If damage is found the test shall be halted and the UUT evaluated to confirm it is still fully operational. If the damage has affected the MPJs ability to operate, this shall constitute a failure of the test. Drop testing may continue only if the UUT is deemed to be fully operational by the Navy's witness for this testing.

After the third drop the UUT shall lift a rated load and hold it a maximum lift height for 2 minutes. After that time, lower the forks and remove the UUT from the load and inspect the UUT for leaks, and damage. Uncommand lowering of the lifted load, leaks, or damage impacting safety and/or operation of the UUT shall constitute a failure of the test.

4.15 Heavyweight High-Impact (HI) Shock Test.

The UUT shall be tested by the contractor in accordance with MIL-DTL-901 as specified in paragraph 3.22. The contractor shall locate a non-government shock test facility, arrange the test, ensure the specified tiedown assemblies are purchased and utilized, and take account of all related costs of this test. Deficiencies identified during testing that prohibit the MPJ from meeting Grade A requirements shall constitute as a failure of this test.

4.15.1 Instrumentation.

A single accelerometer shall be installed to verify charge efficacy.

4.15.2 HI-Shock Test Plan.

60 days prior to testing, contractor shall submit a formal test plan for approval by the Navy HI-Shock technical warrant holder (See CDRL A011 titled: High-Impact Shock Test Procedures). This plan shall follow the requirements listed in the SOW, paragraph 3.22, and include: list of documents referenced, description of test requirements and procedures, description of test equipment, fixtures and instrumentation, drawing of tiedown configuration, inspections and operational test prior to, between shock events and following testing completion, methods for identifying and evaluation of damage, definition of failure.

4.15.3 HI-Shock Final Test Report.

Upon completion of testing, a report shall be compiled following the outline of the approved test plan and including all the data and results from testing (See CDRL A012 titled: High-Impact Shock Test Report). This report shall include: detailed description of the ability of the unit under test to meet HI-Shock requirements, and identified discrepancies or induced failures identified during testing, post-test evaluation findings both at the test facility and during the teardown inspection by the contractor in accordance with the requirements of MIL-DTL-901. Final report shall be submitted to NAVSUP for review and concurrence not later than 30 days after completion of testing.

4.16 Lifting and Tiedown Points.

Design and testing of lift and tiedown points on the UUT shall comply with the requirements of SOW paragraph 3.17 and MIL-STD-209, type 1 (excluding air transport and Helicopter Sling Lift requirements). Incorrect positioning or damage to the lifting and tiedown points during testing shall constitute a failure of this test.

4.17 Deck Loading.

Test the UUT to measure the force applied to the ground (deck of the ship) in accordance with the requirements of in the SOW, paragraph 3.14.1. The deck loading shall be calculated by loading the MPJ to its maximum rated load and measuring the weight at each steer and load wheel as well as the surface contact area of each wheel. A wheel exerting a load greater than 500 psi shall constitute a failure of this test.

4.18 Characteristics Inspection.

Measure the external characteristics of the UUT as specified in the SOW, [Table SOW-1](#) and paragraphs [3.15](#) and [3.15.1](#).

- A) Fork length.
- B) Maximum overall length.
- C) Maximum lowered height.
- D) Minimum raised height.
- E) Maximum width across forks.
- F) Minimum distance between forks.
- G) Minimum under clearance w/ forks lowered.
- H) Degrees of rotation of steering handle from stop to stop.
- I) Steering Handle height when vertical.

Measurements that do not comply with the requirements shall constitute a failure of this inspection.

NOTE

Corrosion of hydraulic components is tested under the resistance to saline requirement, paragraph [4.13](#).

4.19 Maintainability and Serviceability Inspection.

Inspect all reservoirs and lubrication points for ease of accessibility and compliance to the requirements in para [3.8](#) of the SOW. Service points that are not easily accessible or that have

reservoir levels that cannot be clearly identified shall constitute a failure of this inspection. Additionally, inspect brake to confirm they adjust due to wear and that if required brake mechanism and linkage can be lubricated without disassembly as required in para 3.10.1 in the SOW. Failure to comply with maintainability and serviceability requirements shall constitute a failure of this inspection.

4.20 Lubricants and Fluids Inspection.

Prior to initiating/conducting performance testing under FAT, the contractor shall provide information cross-referencing all fluids and lubricants used in the UUT to those identified in MIL-HDBK-267.

4.20.1 Brand/Type.

All FAT tests shall be conducted using the same brand and type of fluids and lubricants.

During FAT, should the contractor require a change in the source or type of fluids/lubricants used, this change must be reported to and approved by NAVSUP WSS Mech, Code 964, prior to being incorporated.

4.21 Paint & Coatings Inspection.

The required thickness of paint shall be measured in several locations to verify it has been applied evenly and complies with the paint requirements of para 3.24 in the SOW. There shall be no significant overspray on to non-painted components or components painted in different colors. All panels, covers and components painted the same color (yellow) shall not significantly vary in appearance (hue, lightness, brightness, gloss, etc.). Nonconformance to these requirements shall constitute the failure of this inspection.

4.21.1 Paint Inspection of UUT.

Under FAT, as noted in para 3.4.4, it is recommended that the paint inspection be conducted before performance or environmental testing.

4.22 Information Plates and Vehicle Markings Inspection.

The UUT shall be inspected to verify that the required information plates and marking as noted in paragraphs 3.25 and 3.26 in the SOW are installed. Nonconformance to these requirements shall constitute the failure of this inspection.

4.23 Structural Test

With the MPJ placed on a surface plate and with forks at maximum height, the following heights shall be measured, the points of measurement marked on the MPJ, and recorded:

- (a) Front end of frame.
- (b) Front pivot point of raising and lowering mechanism.
- (c) Top of forks at heel on both sides.
- (d) Top of forks midway between front and rear pivot points of the raising and lowering mechanism on both sides.
- (e) Rear pivot point of raising and lowering mechanism on both sides.

Prior to conducting this test, and the test specified in para 4.12, the pressure-relief valve, if provided, shall be made inoperative. Then place the MPJ on a smooth, dry, level concrete surface and elevate the forks to the maximum lift height. Place on the elevated forks a load of 12,000 pounds (200% of rated load). Hold the MPJ in this position for not less than 1 hour. At the end of 1 hour, measure downward drift, then remove the load and place the MPJ on the surface plate. Repeat measurements (a) through (e). Examine the MPJ for damage and permanent deformation. Downward drift exceeding .13 inches, variation in height dimensions in excess of .063 inches or evidence of damage or permanent deformation shall constitute failure of this test.

5.0 Production Quality Conformance Testing.

5.1 General Information

Each production MPJs will undergo the Production Quality Conformance testing, demonstration and inspections. Nonconformance identified during this process shall result in a rejection/non-acceptance of the unit. All non-conformances must be investigated to identify its root cause and changes to production identified and enacted to prevent reoccurrence. Once discrepancies are corrected, the MPJ shall be resubmitted for production quality performance testing and acceptance. The MPJ Production Quality Checklist, [Table TE-2](#), shall be completed during testing and inspection of production MPJs and once complete shall be reviewed and signed with a copy included with documents shipped with the MPJ.

5.1.1 Production Readiness.

Production assembly of MPJs shall not be initiated until the contractor receives official acknowledgement from the contracting officer stating:

- (a). The Navy has accepted the testing results from FAT as summarized in the FAT final report (paragraph 4.1.3) provide under The Navy's acceptance of the final report formally ends FAT and establishes the approved configuration of all production MPJ.
- (b). The Navy concurs the technical manual is complete and is acceptable.

5.2 Production Quality Conformance (QC) Inspection and Testing.

All production MPJs shall undergo the production quality conformance inspection and testing indicated in column 2 of [Table TE-1](#). Production Quality Conformance tests shall be witnessed and results verified by a designated Government representative. The specific requirements for production QC inspections and testing are defined in [Table TE-2](#) and [Table TE-3](#). The results of this inspection shall be documented by the contractor in the production checklist provided in. A copy of the completed/signed copy of this checklist shall be provided with each production MPJ and a second (digital) copy shall be sent to the MHE Program Office, NAVSUP WSS, code N964.

5.2.1 Production Quality Conformance.

5.2.1.1 Production Readiness.

Production assembly of MPJs shall not be initiated until the contractor receives official acknowledgement from the contracting officer stating:

- (a). The Navy has accepted the testing results from FAT as summarized in the FAT final report (paragraph 4.1.3) provide under The Navy's acceptance of final report formally ends FAT and establishes the approved configuration of all production MPJ.
- (b). The Navy concurs the technical manual is complete and is acceptable.

5.2.2 Incremental Production Inspections and Testing.

The contractor may utilize quality tests and inspections conducted during the assembly of the MPJ to satisfy the mandatory production quality conformance inspections and testing.

5.2.3 Inspection.

Each production MPJ shall be inspected by the Government for the defects listed in Table TE-1, Table TE-2 and paragraph 5.5. Results shall be recorded on Production Quality Conformance Testing and Inspection Checklist, Figure TE-1.. If defects are identified, this shall be cause for rejection and the MPJ returned for repairs.

5.2.4 Testing.

Each production MPJ shall undergo testing as listed in Table TE-1, Table TE-3 and paragraphs 5.3. Results shall be recorded on Production Quality Conformance Testing and Inspection Checklist, Figure TE-1.. Failure to pass test requirements shall result in rejection and the MPJ returned for repairs.

5.2.5 Documentation.

Documentation of inspections and tests performed during assembly or during production inspection and testing (paragraphs 5.2.3 and 5.2.4) shall be compiled and provided along with the Production Quality Conformance Testing and Inspection Checklist, Figure TE-1., for review when a MPJ is presented for Government acceptance. Inspections done during assembly shall be compiled into one comprehensive listing to accompany the MPJ when submitted for Government acceptance.

5.2.5.1 Technical Manual

A copy of the technical manual shall be packaged to prevent damage during shipment and securely attached to each production MPJ.

5.3 Brake Testing.

For brake testing of production units each MPJ shall:

5.3.1 Operational Weight Test.

As a prerequisite to brake testing, each production MPJ shall first be positioned on a flat surface and then tested for the ability to lift a rated load to the maximum lift height and hold it for 2 minutes. Lower forks and remove load and inspect the MPJ for leaks, and damage. Uncommand lowering of the lifted load, leaks, or damage shall constitute a failure of the test.

5.3.1.1 Operational Weight Test Documentation.

Every production MPJ shall be shipped with written documentation that it underwent an operational load test using a rated load. This documentation shall clearly state the date of testing, place of testing, weight of load and the name of the company performing the test.

5.3.2 Brake Test.

While carrying a rated load on smooth level surface at a walking pace (not more than 2mph) demonstrate that the service brakes function and stop the unit within 12 inches. Demonstrate that the parking and deadman brake systems hold the unit stationary when applied.

5.4 Paint Inspection of Production MPJs.

The paint and coatings on each production MPJ shall be inspected. Defects or damage (chips, scratches, peeling, etc.) shall be documented, reported and shall be corrected by the contractor before the MPJ is accept by the Government and approved for shipment.

5.5 Inspection of Identification Plates and Markings on Production MPJs.

Each production MPJ shall be inspected per paragraph 4.22 and [Table TE-2](#) to verify that the required information plates and markings are installed. Nonconformance to these requirements shall constitute the failure of this inspection. Results shall be marked on the Production Quality Conformance Testing and Inspection Checklist, [Figure TE-1](#).

Figure TE-1. Production Quality Conformance Testing and Inspection Checklist

Manual Pallet Jack		
Production Quality Conformance Testing and Inspection Checklist		
Contract Number:	Manufacturer:	
MPJ Model:	Navy USN:	
Task	Test Result (Circle One)	Tested/Inspected By: (Initials)
Brakes & Travel Disconnect		
Service Brakes: Functioning normally	Pass Fail	
Parking Brake: Functioning normally	Pass Fail	
Deadman Brake: Activates automatically as designed	Pass Fail	
<i>Comments:</i>		
Operational Weight Testing		
100% rated load held for two (2) minutes	Pass Fail	
<i>Comments:</i>		
Paint & Coatings		
Inspect paint for damage, overspray, thickness, uniformity of color and gloss	Pass Fail	
<i>Comments:</i>		
Information Plates & Vehicle Markings		
Identification Plate	Pass Fail	
Shipping Data Plate	Pass Fail	
Instruction, Warning and Caution Plates	Pass Fail	
Wheel Loading Plate	Pass Fail	
Lubrication Data Plate	Pass Fail	
US Navy (USN) Registration (Serial) Number Metal stamped and exterior stencils/labels	Pass Fail	
Vehicle Weight	Pass Fail	
Safe Working Load	Pass Fail	
Page 1 of 2		

Information Plates & Vehicle Markings (continued)			
Lifting and Tiedown	Pass	Fail	
"Shipboard Use" Marking	Pass	Fail	
<i>Comments:</i>			
Documentation			
Technical Manual	Pass	Fail	
General Condition			
No visible fluid leaks	Pass	Fail	
QA Inspector: Recorded data accurately describes the condition and operational status of the MPJ.			
Name (Print):		Date Completed:	
QA Inspector Signature:			
Page 2 of 2			

Table TE-2 - Production Quality Conformance Inspection List

<u>Deficiency</u>	<u>Requirement Paragraph</u>
Paint and coating surface treatment not as specified	5.4*
(* Inspect paint for damage, excessive overspray, even thickness, uniformity of gloss and color)	
MPJ marking not as specified.	5.5**
(**All markings are the correct size and in the correct location)	
Identification plates not as specified	5.5
Copy of technical manual missing.	5.2.5.1

Table TE-3 - Production Quality Conformance Testing

Test	Procedure
Forks lifting and lowering function.	Lift a rated load to maximum height to confirm forks lift smoothly. Hold for 2 minutes. Activate lowering valve controls to verify forks lower smoothly. Remove load and Inspect for leaks.
Service, Parking and Deadman Brakes.	With a rated load, verify service brakes operate smoothly, parking brake engages when required and deadman system functions properly. Refer to paragraph 5.3.2
Travel and steering.	While carrying a rated load the MPJ rolls smoothly forward and reverse. Steering functions as required right and left.
Load Test	Ability to lift/lower and carry a rated load is demonstrated in the above tests. Refer to paragraph 5.3.1

TEST METHOD NO. 1 – RELIABILITY DEMONSTRATION TEST

1.0 Test Course:

- (a) **Layout of Course.** 50-foot diameter circle.
- (b) **Obstacle Inclusion.** The circle shall have two .75 inch high by 2 inch wide iron, wood, concrete, or steel blocks as obstacles, 180 degrees apart
- (c) **Course Surface.** The course shall be paved and shall be clean and free of unplanned obstacles or foreign material while conducting the reliability test.

1.1 Pre-test MPJ Inspection:

- (a) Inspect that MPJ to be used for reliability testing includes all mandatory design changed identified by previous FAT results (production ready configuration).
- (b) Check all fluids are at recommended levels and contractor recommended daily/pre-operational checks have been performed.
- (c) Perform visual inspection of MPJ for obvious damage, excessive wear, leaks, etc.

2.0 Test Procedure:

The MPJ shall be pulled or towed at a speed of 1.5 mph to 2 mph in a 50 foot diameter circle for a period of 6 hours with the rated load on the forks. The minimum number of times around the circle shall be 50 in one hour. The MPJ shall be pulled each time around the circle without reduction in speed. At the end of each hour, the forks shall be completely raised and lowered 10 times, with the load on the forks. The complete cycle shall be repeated five times with the direction of travel around the circle reversed each hour.

Any failures experienced shall be reported within 24 hours with a final investigation report provided within 30 days of the completion of the test. There shall be no repair or adjustments allowed during the reliability test. The replacement of tires/wheels due to wear, as required during endurance testing is acceptable. The following causes will also be considered as failures:

- (a) Failure to commence operation, cessation of operation, or degradation of performance capabilities of the truck.
- (b) Serious damage to the truck by continued operation.
- (c) Serious personnel safety or an environmental hazard.
- (d) Simultaneous malfunctions traced to the same root cause are considered as one failure.

"The Hourly Time Record Sheet" (**Figure TM-1.1. Hourly Time Record Sheet**) contained herein shall be filled out for each operating hour of the performance test. The number of laps per hour, reasons for malfunctions, stoppages and safety hazards shall be recorded.

[illegible]

1. START DECIMAL MINUTE STOP WATCH AT ZERO AT BEGINNING OF EACH HOUR.
2. RECORD WATCH READING AT END OF EACH HOUR AND RECORD ELAPSED TIME.

41

CONTRACT DATA REQUIREMENTS LIST (1 Data Item)						Form Approved OMB No. 0704-0188						
The public reporting burden for this collection of information is estimated to average 110 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. Please do not return your form to the above organization. Send completed form to the Government Issuing Contracting Officer for the Contract/PR No. listed in Block E.												
A. CONTRACT LINE ITEM NO.		B. EXHIBIT A		C. CATEGORY: TDP _____ TM ☒ OTHER _____								
D. SYSTEM/ITEM 6K Manual Pallet Jack			E. CONTRACT/PR NO.		F. CONTRACTOR							
1. DATA ITEM NO. A001	2. TITLE OF DATA ITEM Technical Manual Verification Review				3. SUBTITLE							
4. AUTHORITY (Data Acquisition Document No.) NAVSUP WSS PD-21861			5. CONTRACT REFERENCE SEE BLOCK 16		6. REQUIRING OFFICE NAVSUP WSS, Code N964							
7. DD 250 REQ DD	9. DIST STATEMENT REQUIRED	10. FREQUENCY 1	12. DATE OF FIRST SUBMISSION SEE BLOCK 16		14. DISTRIBUTION							
8. APP CODE A	A	11. AS OF DATE N/A	13. DATE OF SUBSEQUENT SUBMISSION N/A		a. ADDRESSEE		b. COPIES					
							Draft	Final				
16. REMARKS 1. MHE Program Office ISEA shall be notified in advance of the scheduled date for the review of the preliminary copy of the 100% complete technical manual. Included with this notification shall be a copy of the technical manual that will be reviewed. 2. Block 5. Contract References: NAVSUP WSS SOW-MPJ para 5.1.1 3. Block 12. Not less than 14 days before start of technical manual review or prior to 436 DADC which ever occurs first. 4a. Block 14.a MHE WSS, MHE address as follows: DEPARTMENT OF THE NAVY CODE N964 (ATTN: FRANK COLVIN) NAVSUP WSS 5450 CARLISLE PIKE, SUITE 410-WSA12 MECHANISBURG, PA 17050-2411 4.b. Block 14.a. NAVSUP WSS, PCO address as follows: Department of the Navy Code N744.1 (Attn: Brittany Langletzt) NAVSUP WSS 5450 Carlisle Pike Bldg. 311 Bay B17 Mechanicsburg, PA 17050-2411												
					NAVSUP WSS, MHE		0	0	1			
					NAVSUP WSS, PCO		0	0	1			
					15. TOTAL					0	0	2
					G. PREPARED BY			H. DATE		I. APPROVED BY		J. DATE

17. PRICE GROUP
18. ESTIMATED TOTAL PRICE

CONTRACT DATA REQUIREMENTS LIST (1 Data Item)						Form Approved OMB No. 0704-0188							
The public reporting burden for this collection of information is estimated to average 110 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. Please do not return your form to the above organization. Send completed form to the Government Issuing Contracting Officer for the Contract/PR No. listed in Block E.													
A. CONTRACT LINE ITEM NO.		B. EXHIBIT A		C. CATEGORY: TDP _____ TM ☒ OTHER _____									
D. SYSTEM/ITEM 6K Manual Pallet Jack			E. CONTRACT/PR NO.		F. CONTRACTOR								
1. DATA ITEM NO. A004	2. TITLE OF DATA ITEM Planned Maintenance System (PMS) Maintenance Requirement Card (MRC)				3. SUBTITLE								
4. AUTHORITY (Data Acquisition Document No.) DI-PSSS-80991B			5. CONTRACT REFERENCE SEE BLOCK 16		6. REQUIRING OFFICE NAVSUP WSS, Code N964								
7. DD 250 REQ DD	9. DIST STATEMENT REQUIRED	10. FREQUENCY 1	12. DATE OF FIRST SUBMISSION SEE BLOCK 16		14. DISTRIBUTION								
8. APP CODE A	A	11. AS OF DATE N/A	13. DATE OF SUBSEQUENT SUBMISSION N/A		a. ADDRESSEE		b. COPIES						
					Draft	Final Reg Repro							
16. REMARKS 1. Develop MRCs and provide for review and approval by the MHE ISEA. 2. Block 5. Contract References: Statement of Work, NAVSUP WSS SOW-MPJ, para 5.3 3. Not less than 14 days prior to technical manual review or 436 DADC whichever occurs first. 4a. Block 14.a MHE WSS, MHE address as follows: DEPARTMENT OF THE NAVY CODE N964 (ATTN: FRANK COLVIN) NAVSUP WSS 5450 CARLISLE PIKE, SUITE 410-WSA12 MECHANISBURG, PA 17050-2411 4.b. Block 14.a. NAVSUP WSS, PCO address as follows: Department of the Navy Code N744.1 (Attn: Brittany Langletzt) NAVSUP WSS 5450 Carlisle Pike Bldg. 311 Bay B17 Mechanicsburg, PA 17050-2411					MHE WSS, MHE		0	0	1				
					NAVSUP WSS, PCO		0	0	1				
					15. TOTAL →					0	0	2	
					G. PREPARED BY			H. DATE		I. APPROVED BY		J. DATE	

17. PRICE GROUP

18. ESTIMATED
TOTAL PRICE

CONTRACT DATA REQUIREMENTS LIST (1 Data Item)						Form Approved OMB No. 0704-0188	
The public reporting burden for this collection of information is estimated to average 110 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. Please do not return your form to the above organization. Send completed form to the Government Issuing Contracting Officer for the Contract/PR No. listed in Block E.							
A. CONTRACT LINE ITEM NO.		B. EXHIBIT A		C. CATEGORY: TDP _____ TM _____ OTHER <u>Review Meetings</u>			
D. SYSTEM/ITEM 6K Manual Pallet Jack		E. CONTRACT/PR NO.		F. CONTRACTOR			
1. DATA ITEM NO. A005	2. TITLE OF DATA ITEM Conferences/Meetings Agenda and Minutes			3. SUBTITLE			
4. AUTHORITY (Data Acquisition Document No.) DI-ADMN-81249A		5. CONTRACT REFERENCE SEE BLOCK 16		6. REQUIRING OFFICE NAVSUP WSS, Code N964			
7. DD 250 REQ DD	9. DIST STATEMENT REQUIRED A	10. FREQUENCY ASREQ	12. DATE OF FIRST SUBMISSION SEE BLOCK 16	14. DISTRIBUTION			
8. APP CODE A		11. AS OF DATE N/A	13. DATE OF SUBSEQUENT SUBMISSION SEE BLOCK 16	a. ADDRESSEE		b. COPIES	
				Draft		Final Reg Repro	
16. REMARKS 1. Block 5: Contract References: Statement of Work, NAVSUP WSS SOW-MPJ, paragraph 6.2. 2. Block 12 & 13. Agenda shall be provided seven business days prior to the meeting/review as required. Minutes shall be recorded and delivered within seven business days after a meeting. An Action Items list shall be developed and maintained throughout the program. a) Post award guidance meeting shall be held not more than 30 DADC. b) Test Readiness review shall be held not less than 30 days prior to the start of FAT or NLT 150 DADC. 3a. Block 14.a NAVSUP WSS, MHE address as follows: DEPARTMENT OF THE NAVY CODE N964 (ATTN: NAM PHAM / DAYMIAN SHOOP) NAVSUP WSS 5450 CARLISLE PIKE SUITE 410-WSA12 MECHANICSBURG, PA 17050-2411 3b. Block 14.a. NAVSUP WSS, PCO address as follows: Department of the Navy Code N744.1 (Attn: Brittany Langletzt) NAVSUP WSS 5450 Carlisle Pike Bldg. 311 Bay B17 Mechanicsburg, PA 17050-2411 3c. Block 14.a MHE ISEA, NSWC address as follows: Attn: Andrew H. Heinrichs MHE ISEA Ordnance Logistics W63 NSWC IHD DET PICA Bldg 458, Whittemore Avenue Picatinny Arsenal, NJ 07806-5000 4. Block 14b. Copies shall be distributed in electronic format.				NAVSUP WSS, MHE	0	1	0
				NAVSUP WSS, PCO	0	1	0
				MHE ISEA, NSWC	0	1	0
15. TOTAL →				0	3	0	
G. PREPARED BY		H. DATE		I. APPROVED BY		J. DATE	

17. PRICE GROUP

18. ESTIMATED
TOTAL PRICE

CONTRACT DATA REQUIREMENTS LIST (1 Data Item)						Form Approved OMB No. 0704-0188			
The public reporting burden for this collection of information is estimated to average 110 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. Please do not return your form to the above organization. Send completed form to the Government Issuing Contracting Officer for the Contract/PR No. listed in Block E.									
A. CONTRACT LINE ITEM NO.		B. EXHIBIT A		C. CATEGORY: TDP _____ TM _____ OTHER _____ Production _____					
D. SYSTEM/ITEM 6K Manual Pallet Jack			E. CONTRACT/PR NO.		F. CONTRACTOR				
1. DATA ITEM NO. A006	2. TITLE OF DATA ITEM Engineering Change Proposal (ECP) during production				3. SUBTITLE				
4. AUTHORITY (Data Acquisition Document No.) DI-SESS-80639D			5. CONTRACT REFERENCE SEE BLOCK 16		6. REQUIRING OFFICE NAVSUP WSS, Code N964				
7. DD 250 REQ DD	9. DIST STATEMENT REQUIRED A	10. FREQUENCY ASREQ		12. DATE OF FIRST SUBMISSION ASREQ		14. DISTRIBUTION			
8. APP CODE A		11. AS OF DATE N/A		13. DATE OF SUBSEQUENT SUBMISSION N/A		a. ADDRESSEE	b. COPIES		
						Draft	Final		
							Reg	Repro	
16. REMARKS 1. Report to the contracting officer, changes to the production configuration of the MHE under contract. 2. Block 5. Contract References: Statement of Work, NAVSUP WSS SOW-MPJ, paragraph 7.1.4.1. 3. Do not submit the ECP using DD Form 1692. ECP should be prepared in contractor format and shall include, where applicable, the following information: a. the change priority, change classification, and change justification b. a complete description of the change to be made and the need for that change c. complete listing of other configuration items impacted by the proposed change and a description of the impact on those CIs. d. proposed changes to documents (i.e. tech manuals, MIPS/MRCs, etc.). e. proposed serial (or lot) number effectivities of units to be produced in, or retrofitted to, the proposed configuration. f. recommendation about the way a retrofit should be accomplished. g. estimate when updated EDFP will be provided to correct provisioning to new configuration. 4.a. Block 14.a. NAVSUP WSS, MHE address as follows: DEPARTMENT OF THE NAVY CODE N964 (ATTN: NAM PHAM / DAYMIAN SHOOP) NAVSUP WSS 5450 CARLISLE PIKE SUITE 410-WSA12 MECHANICSBURG, PA 17050-2411 4.b. Block 14.a. NAVSUP WSS, PCO address as follows: Department of the Navy Code N744.1 (Attn: Brittany Langletzt) NAVSUP WSS 5450 Carlisle Pike Bldg. 311 Bay B17 Mechanicsburg, PA 17050-2411 4.c. Block 14.a MHE ISEA, NSWC address as follows: Attn: Andrew H. Heinrichs MHE ISEA Ordnance Logistics W63 NSWC IHD DET PICA Bldg 458, Whittemore Avenue Picatinny Arsenal, NJ 07806-5000						NAVSUP WSS, MHE	0	0	1
						NAVSUP WSS, PCO	0	0	1
						MHE ISEA, NSWC	0	0	1
15. TOTAL						0	0	3	
G. PREPARED BY			H. DATE		I. APPROVED BY		J. DATE		

17. PRICE GROUP
18. ESTIMATED TOTAL PRICE

CONTRACT DATA REQUIREMENTS LIST (1 Data Item)						Form Approved OMB No. 0704-0188			
The public reporting burden for this collection of information is estimated to average 110 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. Please do not return your form to the above organization. Send completed form to the Government Issuing Contracting Officer for the Contract/PR No. listed in Block E.									
A. CONTRACT LINE ITEM NO.		B. EXHIBIT A		C. CATEGORY: TDP _____ TM _____ OTHER <u>Testing - FAT Test Plan</u>					
D. SYSTEM/ITEM 6K Manual Pallet Jack			E. CONTRACT/PR NO.		F. CONTRACTOR				
1. DATA ITEM NO. A007	2. TITLE OF DATA ITEM Test Plan for First Artical Testing (FAT)				3. SUBTITLE				
4. AUTHORITY (Data Acquisition Document No.) DI-NDTI-80566A			5. CONTRACT REFERENCE SEE BLOCK 16		6. REQUIRING OFFICE NAVSUP WSS, Code N964				
7. DD 250 REQ DD	9. DIST STATEMENT REQUIRED A	10. FREQUENCY 1		12. DATE OF FIRST SUBMISSION SEE BLOCK 16		14. DISTRIBUTION			
8. APP CODE A		11. AS OF DATE N/A		13. DATE OF SUBSEQUENT SUBMISSION N/A		a. ADDRESSEE	b. COPIES		
							Draft	Final Reg Repro	
16. REMARKS 1. The test plan covering all testing within First Article Testing (FAT) shall be completed and delivered for NAVSUP WSS review prior to the Test Readiness review (Refer to the Statement of Work NAVSUP WSS SOW-MPJ, para 6.2.2). 2. Block 5 Contract References: Test and Evaluation Requirements, NAVSUP WSS TE-MPJ, para 4.1.2 3. Block 12. The test plan covering all of FAT shall be submitted not later than 14 days prior to the test readiness review or 136 DADC whichever occurs first. 4.a. Block 14.a NAVSUP WSS, MHE address as follows: DEPARTMENT OF THE NAVY CODE N964 (ATTN: ATTN: NAM PHAM / DAYMIAN SHOOP) NAVSUP WSS 5450 CARLISLE PIKE SUITE 410-WSA12 MECHANICSBURG, PA 17050-2411 3.b. Block 14.a. NAVSUP WSS, PCO address as follows: Department of the Navy Code N744.1 (Attn: Brittany Langletz) NAVSUP WSS 5450 Carlisle Pike Bldg. 311 Bay B17 Mechanicsburg, PA 17050-2411 3.c. Block 14.a MHE ISEA, NSWC address as follows: Attn: Andrew H. Heinrichs MHE ISEA Ordnance Logistics W63 NSWC IHD DET PICA Bldg 458, Whittemore Avenue Picatinny Arsenal, NJ 07806-5000						NAVSUP WSS, MHE	0	0	1
						NAVSUP WSS, PCO	0	0	1
						MHE ISEA, NSWC	0	0	1
						15. TOTAL →			
G. PREPARED BY			H. DATE		I. APPROVED BY		J. DATE		

17. PRICE GROUP
18. ESTIMATED TOTAL PRICE

CONTRACT DATA REQUIREMENTS LIST (1 Data Item)						Form Approved OMB No. 0704-0188		
The public reporting burden for this collection of information is estimated to average 110 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. Please do not return your form to the above organization. Send completed form to the Government Issuing Contracting Officer for the Contract/PR No. listed in Block E.								
A. CONTRACT LINE ITEM NO.		B. EXHIBIT A		C. CATEGORY: TDP _____ TM _____ OTHER <u>Notification of First Article Test</u>				
D. SYSTEM/ITEM 6K Manual Pallet Jack			E. CONTRACT/PR NO.		F. CONTRACTOR			
1. DATA ITEM NO. A008	2. TITLE OF DATA ITEM Notification of First Article Test				3. SUBTITLE			
4. AUTHORITY (Data Acquisition Document No.) DI-MISC-81624			5. CONTRACT REFERENCE SEE BLOCK 16		6. REQUIRING OFFICE NAVSUP WSS, Code N964			
7. DD 250 REQ DD	9. DIST STATEMENT REQUIRED A	10. FREQUENCY SEE BLOCK 16		12. DATE OF FIRST SUBMISSION ASREQ	14. DISTRIBUTION			
8. APP CODE A		11. AS OF DATE N/A		13. DATE OF SUBSEQUENT SUBMISSION N/A	a. ADDRESSEE	b. COPIES		
						Draft	Final	
							Reg	Repro
16. REMARKS 1. The Government shall be notified: 1a. Not less than 14 days prior to the start of each test required within FAT, unless otherwise stated in the CDRL specific to an individual test. 1b. All notifications shall include the description of the test to be conducted and the related test plan, proposed dates and times, and the event location. 2. Block 5. Contract References; Test and Evaluation Requirements, NAVSUP WSS TE-MPJ, paragraph 4.1.1 3. Block 12. The overall FAT test schedule and initial test event shall be reviewed and discussed during the test readiness review held at 150 DADC. (All following tests will utilize the notification deadline as noted in item 1a. above. 4.a. Block 14.a NAVSUP WSS MHE address as follows: DEPARTMENT OF THE NAVY CODE N964 (ATTN: NAM PHAM / DAYMIAN SHOOP) NAVSUP WSS 5450 CARLISLE PIKE SUITE 410-WSA12 MECHANICSBURG, PA 17050-2411 4.b. Block 14.a. NAVSUP WSS, PCO address as follows: Department of the Navy Code N744.1 (Attn: Brittany Langletzt) NAVSUP WSS 5450 Carlisle Pike Bldg. 311 Bay B17 Mechanicsburg, PA 17050-2411 4.c. Block 14.a MHE ISEA NSWC address as follows: Attn: Andrew H. Heinrichs MHE ISEA Ordnance Logistics W63 NSWC IHD DET PICA Bldg 458, Whittemore Avenue Picatinny Arsenal, NJ 07806-5000					NAVSUP WSS, MHE	0	0	1
					NAVSUP WSS, PCO	0	0	1
					MHE ISEA, NSWC	0	0	1
15. TOTAL					0	0	3	
G. PREPARED BY			H. DATE		I. APPROVED BY		J. DATE	

17. PRICE GROUP
18. ESTIMATED TOTAL PRICE

CONTRACT DATA REQUIREMENTS LIST (1 Data Item)					Form Approved OMB No. 0704-0188		
The public reporting burden for this collection of information is estimated to average 110 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. Please do not return your form to the above organization. Send completed form to the Government Issuing Contracting Officer for the Contract/PR No. listed in Block E.							
A. CONTRACT LINE ITEM NO.		B. EXHIBIT A		C. CATEGORY: TDP _____ TM _____ OTHER _____ Salt Fog Test Report			
D. SYSTEM/ITEM 6K Manual Pallet Jack			E. CONTRACT/PR NO.		F. CONTRACTOR		
1. DATA ITEM NO. A010	2. TITLE OF DATA ITEM Salt Fog Test Report			3. SUBTITLE			
4. AUTHORITY (Data Acquisition Document No.) MIL-STD-810, Test Method 509.8		5. CONTRACT REFERENCE SEE BLOCK 16			6. REQUIRING OFFICE NAVSUP WSS, Code N964		
7. DD 250 REQ DD	9. DIST STATEMENT REQUIRED A	10. FREQUENCY 1	12. DATE OF FIRST SUBMISSION SEE BLOCK 16	14. DISTRIBUTION			
8. APP CODE A		11. AS OF DATE N/A	13. DATE OF SUBSEQUENT SUBMISSION N/A	a. ADDRESSEE	Draft	b. COPIES Final Reg Repro	
1. Following the completion of Salt fog testing, a final test report shall be provided for review and approval to NAVSUP WSS. Report shall be in contractor format. 2. Block 5. Contract References: Test and Evaluation Requirements, NAVSUP WSS TE-MPJ, para 4.13. 3. Block 12. The test report shall be submitted within 30 days following the completion of salt fog testing or not later than 390 DADC whichever occurs first. 4a. Block 14.a NAVSUP WSS, MHE address as follows: DEPARTMENT OF THE NAVY CODE N964 (ATTN: ATTN: NAM PHAM / DAYMIAN SHOOP) NAVSUP WSS 5450 CARLISLE PIKE SUITE 410-WSA12 MECHANICSBURG, PA 17050-2411 4.b. Block 14.a. NAVSUP WSS, PCO address as follows: Department of the Navy Code N744.1 (Attn: Brittany Langletzt) NAVSUP WSS 5450 Carlisle Pike Bldg. 311 Bay B17 Mechanicsburg, PA 17050-2411 4.c. Block 14.a MHE ISEA, NSWC address as follows: Attn: Andrew H. Heinrichs MHE ISEA Ordnance Logistics W63 NSWC IHD DET PICA Bldg 458, Whittemore Avenue Picatinny Arsenal, NJ 07806-5000				NAVSUP WSS, MHE	0	0	1
				NAVSUP WSS, PCO	0	0	1
				MHE ISEA, NSWC	0	0	1
15. TOTAL				0	0	3	
G. PREPARED BY		H. DATE		I. APPROVED BY		J. DATE	

17. PRICE GROUP
18. ESTIMATED TOTAL PRICE

CONTRACT DATA REQUIREMENTS LIST (1 Data Item)					Form Approved OMB No. 0704-0188		
The public reporting burden for this collection of information is estimated to average 110 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. Please do not return your form to the above organization. Send completed form to the Government Issuing Contracting Officer for the Contract/PR No. listed in Block E.							
A. CONTRACT LINE ITEM NO.		B. EXHIBIT A		C. CATEGORY: TDP _____ TM _____ OTHER Pre-Production			
D. SYSTEM/ITEM 6K Manual Pallet Jack			E. CONTRACT/PR NO.		F. CONTRACTOR		
1. DATA ITEM NO. A014	2. TITLE OF DATA ITEM Request for Variance/Deviation/Waiver Pre-production			3. SUBTITLE NAVSUP WSS, Code N964			
4. AUTHORITY (Data Acquisition Document No.) DI-SESS-80640E			5. CONTRACT REFERENCE SEE BLOCK 16		6. REQUIRING OFFICE NAVSUP WSS, Code N964		
7. DD 250 REQ DD	9. DIST STATEMENT REQUIRED a	10. FREQUENCY ASREQ	12. DATE OF FIRST SUBMISSION ASREQ	14. DISTRIBUTION			
8. APP CODE a		11. AS OF DATE N/A	13. DATE OF SUBSEQUENT SUBMISSION N/A	a. ADDRESSEE	b. COPIES		
					Draft	Final	
						Reg	Repro
16. REMARKS 1. Report to the contracting officer, requests for any pre-production change/deviation/waiver for MHE under contract using the form 1694 per instructed in Block 4. 2. Block 5. Contract References: Statement of Work, NAVSUP WSS TE-MPJ, paragraph 4.1.3. 3.a. Block 14.a. NAVSUP WSS, MHE address as follows: DEPARTMENT OF THE NAVY CODE N964 (ATTN: NAM PHAM / DAYMIAN SHOOP) NAVSUP WSS 5450 CARLISLE PIKE SUITE 410-WSA-12 MECHANICSBURG, PA 17050-2411 3.b. Block 14.a. NAVSUP WSS, PCO address as follows: Department of the Navy Code N744.1 (Attn: Brittany Langletz) NAVSUP WSS 5450 Carlisle Pike Bldg. 311 Bay B17 Mechanicsburg, PA 17050-2411 3.c. Block 14.a MHE ISEA, NSWC address as follows: Attn: Andrew H. Heinrichs MHE ISEA Ordnance Logistics W63 NSWC IHD DET PICA Bldg 458, Whittemore Avenue Picatinny Arsenal, NJ 07806-5000				NAVSUP WSS, MHE	0	0	1
				NAVSUP WSS, PCO	0	0	1
				MHE ISEA, NSWC	0	0	1
15. TOTAL				0	0	3	
G. PREPARED BY			H. DATE	I. APPROVED BY		J. DATE	

17. PRICE GROUP
18. ESTIMATED TOTAL PRICE

INSTRUCTIONS FOR COMPLETING DD FORM 1423

(See DoD 5010.12-M for detailed instructions.)

FOR GOVERNMENT PERSONNEL

Item A. Self-explanatory.

Item B. Self-explanatory.

Item C. Mark (X) appropriate category: TDP - Technical Data Package; TM - Technical Manual; Other - other category of data, such as "Provisioning," "Configuration Management," etc.

Item D. Enter name of system/item being acquired that data will support.

Item E. Self-explanatory (to be filled in after contract award).

Item F. Self-explanatory (to be filled in after contract award).

Item G. Signature of preparer of CDRL.

Item H. Date CDRL was prepared.

Item I. Signature of CDRL approval authority.

Item J. Date CDRL was approved.

Item 1. See DoD FAR Supplement Subpart 4.71 for proper numbering.

Item 2. Enter title as it appears on data acquisition document cited in Item 4.

Item 3. Enter subtitle of data item for further definition of data item (optional entry).

Item 4. Enter Data Item Description (DID) number, military specification number, or military standard number listed in DoD 5010.12-L (AMSDL), or one-time DID number, that defines data content and format requirements.

Item 5. Enter reference to tasking in contract that generates requirement for the data item (e.g., Statement of Work paragraph number).

Item 6. Enter technical office responsible for ensuring adequacy of the data item.

Item 7. Specify requirement for inspection/acceptance of the data item by the Government.

Item 8. Specify requirement for approval of a draft before preparation of the final data item.

Item 9. For technical data, specify requirement for contractor to mark the appropriate distribution statement on the data (ref. DoDD 5230.24).

Item 10. Specify number of times data items are to be delivered.

Item 11. Specify as-of date of data item, when applicable.

Item 12. Specify when first submittal is required.

Item 13. Specify when subsequent submittals are required, when applicable.

Item 14. Enter addressees and number of draft/final copies to be delivered to each addressee. Explain reproducible copies in Item 16.

Item 15. Enter total number of draft/final copies to be delivered.

Item 16. Use for additional/clarifying information for Items 1 through 15. Examples are: Tailoring of documents cited in Item 4; Clarification of submittal dates in Items 12 and 13; Explanation of reproducible copies in Item 14.; Desired medium for delivery of the data item.

FOR THE CONTRACTOR

Item 17. Specify appropriate price group from one of the following groups of effort in developing estimated prices for each data item listed on the DD Form 1423.

a. Group I. Definition - Data which is not otherwise essential to the contractor's performance of the primary contracted effort (production, development, testing, and administration) but which is required by DD Form 1423.

Estimated Price - Costs to be included under Group I are those applicable to preparing and assembling the data item in conformance with Government requirements, and the administration and other expenses related to reproducing and delivering such data items to the Government.

b. Group II. Definition - Data which is essential to the performance of the primary contracted effort but the contractor is required to perform additional work to conform to Government requirements with regard to depth of content, format, frequency of submittal, preparation, control, or quality of the data item.

Estimated Price - Costs to be included under Group II are those incurred over and above the cost of the essential data item without conforming to Government requirements, and the administrative and other expenses related to reproducing and delivering such data item to the Government.

c. Group III. Definition - Data which the contractor must develop for his internal use in performance of the primary contracted effort and does not require any substantial change to conform to Government requirements with regard to depth of content, format, frequency of submittal, preparation, control, and quality of the data item.

Estimated Price - Costs to be included under Group III are the administrative and other expenses related to reproducing and delivering such data item to the Government.

d. Group IV. Definition - Data which is developed by the contractor as part of his normal operating procedures and his effort in supplying these data to the Government is minimal.

Estimated Price - Group IV items should normally be shown on the DD Form 1423 at no cost.

Item 18. For each data item, enter an amount equal to that portion of the total price which is estimated to be attributable to the production or development for the Government of that item of data.

These estimated data prices shall be developed only from those costs which will be incurred as a direct result of the requirement to supply the data, over and above those costs which would otherwise be incurred in performance of the contract if no data were required. The estimated data prices shall not include any amount for rights in data. The Government's right to use the data shall be governed by the pertinent provisions of the contract.