

**SALIENT CHARACTERISTICS
FOR
Series 32-055 DRY CHEMICAL FEEDER SYSTEMS**

SUPPORT REQUIREMENT:

USGI Chemical Feed, [REDACTED]

GENERAL SPECIFICATIONS/CHARACTERISTICS:

20 CES is looking to purchase 2 volumetric dry screw feeder, soda ash at 5-10 lbs. per hour to be installed at well 4 and well 6 to replace the existing soda ash mixers.

SERIES 32-055 VOLUMETRIC SCREW FEEDER

- 1-1/2" stainless steel feed screw and discharge spout, granular service
- Low speed gear box 0.60 cu. ft./hr. max feed rate, 4-speed drive pulley
- 1/6 cu. ft. stainless steel inlet hopper with agitation
 - Feeder inlet hopper cover
- 1/6 HP permanent magnet, DC, TENV motor
- Lol-mounted NEMA 12 control unity with
 - Power on/off switch, motor remote – local stop switch, auto-manual switch auto dosage pot, digital feed display and adjustment.

SOLUTION MIXING TANK

- 35 Gallon rectangular stainless tank with cover
- Tank mounting part for feeder on stainless steel cover
- Dust arrestor with water line and spray nozzle
- Mechanical mixer with 1/4 HP, 115/230 VAC, TENV motor, and jet agitator