

Salient Characteristics:

Thermal Camo Netting (UFR - 52 SFS)

Technical Specifications

Feature	Requirement
Quantity	Thirty (30) individual units.
Dimensions	7.5M x 7.5M per net (minimum size to cover one JLTV).
Modularity	Nets must be connectable to facilitate coverage of larger assets.
Mobility	Lightweight and easily transportable between locations.
Thermal Protection	Must mask Mid-Wave Infrared (MWIR) and Long-Wave Infrared (LWIR) signatures.
Signature Management	Significant reduction of thermal signature for personnel, vehicles, and equipment to blend with ambient thermal background to prevent detection by military-grade thermal imagers.
Advanced Materials	Utilization of nanotechnology or advanced composites for signature suppression.
Visual Pattern	Reversible/Two-sided: Evergreen on one side and Woodland on the alternate side.

Deployment & Durability

Requirement	Description
Environmental Standards	Must conform to MIL-STD-810H for ruggedness and environmental durability in harsh field conditions.
Operational Readiness	System must be delivered as a complete, ready-to-deploy kit.
Support Hardware	Includes lightweight carbon fiber support poles, spreaders, and heavy-duty stakes.
Ruggedization	Built to withstand high-stress military use without degradation of thermal masking properties.