

Question and Answer Matrix for FA489026R0015 - North Warning System (NWS) Rotary Airlift Services					
Offerors					Government Only
Q#	Document	Pg #	Paragraph	Comment/Question	Disposition
1	Performance Work Statement (PWS)	4	1.11.1	Confirm that all Main Rotary Airlift aircraft (O&M) are required to have the following year-round: •IFR capability •NVG capability •and consequently (to perform IFR and NVG flights) two pilots	The Government confirms this is a year-round requirement as stated in PWS and Appendix 3.
2	Appendix 3 - Main Rotary Airlift	1	1.2	Please confirm if this a year-round requirement?	The Government confirms this is a year-round requirement as stated in PWS and Appendix 3.
3	Not Specified	N/A	N/A	The draft PWS omits a previous requirement for an aircraft capable of a 350 nautical mile (NM) nonstop range and specific cargo door/cabin dimensions. Can the Government confirm what the required range and capacity will be in the final RFP PWS?	The Government confirms that the required minimum distance for Rotary Wing (RW) airlift is 150 NM nonstop for all zones. This removes the previous requirement for aircraft capable of a 350 NM range. Potential offerors may propose aircraft with greater mileage and cargo capacity to address the NWS RW airlift requirements, but 150 NM is the established minimum.