RAJALAKSHMI ENGINEERING COLLEGE

Ancilin Rose R X 251801021-2025-AIDS A2

Started on	Thursday, 27 August 2026, 10:46 AM
State	Finished
Completed on	Thursday, 27 August 2026, 10:52 AM
Time taken	6 mins 33 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
int main()
{
    int n, a[100], b[100], i, j, temp, sum = 0;
    scanf("%d", &n);
    for (i = 0; i < n; i++)
        scanf("%d", &a[i]);
    for (i = 0; i < n; i++)
        scanf("%d", &b[i]);
    for (i = 0; i < n; i++)
    {
        for (j = i + 1; j < n; j++)
        {
            if (a[i] > a[j])
            {
                temp = a[i];
                a[i] = a[j];
                a[j] = temp;
            }
        }
    }
    for (i = 0; i < n; i++)
    {
        for (j = i + 1; j < n; j++)
        {
            if (b[i] < b[j])
            {
                temp = b[i];
                b[i] = b[j];
                b[j] = temp;
            }
        }
    }
    for (i = 0; i < n; i++)
        sum += a[i] * b[i];
    printf("%d", sum);
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔

	Input	Expected	Got	
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course