PROGRAM - 1

AIM : HTMl Program to implement different tags.

```
<Html>
<head><title> dag Page </title></head>
<body><h1> This is my First program </h1>
<h2> This is my First program </h2>
<p> <b> <i> This is just a paragraph ... <li>
</b></p>
<p> <strong> This is just a paragraph... </strong>
</p>
<p><em> emphasized dag.... Paragraph </em></p>

<small> Small dag </small>
<p> the content will be <del> deleted </del></p>
<p> the content will be <ins> inserted </ins></p>
<p> the content will be <sub> Subscripted </sub></p>
<p> the content will be <sup> Superscripted. </sup></p>

<font face = "verdan" Size = "12" Color = "red" >

font dag </font></body></html>
```

Result

The Program has been executed and the output was verified

Output

This is my First Program

This is my First program.....

This is just a paragraph.....

This is just a paragraph...

emphasized tag... paragraph...

Small tag

the content will be deleted

the content will be inserted

the content will be Subscripted

the content will be Superscripted

Font tag

PROGRAM - 2

AIM : HTML program to link to different HTML
Page

```
<html>
<head>
<title> demonstrate hyperlink </title>
</head>
<body>
<a href = "dag.html"> My First program ! </a>
</body>
</html>
```

Result :-

The program has been executed and the
output was verified.

Output

demonstrate hyperlink

My First program

PROGRAM 3

5.

AIM : HTML program to create table

```
<html>
<head> <title> Show table </title></head>
<body> <h1> This is a table </h1>
<table Style = " width : 20%.">
<caption> Personal information </caption>
<tr> <th> First name </th> <th> Last name </th> <th>
dob </th> </tr>
<tr> <dd> Arun </dd> <td> achu </dd> <dd>
May16 1999 </td></tr>
<tr> <td> Rahul </td> <td> Rahu </td> <td>
June 61998 </td> </tr>
</table > </body>
<html>
```

Result :-

The program has been executed and the output was verified.

Output

Show table

This is a table

Personal Information

Firstname	lastname	dob
Akshay	achu	May 16 1999
Rahul	Rahu	June 6 1998

PROGRAM - 4

AIM : HTML program to create lists

```
<html>
<head> <title> list <title ></head>
<body><h1> unorder list </h1>
<ul><li> html </li> <li> css </li> <li> java </li></ul>

<h2> ordered list </h2>
<ol type = " a " > <li> php </li> <li> python </li><li>
android </li> </ol>

<h3> description list </h3>
<dl> <dt> window </dt>
<dd> This is a paid operating System which is
       commonly used </dd ></dl>
 </body> </html>
```

Result :

The program has been executed and the output was verified

Output

list

unorder list

- html
- css
- java

ordered list

a. php

b. python

c. android

descuiption list

windows

This is a paid operating System which is commonly used

PROGRAM : 5

AIM: HTML program to create HTML Frame

```
<html>
<head><title> this in frames </title></head>
<frameset cols ="500, * ">
<frame src ="dag.html" name =" first frame"/>
<frame src = "link.html" name =" Second frame"/>

<noframes>
<body> your browser doesnot support frames
</body> </noframes>
</frameset>
</html>
```

Result :

   The prgm has been executed and output
was verified

Output

this is frame x

this is my first program

this is my first program

this is just a paragraph...

this is just a Paragraph

emphasized tag... paragraph

Small tag

the content will be deleted

the content will be inverted

The content will be

           Subscripted

the content will be Supscripted

Font tag

My First program!

PROGRAM - 6

AIM: HTML program do Create a Registration form

```html
<html>
<head>
<title>
Registration page
</title>
</head>
<body> <br> <br>
<form><h2> REGISTRATION FOR IT JOBS </h2>
<label> Firstname </label>
<input type = "text" name = "firstname" Size = "15"/>
<br><br>
<label> Middlename : </label>
<input type = "text" name = "Middlename"
Size ="15"/>  <br><br>
<label> Lastname : </label>
<input type = "text" name = "last name" Size="15">
<br><br>
<label> Dob : </label>
<input type = "date" name = "dob" Size="15"/>
<br><br>
<label>
```

```html
<Select ><option value = " Select "> Select </option>
<option value = " Kottayam "> Kottayam </option>
<option value = " Kollam"> Kollam </option>
<option value = "idduki "> Iduki </option></select>
<label> Sector </label>
<Select < option value = " Sector "> Sector </option>
<option value = " programming "> programming </options>
<option value = "draining "> draining </option>
<option value = " testing"> testing </option>
</Select ><br> <br>

<label>
Gender :
</label><br>

<input type = " radio" name = "male "/> male <br>
<input type = " radio " name = " female "/> female
<br>
<input type = "radio" name = " other "/> other

<br> <br>

<label>
Phone : </label>
<input type = "test " name = " coundry code "
value = " +91 " size = "2"/>
```

```
<input type = "text" name = "phone" Size ="10"/>
<br><br>

email:
<input type ="email"  id="email"  name = email ;><br>
<br><br>

Password :
<input type = "password"  id= "pass"  name ="name
="pass"> <br><br ><t

Re-type password:
<input type = "password"  id= "repass"  name: "repass">

<br><br>

<input type ="button"  value =" Submit "/>

</form>
</body>
</html>
```

Result :

The program has been executed and the output was verified.

Output

Registration page

Registration Jon It Jobs

First name

Middle name

Last name

Dob

District : [Select ^]   Sector : [Sector]

Gender :

o Male

o Female

o other

Phone : [+91] [   ]

Email [   ]

Password : [   ]

Re-type password : [   ]

[Submit]

PROGRAM - 7

AIM: HTML file do link do different HTML page which contain images, tables, forms and also link within a page.

```html
<html>
<head>
<title> This is Frames </title>
</head>
<body>
<iframe src ="link.html" width ="500" height ="300">
</iframe>
<iframe src =" image.html" width = "500"
height = "300"> </iframe>
<iframe src = "table.html" width ="500"
height ="300" > </iframe>
<iframe src =" emplay.html" width ="500"
height ="300"> </iframe></body>
</html>
```

Result:
The program has been executed and the output was verified.

Output

this is frames x

My first program!

This is a dable

Personal cuformation

First name	Last name	dob
Akshay	achu	may 61999
Rahul	Rahu	June 61998

REGISTRATION FOR ITJ

First name

Middle name

Last name

Dob

Districts Seled Sector   Sub

Gender
- male
- female
- other

password

email

re type password

Submit

Program - 8

AIM: HTML program to implement if else statement using java script.

```
<html>
<body>
<script language = "javascript" type = "text/
        javascript ">
var x = 12
var y = 18
if ( x == y) {
  document . write ("x and y ARE EQUAL")
} else
{ document . write (" x and y ARE NOT EQUAL")

}
</script ></body>
</html>
```

Result :

The program has been verified executed and output is verified.

Output

if else .html x

X AND Y ARE NOT EQUAL

PROGRAM - 9

AIM: HTML program to implement do while, while and for loop

```html
<html>
<body>
<Script language = "javascript" type = "text/javascript">
var c=0
document.write("This is starting the loop <br>")
do {
document.write("current count is. : "c++ <br/>")
c++
} while (c<5);
document.write("the loop stopped <br/>")
var.x =0
document.write("this is while loop <br/>")
while (x<8)
{
document.write("count is : " +x+ "<br />")
x++
}
```

```
document . write (" the loop end <br/>") 20 ..
  var z .
document . write ("this is for loop. <br/>")
for(z = 0 ; z < 12 ; z++)
{ document . write ("new count is: "+z+"<br/>")
}
document . write ("end of for loop")
</script>
</body>
</html>
```

Result :
   The program has been executed and output was verified.

Output

Loop. html x

This is Starting the Loop

current count is : 0

current count is : 1

current count is : 2

current count is : 3

current count is : 4

the loop stopped

This us while loop

count is : 0

Count is : 1

count is : 2

Count is : 3

count is : 4

Count is : 5

count is : 6

Count is : 7

the loop end

This is for loop

new count is : 1

new count is : 2

new count is : 3

new count is : 4

new count is : 5

new count is : 6

new count is : 7

new count is : 8

new count is : 9

new count is : 10

new count is : 11

end of the loop

PROGRAM : 10

AIM : HTML Program to implement variables using javascript

```
<html>
<body>
<Script language = " Javascript" type = " text/javascript">
var x =10
var y = 12.8
var name = " ansall jyothi "
var z = {first name : " Ancy ", last name : " Alexander "}
document . write (x)
document . write (y)
document . write (name)
document . write (z. first name)
document . write (type of (x)
</Script>
</body> </html>
```

Result :

The program has been executed and the outpu
was verified.

Output

variable list x

10 12.8   amal jyothi Ancy Alexander.

AIM : HTML Program do implement javascript

```
<html>
<head>
<title> java </title>
</head>
<body>

<script language ="javascript" type ="test/javascript
document. write ("hello everyone ! How are you all ")

</script>
</body>
</html>
```

Result :

  The program has been executed and the output was verified

Output

java x

hello everyone ! How are you all

AIM : HTML Program do implement Switch

```
<html>
<body>
<Script language ="javascript" type ="text/javascript">
var g='A'
document.write("next is a Switch case")
Switch (g) {
Case 'A' : document.write("<b> this is grade A <b>")
break;
case 'B' : document.write("<b> this is grade B <b>")

break;
default : document.write("this is no case")
}
</script> </body>
</html>
```

Result:
    The program has been executed and the output was verified.

| Output
| ---

Switch. html. x

next is a Switch case

this is grade A

AIM : HTML Program do implement the concept of Local Variable

```html
<html>
<body>
<Script language = "javascript" type = "test/javascript">
var x = 10

document . write(x)
</Script>
</body>
</html>
```

Result :

The program has been executed and the output was verified.

Output

local variable.Ldrol x

10.

AIM : HTML Programs do implement local and global variable .

```
<html>
<body>
<Script language ="javascript" type="test/javascrip">

var x=10

var g1 ="global " // global variable

document . write (x)

function(hsec)

{
  var lo = "local " // local variable

  document . write (lo)

}

document . write (g1)
(hsec)
</script>
</body></html>
```

Result:

The program has been executed and the output was verified .

Output

Local global . html x

10 global local .

PROGRAM -15

AIM : HTML Program to implement getElement
ById concept

```html
<html>
<body>
<p id ="demo"></p>
<Script language ="Javascript" type ="text/
javascript">
var person ={
    firstname : "Sona",
    last name : "Anu", age :22 , address : "ABCD"
};
document . getElementById ("demo"). inner HTML =
person . firstname + " " + person . last name + " "
is " + person . age + " years old "
</Script></body></html>
```

Result :
The program has been executed and output
was verified .

Output

get Element · td ms\ x

Sona Auce en 15 year old

PROGRAM - 16

AIM : HTML Program to implement the concept of CSS

```html
<HTML>
<head> <link rel = "stylesheet" href = "sdyle.css">
<title> Registration page </title></head>
<style>
.btn2
{
background.color : pink ;
border : none;
Padding : 10px   25px ;
text-align : center;
text - decoration : none;
display : inline -block ;
font - size : 16 px
Margin : 4px   2px
cursor : pointer;
}</style> <body> <br>
<form action = " " method = "post">

</fieldset>
<div style = " background - image : url ('q.jpg');
```

```html
<h1 Style = "colon : blue ;" > REGISTRATION FORM </h1>
<label> Firstname </label>
<input type = "text" name = "firstname" size = "15"/>
<br> <br> <label> Lastname : </label>
<input type = "text" name = "lastname". size = "15"/>
<br> <br> <label> course : </label>
<Select ><option value = "course "> course </options>
<option value = "BCA" > BCA </options> </select>
<br> <br>

<label> Gender : </label> <br>
<input type = "radio" name = "male"/> Male <br>
<input type = "radio" name = "female"/> Female <br>
<input type = "radio" name = "other"/> other <br> <br>
<label> phone : </label> <input type = "test" name = "c
code" value = "+91" size = "2"/> <input type = "text
name = "phone" size = "10"/ > <br> <br>

Email :
<input type = "email" id = "email" name = "em

<br>
<br>
<br>
```

```
<input type="password" id="pass" name="pass">
<br><br><br>

Re-type password:
<input type="password" id="repass" name="repass">
<br><br>

<input type="button" value="submit" class="btn">
<input type="button" value="reset" class="btn">
</div>
</form>
</body>
</html>
```

Style . CSS

```
.btn
{
  background-color :blue';
  border :none';
  color :yellow';
  Padding :12px 30px;
  text-align :center';
  text decoration :none';
  .display :inline-block';
```

```
font size : 16px ;
Margin : 4px 2px ;
cursor : pointer ;
}
```

Result :

The program has been executed and the output was verified.

Output

Registration page x

REGISTRATION FORM

First name [   ]

Last name [   ]

Course [Course ▾]

Gender

* male
○ Female
○ other

Phone : [+91] [   ]

Email [   ]

Password : [   ]

Retype password : [   ]

| Submit | Reset |

AIM : HTML Program to implement the concept of onclick

```
<html>
<head>
<Script language ="javascript". type ="text/javascript">
function fun()
{
    document . write ("hello! How are you");
}
</Script></head>
<body><forms><input type ="button" onclick ="fun()"
value ="Say Hello"></forms>

</body>
</html>
```

Result :

    The program has been executed and the output was verified.

Output

onclick.html x

(Say hello)

PROGRAM -18

AIM : HTML Program for multiplying 2 Number using function

```html
<html>
<head>
<Script language ="javascript" type="text/javascript">
function mul (a,b)
{
    return a*b;
}
</Script></head>
<body>
<Script language ="javascript" type="text/javascript">
var x= mul (2,8);
document.write(x)
</Script>
</body></html>
```

Result:

The program has been executed and the output was verified

Output
_____

Mul function.html   ×

16

Mul function.html   ×

PROGRAM - 19

AIM : HTML Program to implement the Array Concept

```
<html>
<body>
<p id ="demo"></p>
<Script language ="javascript" type ="text/javascript">
var x =["Maruthi","honda","tata"," apple"];
var z = x.length;
document.getElementById("demo").innerHTML = x[0];
document.write(z);
var y = x.sort();
document.getElementById("demo").innerHTML = y;
</Script>
</body> </html>
```

Result :

The program has been executed and output was verified.

Output

array.html   ×

apple , houda , maruali , data

4

AIM : HTML programs to implement input function

```
<html>
<body>
<button onclick = "func()" > your name </button>
<p id = "demo"></p>
<Script language = "javascript" type : "test/javascript">
function func() {

var p = prompt ("Enter your name :", "Ancy");
if (p!=null) {

document.getElementById("demo").innerHTML =

"Hello " +p+ "how are you ? "

}
}
</script> </body>
</html>
```

Result :
    The program has been executed and the output
was verified

output

input function . html   ✕

(Your name)

hello assy how are you

This page says

Enter your name

~~amsla~~ ancy

(OK) (cancel)

PROGRAM : 21

AIM: PHP program to connect to a database and
retrieve data from a table and show the details in
a neat format

```php
<html>
<body>
<?php
  $ Servername = "localhost";
  $ username = "root",
  $ password = "  ",
  $ dname = "info";
  $ conn = new mysqli ($username, $servername, $password,
      $ dname))
  if ($ conn => connect - error) {
    die ("connection failed : " . $conn => connect - error);
  }
  $ sql = " Select * from 'user' ";
  $ result = $ conn => query ($sql);
  if ($ result => num - rows > 0) {
  echo "<table border = '1'>
    <tr>
    <th> Id </th>
    <th> conduct </th>
```

```php
while ($row = mysqli_fetch_array($result))
  { echo "<tr>",
  echo "<td>" . $row['id'] . "</td>";
  echo "<td>" . $row['name'] . "</td>",
  echo "<td>" . $row['coutal'] . "</td>",
  echo "</tr>",
    }
echo "</table">".
    }
  ?>
</body>
</head>
```

Result:

The program has been executed and output was verified

Output

id	Name	Contact
1	Anuy	1234552
2	Anu	678934
3	Aaya	245792
4	Kanju.	2345678

AIM: PHP program to develop a registration forms and do necessary validations

validate.php

```
<html>
<body>
<form action="signup.php" method='post'>
username :<input type="text" name="username"/><br>
Email :<input type="text" name="email"/><br>
Password :<input type="password" name="password"/><br>
Confirm password :<input type="password" name="password_
        Confirm"/><br>
<input type="Submit" value="Register"/>
</form>
</body>
</html>

Signup.php

$data =$_POST;

if (empty($data['username'])||

empty($data['password'])||

empty($data['email'])||
```

```
empty ($data['confirm'])){
    die('please fill all request field!');
}

if($data['password'] !== $data['password_confirm']){
    die('password and confirm password should match!');
}
```

Username [ ]

Email [ ]

Password [ ]

confirm password [ ]

Register

PROGRAM : 23

AIM: php program to compare electricity bill from user input based on given tariff using php

```
<html>
<head>
    <title> Calculate Electricity Bill </title>
</head>

<?php
$result_str = $result";
if (isset ($_POST ['unit_Submit'])) {
    $unit = $POST ['units'],
    if (! empty ($units)) {
        $result = calculate_bill ($units),
        $result_str ='Total amount of ' $units '_' $result)
    }
}

function calculate_bill ($units) {
    $unit_cost_first = 3.50,
    $unit_cost_Second = 4.00;
    $unit_cost_third = 5.20;
    $unit_cost_-fourth = 6.50)
```

```php
if ($unit of <=50) {
    $bill = $units * $unit_cost_first; }
elseif ($units > 50 && $units <= 100) {
    $temp = 50 * $unit_cost_first;
    $remaining_units = $units - 50;
    $bill . $temp + ($remaining_unit * $unit_cost_second); }
elseif ($units > 100 && $units <= 200) {
    $temp = (50 * 3.5) + (100 * $unit_cost_second);
    $remaining_units . $unit_150;
    $bill = $temp + ($remaining_units * $unit_cost_third); }
else { $temp = (50 * 3.5) + (100 * $unit_cost_second) +
    (100 * $unit_cost_third),
    $remaining_unit . $unit = 250,
    $bill . $temp + ($remaining_units * $unit_cost_fourth);
}
    return number_format ((float)) $bill, 2, '', '');
}
?>

<body>
<div id="page_wrap">
    <h1> calculate Electricity Bill </h1>
```

```
<form action ="Method= post">
<input type ="number" name ."units" placeholder. "
Please enter names of units"/>
<input type =" Submit" name." unit - Submit"
   value =" Submit"/>
</form >
</div>
<?php echo '<br/>' $result-StH.?>

<(div>
</div >

</body>
</html>
```

Result :

The program has been executed and the output was verified.

Output

```
┌─────────────────────────────────┐
│                                 │
│   Calculate Electricity Bill    │
│  ┌───────────────────────────┐  │
│  │ Please enter no. of units │  │
│  └───────────────────────────┘  │
│                                 │
│   Submit                        │
│                                 │
│                                 │
└─────────────────────────────────┘
```

Aim : php program to store name of indian cricket
Players in an array and display the Same in
Html table.

```html
<html>
<head>
<title>indian cricket Team </title>
</head>
<body>
<div id = " page . wrap">
<h1> indian cricket team </h1>
<form action = paintvame .php" Method ="post">
<input type ="testname ="pname1" placeholder ."Enter
name of a player '/><br>
<input type = " testname =" pname2"placeholder ."enter
name of a player '/><br>
<input type ="textname =" pname 3" placeholder "Enter
name of a player '/><br>
<input type ="textname = "pname4" placeholder "Enter
name of a player '/><br>
```

```
<input type = "test" name. 'pnames' placeholder:-"enter
name of a player'1><br>
<input type ="Submit" name. "Submit' value. "submit";

</form>
</div>
</body>
</html>

Pourtname. php

<?php
$name1 - $_POST ['Pname1'];
$name 2 - $_POST ['Pname 2'];
$name 3 - $_POST ['Pname 3'];
$name 4 - $_post ['pname 4'];
$name 5 - $_POST ['Pnames'];

$myArray . Array ($name1, $name 2, $name3, $name4
              $name 5))>

<table "border ="1'>
<dr><th> <ld <1th>
<th> Name </th>
<th>< ?php

$x.1:
for (i=0; i<5; i++) ?>. <tr>.
<td>< ?php echo $i, ? ><1dd>.
<td>< ?php echo myArray (10)) </td> <1tr>
<?php ($++){ ?>
<tr>
```

Output

60

id	Name
1	Dhoni
2	virat
3	Sachin
4	Rohit
5	Sehwag

AIM: Php program do store name of student in an
array and display id using print_r function
Sort and display

```
<html>
<head>
<title> Student Name </title>
</head>
<body>
<div id = "Page_wrap">
  <h1> Student Name </h1>
<form action = "print name.php" method = POST">
<input type = 'text' name = "pname1" placeholder = "Enter
name of Student" /><br>
<input type = 'text'. name 'pname2' placeholder. "Enter
name of Student·1><br>
<input type = 'text' name. 'phname 3' placeholder.. 'Enter
name of student'1 <br>
<input type = "Submit' value. 'Submit">
</form>
</div>
<body>
```

Printname.php

```php
<?php
$name = $_POST ['pname 1'];
$name = $_POST ['pname 2'];
$name = $_POST ['pname 3'];

$myarray = Array ($name1, $name2, $name3)

Print_r ($myarray);
asort ($myarray);
print_r ($myarray);
arsort ($myarray);
Print_r ($myarray);
?>
```

Output

Array [[0]⇒peter [1]⇒Ben [2]⇒Joe)

Array ([1]⇒Ben [2]⇒ Joe [0]⇒peter)

Array ([0]⇒peter [2]⇒Joe[1]⇒Ben)

Aim : php program do accept book information viz Accerion number, title, author, edition and publisher from a webpage and store the information in a database and do search book with the title specified by the word user and do display the Search result with proper heading.

DB connection. php

```php
<?php
define ('DB - SERVER', localhost. 3306');
define ('DB- USERNAME', 'root');
define ('DB_ PASSWORD', 'books');
$db=mysqli - Connection (DB.SERVER, DB- USERNAME,
   DB_PASSWORD, DB_DATABASE);
?>
```


Enter Book. php

```html
<html>
<body bgcolor = "orange">
<center ><h2> Simple library management system </h2>
</center>
```

```html
<form action ="Insert Book.php" method : "post">
<table border =2 align . "center" cellpadding :"5" cellspacing :"5">
<tr>

<dd> Accession No.</dd>
<dd> <input type. "unit" name ." accession" size :"76"></dd>
</tr>

<tr>
<dd> Title <dd>
<dd><input type. ="text" name ="title" size "48"></td>
</tr> <tr>

<dd> Author </dd>
<dd> <input type ."text" name "edition" size :" 48"></dd>
</tr><tr>

<dd>publication </dd>
<dd> <input type :"text" name : "publication" size ="48"></td>

</tr> <tr>

<dd> <input type ="Submit" value =" Submit">

<input type = "Reset" value :" text">

</td> </tr>
</table>
</form>
</body>
</html>
```

insert book.php

```php
<?php

include ("DBconnection.php");
$accversion = $_POST ("accversion");
$title - $_POST ("title");
$author $_POST ['author'];
$editions -$ - post ['edition'];
$publication . $ _POST ["publication"];

$query = "insert into book .info( accession ,title ,author ,
    edition, publication) value ('$accversion', $title','$author',
    '$edition' '$ publication)",

$result . mysqli -query ($db, $query);
?>
```

Display book.php

```php
<html>
<body bgcolor="orange">
<center><h2> Simple library mangement </h2><center>

<br>

<?php
include ("DB connection.php");
```

```php
$Search = $_request ("Search");

$query = Select * from book.info where title like '
          ".Search , "")

$result. mysqli-query ($db, $query);

if (mysqli-num-rows ($result)>0)if (mysqli-num-rows
($result)>0)

{?>

<table border = a align - "centil" cellpadding ="5"

cellspacing ="5"> <th>

<th>Accersion No<ldh>

<th >Title <Ihh>

<th> Author <Ith>

<th> Edition <Idh>

<th> Publication<dh>

</dn>

<?php while ($row = mysqli fetch . arroc ($result))

{?>

<dn>

<td> <?php echo $row ("Accersion"); ?><ltd>

<td > <?php echo $row ('Title '] ; ?><ldd>

<td> <?php . echo $row ['Author']?><ltd>
```

```php
<td><?php echo $row ['edition'];?></dd>
<dd> <?php echo $row ['publishion'];?></dd>
</dr>
<?php
   } }
else
echo " No book found";
   ? >
</table>
</body>
</html>
```

Search book.php

```html
<html>

<body> bgcolor ="orage">

<center><h2> Simple library managment System<td>

</center>

<form action ="Display book.php" method ="get">

<br>

<center> <enter> the title of the book do be Searched:

<input type .'text' name -"Search" size :48>

<br>
```

```
<input type = "Submit" value = "Submit">
<input type = "quit" value - "quit">
</center>
</form><body>
</html>
```

Result

The Programs has been executed and the output was verified.

Simple library management System

Accession no [   ]

Title [   ]

Author [   ]

Edition [   ]

Publication [   ]

[Submit] [Reset]

Simple library management System

Enter the title of the book to be Searched : [   ]

[Submit] [Reset]

PROGRAM : 27

AIM : HTML program to perform some function on list

```
<html>
<body>
<p id="demo"> </p>
<script>
var x = ["apple", "banana", "mango"]
var z = ["brinjal", "potato", "onion"]
x.push("lemon"),

x [x.length] = "chikku",

x [3] = "watermelon", x pop ();

x. shift ();
x. unshift ("orange");
x. split (20,"chikku", "kiwi ");

x. reverse ();

var y = x to string ();

document get elementById ("demo") innerHTML = x.to string ();
document getElementById ("demo") innerHTML = x[0];
document getElement ById ("demo") innerHTML = x [0];
document getElementById ("demo") innerHTML . x ,
```

```
document.getElementById("demo") innerHTML a;
</script>
</body></html>
```

Result:

The program has been executed and the output was verified.

Output

Watermelon, mango, kiwi, chikku, banana, orange, brinjal, potato, onion

PROGRAM: 28

Aim : HTML program do create a list using Javascript

```
<html>

<body>

<p id="demo"></p>

<script>

var x = ["BMW", "maruthi", "fiat", "Tata", "honda"].

csanf = " "

var i;

for (i=0 ; i<x.length ; i++)

    {
    tt = "<i>"+x[i] +"</i>"}

document getElementById ("demo") (inerHTML=t;)

<script>
</body>
</html>
```

Result :

The program has been executed and the output
was verified.

Output

- BMW
- Maruthi
- Fiat
- Tata
- Honda.