

LUBRICATING OIL PLAN
RECOMMENDATION BRAND OF LUBRICATING OIL

MAKER	AMBIENT TEMPERATURE	DESCRIPTION			
		HYDRAULIC OILER BOX	ENCLOSED GEAR	WIRE ROPE & OPEN GEAR	BEARINGS
SHELL	-20° ~ 10°C	TELLUS S2 V32	OMALA S2 G68	MALLEUS GL 205	GADUS S2 V220 2
	10° ~ 50°C	TELLUS S2 V46	OMALA S2 G150		
ESSON MOBIL	-20° ~ 10°C	MOBIL DTE 10 EXCEL 32	MOBIL GEAR 600 XP 68	WIRE ROPE: MOBILARAMA 798 OPEN GEAR: MOBILTAC 375 NC	MOBIL GREASE XHP 222
	10° ~ 50°C	MOBIL DTE 10 EXCEL 46	MOBIL GEAR 600 XP 150		
CALTEX TEXACO	-20° ~ 10°C	RANDO OIL HD 32	MEROPA LUBRICANT 68	CRATER 2K	MULTIFAK EP2
	10° ~ 50°C	RANDO OIL HD 46	MEROPA LUBRICANT 150		
TOTAL LUBMARINE	-20° ~ 10°C	VISGA 32	ELF EPONA Z 68	CERAN AD PLUS	CERAN WR 2
	10° ~ 50°C	VISGA 46	ELF EPONA Z 150		
CHEVRON	-20° ~ 10°C	RANDO HDZ 32	MEROPA 68	TEXCLAD 2	MULTIFAK EP2
	10° ~ 50°C	RANDO HDZ 46	MEROPA150		
BP & CASTROL	-20° ~ 10°C	HYPIN AWH-M 32	ALPHA SP 68	BIOTAC MP	SPHEEROL AP 2
	10° ~ 50°C	HYPIN AWH-M 46	ALPHA SP 150		
GULF	-20° ~ 10°C	MECHANISM LP32	EP LUBRICANT R68	LUBCOTENO. 1	CROWN GREASE N2
	10° ~ 50°C	MECHANISM LP46	EP LUBRICANT BD150		
SK	-20° ~ 10°C	ZIC SUPERVIS X32	SUPER GEAR EP 68	SK GEAR COMPOUND NO 1/2	SK CROWN GREASE EP2
	10° ~ 50°C	ZIC SUPERVIS X46	SUPER GEAR EP 150		