




Anatomy of a Apache Flink




The TaskManagers (also called workers) execute the tasks
The number of task slots indicates how many tasks can be processed concurrently.

JobManager




Task Manager




Flink operators

Flink chains operator subtasks together into tasks. Each task is executed by one thread.




High Availability



Leader election
Service discovery
State persistence

High availability service implementations:



Flink Apis

High-level Analytics API	SQL / Table API (dynamic tables)	- Conciseness + + Expressiveness -
Stream- & Batch Data Processing	DataStream API (streams, windows)	
Stateful Event-Driven Applications	ProcessFunction (events, state, time)	



Data stream API



```
// a stream of website clicks
DataStream<Click> clicks = ...

DataStream<Tuple2<String, Long>> result = clicks
    // project clicks to userId and add a 1 for counting
    .map(
        // define function by implementing the MapFunction interface.
        new MapFunction<Click, Tuple2<String, Long>>() {
            @Override
            public Tuple2<String, Long> map(Click click) {
                return Tuple2.of(click.userId, 1L);
            }
        })
    // key by userId (field 0)
    .keyBy(0)
    // define session window with 30 minute gap
    .window(EventTimeSessionWindows.withGap(Time.minutes(30L)))
    // count clicks per session. Define function as lambda function.
    .reduce((a, b) -> Tuple2.of(a.f0, a.f1 + b.f1));
```

Streaming API

```
DataStream<Tuple2<String, String>> stream = ...;

DataStream<Tuple2<String, Long>> result = stream
    .keyBy(value -> value.f0)
    .process(new CountWithTimeoutFunction());

public class CountWithTimestamp {
    ...
}

public class CountWithTimeoutFunction
    extends KeyedProcessFunction<Tuple, Tuple2<String, String>, Tuple2<String, Long>> {

    private ValueState<CountWithTimestamp> state;

    @Override
    public void open(OpenContext openContext) throws Exception {
        state = getRuntimeContext().getState(new ValueStateDescriptor<>("myState", CountWithTimestamp.class));
    }

    @Override
    public void processElement(
        Tuple2<String, String> value,
        Context ctx,
        Collector<Tuple2<String, Long>> out) throws Exception {

        CountWithTimestamp current = state.value();
        if (current == null) {
            current = new CountWithTimestamp();
            current.key = value.f0;
        }

        current.count++;
        current.lastModified = ctx.timestamp();
        state.update(current);
        ctx.timerService().registerEventTimeTimer(current.lastModified + 60000);
    }

    @Override
    public void onTimer(
        long timestamp,
        OnTimerContext ctx,
        Collector<Tuple2<String, Long>> out) throws Exception {
        CountWithTimestamp result = state.value();
        if (timestamp == result.lastModified + 60000) {
            out.collect(new Tuple2<String, Long>(result.key, result.count));
        }
    }
}
```

Table API



```
Table result =  
    table  
        .window(  
            Session  
                .withGap(lit(30).minutes())  
                .on($"clicktime")  
                .as("w"))  
        .groupBy(  
            $"w",  
            $"userId")  
        .select(  
            $"userId",  
            $"userId".count());
```

SQL API



```
SELECT userId, COUNT(*)  
FROM clicks  
GROUP BY SESSION(clicktime, INTERVAL '30' MINUTE), userId
```