CS533

Intelligent Agents and Decision Making Homework 3, Winter 2011

- 1. Construct a simple Markov Decision Process such that the optimal policy for maximizing finite-horizon total reward must be non-stationary. That is, the MDP should not have a stationary policy that maximizes the finite horizon total reward.
- 2. In class it was mentioned that STRIPS is just a representation for a restricted class of MDPs.
 - (a) Describe how, in general, a STRIPS planning problem can be converted into an equivalent MDP. In other words, given a STRIPS planning problem, describe the components of an MDP (i.e. state space, actions, transition function, rewards) such that solutions to the MDP are a solutions to the STRIPS problem.
 - (b) Roughly how many states does the MDP have for a STRIPS problem with n propositions?
 - (c) What is the complexity of finite horizon value iteration (for a horizon of h) in terms of the number of propositions and actions?
- 3. In many problems, not all actions are applicable in all states and many actions only lead to a small number of next states, compared to the total number of states. In this question, we consider how the complexity of finite-horizon value iteration and policy evaluation can be improved for such problems.

To capture the notion of applicable actions, suppose that we have a function LEGAL(s) that takes a state s and returns the set of legal actions in s. Also suppose that we have a function NEXT(s, a), which takes a state s and action a as input and returns the set of states that have non-zero probability of occurring after taking a in state s. That is,

$$NEXT(s, a) = \{s' \mid T(s, a, s') > 0\}.$$

Assume that we are considering an MDP with n states and m actions such that for any state s and action a we have LEGAL $(s) \le k$ and NEXT $(s,a) \le r$. Assume that the time and space complexity of evaluating the functions NEXT and LEGAL are linear in the sizes of their output (i.e. the number of elements in their sets).

- (a) Describe how to modify the finite-horizon policy evaluation algorithm described in class, using one or both of the new functions, so that the time complexity is improved when r < n and k < m. What is the time complexity? The time complexity should be expressed in terms of r and k when possible and may also involve n and m.
- (b) Repeat part (a) but for the finite-horizon value iteration algorithm described in class.