

Nlab-UTokyo at ImageCLEF 2013 Plant Identification Challenge

Augmenting descriptors for fine-grained categorization

Hideki Nakayama


*Graduate School of Information Science and Technology
The University of Tokyo*

Contents

- Overview
- Motivation & Problems
- Our solution
- Challenge results
- Conclusion & Discussion

Overview of our participation

- Basically follows a standard object recognition pipeline based on bag-of-features
 - We implemented our recently proposed method for general-purpose **fine-grained visual categorization**
Hideki Nakayama, "Augmenting descriptors for fine-grained visual categorization using polynomial embedding", *Proc. IEEE ICME*, 2013.
- We focused on extracting powerful image signatures, rather than segmentation and classification algorithms.
 - Obtain strong local descriptors by embedding local spatial information in a supervised learning framework



Fine-grained visual categorization (FGVC)

- **Distinguish hundreds of very similar object categories** under a specific domain (e.g., species of plants, dogs, birds, etc.)
 - Complementary to traditional object recognition problems
- We need highly discriminative image features

Generic Object Recognition



V.S.

Plant Identification



Tilia
cordata

Tilia
dasystyla

Tilia
platyphyllos

Caltech-256

[Griffin *et al.*, 2007]

Two basic ideas

□ 1. Co-occurrence (correlation) of neighboring local descriptors



- Shaplet [Sabzmeydani et al., 2007] Covariance feature [Tuzel et al., 2006]
CoHOG [Ito et al., 2010] GGV [Harada et al., 2012]

☺ Expected to capture middle-level local information

☹ Results in high-dimensional local features

How to relax these problems?

□ 2. Fisher Vector encoding [Perronnin et al., 2010]


- State-of-the-art bag-of-words representation based on higher-order statistics of local features

☺ Remarkably high-performance, enables linear classification


☹ Dimensionality increases in linear to the size of local features

Our approach

- Densely sample local descriptors
- Compress co-occurrence patterns (polynomials) of neighboring local descriptors
 - ⇒ Discriminative latent descriptor
- Encode by means of bag-of-words (Fisher vector)
- Logistic regression classifier




Exploit co-occurrence information



Exploit co-occurrence information

- More spatial information can be integrated with more neighbors (but become high-dimensional)

$$\mathbf{p}_{(x,y)}^2 = \begin{pmatrix} \mathbf{v}_{(x,y)} \\ upperVec(\mathbf{v}_{(x,y)} \mathbf{v}_{(x,y)}^T) \\ Vec(\mathbf{v}_{(x,y)} \mathbf{v}_{(x-\delta,y)}^T) \\ Vec(\mathbf{v}_{(x,y)} \mathbf{v}_{(x+\delta,y)}^T) \end{pmatrix}$$



2-neighbors


10,336dim

$$\mathbf{p}_{(x,y)}^4 = \begin{pmatrix} \mathbf{v}_{(x,y)} \\ upperVec(\mathbf{v}_{(x,y)} \mathbf{v}_{(x,y)}^T) \\ Vec(\mathbf{v}_{(x,y)} \mathbf{v}_{(x,y-\delta)}^T) \\ Vec(\mathbf{v}_{(x,y)} \mathbf{v}_{(x,y+\delta)}^T) \\ Vec(\mathbf{v}_{(x,y)} \mathbf{v}_{(x-\delta,y)}^T) \\ Vec(\mathbf{v}_{(x,y)} \mathbf{v}_{(x+\delta,y)}^T) \\ Vec(\mathbf{v}_{(x,y)} \mathbf{v}_{(x,y+\delta)}^T) \end{pmatrix}$$



4-neighbors


18,528dim



Supervised dimensionality reduction to compress polynomial vector

□ Training set: patch features (polynomial vectors) and category labels

- All patches share the same image label



□ Strong supervision assumption

- Most patches should be related to the category
- (Somewhat) justified for FGVC considering the applications
- Users will more or less target the object




Supervised dimensionality reduction

- Canonical Correlation Analysis (CCA) [Hotelling, 1936]

\mathbf{p} : patch feature (polynomials), \mathbf{l} : label feature

CCA finds linear transformations


$\mathbf{s} = A^T(\mathbf{p} - \bar{\mathbf{p}})$, $\mathbf{t} = B^T(\mathbf{l} - \bar{\mathbf{l}})$ that maximize the correlation between \mathbf{s} and \mathbf{t}



$$C_{pl}C_{ll}^{-1}C_{lp}A = C_{pp}A\Lambda^2 \quad (A^TC_{pp}A = I)$$

C : covariance matrices

Λ : canonical correlations




Latent descriptor

$$\mathbf{s} = A^T(\mathbf{p} - \bar{\mathbf{p}})$$

64 dim

1,000~
10,000 dim



Fisher Vector [Perronnin *et al.*, 2010]

- State-of-the-art bag-of-words encoding method using higher-level statistics of descriptors (mean and var)

http://www.image-net.org/challenges/LSVRC/2010/ILSVRC2010_XRCE.pdf


BOV

Hard Assignment

[0 0 0 1]

Soft Assignment

[.3 .1 .1 .5]



Fisher Vector

Gradient wrt w

[.15 -.2 -.35 .2]

Gradient wrt mean


[.8 -1.5 -3.7 -1.3 -3.8 1.2 -.9 1.4]

Gradient wrt var

[-1.2 -.9 1.4 -.8 1.5 -3.7 1.3 -3.8]

Our final system

- Combine multiple descriptors in late-fusion approach (SIFT, C-SIFT, Opp.-SIFT, HSV-SIFT, Self similarity)
- Sum of log-likelihoods output by each classifier




Plant Identification Challenge

Challenge Overview

- Identify 250 plant species from images of different organs (Leaf, Flower, Fruit, etc.)
- Two main categories:
 - Sheet As Background
 - Natural Background

“Natural Background” has more generic nature (e.g, cluttered background, view, etc.) and is the primary interest in our participation




<http://www.imageclef.org/2013/plant>

Setup

□ Our submitted runs

We trained classifiers independently for each (sub)category

- Run 1: All
- Run 2: SheetAsBackground + NaturalBackground
- Run 3: SheetAsBackground + Leaf, Flower, Fruit, Stem, Entire



□ Validation

- We used roughly 10% of training samples (**in terms of individual plants**) for validation set
- Parameter tuning and selection of local descriptors

Results on the validation set

- Our method consistently improves the performance from the baseline for all descriptors & domains.
- **Particularly effective for Natural Background task.**

Standard implementation of Fisher Vector.





Used descriptor types and classification rates (%) on the validation set.

		SIFT	C-SIFT	Opp.-SIFT	HSV-SIFT	SSIM	Baseline	Ours	Rel. Imp. (%)
Run 1	All	✓	✓	✓	✓		38.2	38.8	1.6
Run 2,3	SB	✓					50.8	52.5	3.3
Run 2	NB		✓	✓	✓	✓	15.9	17.8	11.9
Run 3	Leaf		✓	✓	✓	✓	15.2	17.3	13.8
Run 3	Flower		✓	✓	✓	✓	21.2	24.7	16.5
Run 3	Fruit		✓	✓	✓	✓	7.4	11.1	50.0
Run 3	Stem		✓	✓	✓	✓	13.8	16.5	19.6
Run 3	Entire		✓	✓	✓	✓	8.2	8.5	3.7

Final results

□ We achieved:

- The 1st place in NaturalBackground category (and 4/5 subcategories). **Run 3**
- The 3rd place in SheetAsBackground category. **Run 1**



Conclusion

- A simple but effective method for FGVC
 - Embedding co-occurrence patterns of neighboring descriptors.
 - Obtain discriminative and small-dimensional latent descriptor to make Fisher vector encoding feasible.
 - Particularly effective for Natural Background task.

- Patch-level strong supervision approximation
 - Not always perfect but reasonable for FGVC problems.

- Discussion
 - Standard object recognition approach is not bad, as the task becomes more general.
 - Features are the most important key to success, of course better segmentation & classification algorithms should be implemented as well.

Implementation Details

□ Low-level descriptors

- SIFT, C-SIFT, Opponent-SIFT, HSV-SIFT, Self Similarity
- Dense sampling (5 pixels apart)

<http://koen.me/research/colordescriptors/>

<http://www.robots.ox.ac.uk/~vgg/software/SelfSimilarity/>

□ Fisher Vector

- 64 Gaussians (visual words)
- Entire image + 3 horizontal spatial regions

http://lear.inrialpes.fr/src/inria_fisher/

□ Classifier

- Logistic regression (LIBLINEAR)
- Average scores of multiple classifiers

<http://www.csie.ntu.edu.tw/~cjlin/liblinear/>