

CUDA Memory Model








Hans Henrik Brandenborg Sørensen

DTU Computing Center

DTU Compute

<hhbs@dtu.dk>





Overview




- Memory hierarchy
 - Four basic memory types
- Memory allocation
 - Declarations
 - Dynamic allocation
- Data transfer
 - Host to device
 - Device to host
- Multi-GPU






	Local
Size	1KB (regs)
Speed	N/A






	Local	Shared
Size	1KB (regs)	Up to 96KB
Speed	N/A	1.4 TB/s aggr.





	Local	Shared	Global
Size	1KB (regs)	Up to 96KB	16 GB
Speed	N/A	1.4 TB/s aggr.	900 GB/s





	Local	Shared	Global	CPU "Host"
Size	1KB (regs)	Up to 96KB	16 GB	192 GB
Speed	N/A	1.4 TB/s aggr.	900 GB/s	< 8-16 GB/s

Local memory example



```
// Using different memory types in CUDA

__global__ void use_local_memory(double val)
{
    // Variable tid is in local memory and private to each thread int tid;

    // Built-in variables like threadIdx.x are in local memory tid = threadIdx.x + blockIdx.x * blockDim.x;

    // Parameter val is in local memory and private to each thread printf("tid=%i val=%lf\n", tid, val);
}
```

Local memory example



```
// Using different memory types in CUDA

__global__ void use_local_memory(double val)
{
    // Variable tid is in local memory and private to each thread int tid;

    // Built-in variables like threadIdx.x are in local memory tid = threadIdx.x + blockIdx.x * blockDim.x;

    // Parameter val is in local memory and private to each thread printf("tid=%i val=%lf\n", tid, val);
}
```

```
#define N 30
int main() {
    // Launch kernel using 6 threads per block
    use_local_memory<<<N/6, 6>>>(2.0);
    cudaDeviceSynchronize();
}
```

Local memory limitations



Hardware limits

Query	Compute Capability		
	1.x (Tesla)	2.x (Fermi)	3.x (Kepler) - 7.x (Volta)
Max 32-bit registers per thread	128	63	255
Max 32-bit registers per block	8192	32768	65536

Local memory limitations



Hardware limits

Query	Compute Capability		
	1.x (Tesla)	2.x (Fermi)	3.x (Kepler) - 7.x (Volta)
Max 32-bit registers per thread	128	63	255
Max 32-bit registers per block	8192	32768	65536

- If all registers are used we spill into global memory
 - Variables are quickly cached in L1 and still fast to use

Global memory allocation



- cudaMalloc()
 - Dynamically allocate global memory on device
 - Requires two parameters
 - Address of a pointer of type void*
 - Number of bytes to allocate

Global memory allocation



- cudaMalloc()
 - Dynamically allocate global memory on device
 - Requires two parameters
 - Address of a pointer of type void*
 - Number of bytes to allocate
- cudaFree()
 - Frees global memory

Global memory allocation



- cudaMalloc()
 - Dynamically allocate global memory on device
 - Requires two parameters
 - Address of a pointer of type void*
 - Number of bytes to allocate
- cudaFree()
 - Frees global memory


"d_" on the variable name is useful to indicate that this points to device memory (not required syntax)

```
// Allocate mem for an array of N doubles
double *d_a;
int size = N * sizeof(double);
cudaMalloc((void**)&d_a, size);
...
cudaFree(d_a);
```

Data transfer




- cudaMemcpy()
 - Memory transfer
 - Host to host (completeness)
 - Host to device
 - Device to host
 - Device to device (copy data)



Data transfer



- cudaMemcpy()
 - Memory transfer
 - Host to host (completeness)
 - Host to device
 - Device to host
 - Device to device (copy data)
 - Bandwidth limited by PCI-express
 - Typical ~8-12 GB/s each way (host ←→ device)




Data transfer



- cudaMemcpy()
 - Memory transfer
 - Host to host (completeness)
 - Host to device
 - Device to host
 - Device to device (copy data)
 - Bandwidth limited by PCI-express
 - Typical ~8-12 GB/s each way (host ←→ device)

```
// Transfer data from host to device
cudaMemcpy(d_a, h_a, size, cudaMemcpyHostToDevice);


// Transfer data from device to host
cudaMemcpy(h_a, d_a, size, cudaMemcpyDeviceToHost);
```



Pinned host memory




Staging area




Pinned host memory





Pinned host memory





Allocating pinned host memory



- cudaHostAlloc(), cudaMallocHost()
 - Dynamically allocate page-locked memory on host
- cudaFreeHost()
 - Frees page-locked host memory
- cudaHostRegister()
 - □ Page-locks a range of memory allocated by malloc()

Global memory example



```
// Using different memory types in CUDA
__global__ void use_global_memory(int *a)
{
    // Variable tid is in local memory and private to each thread
    int tid = threadIdx.x + blockIdx.x * blockDim.x;

    // Parameter a is a pointer into global memory
    a[tid] = tid; // Sets a to [0,1,2,3,..]
}
```

Global memory example



```
#define N 30
int main() {
  // Array pointers on host and device
  int *h a, *d a;
  // Alloc mem on host and device
   cudaMallocHost((void **)&h a, N * sizeof(int));
   cudaMalloc((void **)&d a, N * sizeof(int));
  // Launch kernel using 6 threads per block
  use global memory << N/6, 6>>> (d a);
   // Copy result back to host
   cudaMemcpy(h_a, d_a, N * sizeof(int), cudaMemcpyDeviceToHost);
  // Print result
  print ints(h a, N, "a: ");
  // Cleanup
   cudaFreeHost(h a); cudaFree(d a);
```

Shared memory allocation



Static allocation using shared

```
#define N 128

__global__ void kernelFunc(...)
{
    __shared__ double smem[N]; // Static allocation
    ...
}
```

Shared memory allocation



Static allocation using shared

```
#define N 128

__global__ void kernelFunc(...)
{
    __shared__ double smem[N]; // Static allocation
    ...
}
```

Dynamic allocation within <<<...>>>

```
kernelFunc<<<dimGrid, dimBlock, N * sizeof(double)>>>(...);

__global__ void kernelFunc(...)
{
   extern __shared__ double smem[]; // Dynamic allocation
   ...
}
```

Shared memory example



```
// Using different memory types in CUDA
 global void use shared memory(int *a)
  // Allocate shared memory statically
  shared int smem[THREADS PER BLOCK];
  // Read from global memory to shared memory
  int tid = threadIdx.x + blockIdx.x * blockDim.x;
  smem[threadIdx.x] = a[tid];
  syncthreads(); // Ensure all reads have completed
  // Adds even and odd elements in shared memory
  int i = 1 - 2 * (threadIdx.x & 1);
   smem[threadIdx.x] += smem[threadIdx.x + i];
   syncthreads(); // Ensure all writes have completed
  // Write back to global memory
  a[tid] = smem[threadIdx.x]; // [0,1,2,3,...] -> [1,1,5,5,...]
```



Multi-GPU

Multi-GPU systems



Multi-GPU systems appear in several flavors







■ Nvidia Tesla K80, while physically occupying a single expansion slot, will appear to your CUDA applications as two separate GPUs

Multi-GPU systems



- Using multiple GPUs within the same application can improve the performance
 - Splitting the task (extra level of parallelism)
 - Scales the peak performance
 - Scales the memory bandwidth
 - Does NOT always scale the PCI-e bandwidth!

Multi-GPU systems



- Using multiple GPUs within the same application can improve the performance
 - Splitting the task (extra level of parallelism)
 - Scales the peak performance
 - Scales the memory bandwidth
 - Does NOT always scale the PCI-e bandwidth!
- The CUDA runtime requires that each GPU must be associated to a separate thread running on the CPU (started automatically)

Multi-GPU with CUDA



- cudaGetDeviceCount() gets the number of available GPUs
- cudaSetDevice() sets the device to run on
- cudaGetDevice() gets the current device

```
// Run independent kernel on each CUDA device
int numDevs = 0;
cudaGetDeviceCount(&numDevs);
...
for (int d = 0; d < numDevs; d++) {
   cudaSetDevice(d);
   kernel < < dimGrid, dimBlock >>> (args);
}
...
```

Memory allocation / transfers



You can handle memory on multiple GPUs by applying cudaSetDevice () multiple times

```
// Allocate half a matrix on two GPUs, copy top and bottom part to
each GPU and run independent kernels
cudaSetDevice(0);
double *d0 A;
cudaMalloc((void**)&d0 A, A size/2);
cudaMemcpy(d0 A, h A, A size/2, cudaMemcpyHostToDevice);
kernel<<<dimGrid, dimBlock>>>(d0 A);
cudaSetDevice(1);
double *d1 A;
cudaMalloc((void**)&d1 A, A size/2);
cudaMemcpy(d1_A, h_A + A_size/2, A_size/2, cudaMemcpyHostToDevice);
kernel<<<dimGrid, dimBlock>>>(d1 A);
```

Peer-to-peer memory access



Use cudaDeviceEnablePeerAccess() to get unidirectional peer access to other GPUs

```
// Enable peer-to-peer access and run kernels
cudaSetDevice(0);
cudaDeviceEnablePeerAccess(1, 0); // (dev 1, future flag)
kernel<<<dimGrid, dimBlock>>>(d0_A, d1_A);

cudaSetDevice(1);
cudaDeviceEnablePeerAccess(0, 0); // (dev 0, future flag)
kernel<<<dimGrid, dimBlock>>>(d0_A, d1_A);
```

Check peer access support with deviceQuery



- Finish up the first two exercises
 - ex1_deviceQuery
 - ex2_helloworld

- Do the third exercises
 - ex3_mandelbrot
 - □ If you have issues (segmentation fault) get the new version of pngwriter from CampusNet week 2



End of lecture