

Robust Software Systems Final Project Spring 2013

By David Harboe (s103432), Anders Emil Nielsen (s103457), Joachim Friis (s093256), Anders Gotfredsen (s103465)

API Documentation

This API is a JSON api accepts therefore only JSON request. A JSON request is executed by adding `application/json` to the header `Content-Type`.

The host of this API is `robust02241.herokuapp.com`.

Routes

Public

The following routes are public and therefore accessible by anyone

Action	HTTP method	URL	Require params	Optional params
See a list of products	GET	/products		
See details of a product	GET	/products/:id		
Register as customer	POST	/customers	email, password	address, name

Customer authentication

The following route is for authenticating a customer. This action creates a session for the given customer and returns a session key, which should be used for the actions that requires token authorization.

This action requires [Basic authentication](#)

Action	HTTP method	URL	Require params	Optional params
Create a customer session	POST	/customer/authentications		

Customer specific actions

These actions are specific for a given customer and can only be executed by the authorized customer.

This action requires [Token authentication](#). The token is the access token from [authentication](#).

Action	HTTP method	URL	Required params	Optional params
See a list of orders	GET	/orders		
Create an order	POST	/orders/:id	product_ids, paymentinfo	date
Get details of an order	GET	/orders/:id		
Delete an order	DELETE	/orders/:id		

Administrator authentication

The following route is for authenticating a administrator. This action creates a session for the given administrator and returns a session key, which should be used for the actions that requires token authorization.

This action requires [Basic authentication](#)

Action	HTTP method	URL	Require params	Optional params
Create a admin session	POST	/admin/authentications		

Administrator specific actions

These actions are specific for a given administrator and can only be executed by the authorized administrator.

This action requires [Token authentication](#). The token is the access token from [authentication](#).

Action	HTTP method	URL	Required params	Optional params
See a list of customers	GET	/admin/customers		
Create a customer	POST	/admin/customers/:id	email, password	address, name
Edit a customer	POST	/admin/customers/:id	email, password	address, name
Get details of a customer	GET	/admin/customers/:id		
Delete a customer	DELETE	/admin/customers/:id		
See a list of products	GET	/admin/products		
Create a product	POST	/admin/products/:id	name, price	name, price
Edit a product	POST	/admin/products/:id	name, price	name, price

Get details of a product	GET	/admin/products/:id		
Delete a product	DELETE	/admin/products/:id		
See a list of administrators	GET	/admin/administrators		
Create a administrator	POST	/admin/administrators/:id	email, password	address, name
Edit a administrator	POST	/admin/administrators/:id	email, password	address, name
Get details of a administrator	GET	/admin/administrators/:id		
Delete a administrator	DELETE	/admin/administrators/:id		

Basic Authentication

Basic authentication is used by encoding the string `email:password` (where email is your email and password is your password) with **Base64**. This value is the inserted in the header `Authorization` as follows:

```
Authorization: Basic encodedvalue
```

Token Authentication

Token authentication is used by inserting the token in the `Authorization` header as follows:

```
Authorization: Token token="myaccesstoken"
```