

Adaptive batch SOM for multiple dissimilarity data tables

Anderson Dantas

absd@cin.ufpe.br



Introduction

- Clustering methods organize a set of items into clusters
- Items within a given cluster have a high degree of similarity
- Feature data and Relational data

Objective

Hard clustering algorithm that is able to partition objects taking into account simultaneously their relational descriptions given by multiple dissimilarity matrices

Objective

- Partition
- Prototype for each cluster
- **Relevance weight**

Adaptive batch SOM for data based on multiple dissimilarity matrices

Iterative three-step algorithm
Representation, weighting and affectation

Cost function

$$J = \sum_{e_i \in E} \sum_{l=1}^c K^T(\delta(\chi(e_i), l)) D_{\lambda_l}(e_i, G_l)$$

- D_{λ_l} is the global matching
- relevance weight vector $\lambda_l = (\lambda_{l1}, \dots, \lambda_{lp})$ of the dissimilarity matrices \mathbf{D}_j
- Neighbourhood through kernel functions K

Matching function

$$D_{\lambda_l}(e_i, G_l) = \sum_{j=1}^p \lambda_{lj} D_j(e_i, G_l) = \sum_{j=1}^p \lambda_{lj} d_j(e_i, G_l)$$

Representation step: computation of the best prototypes

Compute the prototype $G_l^{(t)} = G^* \in E^{(q)}$ of cluster $P_l^{(t-1)}$ ($l = 1, \dots, c$) according to:

$$G^* = \underset{e_i \in E^{(q)}}{\operatorname{argmin}} \sum_{e_i \in E} K^T(\delta(\chi^{(t-1)}(e_i), l)) \sum_{j=1}^p \lambda_{lj}^{(t-1)} d_j(e_i, G_l)$$

Weighting step: definition of the best vectors of weights

The vectors of weights $\lambda_l^{(t)} = (\lambda_{l1}^{(t)}, \dots, \lambda_{lp}^{(t)})$ ($l = 1, \dots, c$), under $\lambda_{lj}^{(t)} > 0$ and $\prod_{j=1}^p \lambda_{lj}^{(t)} = 1$, have their weights $\lambda_{lj}^{(t)}$ ($j = 1, \dots, p$) calculated according to:

$$\lambda_{lj}^{(t)} = \frac{\left\{ \prod_{h=1}^p \left[\sum_{e_i \in E} K^T(\delta(\chi^{(t-1)}(e_i), l)) d_h(e_i, G_l) \right] \right\}^{\frac{1}{p}}}{\left[\sum_{e_i \in E} K^T(\delta(\chi^{(t-1)}(e_i), l)) d_j(e_i, G_l) \right]}$$

Affectation step: definition of the best partition

$$m = (\chi^{(t)}(e_i))^{(t)} = \underset{1 \leq r \leq c}{\operatorname{argmin}} \sum_{l=1}^c K^T(\delta(r, l)) \sum_{j=1}^p \lambda_{lj}^{(t)} d_j(e_i, G_l)$$

Empirical results

- Databases from the UCI Machine Learning Repository
- Measures: corrected Rand index (CR), F-measure, overall error rate of classification (OERC)
- Confusion matrix
- Data sets described by a matrix of objects x real-valued attributes
- All attributes x single attributes

Wine dataset

Parameters

- Topology: 2x5;
- T_{min} : 0.3;
- T_{max} : 3.0;
- N_{iter} : 500

Indexes	B-SOM	AB-SOM
CR	0.31	0.42
$F - measure$	0.45	0.52
$OERC$	27.00%	9.00%

Confusion matrix

Cluster/Class	1	2	3	Majority Class
0,0	0	5	16	3
0,1	0	1	4	3
0,2	0	21	0	2
0,3	2	22	0	2
0,4	6	10	0	2
1,0	0	0	15	3
1,1	0	0	13	3
1,2	0	9	0	2
1,3	24	2	0	1
1,4	27	1	0	1

Final relevance weight matrix

Cluster/Matrix	1	2	3	4	5	6	7	8	9	10	11
0,0	1.03	0.27	1.31	1.07	0.48	0.90	3.05	0.33	1.87	1.25	0.5
0,1	0.99	1.05	0.55	1.09	0.27	0.69	0.79	0.52	0.41	0.92	1.8
0,2	1.28	0.52	0.41	0.43	1.47	0.60	2.42	0.90	1.57	5.17	0.1
0,3	0.69	0.33	0.93	2.64	1.32	0.48	2.29	1.22	0.45	2.39	0.3
0,4	0.77	4.19	0.27	0.99	0.16	1.92	0.84	1.96	0.24	3.04	3.7
1,0	1.02	0.37	0.63	0.89	0.47	1.68	2.42	0.25	2.79	0.45	1.4
1,1	0.46	0.21	0.79	0.90	1.85	0.49	5.07	0.86	0.24	0.36	2.2
1,2	0.42	0.61	0.51	1.35	0.16	2.93	3.12	0.24	2.27	2.96	1.3
1,3	0.77	0.55	0.69	0.16	0.29	1.38	3.13	2.14	1.12	1.95	1.0
1,4	0.48	6.01	0.37	0.33	0.61	1.64	1.65	0.94	0.40	1.50	1.7

Adaptive batch SOM for multiple dissimilarity data tables

Anderson Dantas

absd@cin.ufpe.br

