

JavaEE examples java-ee-examples (0.0.1) [\[Build Status\]](#)

Maksim Kostromin

Version 0.0.1, 2018-07-06 18:48:18 UTC

Table of Contents

1. async	2
2. micro-profile	3
3. JBOSS 4 JAX-RS	4
4. maven is not working properly	5
5. JavaEE Wildfly-Swarm Micro-Profile using Gradle	7
5.1. wildfly-swarm-gradle	7
6. JavaEE Wildfly-Swarm Micro-Profile using Maven	9
6.1. wildfly-swarm-maven	9
7. Kumuluzee MicroProfile 1.0	11
7.1. kumuluzee-microprofile-1.0	11
8. JavaEE Kubernetes	12
8.1. java-kube-ee	12
8.2. old	14
9. JavaEE using Kotlin	15
9.1. java-kube-ee	15
9.2. old	17
9.3. kotlin-plugins-java-ee	17
9.4. main-swarm-rest-api	18
9.5. main-swarm-static-content	18
9.6. kotlin-java-ee-payara-docker	18
9.7. kotlin-javaee-cdi-h2	18
10. JBoss EAP in Docker	20
10.1. faces	20
10.2. jboss-eap-ext.js	21
10.3. xmlrpc	21
10.4. ear	21
10.5. ejb-2	22
10.6. timer	23
10.7. timer-async-ejb	23
10.8. ejb-3-java-ee-7	23
10.9. ejb-stateful-singleton	23
10.10. jboss-eap-h2-ejb	24
10.11. plain HTTP Servlet	24
11. TomEE in Docker	28
11.1. tomee-ext.js	28
12. Glassfisg in Docker	29
12.1. glassfish-ext.js	29
13. JBoss WildFly (mvnw / gradlew) in Docker	30

13.1. forge-ws	30
14. JBoss forge / WildFly Java EE 6 / JAX-WS	32
14.1. forge-javaee-6-ws	32
15. Kumuluzee MicroProfile 2.0 (config.yaml)	33
15.1. kumuluzee-config	33
16. Kumuluzee MicroProfile 2.0 (JAX-WS)	34
16.1. kumuluzee-mp-2.0-jax-ws	34
17. links	35
18. Enjoy! :).	36

Introduction

This documentation contains some help to [examples from java-ee-examples repository](#). It's contains some JavaEE Micro-profile playground projects

Chapter 1. async

TODO: in progress...

Initially generated by using [generator-jvm](#) yeoman generator (kotlin-ee)

TODO: in progress...

Initially generated by using [generator-jvm](#) yeoman generator (kotlin-ee)

Chapter 2. micro-profile

MicroProfile 1.0 (CDI + JAX-RS + JSON-P)

```
<dependencyManagement>
  <dependencies>
    <dependency>
      <groupId>org.wildfly.swarm</groupId>
      <artifactId>bom-all</artifactId>
      <version>${version.wildfly.swarm}</version>
      <scope>import</scope>
      <type>pom</type>
    </dependency>
  </dependencies>
</dependencyManagement>
```

Chapter 3. JBOSS 4 | JAX-RS

build

```
./mvnw clean package com.dkanejs.maven.plugins:docker-compose-maven-plugin:1.0.1:up
./mvnw com.dkanejs.maven.plugins:docker-compose-maven-plugin:1.0.1:down

./gradlew clean build composeUp
./gradlew composeDown
```

generated by [daggerok-fatjar](#) yeoman generator

in fucking progress...

1. [book](#)
2. [youtube](#)
3. [Github: sdaschner/scalable-coffee-shop](#)

kafka

```
cd /tmp
wget -O kafka.jar https://github.com/daggerok/embedded-kafka/raw/mvn-repo/daggerok/embedded-kafka/0.0.1/embedded-kafka-0.0.1.jar
java -jar kafka.jar
```

gradle

```
./gradlew
bash build/libs/*jar

./gradlew build composeUp
./gradlew composeDown
```

Chapter 4. maven is not working properly

actually working but with hack (see src/main/webapp/WEB-INF/classes/README)

maven

```
./mvnw  
java -jar target/*.jar  
  
./mvnw; ./mvnw com.dkanejs.maven.plugins:docker-compose-maven-plugin:1.0.1:up  
./mvnw com.dkanejs.maven.plugins:docker-compose-maven-plugin:1.0.1:down
```

generated using [daggerok-fatjar](#) yeoman generator

inside:

1. java 8 based project
2. javaee 8.0 using wildfly-swarm micro-profile
3. kotlin support
4. lombok (slf4j + logback logging)
5. vavr (javaslang)
6. support maven
7. support gradle
8. supports testing junit 4 / 5
9. docker / docker-compose support

```
./gradlew  
bash build/libs/*.jar  
  
./gradlew build composeUp  
./gradlew composeDown
```

```
./mvnw  
java -jar target/*.jar  
  
./mvnw; ./mvnw com.dkanejs.maven.plugins:docker-compose-maven-plugin:1.0.1:up  
./mvnw com.dkanejs.maven.plugins:docker-compose-maven-plugin:1.0.1:down
```

generated using [daggerok-fatjar](#) yeoman generator

inside:

1. java 8 based project

2. javaee 8.0
3. lombok (slf4j + logback logging)
4. vavr (javaslang)
5. support maven
6. support gradle
7. supports testing junit 4 / 5
8. docker / docker-compose support (JBoss EAP 7)

build

```
./mvnw clean package com.dkanejs.maven.plugins:docker-compose-maven-plugin:1.0.1:up
./mvnw com.dkanejs.maven.plugins:docker-compose-maven-plugin:1.0.1:down

./gradlew clean build composeUp
./gradlew composeDown
```

Chapter 5. JavaEE Wildfly-Swarm Micro-Profile using Gradle

5.1. wildfly-swarm-gradle

This repository contains simple JavaEE JAX-RS Wildfly Swarm Micro-profile example playground application

using gradle / java microprofile

```
bash gradlew clean build
java -Djava.net.preferIPv4Stack=true -jar build/libs/wildfly-swarm-gradle-swarm.jar
http :8080
```

using docker

```
docker build --force-rm -f ./docker/src/Dockerfile -t docker-java-ee-examples .
docker run -d -p 8080:8080 --rm --name wildfly-swarm-gradle docker-java-ee-examples
http :8080
docker rm -f -v wildfly-swarm-gradle
```

using docker-compose

```
docker-compose -f ./docker/src/docker-compose.yml up -d
http :8080
docker-compose -f ./docker/src/docker-compose.yml down -v
```

using docker swarm stack deploy

```
docker swarm init
docker service create --detach=false --name registry --publish 5000:5000 registry:2
docker build -f ./docker/src/Dockerfile -t 127.0.0.1:5000/app .
docker push 127.0.0.1:5000/app
#docker-compose -f ./docker/src/stack-deploy.yml build --force-rm --no-cache --pull
#docker-compose -f ./docker/src/stack-deploy.yml push
docker stack deploy --compose-file ./docker/src/stack-deploy.yml java-ee
docker stack services --filter name="java-ee_app" --format="{{.Name}} {{.Replicas}}"
java-ee
docker service scale --detach=false java-ee_app=2

sleep 15
docker stack services java-ee

http :8080

docker swarm leave --force
docker system prune -af
```

links:

1. [Eclipse MicroProfile](#)
2. [Wildfly Swarm Micro-Profile](#)
3. [Wildfly Swarm Book](#)
4. [wildfly-swarm fails on travis-ci](#)
5. [wildfly-swarm gradle plugin](#)

Chapter 6. JavaEE Wildfly-Swarm Micro-Profile using Maven

6.1. wildfly-swarm-maven

This repository contains simple JavaEE JAX-RS Wildfly Swarm Micro-profile example playground application

using maven

```
mvn -Djava.net.preferIPv4Stack=true wildfly-swarm:run  
http :8080
```

using wildfly swarm microprofile

```
mvn clean package  
java -Djava.net.preferIPv4Stack=true -jar target/java-ee-examples-0.0.0-swarm.jar  
http :8080
```

using docker

```
docker build --force-rm -f ./docker/src/Dockerfile -t docker-java-ee-examples .  
docker run -d -p 8080:8080 --rm --name wildfly-swarm-maven docker-java-ee-examples  
http :8080  
docker stop wildfly-swarm-maven
```

using docker-compose

```
docker-compose -f ./docker/src/docker-compose.yml up -d  
http :8080  
docker-compose -f ./docker/src/docker-compose.yml down -v
```

using docker swarm stack deploy

```
docker swarm init
docker service create --detach=false --name registry --publish 5000:5000 registry:2
docker build -f ./docker/src/Dockerfile -t 127.0.0.1:5000/app .
docker push 127.0.0.1:5000/app
#docker-compose -f ./docker/src/stack-deploy.yml build --force-rm --no-cache --pull
#docker-compose -f ./docker/src/stack-deploy.yml push
docker stack deploy --compose-file ./docker/src/stack-deploy.yml java-ee
docker stack services --filter name="java-ee_app" --format="{{.Name}} {{.Replicas}}"
java-ee
docker service scale --detach=false java-ee_app=2

sleep 30
docker stack services java-ee

http :8080

docker swarm leave --force
docker system prune -af
```

links:

1. [Eclipse MicroProfile](#)
2. [Wildfly Swarm Micro-Profile](#)
3. [Wildfly Swarm Book](#)
4. [wildfly-swarm fails on travis-ci](#)

Chapter 7. Kumuluzee MicroProfile 1.0

7.1. kumuluzee-microprofile-1.0

This repository contains simple JavaEE Wildfly Swarm Micro-profile example - serving static content

using gradle / java microprofile

```
bash gradlew clean build
java -Djava.net.preferIPv4Stack=true -jar build/libs/wildfly-swarm-gradle-swarm.jar
http :8080
```

Chapter 8. JavaEE Kubernetes

8.1. java-kube-ee

This repository contains simple JavaEE JAX-RS Wildfly Swarm Micro-profile example playground application

prepare kubernetes cluster, build docker image, push into local registry

```
minikube start --cpus=4 --memory=4096
eval (minikube docker-env)
docker run -d --rm --name registry -p 5000:5000 registry:2
docker build -t 127.0.0.1:5000/app -f ./docker/src/Dockerfile .
docker push 127.0.0.1:5000/app
```

create kubernete yaml file

```
vim ./docker/k8s/app.yml

kubectl apply -f ./docker/k8s/app.yml --validate=false

kubectl get svc -o wide
NAME          TYPE          CLUSTER-IP    EXTERNAL-IP    PORT(S)          AGE
SELECTOR
app           NodePort      10.0.0.189    <none>         8080:32464/TCP   3m           app=app

curl 192.168.99.100:32464
# or
http (minikube service app --url)
22:21:09

[
  "one",
  "two",
  "three",
  "kubeee"
]
```

now update code and redeploy app

deploy app

```
bash gradlew clean build
docker build -t 127.0.0.1:5000/app:v2 -f ./docker/src/Dockerfile .
docker push 127.0.0.1:5000/app:v2
vim ./docker/k8s/app.yml # update image: 127.0.0.1:5000/app:v2
kubectl apply -f ./docker/k8s --validate=false
```

terminal 1

```
kubectl get pods -w                23:59:35
NAME                                READY   STATUS    RESTARTS   AGE
app-1515935557-411m1               1/1     Running   0           10m
app-1515935557-4d3gf               1/1     Terminating   0           4m
app-1515935557-4d3gf               0/1     Terminating   0           4m
app-3366916455-bw6m9               0/1     Pending       0           0s
app-3366916455-bw6m9               0/1     ContainerCreating   0           0s
app-3366916455-bw6m9               1/1     Running       0           1s
```

terminal 2

```
while true; curl (minikube service app --url); echo""; sleep 1; end
["one","two","three","kubeee"]
["one","two","three","kubeee"]
Waiting, endpoint for service is not ready yet...
["one","two","three","kubeee","2017-10-02T21:12:34.095Z"]
["one","two","three","kubeee","2017-10-02T21:12:36.182Z"]
```

second test but using ip, not minikube service

redploy app prev version

```
vim ./docker/k8s/app.yml # update image: 127.0.0.1:5000/app
kubectl apply -f ./docker/k8s --validate=false
```

terminal 1

```
kubectl get pods -w                23:59:35
NAME                                READY   STATUS    RESTARTS   AGE
app-1515935557-411m1               1/1     Running   0           10m
...
app-1515935557-4d3gf               1/1     Terminating   0           4m
app-1515935557-4d3gf               0/1     Terminating   0           4m
...
app-3366916455-bw6m9               0/1     Pending       0           0s
app-3366916455-bw6m9               0/1     ContainerCreating   0           0s
app-3366916455-bw6m9               1/1     Running       0           1s
```

terminal 2

```
while true; curl 192.168.99.100:32161; echo""; sleep 1; end
["one","two","three","kubeee"]
["one","two","three","kubeee"]
Waiting, endpoint for service is not ready yet...
["one","two","three","kubeee","172.17.0.5"]
["one","two","three","kubeee","172.17.0.6"]
```


autoscale

```
kubectl autoscale deployment app --min=2 --max=3
```

scale down

```
kubectl scale deployment app --replicas=3
```

cleanup

```
kubectl delete all -l name=app
# or
kubectl delete service app; kubectl delete deployment app

minikube stop; minikube delete
```

8.2. old

using gradle / java microprofile

```
bash gradlew clean build
java -Djava.net.preferIPv4Stack=true -jar build/libs/java-kube-ee-swarm.jar
http :8080
```

e2e tests using bash scripts)

```
bash ./docker/bin/test-dockerfile.bash      # docker
bash ./docker/bin/test-docker-compose.bash  # docker compose
bash ./docker/bin/test-stack-deploy.bash    # docker swarm cluster
```

links

1. [like so](#)

Chapter 9. JavaEE using Kotlin

9.1. java-kube-ee

This repository contains simple JavaEE JAX-RS Wildfly Swarm Micro-profile example playground application

prepare kubernetes cluster, build docker image, push into local registry

```
minikube start --cpus=4 --memory=4096
eval (minikube docker-env)
docker run -d --rm --name registry -p 5000:5000 registry:2
docker build -t 127.0.0.1:5000/app -f ./docker/src/Dockerfile .
docker push 127.0.0.1:5000/app
```

create kubernete yaml file

```
vim ./docker/k8s/app.yml

kubectl apply -f ./docker/k8s/app.yml --validate=false

kubectl get svc -o wide
NAME          TYPE          CLUSTER-IP    EXTERNAL-IP    PORT(S)          AGE
SELECTOR
app           NodePort      10.0.0.189    <none>         8080:32464/TCP   3m           app=app

curl 192.168.99.100:32464
# or
http (minikube service app --url)
22:21:09

[
  "one",
  "two",
  "three",
  "kubeee"
]
```

now update code and redeploy app

deploy app

```
bash gradlew clean build
docker build -t 127.0.0.1:5000/app:v2 -f ./docker/src/Dockerfile .
docker push 127.0.0.1:5000/app:v2
vim ./docker/k8s/app.yml # update image: 127.0.0.1:5000/app:v2
kubectl apply -f ./docker/k8s --validate=false
```

terminal 1

```
kubectl get pods -w          23:59:35
NAME          READY   STATUS    RESTARTS   AGE
app-1515935557-411m1  1/1     Running   0           10m
app-1515935557-4d3gf  1/1     Terminating 0           4m
app-1515935557-4d3gf  0/1     Terminating 0           4m
app-3366916455-bw6m9  0/1     Pending   0           0s
app-3366916455-bw6m9  0/1     ContainerCreating 0           0s
app-3366916455-bw6m9  1/1     Running   0           1s
```

terminal 2

```
while true; curl (minikube service app --url); echo""; sleep 1; end
["one","two","three","kubeee"]
["one","two","three","kubeee"]
Waiting, endpoint for service is not ready yet...
["one","two","three","kubeee","2017-10-02T21:12:34.095Z"]
["one","two","three","kubeee","2017-10-02T21:12:36.182Z"]
```

second test but using ip, not minikube service

redploy app prev version

```
vim ./docker/k8s/app.yml # update image: 127.0.0.1:5000/app
kubectl apply -f ./docker/k8s --validate=false
```

terminal 1

```
kubectl get pods -w          23:59:35
NAME          READY   STATUS    RESTARTS   AGE
app-1515935557-411m1  1/1     Running   0           10m
...
app-1515935557-4d3gf  1/1     Terminating 0           4m
app-1515935557-4d3gf  0/1     Terminating 0           4m
...
app-3366916455-bw6m9  0/1     Pending   0           0s
app-3366916455-bw6m9  0/1     ContainerCreating 0           0s
app-3366916455-bw6m9  1/1     Running   0           1s
```

terminal 2

```
while true; curl 192.168.99.100:32161; echo""; sleep 1; end
["one","two","three","kubeee"]
["one","two","three","kubeee"]
Waiting, endpoint for service is not ready yet...
["one","two","three","kubeee","172.17.0.5"]
["one","two","three","kubeee","172.17.0.6"]
```

autoscale

```
kubectl autoscale deployment app --min=2 --max=3
```

scale down

```
kubectl scale deployment app --replicas=3
```

cleanup

```
kubectl delete all -l name=app
# or
kubectl delete service app; kubectl delete deployment app

minikube stop; minikube delete
```

9.2. old

using gradle / java microprofile

```
bash gradlew clean build
java -Djava.net.preferIPv4Stack=true -jar build/libs/java-kube-ee-swarm.jar
http :8080
```

e2e tests using bash scripts)

```
bash ./docker/bin/test-dockerfile.bash      # docker
bash ./docker/bin/test-docker-compose.bash  # docker compose
bash ./docker/bin/test-stack-deploy.bash    # docker swarm cluster
```

links

1. [like so](#)

9.3. kotlin-plugins-java-ee

This repository contains simple JavaEE JAX-RS Wildfly Swarm Micro-profile example using Kotlin

```
bash gradlew clean build
bash build/libs/*-swarm.jar

http :8080
http :8080/max
```

9.4. main-swarm-rest-api

This repository contains simple JavaEE JAX-RS Wildfly Swarm Micro-profile example playground application

using gradle / java microprofile

```
bash gradlew clean build
java -Djava.net.preferIPv4Stack=true -jar build/libs/wildfly-swarm-gradle-swarm.jar
http :8080
http :8080/api
http :8080/api/max
```

9.5. main-swarm-static-content

This repository contains simple JavaEE Wildfly Swarm Micro-profile example - serving static content

using gradle / java microprofile

```
bash gradlew clean build
java -Djava.net.preferIPv4Stack=true -jar build/libs/wildfly-swarm-gradle-swarm.jar
http :8080
```

9.6. kotlin-java-ee-payara-docker

This repository contains simple JavaEE JAX-RS Wildfly Swarm Micro-profile example using Kotlin

```
./gradlew clean war
docker-compose up --force-recreate --build --remove-orphans
http :8080/payara-app/
http :8080/payara-app/max
docker-compose down -v
```

9.7. kotlin-javaee-cdi-h2

according to default \${JBOSS_HOME}/standalone/configuration/standalone.xml

```
<!-- skepped... -->
<datasource jndi-name="java:jboss/datasources/ExampleDS" pool-name="ExampleDS"
enabled="true" use-java-context="true">
<!-- skepped... -->
```

build and test

```
docker-compose down -v; ./gradlew; ./mvnw; docker-compose up --build --force-recreate
--remove-orphans
# gradle
http get :8080/kotlin-ee/
http get :8080/kotlin-ee/get-all
http post :8080/kotlin-ee/save-some
http get :8080/kotlin-ee/get-all
# maven
http get :8081/kotlin-ee/
http get :8081/kotlin-ee/get-all
http post :8081/kotlin-ee/save-some
http get :8081/kotlin-ee/get-all
```

Just JBoss EAP in Docker

Chapter 10. JBoss EAP in Docker

10.1. faces

build

```
./mvnw clean package com.dkanejs.maven.plugins:docker-compose-maven-plugin:1.0.1:up
./mvnw com.dkanejs.maven.plugins:docker-compose-maven-plugin:1.0.1:down

http :8080/app/

./gradlew clean build composeUp
./gradlew composeDown
```

links:

1. [facelets oracle tutorial](#)
2. [JAX-RS redirect](#)
3. [Java Platform, Enterprise Edition \(Java EE\) 8 The Java EE Tutorial](#)
4. [Java Platform, Enterprise Edition \(Java EE\) 8 Your First Cup: An Introduction to the Java EE Platform](#)

generated by [daggerok-fatjar](#) yeoman generator === facelets-example

build

```
./mvnw clean package com.dkanejs.maven.plugins:docker-compose-maven-plugin:1.0.1:up
./mvnw com.dkanejs.maven.plugins:docker-compose-maven-plugin:1.0.1:down

http :8080/app/
http :8080/app/health
http :8080/app/faces/index.xhtml

./gradlew clean build composeUp
./gradlew composeDown
```

links:

1. [facelets oracle tutorial](#)
2. [JAX-RS redirect](#)
3. [Java Platform, Enterprise Edition \(Java EE\) 8 The Java EE Tutorial](#)
4. [Java Platform, Enterprise Edition \(Java EE\) 8 Your First Cup: An Introduction to the Java EE Platform](#)

generated by [daggerok-fatjar](#) yeoman generator

10.2. jboss-eap-ext.js

packaging two WARs into jboss AS

Using JBoss EAP 6.4 in docker

```
./mvnw clean install -U -T 4; docker-compose up --build --force-recreate  
  
open localhost:8080/ui/  
  
docker-compose down -v
```

10.3. xmlrpc

Apache XML-RPC (org.apache.xmlrpc)

variations:

1. [monolith](#)
2. [micro-server](#)
3. [micro-client](#)

build and test

```
docker-compose down -v; ./mvnw clean package; docker-compose up --build
```

10.4. ear

build

```
./mvnw clean package -U
```

docker

```
docker-compose up --build --force-recreate --remove-orphans  
docker-compose down -v  
# docker rm -f -v (docker ps -a|grep -v CONTAINER|awk '{print $1}')
```

testing

```
http :8080/module-1/  
http :8080/module-2/  
http :8080/module-3/  
http :8080/module-4/
```


lombok for java 7 (maven)

```
<dependency>
  <groupId>org.projectlombok</groupId>
  <artifactId>lombok</artifactId>
  <version>1.14.2</version>
  <scope>provided</scope>
</dependency>
```

lombok for java 7 (gradle)

```
dependencies {
  compileOnly 'org.projectlombok:lombok:1.14.2'
}
```

10.5. ejb-2

build

```
./mvnw clean package -U
```

docker

```
docker-compose up --build --force-recreate --remove-orphans
docker-compose down -v
# docker rm -f -v (docker ps -a|grep -v CONTAINER|awk '{print $1}')
```

1. Classic EJB 2.1 Local + Remote interfaces:

1. ejb-modules/greeter-impl
2. ejb-modules/greeter-local-api
3. ejb-modules/greeter-remote-api
4. client-modules/greeter-remote-client

2. Using remote EJB interface only:

1. ejb-modules/remote-only-api
2. ejb-modules/remote-only-impl
3. client-modules/remote-only-client

3. Access EJB locally:

1. ejb-modules/goodbyer-impl
2. ejb-modules/goodbyer-local-api
3. client-modules/goodbyer-local-client

testing (remote ejb call)

```
http :8080/greeter-remote-client/  
http :8080/remote-only-client/  
http :8080/goodbyer-local-client/
```

links:

1. [EJB 2.1 deployment descriptor](#)

10.6. timer

build and test

```
docker-compose down -v; ./mvnw; docker-compose up --build  
http :8080/client/start  
http :8080/client/stop
```

10.7. timer-async-ejb

build and test

```
docker-compose down -v; ./mvnw; docker-compose up --build  
http :8080/client/start; sleep 3; http :8080/client/stop  
http :8080/client/max\?name=bax  
http :8080/client/max  
http :8080/client
```

10.8. ejb-3-java-ee-7

build and test

```
docker-compose down -v; ./mvnw; docker-compose up --build  
http :8080/client/start; sleep 3; http :8080/client/stop  
http :8080/client/fax\?name=max  
http :8080/client/bax  
http :8080/client
```

10.9. ejb-stateful-singleton

build and test

```
docker-compose down -v; ./mvnw; docker-compose up --build
http :8080/client/
http :8080/client/get?key=EJB
http post :8080/client/set?key=EJB&value=some-value
http :8080/client/get?key=EJB
http post :8080/client/counter/increment
http post :8080/client/counter/decr
http post :8080/client/counter/incr
http :8080/client/get?key=EJB
http post :8080/client/reset
```

10.10. jboss-eap-h2-ejb

according to default `${JBOSS_HOME}/standalone/configuration/standalone.xml`

```
<!-- skepped... -->
<datasource jndi-name="java:jboss/datasources/ExampleDS" pool-name="ExampleDS"
enabled="true" use-java-context="true">
<!-- skepped... -->
```

build and test

```
docker-compose down -v; ./mvnw; docker-compose up --build --force-recreate --remove
-orphans
http post :8080/client/update/max
http post :8080/client/update/maxp
http post :8080/client/update/amaxp
http :8080/client/
http post :8080/client/update/max?remove=true
http :8080/client/
```

links:

1. [eap 6](#)

10.11. plain HTTP Servlet

JBoss EAP 7.1

build and run using docker

```
docker-compose down -v; ./mvnw clean package; ./gradlew clean build; docker-compose up --build --force-recreate --remove-orphans
```

```
http :8081/plain-http-servlet/  
http :8082/plain-http-servlet/
```

project structure

```
mkdir -p src/main/java/daggerok \  
        src/main/webapp/WEB-INF  
  
touch src/main/java/daggerok/AppServlet.java \  
        src/main/webapp/WEB-INF/web.xml \  
        build.gradle \  
        pom.xml
```

vim src/main/java/daggerok/AppServlet.java

```
@WebServlet("/")  
public class AppServlet extends HttpServlet {  
  
    @Override  
    public void service(final ServletRequest req, final ServletResponse res) throws  
ServletException, IOException {  
        final PrintWriter writer = res.getWriter();  
        writer.println("<b>hi!</b>");  
        writer.close();  
    }  
}
```

vim src/main/webapp/WEB-INF/web.xml

```
<?xml version="1.0" encoding="UTF-8"?>  
<web-app xmlns="http://xmlns.jcp.org/xml/ns/javaee"  
        xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"  
        xsi:schemaLocation="http://xmlns.jcp.org/xml/ns/javaee  
http://xmlns.jcp.org/xml/ns/javaee/web-app_3_1.xsd"  
        version="3.1">  
</web-app>
```

vim build.gradle

```
plugins {  
    id "war"  
}  
  
group "daggerok"  
version "0.0.1"  
description "ololo trololo"  
sourceCompatibility = targetCompatibility = JavaVersion.VERSION_1_7  
  
war {  
    archiveName = "${project.name}.war"  
}  
  
repositories {  
    mavenCentral()  
}  
  
dependencies {  
    providedCompile "javax.servlet:javax.servlet-api:3.1.0"  
}
```

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns=
"http://maven.apache.org/POM/4.0.0"
    xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
http://maven.apache.org/xsd/maven-4.0.0.xsd">

    <modelVersion>4.0.0</modelVersion>

    <groupId>daggerok</groupId>
    <artifactId>plain-http-servlet</artifactId>
    <version>0.0.1</version>
    <packaging>war</packaging>

    <name>plain-http-servlet</name>
    <description>ololo trololo</description>

    <properties>
        <maven.compiler.source>1.7</maven.compiler.source>
        <maven.compiler.target>1.7</maven.compiler.target>
        <project.build.sourceEncoding>UTF-8</project.build.sourceEncoding>
    </properties>

    <dependencies>
        <dependency>
            <groupId>javax.servlet</groupId>
            <artifactId>javax.servlet-api</artifactId>
            <version>3.1.0</version>
            <optional>true</optional>
        </dependency>
    </dependencies>

    <build>
        <finalName>${project.artifactId}</finalName>
        <defaultGoal>clean package</defaultGoal>

        <plugins>
            <plugin>
                <groupId>org.apache.maven.plugins</groupId>
                <artifactId>maven-war-plugin</artifactId>
                <version>2.5</version>
                <configuration>
                    <failOnMissingWebXml>>false</failOnMissingWebXml>
                </configuration>
            </plugin>
        </plugins>
    </build>
</project>
```

Chapter 11. TomEE in Docker

11.1. tomee-ext.js

packaging two WARs in TomEE in Docker

Using TomEE in docker

```
./mvnw clean package -U -T 2
docker-compose up --build

open localhost:8080/ui/
open localhost:8080/rest-api/health

docker-compose down -v
```

Chapter 12. Glassfisg in Docker

12.1. glassfish-ext.js

packaging two WARs in glassfish in Docker

Using Glassfish 5.0 in docker (alpine)

```
./mvnw clean package -U -T 2
docker-compose up --build --force-recreate --remove-orphans
http :8080/ui/
docker-compose down -v
```


Chapter 13. JBoss WildFly (mvnw / gradlew) in Docker

13.1. forge-ws

init new maven project using forge cli

```
forge
project-new \
  --named forge-ws2 \
  --top-level-package daggerok \
  --final-name forge-ws \
  --type war
```

add maven wrapper

```
cd maven-forge-project/
mvn -N io.takari:maven:wrapper
```

build

```
./mvnw clean package -U -T 4
```

docker - see docker-compose and src/main/docker/Dockerfile

```
docker-compose up --build --force-recreate --remove-orphans
docker-compose down -v
# docker rm -f -v (docker ps -a|grep -v CONTAINER|awk '{print $1}')
```

testing

```
http :8080/app/v1/api
http :8080/app/UserService?wsdl
curl -XPOST http://localhost:8080/app/User --header "content-type:text/xml" -d
@./src/test/resources/empty-request.xml | xmllint --format -
curl -XPOST http://localhost:8080/app/User --header "content-type:text/xml" -d
@src/test/resources/named-request.xml | xmllint --format -
```

lombok for java 7 (maven)

```
<dependency>
  <groupId>org.projectlombok</groupId>
  <artifactId>lombok</artifactId>
  <version>1.14.2</version>
  <scope>provided</scope>
</dependency>
```

lombok for java 7 (gradle)

```
dependencies {
  compileOnly 'org.projectlombok:lombok:1.14.2'
}
```

links:

1. [jax-ws oracle tutorial](#)
2. [JBoss Forge 2, Java EE easily, so easily](#)

Chapter 14. JBoss forge / WildFly Java EE 6 / JAX-WS

14.1. forge-javaee-6-ws

up and running

```
./mvnw clean package -U -T 2; docker-compose up --build --force-recreate --remove-orphans
```

```
http :8080/app/health  
http :8080/app/AppEndpoint\?wsdl
```

```
curl -XPOST http://localhost:8080/app/AppEndpoint --header "content-type:text/xml" -d  
@request.xml | xmllint --format -
```

MicroProfile 1.1.0 (CDI + JAX-RS + JSON-P)

TODO

MicroProfile 1.2 (CDI + JAX-RS + JSON-P)

Chapter 15. Kumuluzee MicroProfile 2.0 (config.yaml)

15.1. kumuluzee-config

[see rpc-app module](#)

Chapter 16. Kumuluzee MicroProfile 2.0 (JAX-WS)

16.1. kumuluzee-mp-2.0-jax-ws

in progress...

up and running

```
./mvnw clean package -U; java -jar target/*.jar

http :8000
http :8000/api/v1/ws
http :8000/api/v1/ws?WSDL

curl -XPOST http://localhost:8000/api/v1/ws --header "content-type: text/xml" -d
@./request.xml | xmllint --format -
```

docker / docker-compose

```
./mvnw
docker-compose up --force-recreate --remove-orphans

http :8000
http :8000/api/v1/ws
http :8000/api/v1/ws?WSDL

curl -XPOST http://localhost:8000/api/v1/ws --header "content-type: text/xml" -d
@./request.xml | xmllint --format -

docker-compose down -v
```

Chapter 17. links

1. [Java Platform, Enterprise Edition \(Java EE\) 8 The Java EE Tutorial](#)
2. [Java Platform, Enterprise Edition \(Java EE\) 8 Your First Cup: An Introduction to the Java EE Platform](#)
3. [Reactive JavaEE \(Vert.x / KumuluzEE\)](#)
4. [KumuluzEE tutorials](#)
5. [KumuluzEE samples](#)
6. [Configuration beyond Java EE 8](#)
7. [Unit Testing for Java EE](#)
8. [Interfaces on Demand with CDI and EJB 3.1](#)
9. [The Java EE 6 Tutorial](#)
10. [Asciidoctor attributes](#)

Chapter 18. Enjoy! :)