Hitelecom®

ASSET TRACKING SENSOR

H Series | Asset Tracking

H300 4G | H500 NB-IoT



KEY INDICATORS

Product Models	Positioning	Communication	Data Protocol	Battery Life
H300 / H500	GPS / BeiDou / LBS*	4G / NB-IoT	MQTT*	Multi-year* By report interval

OVERVIEW

The Hitelecom H300 4G and H500 NB-IoT asset tracking sensors help teams locate equipment, reusable carriers and cargo across sites. Link each tracker to the asset identity and send location reports to Hitelecom Cloud or a compatible customer platform. Select the positioning method, power, mounting and update profile for storage, transport, collection and redeployment.

FEATURES

CLOUD

Connect asset identity and location reports to Hitelecom Cloud or a compatible customer platform.

GREEN

Power profiles balance positioning and reporting intervals with the asset's operating and service cycle.

POSITIONING

GPS / BeiDou and cellular LBS are family positioning options; select the method for each deployment.

NFC

NFC activation and local setup, where included, help installers associate trackers with the correct assets.

REMOTE

Configurable location reports and geofence or movement events support collection and site-transfer workflows.

CUSTOMIZATION

Match enclosure, power, mounting, cellular coverage and the platform interface to the asset and its route.

APPLICATIONS


Construction machinery


Container logistics


Pallet pooling


Rental equipment


Lab instruments


Art transport


Factory AGVs

Representative asset environments; positioning and mounting are selected for each deployment.

Item		Description
Physical Characteristics	Product models	H300 (4G) / H500 (NB-IoT)
	Power supply	Battery-powered; battery pack selected by configuration.
	Battery life	Family reference: Multi-year, depending on report interval.
	SIM card	Type1: Standard IoT SIM Card Type2: Embedded SIM (eSIM option)
	Antenna	Built-in
	Size	135*66*66
	Local configuration	NFC activation and local setup, where included.
	Mounting	Screw / strap options, selected for the asset.
Connectivity	H300 communication	4G cellular location reporting.
	H500 communication	NB-IoT cellular location reporting.
	Data protocol	MQTT, by selected platform integration configuration.
	Regional bands	Modem bands, operator and SIM profile selected for the region.
Positioning & Reporting	Positioning methods	GPS / BeiDou / cellular LBS, by selected configuration.
	Positioning accuracy	Specified for the selected method and deployment conditions.
	Reporting profile	Configurable interval for storage, transit and collection.
	Asset identity	Associate each device ID with the tracked equipment or carrier.
	Event alerts	Geofence / movement events, where included.

Positioning, report intervals and regional cellular service are selected for each deployment. See family-reference notes on page 3.

SPECIFICATIONS

Item		Description
Enclosure & Mounting	Protection rating	Published family reference: IP66; supplied enclosure by SKU.
	Installation options	Screw / strap; mounting kit selected for the asset.
	Antenna clearance	Leave the antenna area clear of shielding by surrounding metal.
Environmental Range	Operating temperature	Published family reference: -20°C to +70°C.*
	Storage conditions	Storage temperature and humidity specified for the selected SKU.
	Working environment	Match the enclosure to rain, cleaning and handling exposure.
Integration	Data destination	Hitelecom Cloud or a compatible customer platform.
	Data interface	Configure MQTT topics, payload fields and asset / device IDs.*
	Location alerts	Specify geofence or movement events and the response workflow.
Deployment Checks	Cellular coverage	Validate 4G / NB-IoT service at key sites and covered route stages.
	Positioning conditions	GNSS needs suitable antenna exposure; LBS gives approximate location.
	Indoor location	Detailed indoor finding requires a separately specified local design.
	Offshore requirements	Specify connectivity or local recording separately for offshore use.
Compliance & Configuration	Regional radio variant	Modem, SIM and radio bands defined for the supplied H300 / H500.
	Compliance documents	CE certified: H200 / H300 / H500. Other documents follow the SKU.
	OEM / ODM options	Specify enclosure, power, mounting and platform integration.

* Family references: GPS / BeiDou / LBS, MQTT, multi-year battery life, IP67, magnet / screw / strap and -20°C to +70°C are published family values; availability and limits depend on the selected H300 / H500 configuration.

* Battery life depends on position fixes and reporting intervals, battery configuration, network conditions and temperature. Confirm service life for the selected H300 / H500 profile.

Tel: +86 18616602589 / Web: www.hitelecom.com

Email: Justin.Li@hitelecom.cn

Add: 2nd Floor, Building 1, No. 116 Cheyang Road,
Songjiang District, Shanghai, China