Hitelecom®

WATER LEAK SENSOR

H Series | External Probe

Wireless Water Leak Monitoring



KEY INDICATORS

Detection	4G Model	Wireless	Protection	Battery Life
Water presence At selected point	H300-WL002A H Series	4G / NB-IoT / LoRa	IP67/IP68 Transmitter enclosure	Over 10 years* 10-min sampling 4-hour reporting

OVERVIEW

The Hitelecom H Series wireless water leak sensor brings water-event readings from distributed sensing points to Hitelecom Cloud or a compatible customer platform. Select the sensing assembly, enclosure and 4G, NB-IoT or LoRa variant for the installation. H300-WL002A is the specified 4G model. Detect water reaching selected points around industrial equipment, utilities, data centres and storage areas. Data collection is customer-defined. Reporting is every 4 hours, with a customer-configurable interval; agree notification and recovery settings for the supplied configuration.

FEATURES

CLOUD

Connect to Hitelecom Cloud or a compatible customer platform for water-event data and trends.

GREEN

Low-power design: over 10 years with 10-min sampling and 4-hour reporting at 25°C with normal signal.*

IP68

IP68-rated transmitter enclosure options for demanding indoor and outdoor installations.

NFC

NFC activation and local configuration on supported models; select the method with your variant.

REMOTE

Remote readings and configurable threshold alerts help teams respond to water events and recovery.

CUSTOMIZATION

Match sensing assembly, cable, enclosure and wireless connection to the installation.

* See sensing, battery-life and platform-reference notes on page 3.

APPLICATIONS


Machine cooling


Pump skids


Cable trenches


Data centres


Material storage


Outdoor cabinets


Service tunnels

Illustrative water-leak environments; select sensing points around the actual water source, flow path and installation.

Item		Description
Physical Characteristics	Product models	H200 / H300 / H500
	Power supply	Battery-powered; battery pack selected by configuration.
	Battery life	Over 10 years: 10-min sampling, 4-hour reporting; 25°C ambient, normal signal.*
	SIM card	Type1: Standard IoT SIM Card Type2: Embedded SIM (eSIM option)
	Antenna	Built-in
	Size	135*66*66
	Data protocol	MQTT; agree the data path for the selected wireless variant.
	Reporting profile	Every 4 hours; reporting interval is customer-configurable.
	Local configuration	NFC activation and local setup, where fitted.
	Mounting	Mounting lugs / pole clamp / slotted mount.
Connectivity	Wireless options	4G / NB-IoT / LoRa, by selected variant.
	LTE-FDD bands	B1 / B3 / B5 / B8
	LTE-TDD bands	B34 / B38 / B39 / B40 / B41
Water Detection	Specified 4G model	H300-WL002A
	Monitoring function	Water presence at a selected point; event and recovery by configuration.
	Sensing layout	Point sensing; supported route / coverage by selected assembly.
	Data collection interval	Customer-defined; event settings agreed per project.
	Probe and cable	Probe type, probe length and cable length can be customized.

LTE bands shown are the published family reference. Regional modem, SIM and radio settings depend on the supplied variant.

SPECIFICATIONS

Item		Description
Waterproof Rating	Physical body protection	IP67/IP68 (transmitter enclosure)
	Ingress protection	IP67/IP68 (option)
Reliability	Electrostatic discharge immunity	Contact discharge: 6 kV; air discharge: 8 kV
	Surge immunity	Differential mode: 1 kV; common mode: 2 kV
	Fast transient burst	Power supply circuit: 2 kV
Environmental Range	Operating temperature	-30°C to +75°C (transmitter platform reference)
	Operating humidity	5% to 95% RH (non-condensing)
	Storage temperature	-40°C to +85°C (transmitter platform reference)
Integration	Data destination	Hitelecom Cloud or a compatible customer platform.
	LoRa integration	Match the radio protocol and compatible receiver / gateway.
	Threshold alerts	Agree water-event conditions and the notification workflow.
Certification References CCC / CE / FCC / RoHS	Safety	EN IEC 62368-1:2020+A11:2020
	Health	EN IEC 62311:2020
	EMC	ETSI EN 301 489-1 V2.2.3 (2019-11) ETSI EN 301 489-52 V1.2.1 (2021-11)
	Radio	ETSI EN 301 908-1 V15.2.1 (2023-01) ETSI EN 301 908-13 V13.2.1 (2022-02)
	Frequency range	FDD B1: 1920-1980 MHz TX; 2110-2170 MHz RX FDD B3: 1710-1785 MHz TX; 1805-1880 MHz RX FDD B8: 880-915 MHz TX; 925-960 MHz RX TDD B40: 2300-2400 MHz TX / RX
	Maximum output power	FDD B1: 22.89 dBm max. FDD B3: 23.23 dBm max. FDD B8: 24.02 dBm max. TDD B40: 22.24 dBm max.
	Modulation	QPSK, 16QAM

* Sensing: select the probe and contact arrangement for the liquid and installation. Water detection and transmitter ambient operating limits are separate specifications.

* Battery life: over 10 years with sampling every 10 minutes and reporting every 4 hours, at 25°C ambient with normal signal. Actual service life depends on battery, network and operating conditions.

Platform references: reliability, environmental limits and compliance / radio values are retained from the supplied datasheets; confirm applicability and certificates for the supplied H Series water-leak configuration.

Tel: +86 18616602589 / Web: www.hitelecom.com

Email: Justin.Li@hitelecom.cn

Add: 2nd Floor, Building 1, No. 116 Cheyang Road,
Songjiang District, Shanghai, China