Hitelecom®

EXPLOSION-PROOF GAS SENSOR

H Series | Custom Gas Monitoring

H200 / H300 / H500 | 4G / NB-IoT / LoRa



KEY INDICATORS

CO example shown; supplied channels by order

Gas Options
Gas-specific
More on request

Power Supply
9-24 V DC
External power

Wireless
4G / NB-IoT
/ LoRa

Protection
IP68 option*
Assembly by order

Sampling
Customer-defined
Separate reporting

OVERVIEW

The Hitelecom H Series custom gas sensor combines a gas-specific sensing channel with an externally powered wireless terminal for industrial monitoring. Configure CH4, H2, NH3, O2, SF6, CO2, H2S, CO, SO2 and additional target gases to match the site. Select the sensing principle, range, units, protection and local warning requirements for the actual duty. External 9-24 V DC power supports fixed or ducted installation. Data collection is customer-defined; reporting is set separately through the selected 4G, NB-IoT or LoRa variant to Hitelecom Cloud or an agreed platform.

FEATURES

CLOUD
Send configured gas readings to Hitelecom Cloud or an agreed customer / private platform.

GAS OPTIONS
CH4 / H2 / NH3 / O2 / SF6 / CO2 / H2S / CO / SO2 and more. Channels selected for each project.

YOUR INTERVAL
Customer-defined data collection. Define reporting and alarm timing for the selected monitoring duty.

EXTERNAL POWER
External 9-24 V DC supply. Match the power wiring and entries to the ordered installation.

EXPLOSION-PROOF
Match the required Ex marking, certificate scope and conditions to the classified installation.

NFC / ALERTS
NFC activation and local setup. Agree threshold notifications and required local warning interfaces.

APPLICATIONS


Natural gas & petrochemical


Hydrogen systems


Ammonia refrigeration


Wastewater & biogas


SF6 electrical equipment


Metals & process gas


Industrial CO2 & fermentation

Illustrative industrial environments; gas selection, monitoring points and protection follow the site assessment.

Item		Description
Physical Characteristics	Product models	H200 / H300 / H500; supplied wireless variant confirmed by order.
	Power supply	External power supply
	Input voltage	9-24 V DC
	Sensor Assembly	Selected gas channel, sensing head and gas inlet arrangement follow the supplied configuration.
	Mounting	Fixed or ducted installation, by selected arrangement.
	Display / local warning	Display, sound / light warning and local interfaces follow the ordered configuration.
	Product form / dimensions	Detector, sensing head and accessory dimensions follow the supplied configuration.
Connectivity	Wireless options	4G LTE / NB-IoT / LoRa, by supplied variant and regional network support.
	Data protocol	MQTT for cellular reporting; agree the LoRa receiver / gateway and onward data route.
Gas Measurement	Target gas examples	CH4 / H2 / NH3 / O2 / SF6 / CO2 / H2S / CO / SO2 and more. Select the actual channels by project.
	Measuring range / units	Customized for the target gas and duty; ppm, vol% or %LEL as appropriate.
	Sensing principle	Electrochemical / NDIR / PID options; select a gas-appropriate sensing channel.
	Measurement performance	Range, resolution, accuracy and response time follow the selected gas channel and operating conditions.
	Data collection interval	Customer-defined; supported settings follow the selected configuration and monitoring duty.

The listed gases and sensing principles are configuration choices. Each supplied unit has an agreed channel arrangement, range and units; further target gases can be configured for the project.

SPECIFICATIONS

Item		Description
Waterproof Rating	Published protection option	IP68 customization is listed; the complete supplied assembly rating follows the order.
	Gas inlet / cable entries	Confirm gas-inlet function and protection for the sensing head, cable entries and accessories.
Reliability	Calibration / function tests	Agree target-gas calibration, function testing and reference methods for the selected sensing channel.
	Service / replacement	Follow the selected detector instructions and site service plan; retain calibration and inspection records.
Environmental Range	Operating conditions	Confirm temperature, humidity, condensation, airflow and chemical-exposure limits for the selected detector and supplied assembly.
	Storage conditions	Follow the supplied detector and sensing-element storage conditions; numeric limits are configuration-specific.
Integration	Data destination	Cellular MQTT to Hitelecom Cloud or a customer platform; agree endpoint, payload and authentication.
	LoRa integration	Agree radio protocol, regional channel plan, receiver / gateway and the server route.
	LTE band reference	TDD B34 / B38 / B39 / B40 / B41; FDD B1 / B3 / B5 / B8. Confirm the supplied cellular variant and regional compatibility.
	Reporting / alarms	Set reporting separately from collection. Agree alarm evaluation, upload timing, fault behavior and any required local warning / control path.
Explosion-proof Configuration	Ex marking / certificate	Match the ordered Ex marking, applicable certificate scope and special conditions to the installation.
	Area requirements	Specify site classification, gas / dust group and required temperature class for configuration review.
	Complete assembly	Review detector, gas inlet, enclosure, external power, cable entries and alarm accessories within the required approval.
Certification References CCC / CE / FCC / RoHS	CE platform status	H200 / H300 / H500 CE completed; shared wireless-platform scope.
	Ex / other documents	Confirm the explosion-protection and applicable CCC / FCC / RoHS documents for the supplied configuration.

* Gas lists and sensing technologies are configuration choices. Range, accuracy, response and interference performance follow the selected channel.

* External 9-24 V DC supply. Data collection is customer-defined; sensing, alarm evaluation and reporting requirements are agreed separately.

Tel: +86 18616602589 / Web: www.hitelecom.com

Email: Justin.Li@hitelecom.cn

Add: 2nd Floor, Building 1, No. 116 Cheyang Road, Songjiang District, Shanghai, China