Hitelecom®

LIQUID LEVEL SENSOR

H Series | Submersible Level Monitoring

H200 LoRa | H300 4G | H500 NB



KEY INDICATORS

Measuring Range	Accuracy	Wireless	Protection	Sampling
0-200 m Customizable	±0.5% FS Higher precision option	4G / NB-IoT / LoRa	IP68 enclosure* By configuration	Customer-defined 4-hour reporting

OVERVIEW

The Hitelecom H Series liquid level sensor combines a submersible probe, cable and wireless terminal for tanks, sumps, wells and water sites. Select an application-specific range within the published 0-200 m capability, with ±0.5% FS accuracy and higher precision on request. Match the liquid, probe cable, installation and H200 LoRa, H300 4G or H500 NB-IoT data path to the project. Data collection is customer-defined; data is reported every 4 hours. Send level trends and configured high / low alerts to Hitelecom Cloud or an agreed customer platform.

FEATURES

CLOUD

Send liquid-level readings to Hitelecom Cloud or an agreed customer / private platform.

RANGE / ACCURACY

Up to 200 m, range by application. ±0.5% FS accuracy; higher precision available on request.

YOUR INTERVAL

Customer-defined data collection. 4-hour reporting for level trends and the site response workflow.

CUSTOM CABLE

Specify probe cable and mounting for the liquid, sensing position and practical maintenance access.

LONG LIFE


Published >10-year battery reference. 4-hour reporting profile; runtime reviewed for selected configuration.

NFC / OTA

Supported NFC activation and local setup, with remote firmware updates for the supplied configuration.

APPLICATIONS


Factory water storage


Cooling towers


Process water


Effluent collection


Drainage & pump stations


Mine dewatering


Reservoirs & source water

Illustrative liquid-level environments; match the probe, cable and range to the actual liquid and installation.

Item		Description
Physical Characteristics	Product models	H200 (LoRa) / H300 (4G) / H500 (NB-IoT)
	Power supply	Internal battery; power arrangement by supplied configuration.
	Battery life	Published reference: >10 years under specified test conditions. Reporting profile: every 4 hours. Runtime depends on sensing configuration, sampling, coverage, retransmissions and temperature.
	Probe Assembly	Submersible liquid-level probe with cable and a separate wireless communication terminal.
	Probe cable	Cable length can be adapted to the site; probe, cable and liquid compatibility follow the selected configuration.
	Transmitter mounting	Mounting lugs / pole clamp / slotted mount, by configuration. Place the terminal for reception and service access.
	Product form / dimensions	Probe, cable and terminal dimensions follow the supplied configuration.
Connectivity	Wireless variants	H200 LoRa / H300 4G LTE / H500 NB-IoT; regional radio configuration and coverage by order.
	Data protocol	MQTT for 4G / NB-IoT delivery. Agree the LoRa receiver / gateway and onward server route.
Level Measurement	Measuring range	0-200 m, customizable. Select the full-scale span for the actual level-monitoring task.
	Accuracy	±0.5% FS; higher precision customizable.
	Full-scale basis	Accuracy is a percentage of the selected full scale; match the range to the required level tolerance.
	Data collection interval	Customer-defined; supported settings follow the selected sensing configuration.

Published values are family references for the selected configuration. Define the liquid, maximum level, reference position and required tolerance; confirm probe, cable and vessel suitability with the supplied specification.

SPECIFICATIONS

Item		Description
Waterproof Rating	Published protection	IP68 enclosure listed; component placement and immersion conditions follow the supplied configuration.
	Immersion / cable entries	Confirm maximum probe immersion, cable routing and entry protection. Mount the wireless terminal for coverage and service access.
Reliability	Long-term stability	±0.2% FS/year (published reference); distinct from initial measurement accuracy.
	Checks / maintenance	Verify against the defined site level reference; inspect fouling, probe position and cable condition on the agreed schedule.
Environmental Range	Operating temperature	-20°C to +70°C (published). Confirm the probe, liquid and cable limits for the selected configuration.
	Storage temperature	-20°C to +80°C (published).
	Liquid / vessel conditions	Match liquid composition, temperature, solids, vessel pressure and material compatibility to the ordered assembly.
Integration	Data destination	4G / NB-IoT MQTT to Hitelecom Cloud or a customer platform; agree endpoint, payload and authentication.
	LoRa integration	Agree radio protocol, regional channel plan, receiver / gateway and the onward server route.
	Reporting / alerts	Report every 4 hours; sampling is customer-defined. Agree high / low level thresholds, notifications and the site response workflow.
Certification References CCC / CE / FCC / RoHS	CE platform status	H200 / H300 / H500 CE completed; shared wireless-platform scope.
	Other references	CCC / FCC / RoHS documentation follows the applicable supplied configuration and market requirements.

* ±0.5% FS is based on the selected full scale. The 0-200 m family range does not establish a 200 m immersion rating for every component.

* Battery life is a published >10-year family reference under specified test conditions. Review runtime for the selected sensing configuration, customer-defined sampling and 4-hour reporting profile.

Tel: +86 18616602589 / Web: www.hitelecom.com

Email: Justin.Li@hitelecom.cn

Add: 2nd Floor, Building 1, No. 116 Cheyang Road,
Songjiang District, Shanghai, China