

Five9 QM REST API Cookbook

Developer's Guide

February 2024

Version 5.20231127

This guide describes the Five9 QM API that consists of a series of Representational State Transfer (REST) Controllers and Endpoints that accept and reply with JavaScript Object Notation (JSON).

Five9 and the Five9 logo are registered trademarks of Five9 and its subsidiaries in the United States and other countries. Other marks and brands may be claimed as the property of others. The product plans, specifications, and descriptions herein are provided for information only and subject to change without notice, and are provided without warranty of any kind, express or implied. Copyright © 2024 Five9, Inc.

About Five9

Five9 is the leading provider of cloud contact center software, bringing the power of the cloud to thousands of customers and facilitating more than three billion customer interactions annually. Since 2001, Five9 has led the cloud revolution in contact centers, delivering software to help organizations of every size transition from premise-based software to the cloud. With its extensive expertise, technology, and ecosystem of partners, Five9 delivers secure, reliable, scalable cloud contact center software to help businesses create exceptional customer experiences, increase agent productivity and deliver tangible results. For more information visit www.five9.com.

Trademarks

Five9®

Five9 Logo

Five9® SoCoCare™

Five9® Connect™

What's New

Release	Change	Topic
Feb 2024	Remove the MediaDownload endpoint and recorded media.	• Page 36 – Removed Endpoint Details. • Page 17 – Removed RecordedMedia /VOWebAPI/v5/Recordings/RecordedEvent Gets Recorded Event Information. • Page 51 – Removed RecordedMedia /VOWebAPI/v5/RecordedMedia/MediaDownload Gets Links to Download Media Files.
Nov 2023	json update to availability and note.	Endpoint Details, page 36.
June 2023	json update to availability and note.	Endpoint Details, page 36.
Spring 2021	Initial Release	

TABLE OF CONTENTS

REST Compatibility	.	.	.	.	.	.	.	5
Loosely Coupled vs. Tightly Coupled	.	.	.	.	.	.	.	5
cURL	.	.	.	.	.	.	.	5
Base URL	.	.	.	.	.	.	.	6
Supported Verbs	.	.	.	.	.	.	.	6
Authentication	.	.	.	.	.	.	.	6
Content Type	.	.	.	.	.	.	.	7
vFilter Syntax	.	.	.	.	.	.	.	8
Single Items vs. Collections	.	.	.	.	.	.	.	9
Returned Fields	.	.	.	.	.	.	.	11
Requesting Schemas	.	.	.	.	.	.	.	12
Paging	.	.	.	.	.	.	.	13
Order By	.	.	.	.	.	.	.	14
Query String Parameters	.	.	.	.	.	.	.	15
REST Controllers	.	.	.	.	.	.	.	16
REST Controller Endpoints	.	.	.	.	.	.	.	17
Endpoint Details	.	.	.	.	.	.	.	19
REST cURL Samples.	.	.	.	.	.	.	.	51

REST Compatibility

The Five9 QM REST API's are considered RESTful in that they are accessed via Hyper Text Transfer Protocol, contain controllers, offer paging and many other REST features. However, the API's are not considered 100% REST compliant according to the RFC as they do not support all elements of REST, such as oData, order-by, count and other elements considered REST standards. Some of the Five9 QM API elements used for filtering, querying, paging and other features, are proprietary to the Five9 QM API and are explained herein but may not be considered truly RESTful Compliant.

Loosely Coupled vs. Tightly Coupled

The QM REST API is highly dynamic in its ability to accept any incoming data from a sender on POST and report back any data to a getter on GET. Sure, the REST controllers have static defaults that are expected and should be used most of the time, however QM can adjust the class objects based on specific partner and user needs if necessary to dynamically accept and deliver any data. The default is a tightly coupled interface where specific data is expected but the extensibility offers a loosely coupled interface when necessary. Contact your account representative for more details if the defaults are not sufficient.

cURL

Curl is a standard Command line URL tool used to test REST API's. All examples in this document will use curl as their example. In a Windows environment, you may need to escape quotes within your json with a back slash. The json value {"field":"value"} would need to be listed on the command line as {"field\"":"value\""}.

```
curl https://serveraddress/vowebapi/v5/agents/agentinfo
-H "Header"
-d "{\"field\":\"value\"}"
```

Base URL

All REST API Controllers start with a base URL. This base url precedes the controller endpoint and any query string parameters you may be passing. The base url for the REST Controllers is located at <https://serveraddress/vowebapi/v5/>. This location indicates the http or https protocol, the server address, the VOWebApi path and the version of the API. As of the writing of this document the current version of the API is v5. The ServerAddress will be the IP or DNS name of your QM Server. If your instance of QM exists in the QM Cloud, QM Support will provide you with your API server address.

```
curl https://serveraddress/vowebapi/v5/agents/agentinfo
```

Supported Verbs

The REST API controllers support the **POST** verb where appropriate and the **GET** verb where appropriate. Some REST controllers are designed to receive data and therefore expect a **POST** whereas others give back data and therefore expect a **GET**. A REST action with an incorrect verb will result in a response of “*http 501 Not Supported*”. The QM REST API does not support verbs other than **GET** and **POST**. This API is not designed for full data manipulation. There are no provisions for **DELETE** or **UPDATE**.

Authentication

The REST API uses **Bearer Token** authentication in all the controllers. You must include the header “**ApiToken: XXXXX**” in all your REST transactions, where XXXXX is your valid Token. Contact your account representative for an API Bearer Token.

```
curl https://serveraddress/vowebapi/v5/agents/agentinfo  
-H “ApiToken: XXXXX”
```

Content Type

The REST API should use only **JSON**. Do not use the headers **“Content-Type:”** or **“Accept:”** with a value of **“application/xml”** or **“text/xml”**. Always use the header **“Content-Type: application/json”**.

```
curl https://serveraddress/vowebapi/v5/agents/agentinfo  
-H “Content-Type: application/json”  
-H “ApiToken: XXXXX”
```

vFilter Syntax

Although based on similar concepts of the oData ‘filter’ query string parameter, the QM REST API uses a proprietary syntax for filtering similar to the SQL SELECT statement known as **vFilter Syntax**. This syntax uses AND’s, OR’s and Parenthesis allowing for algebraic expressions.

There are 6 main elements to the syntax known as **Field**, **Operator**, **Value**, **Parenthesis**, **Relationship** and **Separator**.

A **Field** is prefixed with **“f.”** then the field name. For example **“f.LName”**.

An **Operator** is prefixed with **“o.”** then any one of the following operator identifiers. For example **“o.eq”**.

eq	EQUAL (=)
ne	NOT EQUAL (<> or !=)
gt	GREATER THAN (>)
ge	GREATER THAN OR EQUAL (>=)
lt	LESS THAN (<)
le	LESS THAN OR EQUAL (<=)
lk	LIKE (LIKE, also supporting % and ? in the data)

vFilter Syntax

A **Value** is prefixed with “**v.**” then any value. For example “v.Smith”. DO NOT use additional characters such as quotes, commas, apostrophes or any other special character, even for string data. Additional characters will be considered part of the data itself and should only be used when the actual value truly exists in the data, such as O’Neil.

A **Parenthesis** is a standalone character. Either open paren (or close paren).

A **Relationship** is an AND or an OR and spelled as such.

A **Separator** is the PIPE symbol |. Remove all pipe symbols from your string data prior to referencing string data via a v.Value element.

Every element of a vFilter syntax must be separated by the PIPE. To filter on agent last name equal to Smith, the vFilter Syntax would be formatted as:

```
curl https://serveraddress/vowebapi/v5/agents/agentinfo  
?filter=f.LName|o.eq|v.Smith
```

The above statement indicates the field (f.) LName should have the operator (o.) Equal to the Value (v.) Smith. Notice the pipe symbol between every element.

To use relationships (AND or OR), string together your syntax accordingly, remembering that every element needs to be separated by a pipe. This statement indicates last name equal Smith or first name equal Joe.

```
curl https://serveraddress/vowebapi/v5/agents/agentinfo  
?filter=f.LName|o.eq|v.Smith|OR|f.FName|o.eq|v.Joe
```


vFilter Syntax

To use algebraic expressions with parenthesis, string together your syntax accordingly, remembering that every element needs to be separated by a pipe, including multiple parens together. This statement indicates ((last name equal Smith or first name equal Joe) and supervisor ID not equal 100).

```
curl https://serveraddress/vowebapi/v5/agents/agentinfo
?filter=(|(|f.LName|o.eq|v.Smith|OR|f.FName|o.eq|v.Joe
|)|AND|f.SupID|o.ne|v.100|)
```

You may essentially type out any combination of Field, Operator, Value, Relationship, Parenthesis and Separator that would equate to a valid parameterized SQL Select Statement. NOTE: Parameterized queries are used internally to prevent SQL injection.

Single Items vs. Collections

In traditional REST fashion, the API controllers are designed to allow **GET** and **GET/Id**. When accessing **GET/Id** you are asking for a single item based on the given Id. This will result in no match or a single element. When accessing **GET**, with or without a filter, you will receive no match, a single element or a collection of elements. See the **Paging** section for dealing with paged collections.

Single Item Sample:

```
curl https://serveraddress/vowebapi/v5/agents/agentinfo/123
-H "Content-Type: application/json"
-H "ApiToken: XXXXX"
```

This example would return the agent information object for the agent with the Id 123.

Single Items vs. Collections

Single Item Result:

```
{
  "ID":"123", "LName":"Smith", "FName":"Joe"
}
```

Collection Sample:

```
curl https://serveraddress/vowebapi/v5/agents/agentinfo/?
filter=f.LName|o.eq|v.Smith&fields=ID,FName,LName&perpag
e=2
```

```
-H "Content-Type: application/json"
```

```
-H "ApiToken: XXXXX"
```

This example would return all agents with the Last Name Smith.

Collection Result:

```
{
  "TotalAgents":5,
  "TotalPages":3,
  "AgentsThisPage":2,
  "ThisPageNumber":1,
  "MaxPerPage":2,
  "NextPageUri":"https://servername/vowebapi/v5/agents/agentinfo?filter=f.LName|o.eq|
    v.Smith&fields=ID,LName,FName&perpage=2&after=345&pagenum=1",
  "AgentsInfo":[
    {"ID":"123","LName":"Smith","FName":"Joe"},
    {"ID":"345","LName":"Smith","FName":"Sue"}
  ]
}
```

Returned Fields

As explained earlier, the API is tightly coupled by default but can be loosely coupled meaning you may specify which fields you would like returned. By default, a call to the API will return all fields in the schema for the controller you are referencing. However, by using the **fields** query string parameter you can list only specific fields you would like returned. In some cases, a few fields may be defaulted in your returned data even if you do not ask for them. This is usually reserved for key data. Request the Controllers Schema to see a list of valid fields.

All Fields Sample:

```
curl https://serveraddress/vowebapi/v5/agents/agentinfo/123
-H "Content-Type: application/json"
-H "ApiToken: XXXXX"
```

The above sample would return all fields for the agent with the Id 123. Notice there is no **fields** query string parameter included.

Individual Fields Sample:

```
curl https://serveraddress/vowebapi/v5/agents/agentinfo/123
&fields=ID,LName,FName
-H "Content-Type: application/json"
-H "ApiToken: XXXXX"
```

This sample would return just the fields ID,LName,FName for the agent with the Id 123. Notice the **fields** query string parameter is included.

Requesting Schemas

All the REST API Controllers support a unique feature that allows you to view its schema, or essentially a list of fields it can return. To access a Controllers Schema, use a **GET/Id** with an Id of **-1**.

```
curl https://serveraddress/vowebapi/v5/agents/agentinfo/-1
-H "Content-Type: application/json"
-H "ApiToken: XXXXX"
```

This example would return all the agent fields with values of null.

The list of fields is truncated for spacing.

```
{
  "ID":null,
  "LName":null,
  "FName":null,
  "Type":null,
  "SupID":null,
  "EvaluatorID":null,
  "WinName":null,
  "Email":null,
  "Active":null,
  "AgentLocation":null,
  "AgentDepartment":null,
  "AgentGroup":null,
  "ScreenCap":null,
  "IP":null,
  "Ext":null
  ...
}
```

Paging

Some REST API controllers require a **filter** query string parameter to limit the number of elements you are returning and some allow you to return all the elements. In either case, there is a default underlying maximum number of elements the API will return in a single call to the server. You may adjust this using the **perpage** query string parameter.

When accessing a REST API controller where you are expecting to receive more than one element, as in **GET**. You will receive the collection of returned elements and the following parameters **TotalElements**, **TotalPages**, **ElementsThisPage**, **ThisPageNumber**, **MaxPerPage** and **NextPageUri**.

TotalElements are the total number of elements found matching your request.

TotalPages are the number of pages it will take to deliver all the elements matching your request.

ElementsThisPage is the number of elements on the current page. This should match the perpage parameter you provided, the built-in default or the remaining items on the last page.

ThisPageNumber is the current page number.

MaxPerPage is the maximum number per page. This should match your perpage parameter or the built-in default, whichever is smaller.

NextPageUri is the location of the next page of data. You should make your initial request, then loop making a request to the NextPageUri until the NextPageUri is null.

Order By

The REST API does not support **OrderBy**. All Controllers will sort their collection of elements based on a logical internal key used for paging. If you absolutely must sort your data, you should retrieve all elements first then supply your own client side method of sorting.

Query String Parameters

Query string parameters are elements added to the URL after the controller end point. These parameters are used to change the behavior of the data returned from the controller. Valid query string parameters that you may list are **filter**, **perpage** and **fields**.

filter is the vFilter Syntax query string you would like to use to select only a subset of data.

perpage is the maximum number of elements you would like returned on any given page of data. If omitted, the API will use its built in default. If your value exceeds the built in default the default will be used.

fields is a list of fields you would like returned. You must list valid fields for the particular controller. Use the -1 ID to get the controller schema. NOTE: Your data may contain some key fields that are necessary even if you did not ask for them.

When retrieving data from a controller that contains multiple pages, you may see a Next Page Uri that has additional query string parameters. These parameters are reserved for built-in paging and should not be used by you on your initial GET to the controller. These parameters are **after** and **pagenum**.

after is the maximum key for this controller that was returned from your query. It will be used to get the next page of data. Do not alter this value.

pagenum is the page number of the current page. It will be incremented by 1 each time you call the next page uri. Do not alter this value.

Query String Parameters

Query String Parameters need not be listed in any particular order. They must follow the controller endpoint and start with a question mark and be separated with an ampersand.

```
?filter=XXX
```

```
?fields=XXX,XXX&perpage=X
```

```
?perpage=X&filter=XXXX&fields=XXX,XXX
```

```
curl https://serveraddress/vowebapi/v5/agents/agentinfo  
/?filter=f.LName|o.eq|v.Smith&fields=ID,FName,LName&  
perpage=2
```

```
-H "Content-Type: application/json"
```

```
-H "ApiToken: XXXXX"
```

REST Controllers

The QM REST API Supports the following Controllers.

Agents - Get Agent Information
</VOWebAPI/v5/Agents/>

Evaluations - Get Evaluation, Assignment, Survey and Agent Review information
</VOWebAPI/v5/Evaluations/>

Recordings - Get Recorded Event information
</VOWebAPI/v5/Recordings/>

SpeechAnalytics - Get Discovery and Transcription information
</VOWebAPI/v5/SpeechAnalytics/>

Admin - Get Users and Profile information
</VOWebAPI/v5/Admin/>

Audit - Get System Audit Information
</VOWebAPI/v5/Audit/>

ValueAddedMetadata - Post Tag Transactions to add metadata to recordings
</VOWebAPI/v5/ValueAddedMetadata/>

PCI - Post Lights Out Pause and Resume messages to control recording
</VOWebAPI/v5/PCI/>

Adherence - Post Agent State messages for agent activity
</VOWebAPI/v5/Adherence/>

CTI - Post Call Event messages to add metadata to recordings
</VOWebAPI/v5/CTI/>

RecordingMetadata - Post End of Call messages for integration and auto import
</VOWebAPI/v5/RecordingMetadata/>

REST Controller Endpoints

The QM REST API Supports the following Controller Endpoints.

Agents

[/VOWebAPI/v5/Agents/AgentInfo](#)
[/VOWebAPI/v5/Agents/AgentType](#)
[/VOWebAPI/v5/Agents/Supervisor](#)

Gets Agent Information
Gets Agent Types
Gets Supervisors

Evaluations

[/VOWebAPI/v5/Evaluations/Evaluator](#)
[/VOWebAPI/v5/Evaluations/Assignment](#)
[/VOWebAPI/v5/Evaluations/Review](#)
[/VOWebAPI/v5/Evaluations/ScoringSession](#)
[/VOWebAPI/v5/Evaluations/Survey](#)

Gets Evaluator Information
Gets Assignment Information
Gets Agent Review Information
Gets Scoring Session Information
Gets Customer Survey Information

Recordings

[/VOWebAPI/v5/Recordings/RecordedEvent](#)

Gets Recorded Event Information

SpeechAnalytics

[/VOWebAPI/v5/SpeechAnalytics/CallDetail](#)
[/VOWebAPI/v5/SpeechAnalytics/CallMetadata](#)
[/VOWebAPI/v5/SpeechAnalytics/CallMark](#)
[/VOWebAPI/v5/SpeechAnalytics/Transcript](#)
[/VOWebAPI/v5/SpeechAnalytics/Discovery](#)

Gets Speech Call Details
Gets Speech Call Metadata
Gets Speech Call Marks
Gets the Recorded Event Transcript
Gets Speech Discovery Information

Admin

[/VOWebAPI/v5/Admin/User](#)
[/VOWebAPI/v5/Admin/Profile](#)

Gets User Information
Gets User Permission Information

REST Controller Endpoints

The QM REST API Supports the following Controller Endpoints.

Audit

</VOWebAPI/v5/Audit/AuditInfo>

Gets System Audit Information

ValueAddedMetadata

</VOWebAPI/v5/ValueAddedMetadata/Tag>

Posts Enterprise Metadata to Events

PCI

</VOWebAPI/v5/PCI/LightsOut>

Posts Event Pause & Resume Msgs

Adherence

</VOWebAPI/v5/Adherence/AgentState>

Posts Agent State for Adherence

CTI

</VOWebAPI/v5/CTI/CallEvent>

Posts CTI Call Events & Metadata

RecordingMetadata

</VOWebAPI/v5/RecordingMetadata/CallObject>

Posts End-of-Call Events & Metadata

Endpoint Details

Uri:	/VOWebApi/v5/agents/agentinfo
Description:	Get Agent Information
Verbs:	GET, GET/Id
Query String Parameters:	GET: filter, fields, perpage GET/Id: fields
Incoming Data:	NONE
Returned Data:	AgentInfo JSON Object
ID	Agent ID
LName	Last Name
FName	First Name
Type	Agent Type
SupID	Supervisor ID
EvaluatorID	Evaluator ID
WinName	Windows Login Name
Email	Email Address
Active	Active Flag
AgentLocation	Agent Location
AgentDepartment	Agent Department
AgentGroup	Agent Group
RecID	Agent ID
ConType	Connection Type
StartTime	Start Time
EndTime	End Time
UseLunch	Use Lunch
LunchStart	Lunch Start
LunchEnd	Lunch End
ScreenCap	Use Screen Capture
CapRate	Capture Rate

Endpoint Details

WrkDays	Working Days
DialStrng	Dial String
IP	IP Address
Ext	Extension
NumRecs	Number Recordings
LenRecs	Length of Recordings
RecSpaceDays	Days Between
RecSpaceTime	Seconds Before Reschedule
LastRec	Last Recording
CurRec	Recordings This Period
NumRetries	Number of Retries
USE_VOX	Use Start VOX
VOX_TIME	Start VOX Time
USE_IN_VOX	Use In VOX
IN_VOX_TIME	In VOX Time
MON_BY_AGENT_ID	Monitor By Agent ID
USE_AUTO_EXTEND	Use Auto Extend
AUTO_EXT_CHECK_TIME	Auto Extend Check Time
AUTO_EXTEND_BY	Auto Extend By
AUTO_EXTEND_AMOUNT	Auto Extend Amount
REMOVE_SILENCE	Remove Silence
FAIL_ON_SCREENCAP	Fail When No Screens
DELETE_FAILED_EVENTS	Delete Failed Events
TCP_TIMEOUT	Wait for Screens
RECEIVE_EVAL_FEEDBACK	Use Feedback
RECEIVE_FEEDBACK_AUDIO	Deliver Audio in Feedback
RECEIVE_FEEDBACK_SCRN	Deliver Screens in Feedback
DisconnectString	Disconnect String
VOX_PAUSE	Pause Before VOX Check
UseFileTrace	Use Debugging

Endpoint Details

ServerTempFolder	Server Temp Screen Folder
LocalTempFolder	Local Temp Screen Folder
CaptureType	Screen Capture Type
AgentClientStatus	Last Agent Status
RecordingMethod	Recording Method
MaxCTIEventLength	Max CTI Event Length
MinCTIEventLength	Min CTI Event Length
ExtCTIEventLength	Extend CTI Events
CTIStartEvents	CTI Start Triggers
CTIStopEvents	CTI End Triggers
BackToBackEvents	Back to Back Events
GrayScale	Discard Calls Unless Saved On Demand

Uri:	/VOWebApi/v5/agents/agenttype
Description:	Get Agent Type Information
Verbs:	GET, GET/Id
Query String Parameters:	GET: filter, fields, perpage GET/Id: fields
Incoming Data:	NONE
Returned Data:	AgentType JSON Object
ID Type	Type ID Type Description

Endpoint Details

Uri:	/VOWebApi/v5/agents/supervisor
Description:	Get Supervisor Information
Verbs:	GET, GET/Id
Query String Parameters:	GET: filter, fields, perpage GET/Id: fields
Incoming Data:	NONE
Returned Data:	Supervisor JSON Object
ID Init LName FName WinName Email	Supervisor ID Initials Last Name First Name Windows Login Name Email Address

Uri:	/VOWebApi/v5/evaluations/evaluator
Description:	Get Evaluator Information
Verbs:	GET, GET/Id
Query String Parameters:	GET: filter, fields, perpage GET/Id: fields
Incoming Data:	NONE
Returned Data:	Evaluator JSON Object
ID LName FName WinName Email	Evaluator ID Last Name First Name Windows Login Name Email Address

Endpoint Details

Uri:	/VOWebApi/v5/evaluations/assignment
Description:	Get Evaluator Assignment Information
Verbs:	GET, GET/Id
Query String Parameters:	GET: filter, fields, perpage GET/Id: fields
Incoming Data:	NONE
Returned Data:	Assignment JSON Object
KeyFld EventNum EvaluatorID Sequence EvaluatorName AgentID AgentName AgentTypeID AgentLocation AgentDepartment AgentGroup SupID SupName DateTimeCreated DateTimeScheduledToStart DateTimeActuallyStarted DateTimeCompleted Status HeaderKey AssignedByWinName Priority	Key Field Event Number Evaluator ID Sequence Num Evaluator Name Agent ID Agent Name Agent Type ID Agent Location Agent Department Agent Group Supervisor ID Supervisor Name Date Created Date Scheduled Date Started Date Completed Status Header Key Assigner Priority

Endpoint Details

Calibration	Calibration
XACTN_TS	Timestamp
RuleKey	Rules Key Field
KeyFld	Key Field
Description	Rule Description
ApplyToEventFilter	Apply To Event Filters
ApplyToEventField	Apply To Event Field
ApplyToEventQuantityType	Amount Type
ApplyToEventQtyAmount	Amount
ApplyToEvaluatorType	Apply To Evaluator Type
ApplyToEvaluatorFilter	Apply To Evaluator Filters
RunInterval	Run Every Interval
RunTimeOfDay	Run Interval Time of Day
RunQuantity	Run Interval Quantity
RunStartDate	Run Start Date
RunEndDate	Run End Date
RunNextDateTime	Next Run Date and Time
LastKnownEndTime	Last Known End Time
StayMinutesBehind	Stay Minutes Behind
ServerNumber	Run on Server Number
CreatedByWinName	Created By User
ScoringQuotaRange	Quota Range
ScoringQuotaQuantity	Quota Amount

Endpoint Details

Uri:	/VOWebApi/v5/evaluations/review
Description:	Get Evaluation Review Information
Verbs:	GET, GET/Id
Query String Parameters:	GET: filter, fields, perpage GET/Id: fields
Incoming Data:	NONE
Returned Data:	Review JSON Object
ReviewHeaderKey	Review ID
ScoreHeaderKey	Evaluation ID
EventNumber	Event Number
AgentID	Agent Name
AgentTypeID	Agent Type
SupervisorID	Supervisor Name
EvaluatorID	Evaluator Name
WinName	Created By Username
EventType	Event Type
PostedDate	Posted Date
ReceiverStatus	Receiver Status
ReviewedDate	Last Reviewed
ReviewedNotes	Agent Notes
ReviewStatus	Review Status
AcceptedDate	Accepted Date
AgentSignatureText	Agent Signature
WaitingOn	Waiting For
RecentlyUpdated	Recently Updated
Collection—>ReviewDisputes	[N] Number of Disputes
Collection—>ReviewActivity	[N] Number of Activity

Endpoint Details

ReviewDisputes

KeyFld	Dispute Key Field
ReviewHeaderKey	Review ID
ScoreHeaderKey	Evaluation ID
EventNumber	Event Number
AgentID	Agent Name
SupervisorID	Supervisor Name
DisputeDate	Dispute Date
DisputedBy	Disputed By
DisputedWinName	Disputed By UserName
DisputedKey	Disputed Item Key
DisputedText	Disputed Item Text
DisputedComment	Disputed Comment
DisputeResult	Dispute Result

ReviewActivity

KeyFld	Activity Key Field
ReviewHeaderKey	Review ID
ScoreHeaderKey	Evaluation ID
EventNumber	Event Number
ActivityBy	Activity By
ActivityWinName	Activity By UserName
ActivityDate	Activity Date
ActivityDescription	Activity Description

Endpoint Details

Uri:	/VOWebApi/v5/evaluations/scoringsession
Description:	Get Evaluation Scoring Session Information
Verbs:	GET, GET/Id
Query String Parameters:	GET: filter, fields, perpage GET/Id: fields
Incoming Data:	NONE
Returned Data:	ScoringSession JSON Object
HeaderKey	Scoring Session ID
EventNum	Recorded Event Number
Segment	Segment Num
Sequence	Sequence Num
Rescore	Rescore Flag
Date	Score Date
EvaluatorID	Evaluator ID
EvaluatorName	Evaluator Name
CallType	Event Type
Template	Scoring Template File
AgentID	Agent ID
AgentName	Agent Name
AgentTypeID	Agent Type ID
SupID	Supervisor ID
SupName	Supervisor Name
OpenComment	Opening Comment
TotalX	Total X
TotalY	Total Y
TotalPercent	Score Percent
TotalDollars	Total Dollars
UpsellDollars	Upsell Dollars

Endpoint Details

CloseComment1	Closing Comment 1
CloseComment2	Closing Comment 2
CloseComment3	Closing Comment 3
CloseComment4	Closing Comment 4
AudioLocation	Audio Location
LearningContent	Learning Content
WithoutKillTotalX	Without Kill Total X
WithoutKillTotalY	Without Kill Total Y
WithoutKillTotalPercent	Without Kill Score Percent
AgentLocation	Agent Location
AgentDepartment	Agent Department
AgentGroup	Agent Group
Collection—>ScoreDetails	[N] Number of Score Details
Collection—>ScoreLearning	[N] Number of Score Learning
ScoreDetails	
DetailKey	Detail Key
HeaderKey	Header Key
Type	Type
Label	Label
EntryType	Entry Type
ThisGeneration	This Generation
PreviousGeneration	Previous Generation
Required	Required
MinValue	Minimum Value
MaxValue	Maximum Value
DefaultValue	Default Value
ApplyToTotal	Apply To Totoal Score
RequireComment	Require a Comment
CommentWhen	Comment when
CommentValue	Comment Value

Endpoint Details

UseColor	Use Color
LessThanValue	Less Than Value
LessThanColor	Less Than Color
GreaterThanValue	Greater Than Value
GreaterThanColor	Greater Than Color
ActualScore	Actual Score
XofY	X of Y
TotPercent	Total Percent
Comment	Comment
EntireTag	Entire Tag
DetailLevel	Detail Level
Color	Color
LearningContentWhen	Deliver Learning Condition
LearningContentAmt	Deliver Learning Amt
LearningContentTitle	Learning Title
LearningContentDocument	Learning Document
LearningContentRequired	Learning Content Is Necessary
WithoutKillActualScore	Without Kill Actual Score
WithoutKillXofY	Without Kill X of Y
WithoutKillTotPercent	Without Kill Total Percent
QuestionValue	Question Value
QuestionMinimum	Question Minimum
QuestionMaximum	Question Maximum
ScoreLearning	
LearningDetailKey	Detail Key
LearningHeaderKey	Header Key
LearningTitle	Title
LearningDocument	Document
LearningDate	Date
LearningAddedOrForced	Added or Forced

Endpoint Details

LearningAgentID	Agent ID
LearningAgentTypeID	Agent Type ID
LearningEvaluatorID	Evaluator ID
LearningSupervisorID	Supervisor ID
LearningCallType	Event Type
LearningTemplate	Template File
LearningEventNum	Event Number
LearningNumClicks	Times Clicked
LearningLastClickDate	Day Last Clicked

Uri:	/VOWebApi/v5/agents/survey
Description:	Get Customer Survey Information
Verbs:	GET, GET/Id
Query String Parameters:	GET: filter, fields, perpage GET/Id: fields
Incoming Data:	NONE
Returned Data:	Survey JSON Object
HeaderKey	Header Key
SurveyEventNum	Event Number
LinkedRecordingEventNum	Linked To Event Number
SurveyUCID	Survey UCID
LinkedRecordingUCID	Linked Event UCID
Date	Survey Date
SurveyDMCCallID	DMCC Call ID
AlertingDevice	Alerting Device
CalledDevice	Called Device
CallingDevice	Calling Device
SurveyDevice	Survey Device

Endpoint Details

SurveyDescription	Survey Description
SurveyConfigurationFile	Survey Configuration File
AgentID	Agent ID
AgentName	Agent Name
AgentType	Agent Type
SupID	Supervisor ID
SupName	Supervisor Name
TotalX	Total X
TotalY	Total Y
TotalPercent	Total Percent
AgentLocation	Agent Location
AgentDepartment	Agent Department
AgentGroup	Agent Group
Collection —> SurveyDetails	[N] Number of Survey Details
Survey Details	
DetailKey	Detail Key
HeaderKey	Header Key
QuestionText	Question Text
Topic	Topic
MinValue	Min Values
MaxValue	Max Value
ApplyToTotal	Apply To Total
Score	Score
ActualValue	Actual Value
QuestionPromptFile	Question Prompt File
QuestionPromptDescription	Question Prompt Description
OptionsPromptFile	Options Prompt File
OptionsPromptDescription	Options Prompt Description
AcceptableDigits	Acceptable Digits
WeightedValues	Weighted Values
Branching	Branching

Endpoint Details

Uri:	/VOWebApi/v5/recordings/recordedevent
Description:	Get Recorded Event Information
Verbs:	GET, GET/Id
Query String Parameters:	GET: filter, fields, perpage GET/Id: fields
Incoming Data:	NONE
Returned Data:	RecordedEvent JSON Object
EVENT_NUM AGENT_ID SUP_ID EXT CHANNEL START_TIME END_TIME EVENT_CODE EVENT_DIR SCAP_RATE EVALUATOR_ID NUM_EVALS NUM_PLAYED NUM_SEGMENTS TOT_HOLD_TIME SCAP_TYPE AGENT_LNAME AGENT_FNAME SUP_LNAME SUP_FNAME AGENT_TYPE	Event Number Agent ID Supervisor ID Extension Recording Port Start Time End Time Result Code Event Location Screen Capture Rate Evaluator ID Times Evaluated Times Played Number of Segments Total Hold Time Screen Capture Type Agent Last Name Agent First Name Supervisor Last Name Supervisor First Name Agent Type

Endpoint Details

EVAL_LNAME	Default Evaluator Last Name
EVAL_FNAME	Default Evaluator First Name
CALL_DURATION	Event Duration
CALL_DIRECTION	Event Direction
CALL_TRUNK	Call Trunk
CALL_ANI	Call ANI
CALL_DNIS	Call DNIS
CTI_CALL_NUM	CTI Call Number
CTI_SERVER_ID	CTI Server ID
CTI_QUEUE	CTI Queue
CTI_USER_DATA	CTI User Data
RETAIN	Retention Flag
EVENT_TYPE	Event Type
INITIATOR	Initiator
SPEECH_INDEXED_DATE	Speech Indexed Date
AGENT_LOCATION	Agent Location
AGENT_DEPARTMENT	Agent Department
AGENT_GROUP	Agent Group
ACCOUNT_NUM	Customer Acct#
FCR_FLAG	FCR Flag
FCR_NUM	FCR Count
FCR_LINKS	FCR Links
ACD_SKILL	ACD Skill
ACD_QUEUE	ACD Queue
ACD_VDN	ACD VDN
HANGUP	Hang Up
CATEGORY	Call Category
CALL_TAG_1	Call Tag 1
CALL_TAG_2	Call Tag 2
CALL_TAG_3	Call Tag 3
HOLD_PERCENT	Hold Time Percent

Endpoint Details

AVOIDANCE	Call Avoidance
FILESIZE_AUDIO	Audio File Size
FILESIZE_VIDEO	Video File Size
FILESIZE_SPEECHINDEX	Speech Index File Size
FILESIZE_TEXTTRANSCRIPT	Text Transcription File Size
EVENT_USER_NUM	User Event Number
EVENT_USER_1	User Defined Field 1
EVENT_USER_2	User Defined Field 2
EVENT_USER_3	User Defined Field 3
EVENT_USER_4	User Defined Field 4
EVENT_USER_5	User Defined Field 5
EVENT_USER_6	User Defined Field 6
EVENT_USER_7	User Defined Field 7
EVENT_USER_8	User Defined Field 8
EVENT_USER_9	User Defined Field 9
EVENT_USER_10	User Defined Field 10
LINK_TO_VO_PLAYER	A url to Play the Event in Virtual Observer
LINK_TO_VO_EVAL	A url to Evaluate the Event in Virtual Observer
LINK_TO_HD_AUDIO	A url to an HD Audio file if it exists
Collection—>UCIDs	[N] Number of Call UCIDs
Collection—>CTIEvents	[N] Number of CTI Events
Collection—>Notes	[N] Number of Event Notes
Collection—PostLog	[N] Number of Posting Log Details
UCIDs	
KEY_FLD	Key Field
EVENT_NUM	Event Number
UCID	Universal Call ID
EVENT_START	Event Start Time

Endpoint Details

CTIEvents

EVENT_NUM	Event Number
SEQ_NUM	Sequence
CTI_EVENT_DATE	Date
CTI_EVENT_TYPE	Type
CTI_EVENT_DURATION	Duration
CTI_CALL_APPEARANCE	Call Appearance
CTI_OTHER_Ext	Other Ext
CTI_OTHER_ID	Other ID

Notes

EVENT_NUM	Event Number
SEQ_NUM	Sequence
NOTES_SECONDS	Seconds Within Event
NOTES_DATE	Date
NOTES_TEXT	Note

PostLog

EVENT_NUM	Event Number
SEQ_NUM	Sequence
AGENT_ID	Agent ID
EVENT_TIME	Time
EVENT_MESSAGE	Message
EVENT_DETAIL	Detail

Endpoint Details

Uri:	/VOWebApi/v5/speechanalytics/calldetail
Description:	Get Speech Call Details
Verbs:	GET, GET/Id
Query String Parameters:	GET: filter, fields, perpage GET/Id: fields
Incoming Data:	NONE
Returned Data:	Speech Detail JSON Object
EVENT_NUM isSuccess errorMessage resultStatus resultMessage estimatedAnalysisComple- tionInHours callStartTime callEndTime duration maskedConversationText originalConversationText originalConversation- TextWithoutHtml isConversationMasked isAnalysed agentText customerText extId callId callerNumber calledNumber	Event Number . . . Various Speech Detail Information . . .

Endpoint Details

callTopics	agentInterruptCount
agentAngerDuration	customerInterruptCount
customerAngerDuration	silenceCount
agentAngerRatio	agentBlockCount
customerAngerRatio	customerBlockCount
agentInterruptRatio	overlapRatio
customerInterruptRatio	agentSpeechDuration
overlapDuration	customerSpeechDuration
agentSpeed	silenceCountPerMinute
agentMonotonicity	agentBlockCountPerMinute
customerGender	customerBlockCountPerMinute
silenceRatio	agentInterruptCountPerMinute
agentConfidence	customerInterruptCountPerMinute
customerConfidence	agentHesitationCountPerMinute
totalSilence	agentMaxAngerRatio
maximumSilence	customerMaxAngerRatio
maximumSilenceStart	holdDuration
maximumSilenceEnd	callMarks
customerShare	
agentBlockRatio	
customerBlockRatio	
agentAngerBeginningLocation	
agentAngerMiddleLocation	
agentAngerEndLocation	
customerAngerBeginningLocation	
customerAngerMiddleLocation	
customerAngerEndLocation	
agentInterruptCount	
customerInterruptCount	
silenceCount	
agentBlockCount	

Endpoint Details

Uri:	/VOWebApi/v5/speechanalytics/callmetadata
Description:	Get Speech Call Metadata
Verbs:	GET, GET/Id
Query String Parameters:	GET: filter, fields, perpage GET/Id: fields
Incoming Data:	NONE
Returned Data:	Speech Metadata JSON Object
EVENT_NUM fullUserName topics isEvaluated callId averageConfidence direction agentAngerLocation customerAngerLocation relatedCallsCount genderText ageText userGroupName userGroupCode nonFcrResolvedStatus articulationScore callUniqueld callTime duration callerNumber calledNumber	Event Number . . . Various Speech Metadata Information . . .

Endpoint Details

isOutOfLicense	agentInterruptCount
ldcServerId	customerInterruptCount
remark	silenceCount
extId	agentBlockCount
isActive	customerBlockCount
creationDate	overlapRatio
agentAngerDuration	agentSpeechDuration
customerAngerDuration	customerSpeechDuration
agentAngerRatio	comment
customerAngerRatio	isAnalysed
agentInterruptRatio	silenceCountPerMinute
customerInterruptRatio	agentBlockCountPerMinute
overlapDuration	customerBlockCountPerMinute
agentSpeed	agentInterruptCountPerMinute
agentMonotonicity	customerInterruptCountPerMinute
customerGender	agentHesitationCountPerMinute
silenceRatio	agentMaxAngerRatio
agentConfidence	customerMaxAngerRatio
customerConfidence	isInvalid
totalSilence	invalidateDate
maximumSilence	invalidateReason
customerShare	holdDuration
agentBlockRatio	nonFcrGroupCode
customerBlockRatio	nonFcrTaggingState
agentAngerBeginningLocation	contentType
agentAngerMiddleLocation	silenceDurationBeginning
agentAngerEndLocation	silenceDurationEnd
customerAngerBeginningLocation	maxOverlap
customerAngerMiddleLocation	userGroupId
customerAngerEndLocation	userId

Endpoint Details

Uri:	/VOWebApi/v5/speechanalytics/callmark
Description:	Get Speech Call Marks
Verbs:	GET, GET/Id
Query String Parameters:	GET: filter, fields, perpage GET/Id: fields
Incoming Data:	NONE
Returned Data:	Speech Call Mark JSON Object
Key EVENT_NUM callId id markType startSecond startDateTime endSecond endDateTime callSide creationDate	Database Key {id} used on GET/{id} Recorded Event Number Internal Number Internal Number Mark Type Start of the Mark, in seconds Start of the Mark, in datetime End of the Mark, in seconds End of the Mark, in datetime Talker that made the mark Datetime when the mark was created MarkType 0 = Block MarkType 1 = Emotion MarkType 2 = Hesitation MarkType 3 = Overlap MarkType 4 = Silence MarkType 5 = MaxSilence MarkType 6 = Hold

Endpoint Details

Uri:	/VOWebApi/v5/speechanalytics/discovery
Description:	Get Speech Discovery Information (Tags/Topics)
Verbs:	GET, GET/Id {Id must be Base64 Encoded}
Query String Parameters:	GET: filter, fields, perpage GET/Id: fields
Incoming Data:	NONE
Returned Data:	Speech Call Discovery JSON Object
ResultKey DetailKey HeaderKey WinName Tag Description Phrase Confidence Location EventNum DateTimeSpoken PostTime Channel	Database Key {id} used on GET/{id} Internal Number Internal Number Internal String Topic Description Spoken Phrase Always 100 Number of Seconds into the call Recorded Event Number Date Time Spoken Date Time Posted Talker

Endpoint Details

Uri:	/VOWebApi/v5/speechanalytics/transcript/id
Description:	Get Speech Transcript
Verbs:	GET/Id {The Id is the recorded event number}
Query String Parameters:	GET: filter, fields, perpage GET/Id: fields
Incoming Data:	NONE
Returned Data:	Speech Transcript JSON Object (Collection)
Key EVENT_NUM Talker SecondsFromStart DateTime Text	Internal Number Recorded Event Number Talker Location in Seconds Location in datetime Spoken Text This endpoint does not support GET. It only supports GET/{id} where ID is the recorded event number. This endpoint returns a collection of conversation blocks. Each time a person speaks, one block is returned. Similar to paragraphs. Only 1 recorded event number can be retrieved at a time. To get recorded event numbers, use the controller: [recordings/recordedevent]

Endpoint Details

Uri:	/VOWebApi/v5/admin/user /VOWebApi/v5/admin/user2
Description:	Get User Information
Verbs:	GET, GET/Id (Note user2 requires base64 id)
Query String Parameters:	GET: filter, fields, perpage GET/Id: fields
Incoming Data:	NONE
Returned Data:	User JSON Object
User Profile	User Name Profile Name

Uri:	/VOWebApi/v5/admin/profile /VOWebApi/v5/admin/profile2
Description:	Get Profile Information
Verbs:	GET/Id (Note profile2 requires base64 id)
Query String Parameters:	NONE
Incoming Data:	NONE
Returned Data:	Profile JSON Object
Profile ProfileSettings	Profile Name Variable Object with Various Settings

Endpoint Details

Uri:	/VOWebApi/v5/audit/auditinfo
Description:	Get System Audit Information
Verbs:	GET, GET/Id
Query String Parameters:	GET: type, filter, fields, perpage GET/Id: type, fields NOTE: For Get and Get/id, both require the type field. Valid values are type=program or type=data.
Incoming Data:	NONE
Returned Data:	User JSON Object
Type=Program AuditProgramKey AuditProgramWinName AuditProgramIPAddress AuditProgramMachineName AuditProgramProgramName AuditProgramVersion AuditProgramDateTime AuditProgramFunction AuditProgramDataKey	Internal Key Users Name who performed the action IP Address of the user performing the action Machine name performing the action Program name that performed the action Program Version Date and Time of the Action The Action Performed Key to the data the action was performed on

Endpoint Details

Type=Data

AuditDataKey	Internal Key
AuditDataWinName	Users Name who performed the action
AuditDataIPAddress	IP Address of the user performing the action
AuditDataMachineName	Machine name performing the action
AuditDataProgramName	Program name that performed the action
AuditDataProgramVersion	Program Version
AuditDataDateTime	Date and Time of the Action
AuditDataTableName	Data table the action was performed on
AuditDataFieldName	Data field the action was performed on
AuditDataAddChangeDelete	Indicates if data was 'Added', 'Changed' or 'Del'
AuditDataOldValue	Value of data prior to change
AuditDataNewValue	Value of data after the change
AuditDataDataKey	Key to the data row that was changed

Endpoint Details

Uri:	/VOWebApi/v5/adherence/agentstate
Description:	Post Agent State Changes
Verbs:	POST
Query String Parameters:	NONE
Returned Data:	HTTP Status, JSON Message
Input Data:	AgentState JSON Object
Valid JSON Input	<pre>{ "User": "jsmith", "PreviousState": "Ready", "State": "NotAvailable", "Reason": "Break" }</pre>

Uri:	/VOWebApi/v5/pci/lightsout
Description:	Post Pause and Resume Recording Messages
Verbs:	POST
Query String Parameters:	NONE
Returned Data:	HTTP Status, JSON Message
Input Data:	LightsOut JSON Object
Valid JSON Input	<pre>{ "User": "jsmith", "Function": "Pause" }</pre>

Endpoint Details

Uri:	/VOWebApi/v5/valueaddedmetadata/tag
Description:	Post Enterprise Metadata to Recorded Events
Verbs:	POST
Query String Parameters:	NONE
Returned Data:	HTTP Status, JSON Message
Input Data:	Tag JSON Object
Valid JSON Input	<pre>{ "User": "jsmith", "Extension": "1234", "TagField1", "medata1", "TagField2", "medata2", "TagField3", "medata3", "TagField4", "medata4", "TagField5", "medata5", "TagField6", "medata6", "TagField7", "medata7", "TagField8", "medata8", "TagField9", "medata9", "TagField10", "medata10" }</pre>

Endpoint Details

Uri:	/VOWebApi/v5/cti/callevnt
Description:	Post Call Events to Recordings
Verbs:	POST
Query String Parameters:	NONE
Returned Data:	HTTP Status, JSON Message
Input Data:	CallEvent JSON Object
Valid JSON Input	<pre>{ "DateTime": "2017-09-20 13:35:10", "EventType": "Ring", "AgentID": "752100", "Extension": "892100", "CallID": "1234567890", "SessionID": "000860123456789123456", "ANI": "8602982151", "DNIS": "8607897478" }</pre>

Endpoint Details

Uri:	/VOWebApi/v5/recordingmetadata/callobject
Description:	Post End-Of-Call Events for Integration/Import
Verbs:	POST
Query String Parameters:	NONE
Returned Data:	HTTP Status, JSON Message
Input Data:	CallObject JSON Object
Valid JSON Input	<pre>{ "SessionID": "000860123456789123456", "CallID": "1234567890", "Agent": "jsmith", "Extension": "892100", "ANI": "8602982151", "DNIS": "8607897478", "StartDate": "2017-09-20 13:35:10", "EndDate": "2017-09-20 13:37:10", "Duration": "120", "MediaUrl": "http://10.10.20.164/recordings/000860123456789123456789.mp3", "HoldTime": "30", "Direction": "Inbound", "ACDSkill": "100102", "ACDQueue": "100101", "ACDVDN": "100123", "UserData1": "anydata", "UserData2": "anydata", "UserData3": "anydata" }</pre>

REST cURL Samples

The following curl samples are listed as though they were run on a Windows machine at the Command Prompt. Notice the escaped quote symbols \".

Agents

```
curl https://server/vowebapi/v5/agents/agentinfo/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

```
curl https://server/vowebapi/v5/agents/agenttype/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

```
curl https://server/vowebapi/v5/agents/supervisor/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

Evaluations

```
curl https://server/vowebapi/v5/evaluations/evaluator/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

```
curl https://server/vowebapi/v5/evaluations/assignment/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

```
curl https://server/vowebapi/v5/evaluations/review/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

```
curl https://server/vowebapi/v5/evaluations/scoringssession/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

```
curl https://server/vowebapi/v5/evaluations/survey/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

Recordings

```
curl https://server/vowebapi/v5/recordings/recordedevent/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

REST cURL Samples

Speech Analytics

```
curl https://server/vowebapi/v5/speechanalytics/calldetail/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

```
curl https://server/vowebapi/v5/speechanalytics/callmetadata/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

```
curl https://server/vowebapi/v5/speechanalytics/callmark/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

```
curl https://server/vowebapi/v5/speechanalytics/discovery/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

```
curl https://server/vowebapi/v5/speechanalytics/transcript/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

Admin

```
curl https://server/vowebapi/v5/admin/user/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

```
curl https://server/vowebapi/v5/admin/profile/-1 -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

REST cURL Samples

Audit

```
curl https://server/vowebapi/v5/audit/auditinfo/-1?type=program -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

```
curl https://server/vowebapi/v5/audit/auditinfo/-1?type=data -H "Content-Type: application/json" -H "ApiToken: XXXXX"
```

Adherence

```
curl https://server/vowebapi/v5/adherence/agentstate -H "Content-Type: application/json" -H "ApiToken: XXXXX" -d '{"User": "jsmith", "PreviousState": "", "State": "Ready", "Reason": ""}' -X POST
```

REST cURL Samples

Value Added Metadata

```
curl https://server/vowebapi/v5/valueaddedmetadata/tag -H "Content-Type: application/json" -H "ApiToken: XXXXX" -d '{"User": "jsmith", "TagField1": "metadata1", "TagField2": "metadata2", "TagField3": "metadata3", "TagField4": "metadata4", "TagField5": "metadata5", "TagField6": "metadata6", "TagField7": "metadata7", "TagField8": "metadata8", "TagField9": "metadata9", "TagField10": "metadata10"}' -X POST
```

PCI

```
curl https://server/vowebapi/v5/pci/lightout -H "Content-Type: application/json" -H "ApiToken: XXXXX" -d '{"User": "1234", "Function": "Pause"}' -X POST
```

CTI

```
curl https://server/vowebapi/v5/cti/callevnt -H "Content-Type: application/json" -H "ApiToken: XXXXX" -d '{"SessionID": "ABCDEF123456", "CallID": "123456789", "Agent": "jsmith", "Extension": "892101", "DateTime": "2017-09-20 10:00:00AM", "Event": "Ring", "CallAppearance": "1", "ANI": "8602982151", "DNIS": "18005551212"}' -X POST
```

Recording Metadata

```
curl https://server/vowebapi/v5/recordingmetadata/callobject -H "Content-Type: application/json" -H "ApiToken: XXXXX" -d '{"SessionID": "ABCDEF123456", "CallID": "123456789", "Agent": "jsmith", "Extension": "892101", "ANI": "8602982151", "DNIS": "18005551212", "StartDate": "2017-09-20 10:00:00AM", "EndDate": "2017-09-20 10:30:00AM", "Duration": "1800", "MediaUrl": "http://10.10.20.164/recordings/ABCDEF123456-123456789.mp3", "HoldTime": "30", "Direction": "Inbound", "ACDSkill": "100102", "ACDQueue": "100101", "ACDVDN": "100123", "AdditionalField1": "SomeData", "AdditionalField2": "SomeData", "AdditionalField3": "SomeData", "AdditionalField4": "SomeData", "AdditionalField5": "SomeData"}' -X POST
```