

esclipse gdb jlink server config

eslipse

Name: gd32vf103_freertos Default

Main Debugger Startup Source Common

GDB Setup

GDB Command:

riscv-none-embed-gdb -ex "set arch riscv:rv32" Browse... Variables...

Remote Target

☒ Use remote target

☐ Remote timeout (seconds):

JTAG Device: J-Link

Host name or IP address: localhost

Port number: 2331

☐ Force thread list update on suspend

Create, manage, and run configurations



Name: gd32vf103_freertos Default

Main Debugger Startup Source Common

Initialization Commands

☐ Reset and Delay (seconds): 3

☐ Halt

Load Image and Symbols

☒ Load image

☒ Use project binary: gd32vf103_freertos\build\gd32vf103.elf

☐ Use file: Workspace... File System...

Image offset (hex):

☒ Load symbols

☒ Use project binary: gd32vf103_freertos\build\gd32vf103.elf

☐ Use file: Workspace... File System...

Symbols offset (hex):

Run Commands

☐ Set program counter at (hex):

☒ Set breakpoint at: main

file ./build/gd32vf103.elf
load
monitor reset halt

☐ Resume

Filter matched 13 of 13 items

Revert Apply

Debug Close

file ./build/gd32vf103.elf

load

monitor reset halt

