




Computer Science and Data Analysis Series

R Graphics



Paul Murrell

Contents

List of Figures

List of Tables

1 An Introduction to R Graphics

- 1.1 R graphics examples
 - 1.1.1 Standard plots
 - 1.1.2 Trellis plots
 - 1.1.3 Special-purpose plots
 - 1.1.4 General graphical scenes
- 1.2 The organization of R graphics
 - 1.2.1 Types of graphics functions
 - 1.2.2 Traditional graphics versus grid graphics
- 1.3 Graphical output formats
 - 1.3.1 Graphics devices
 - 1.3.2 Multiple pages of output
 - 1.3.3 Display lists

I TRADITIONAL GRAPHICS

2 Simple Usage of Traditional Graphics

- 2.1 The traditional graphics model
- 2.2 Plots of one or two variables
 - 2.2.1 Arguments to graphics functions
 - 2.2.2 Standard arguments
- 2.3 Plots of multiple variables
- 2.4 Modern plots and specialized plots
- 2.5 Interactive graphics

3 Customizing Traditional Graphics

- 3.1 The traditional graphics model in more detail
 - 3.1.1 Plotting regions
 - 3.1.2 The traditional graphics state
- 3.2 Controlling the appearance of plots
 - 3.2.1 Colors
 - 3.2.2 Lines

- 3.2.3 Text
 - 3.2.4 Data symbols
 - 3.2.5 Axes
 - 3.2.6 Plotting regions
 - 3.2.7 Clipping
 - 3.2.8 Moving to a new plot
- 3.3 Arranging multiple plots
 - 3.3.1 Using the traditional graphics state
 - 3.3.2 Layouts
 - 3.3.3 The split-screen approach
- 3.4 Annotating plots
 - 3.4.1 Annotating the plot region
 - 3.4.2 Missing values and non-finite values
 - 3.4.3 Annotating the margins
 - 3.4.4 Legends
 - 3.4.5 Axes
 - 3.4.6 Mathematical formulae
 - 3.4.7 Coordinate systems
 - 3.4.8 Bitmap images
 - 3.4.9 Special cases
- 3.5 Creating new plots
 - 3.5.1 A simple plot from scratch
 - 3.5.2 A more complex plot from scratch
 - 3.5.3 Writing traditional graphics functions

II GRID GRAPHICS

4 Trellis Graphics: the Lattice Package

- 4.1 The lattice graphics model
 - 4.1.1 Lattice devices
- 4.2 Lattice plot types
 - 4.2.1 The `formula` argument and multipanel conditioning
 - 4.2.2 A nontrivial example
- 4.3 Controlling the appearance of lattice plots
- 4.4 Arranging lattice plots
- 4.5 Annotating lattice plots
 - 4.5.1 Panel functions and strip functions
 - 4.5.2 Adding output to a lattice plot
- 4.6 Creating new lattice plots

5 The Grid Graphics Model

- 5.1 A brief overview of grid graphics
 - 5.1.1 A simple example
- 5.2 Graphical primitives

- 5.2.1 Standard arguments
- 5.3 Coordinate systems
 - 5.3.1 Conversion functions
 - 5.3.2 Complex units
- 5.4 Controlling the appearance of output
 - 5.4.1 Specifying graphical parameter settings
 - 5.4.2 Vectorized graphical parameter settings
- 5.5 Viewports
 - 5.5.1 Pushing, popping, and navigating between viewports
 - 5.5.2 Clipping to viewports
 - 5.5.3 Viewport lists, stacks, and trees
 - 5.5.4 Viewports as arguments to graphical primitives
 - 5.5.5 Graphical parameter settings in viewports
 - 5.5.6 Layouts
- 5.6 Missing values and non-finite values
- 5.7 Interactive graphics
- 5.8 Customizing lattice plots
 - 5.8.1 Adding grid output to lattice output
 - 5.8.2 Adding lattice output to grid output

6 The Grid Graphics Object Model

- 6.1 Working with graphical output
 - 6.1.1 Standard functions and arguments
- 6.2 Grob lists, trees, and paths
 - 6.2.1 Graphical parameter settings in gTrees
 - 6.2.2 Viewports as components of gTrees
 - 6.2.3 Searching for grobs
- 6.3 Working with graphical objects off-screen
 - 6.3.1 Capturing output
- 6.4 Placing and packing grobs in frames
 - 6.4.1 Placing and packing off-screen
- 6.5 Other details about grobs
 - 6.5.1 Calculating the sizes of grobs
 - 6.5.2 Editing graphical context
- 6.6 Saving and loading grid graphics
- 6.7 Working with lattice grobs

7 Developing New Graphics Functions and Objects

- 7.1 An example
 - 7.1.1 Modularity
- 7.2 Simple graphics functions
 - 7.2.1 Embedding graphical output
 - 7.2.2 Facilitating annotation
 - 7.2.3 Editing output
 - 7.2.4 Absolute versus relative sizes

- 7.3 Graphical objects
 - 7.3.1 Overview of creating a new graphical class
 - 7.3.2 Defining a new graphical class
 - 7.3.3 Validating grobs
 - 7.3.4 Drawing grobs
 - 7.3.5 Editing grobs
 - 7.3.6 Sizing grobs
 - 7.3.7 Pre-drawing and post-drawing
 - 7.3.8 Completing the example
 - 7.3.9 Reusing graphical elements
 - 7.3.10 Other details
- 7.4 Querying grid

A A Brief Introduction to R

- A.1 Obtaining and installing R
- A.2 An environment for statistical computing and graphics
 - A.2.1 Batch processing
 - A.2.2 Data types
 - A.2.3 Variables
 - A.2.4 Indexing
 - A.2.5 Data structures
 - A.2.6 Formulae
 - A.2.7 Expressions
 - A.2.8 Packages
 - A.2.9 Accessing data sets
 - A.2.10 Getting help
- A.3 A programming language
 - A.3.1 Debugging
- A.4 An object-oriented language

B Combining Traditional Graphics and Grid Graphics

- B.1 The `gridBase` package
 - B.1.1 Annotating base graphics using grid
 - B.1.2 Embedding base graphics plots in grid viewports
 - B.1.3 Problems and limitations

Bibliography

List of Figures

- 1.1 A simple scatterplot
- 1.2 Some standard plots
- 1.3 A customized scatterplot
- 1.4 A Trellis dotplot
- 1.5 A map of New Zealand produced using R
- 1.6 Some polar-coordinate plots
- 1.7 A novel decision tree plot
- 1.8 A table-like plot
- 1.9 Didactic diagrams
- 1.10 A music score
- 1.11 A piece of clip art
- 1.12 The structure of the R graphics system

- 2.1 Four variations on a scatterplot
- 2.2 Plotting an `lm` object
- 2.3 Plotting an `agnes` object
- 2.4 Modifying default `barplot()` and `boxplot()` output
- 2.5 Standard arguments for high-level functions
- 2.6 Plotting three variables
- 2.7 Plotting multivariate data
- 2.8 Some modern and specialized plots

- 3.1 The plot regions in traditional graphics
- 3.2 Multiple figure regions in traditional graphics
- 3.3 The user coordinate system in the plot region
- 3.4 Figure margin coordinate systems
- 3.5 Outer margin coordinate systems
- 3.6 Predefined and custom line types
- 3.7 Line join and line ending styles
- 3.8 Alignment of text in the plot region
- 3.9 Font families and font faces
- 3.10 Data symbols available in R
- 3.11 Basic plot types
- 3.12 Different axis styles
- 3.13 Graphics state settings controlling plot regions
- 3.14 Some basic layouts

- 3.15 Some complex layouts
- 3.16 Annotating the plot region
- 3.17 More examples of annotating the plot region
- 3.18 Drawing polygons
- 3.19 Annotating the margins
- 3.20 Some simple legends
- 3.21 Customizing axes
- 3.22 Mathematical formulae in plots
- 3.23 Custom coordinate systems
- 3.24 Overlaying plots
- 3.25 Overlaying output
- 3.26 Adding a bitmap to a plot
- 3.27 Special-case annotations
- 3.28 A panel function example
- 3.29 Annotating a 3D surface
- 3.30 A back-to-back barplot
- 3.31 A graphics function template

- 4.1 A scatterplot using lattice
- 4.2 The result of modifying a lattice object
- 4.3 Plot types available in lattice
- 4.4 A lattice multipanel conditioning plot
- 4.5 A complex lattice plot
- 4.6 Some default lattice settings
- 4.7 Controlling the layout of lattice panels
- 4.8 Arranging multiple lattice plots
- 4.9 Annotating a lattice plot

- 5.1 A simple scatterplot using grid
- 5.2 Primitive grid output
- 5.3 Drawing arrows
- 5.4 Drawing polygons
- 5.5 A demonstration of grid units
- 5.6 Graphical parameters for graphical primitives
- 5.7 Recycling graphical parameters
- 5.8 Recycling graphical parameters for polygons
- 5.9 A diagram of a simple viewport
- 5.10 Pushing a viewport
- 5.11 Pushing several viewports
- 5.12 Popping a viewport
- 5.13 Navigating between viewports
- 5.14 Clipping output in viewports
- 5.15 The inheritance of viewport graphical parameters
- 5.16 Layouts and viewports
- 5.17 Layouts and units

- 5.18 Nested layouts
- 5.19 Non-finite values for line-tos, polygons, and arrows
- 5.20 Controlling the size of lattice panels
- 5.21 Adding grid output to a lattice plot
- 5.22 Embedding a lattice plot within grid output

- 6.1 Modifying a `circle` grob
- 6.2 Editing grobs
- 6.3 The structure of a `gTree`
- 6.4 Editing a `gTree`
- 6.5 Using a `gTree` to group grobs
- 6.6 Packing grobs by hand
- 6.7 Calculating the size of a grob
- 6.8 Grob dimensions by reference
- 6.9 Editing the graphical context
- 6.10 Editing the grobs in a lattice plot

- 7.1 A plot of oceanographic data
- 7.2 A `grid.imageFun()` function
- 7.3 Output from the `grid.imageFun()` function
- 7.4 A `grid.ozFun()` function
- 7.5 Example output from `grid.ozFun()`
- 7.6 Annotating `grid.ozFun()` output
- 7.7 Editing `grid.ozFun()` output
- 7.8 An `"imageGrob"` class
- 7.9 Some `validDetails()` methods
- 7.10 An `"ozGrob"` class
- 7.11 An `"ozImage"` class
- 7.12 Some `editDetails()` methods
- 7.13 Editing an `imageGrob`
- 7.14 Low-level editing of an `imageGrob`
- 7.15 Helper functions for a `"ribbonLegend"` class
- 7.16 A `"ribbonLegend"` class
- 7.17 An `"ozKey"` class
- 7.18 A plot of temperature data
- 7.19 A `splitString()` function
- 7.20 Performing calculations before drawing
- 7.21 A `"splitText"` class
- 7.22 Drawing faces
- 7.23 Some face functions
- 7.24 Some face objects

- B.1 Annotating a traditional plot with grid
- B.2 Embedding a traditional plot within lattice output

List of Tables

- 1.1 Graphical output formats
- 3.1 High-level traditional graphics state settings
- 3.2 Low-level traditional graphics state settings
- 3.3 Read-only traditional graphics state settings
- 3.4 Functions to generate color sets
- 3.5 Font faces
- 3.6 Font families
- 4.1 Plotting functions in lattice
- 5.1 Graphical primitives in grid
- 5.2 Coordinate systems in grid
- 5.3 Graphical parameters in grid
- 5.4 Grid font faces
- 6.1 Functions for working with grobs