

Package ‘missRanger’

August 25, 2017

Title Fast Imputation of Missing Values

Version 1.0.0

Description Alternative implementation of the beautiful 'MissForest' algorithm used to impute mixed-type data sets by chaining tree ensembles, introduced by Stekhoven, D.J. and Buehlmann, P. (2012) <doi:10.1093/bioinformatics/btr597>. Under the hood, it uses the lightning fast random jungle package 'ranger'. Between the iterative model fitting, we offer the option of using predictive mean matching. This firstly avoids imputation with values not already present in the original data (like a value 0.3334 in 0-1 coded variable). Secondly, predictive mean matching tries to raise the variance in the resulting conditional distributions to a realistic level. This would allow e.g. to do multiple imputation when repeating the call to missRanger().

Depends R (>= 3.3.2)

License GPL(>= 2)

Encoding UTF-8

LazyData true

Type Package

Date 2017-08-25

Imports stats, FNN (>= 1.1), ranger (>= 0.6.0)

Author Michael Mayer [aut, cre, cph]

Maintainer Michael Mayer <mayermichael79@gmail.com>

RoxygenNote 6.0.1

NeedsCompilation no

R topics documented:

generateNA	2
imputeUnivariate	2
missRanger	3
pmm	4
Index	5

`generateNA`*Adds Missing Values to a Data Set*

Description

Takes a data frame and replaces randomly part of the values by missing values.

Usage

```
generateNA(data, p = 0.1, seed = NULL)
```

Arguments

<code>data</code>	A <code>data.frame</code> .
<code>p</code>	Proportion of missing values to approximately add to each column of data.
<code>seed</code>	An integer seed.

Value

data with missing values.

Examples

```
head(generateNA(iris))
```

`imputeUnivariate`*Univariate Imputation*

Description

Fills missing values of a vector of any type by sampling with replacement from the non-missing values. Requires at least one non-missing value to run.

Usage

```
imputeUnivariate(x)
```

Arguments

<code>x</code>	A vector of any type possibly containing missing values.
----------------	--

Value

A vector of the same length and type as `x` but without missing values.

Examples

```
imputeUnivariate(c(NA, 0, 1, 0, 1))  
imputeUnivariate(c("A", "A", NA))
```

Description

Uses the "ranger" package [1] to do fast missing value imputation by chained random forests, see [2] and [3]. Between the iterative model fitting, we offer the option of using predictive mean matching. This firstly avoids the imputation with values not present in the original data (like a value 0.3334 in 0-1 coded variable). Secondly, predictive mean matching tries to raise the variance in the resulting conditional distributions to a realistic level. This would allow e.g. to do multiple imputation when repeating the call to "missRanger".

Usage

```
missRanger(data, maxiter = 10L, pmm.k = 0L, seed = NULL, ...)
```

Arguments

data	A data.frame with missing values to impute.
maxiter	Maximum number of chaining iterations.
pmm.k	Number of candidate non-missing values to sample from in the predictive mean matching step. 0 to avoid this step.
seed	Integer seed to initialize the random generator.
...	Arguments passed to ranger. Don't use formula, data or seed. They are already handled by the algorithm. Not all ranger options do make sense (e.g. write.forest = FALSE will cause the algorithm to crash. If the data set is large, better use less trees num.trees = 100 and/or a low value of sample.fraction.

Value

A data.frame as data but with imputed missing values.

References

- [1] Wright, M. N. & Ziegler, A. (2016). ranger: A Fast Implementation of Random Forests for High Dimensional Data in C++ and R. Journal of Statistical Software, in press. <http://arxiv.org/abs/1508.04409>.
- [2] Stekhoven, D.J. and Bühlmann, P. (2012). 'MissForest - nonparametric missing value imputation for mixed-type data', Bioinformatics, 28(1) 2012, 112-118, doi: 10.1093/bioinformatics/btr597
- [3] Van Buuren, S., Groothuis-Oudshoorn, K. (2011). mice: Multivariate Imputation by Chained Equations in R. Journal of Statistical Software, 45(3), 1-67. <http://www.jstatsoft.org/v45/i03/>

Examples

```
irisWithNA <- generateNA(iris)
irisImputed <- missRanger(irisWithNA, pmm.k = 3, num.trees = 100)
head(irisImputed)
head(irisWithNA)

# With extra trees algorithm
irisImputed_et <- missRanger(irisWithNA, pmm.k = 3, num.trees = 100, splitrule = "extratrees")
head(irisImputed_et)
```

pmm

*Predictive Mean Matching***Description**

This function is used internally only but might help others to implement an efficient way of doing predictive mean matching on top of any prediction based missing value imputation. It works as follows: For each predicted value of a vector `xtest`, the closest `k` predicted values of another vector `xtrain` are identified by `k`-nearest neighbour. Then, one of those neighbours are randomly picked and its corresponding observed value in `ytrain` is returned.

Usage

```
pmm(xtrain, xtest, ytrain, k = 1L, seed = NULL)
```

Arguments

<code>xtrain</code>	Vector with predicted values in the training data set.
<code>xtest</code>	Vector with predicted values in the test data set.
<code>ytrain</code>	Vector with observed response in the training data set.
<code>k</code>	Number of nearest neighbours to choose from. Set <code>k = 0</code> if no predictive mean matching is to be done.
<code>seed</code>	Integer random seed.

Value

Vector with predicted values in the test data set based on predictive mean matching.

Examples

```
pmm(xtrain = c(0.2, 0.2, 0.8), xtest = 0.3, ytrain = c(0, 0, 1), k = 1) # 0
pmm(xtrain = c(0.2, 0.2, 0.8), xtest = 0.3, ytrain = c(0, 0, 1), k = 3) # 0 or 1
pmm(xtrain = c("A", "A", "B"), xtest = "B", ytrain = c("B", "A", "B"), k = 1) # B
pmm(xtrain = c("A", "A", "B"), xtest = "B", ytrain = c("B", "A", "B"), k = 2) # A or B
```

Index

`generateNA`, [2](#)

`imputeUnivariate`, [2](#)

`missRanger`, [3](#)

`pmm`, [4](#)