JASPY Web

Technical Documentation & Main Functions List

Project Overview

JASPY Web is a web application developed using **Python (Flask)** for the server side, and **JavaScript, CSS, and HTML** for the client side.

The core objective is to conceal direct HTML structures. Instead, JavaScript and CSS manage, create, and build all pages dynamically via functions, while the Python backend automatically handles route generation and new pages.

Python **JavaScript** **CSS** **HTML**

1. First Section: head.js

Functions responsible for building and setting elements within the page header (`<head>`):

- `title(a)`: Creates and sets the page title (`<title>`).
- `h_script(a): Imports additional JavaScript script files into the head.`
- `link(a): Imports CSS stylesheet files.`
- `icon(a): Sets the browser tab icon (favicon).`

2. Second Section: main.js (Elements & Structure Creation)

Element Creation Functions

- `Create_Element_simple_after_root(a)`: Creates an HTML element and appends it directly inside the `root` container.
- `Create_other_Element_simple(tg, isa, a)`: Creates an element inside a specified tag using its index.
- `Create_Element_text_after_root(a, b, c, d)`: Creates an element with text content and an attribute, then appends it to `root`.
- `Create_Element_after_root(a, c, d)`: Creates an element with an attribute inside `root`.
- `Create_other_Element_text(id, a, b, c, d)`: Creates an element with text and an attribute inside a specified element ID.
- `Create_other_Element(id, a, c, d)`: Creates a new element with an attribute inside a specified ID.
- `Create_other_Element_ByTag(tg, isa, a)`: Creates an element inside a tag and index.

Attributes & Control Functions

- `Set_Attribut(id, c, d)`: Modifies or sets an attribute on an element specified by ID.
- `Set_Attribut_ByTag(tg, isa, c, d)`: Modifies attributes on an element specified by tag.
- `script(src_name)`: Imports a JavaScript script by creating an element.
- `Jaspy()`: Calls and loads the core `jaspy.js` script file.

Text, Class & ID Management

- `Add_Text(id, a): Appends text inside an element specified by ID.`
- `Add_Text_ByClass(clas, isa, a): Appends text inside an element specified by class.`
- `Add_Text_ByTag(tg, isa, a): Appends text inside an element specified by tag.`
- `Add_ClassByTag(tg, isa, cln) /  Add_ClassById(id, cln): Assigns a class name.`
- `Add_IdByTag(tg, isa, idn) /  Add_IdByClass(cln, isa, idn): Assigns an ID.`

Templates & Export Functions

- `create_landing_page(pageTitle, description, colors): Generates a complete landing page (Logo, Title, Description, Custom Colors).`
- `create_portfolio(name, projects): Generates a portfolio page featuring card layouts for each project.`
- `create_business_website(business_name, services): Generates a business website showcasing a list of services.`
- `export_website(file_name): Clones the entire page, converts images to Base64 data URLs, and exports it as a standalone, downloadable HTML file.`