

♦ ROCK SOLID REINFORCING

The Future of Reinforcement

Pioneering Basalt Fiber Reinforced Polymer (BFRP) Composites — the sustainable, high-performance alternative to steel and glass fiber for the modern construction industry.

3×

STRONGER THAN STEEL

4.5×

LIGHTER THAN STEEL

74%

SMALLER CARBON FOOTPRINT

700°

MAX OPERATING TEMP (°C)

BFRP MESH

BasaltechSA Reinforcing Mesh

Designed to strengthen roadways, highways, and structures by reducing reflective cracking. A superior, lightweight alternative to traditional steel reinforcement.

KEY FEATURES & BENEFITS

-  **Superior Tensile Strength**
Higher than E-glass and steel, ensuring robust reinforcement across all applications.
-  **Alkali & Corrosion Resistance**
Prevents rust in high-alkali environments. Unlike steel, it will never rust or degrade.
-  **Ease of Installation**
Over 1000 m² fits on a 1-ton bakkie. No special equipment needed.
-  **High Temperature Tolerance**
Withstands paving and operational temperatures without losing strength.
-  **Environmentally Friendly**
Natural volcanic basalt rock with 74% less carbon footprint than steel.

LOGISTICS ADVANTAGE

Over 1000 m² of reinforcing mesh can be transported on a standard 1-ton bakkie — dramatically reducing delivery costs compared to steel.



♦ LEARN MORE

Scan for the Full Product Range

Detailed specifications, case studies, and technical datasheets.

www.basaltechsa.com

WHY CHOOSE BFRP MESH

- ✓ Will not rust or corrode
- ✓ Easy to transport & install
- ✓ Lower life cycle cost
- ✓ Superior mechanical strength
- ✓ Reduced shrinkage & cracking

BFRP FIBER

BasaltechSA Fiber

An innovative reinforcing material derived from volcanic basalt rock that dramatically improves concrete properties. High tensile strength, total corrosion resistance, and outstanding durability.

APPLICATIONS

- Road Surfaces**
Reinforces asphalt and cement concrete roads, runways, and pavements.
- Industrial Floors**
Ideal for logistics centres, parking lots, helipads, and screeds.
- Underground & Civil Structures**
Enhances durability in metros, underground foundations, and communications.
- Buildings & Bridges**
Strengthens structural elements, concrete structures, and dry mix applications.
- Soil Stabilisation**
Improves ground stability for slopes, embankments, and foundations.

PERFORMANCE COMPARISON

PROPERTY	BASALT FIBER ♦	STEEL	GLASS	PP
Tensile (MPa)	1100–1400	360–420	35–530	170–260
Temp. (°C)	–260 to 700	–60 to 540	–60 to 250	–5 to 80
Density (g/cm³)	2.8–3.0	7.8	2.6–2.7	0.89–0.92
Elastic Mod. (GPa)	79–110	190–200	≤50	≤35
Corrosion	Very High	Low	High	Low



KEY FIBER PROPERTIES

- ✓ 100% Corrosion Proof
- ✓ 75% Lighter than Steel
- ✓ Non-Conductive / Non-Magnetic
- ✓ Eco-Friendly Volcanic Rock
- ✓ Reduces Microcracks by 90%
- ✓ +55% Flexural Strength

OUR LOCATIONS

G GAUTENG
Plot 112, Oak Tree R563
Mogale City, Gauteng

L LIMPOPO
118 OR Tambo Drive
Lephalale, Limpopo

DIRECT CONTACTS

J Johan
082 456 9705
johan@basaltechsa.com

R Ronnie
082 411 4500
ronnie@basaltechsa.com

WHY BASALTECHSA

Proudly South African
Local knowledge, world-class BFRP standards. Serving Gauteng & Limpopo.

Expert Technical Support
From specification to installation, our team provides end-to-end guidance.



SCAN OR VISIT OUR WEBSITE

Get Quotes, Specs & Case Studies
www.basaltechsa.com