

RED (Rescue Delivery System)

Basilio Caruso, Syed Faique Al Hussain, Murtaza Fatakdawala, George Chen, Miguel Colmenares, Michael Heath, Nishant Sriram Narayanan, Joao Nené, Akshata Patil, Marley Scott, Andrea Swanson

Faculty Advisor(s): Dr. Markus Wilde, Dept. of Aerospace, Physics and Space Sciences, Florida Institute of Technology, Dr. Siddhartha Bhattacharyya, Dept. of Computer Engineering and Sciences, Florida Institute of Technology

Seperation

Loiter


Delivery

Docking

Overview

RED is a two stage delivery system consisting of a fixed wing mothership and a quadcopter. It is designed for fast and precise emergency rescue by delivering medical supplies.

Controls




Software & Avionics

- Autonomous mission-based state machine
- Analyzes GPS, camera, and sensor input
- Sends custom flight commands to Pixhawk flight controller



- **Detects ArUco Marker to** determine absolute position for precise docking
- Aircraft communication via real time database



Takeoff

Landing

Docking System Plate manufactured using foam


- facilitates docking procedure Rail manufactured using 3D
- printing secures the multirotor Pressure sensor locks and release
- multirotor

Deployment System

- Designed to carry and deploy 400g medical supply payload
- Housing and claws are 3D printed with PLA plastic
- Servos and gears are commercially bought

Propulsion

Thrust to weight ratio: 0.9



Aerodynamics & Stability

- CFD simulations on ANSYS Fluent and MATLAB were used to compute flight performance
- **Static Margin: 15%**
- Take Off Distance: 18 m
- Landing Distance: 25 m
- Stall Speed: 11 m/s



Structures

- Max. Take off weight: 6.5kg
- Analysis performed using hand calculations and ANSYS Workbench
- Landing gear manufactured to accommodate multirotor beneath mothership

