



# RISC-V Server Platform Specification

Server Platform Task Group

Version v0.0.0, 2023-11-30: Draft

# Table of Contents

Preamble.....	1
Copyright and license information.....	2
Contributors.....	3
1. Introduction.....	4
1.1. Glossary.....	5
2. Server Platform Hardware Requirements.....	7
2.1. RISC-V SoC.....	7
3. Server Platform Firmware Requirements.....	8
4. Server Platform Security Requirements.....	9
Bibliography .....	10

# Preamble



*This document is in the [Development state](#)*

Assume everything can change. This draft specification will change before being accepted as standard, so implementations made to this draft specification will likely not conform to the future standard.

# Copyright and license information

This specification is licensed under the Creative Commons Attribution 4.0 International License (CC-BY 4.0). The full license text is available at [creativecommons.org/licenses/by/4.0/](https://creativecommons.org/licenses/by/4.0/).

Copyright 2023 by RISC-V International.

# Contributors


This RISC-V specification has been contributed to directly or indirectly by (in alphabetical order):

Andrei Warkentin, Ved Shanbhogue

# Chapter 1. Introduction

The RISC-V Server Platform specification defines a standardized set of hardware and software capabilities, that portable system software, such as operating systems and hypervisors, can rely on being present in a RISC-V server platform.

A server is a computing system designed to manage and distribute resources, services, and data to other computers or devices on a network. It is often referred to as a 'server' because it serves or provides information and resources upon request. Such computing systems are designed to operate continually and have higher requirements for capabilities such as RAS, security, performance, and quality of service. Examples of servers include web servers, file servers, database servers, mail servers, game servers, and more. This specification focuses on defining requirements for general-purpose server computing systems that may be used for one or more of these purposes.



*Figure 1. Components of a RISC-V Server Platform*

The RISC-V server platform is defined as the collection of SoC hardware, peripherals, platform firmware, boot/runtime services, and platform security services. The platform provides hardware interfaces (e.g., harts, timers, interrupt controllers, PCIe root ports, etc.) to portable system software. It also offers a set of standardized boot and runtime services based on the UEFI and ACPI standards. To support provisioning and platform management, it interfaces with a baseboard management controller (BMC) through both in-band and out-of-band (OOB) management interfaces. The in-band management interfaces support the use of standard manageability specifications like MCTP, PLDM, IPMI, and Redfish for provisioning and management of the operating system executing on the platform. The OOB interface supports the use of standard manageability specifications like MCTP, PLDM, Redfish, and IPMI for functions such as power management, telemetry, debug, and provisioning. The platform security model includes guidelines and requirements for aspects such as debug authorization, secure/measured boot, firmware updates, firmware resilience, and confidential computing, among others.

The platform firmware, typically operating at privilege level M, is considered part of the platform and is usually expected to be customized and tailored to meet the requirements of the SoC hardware (e.g., initialization of address decoders, memory controllers, RAS, etc.), boot/runtime services and platform security.

This specification standardizes the requirements for hardware and software interfaces and capabilities by building on top of relevant RISC-V standards, such as the Server SoC, Boot and Runtime Services and Platform Security specifications for server software executing on the application processor harts at privilege levels below M. It enables OS and hypervisor vendors to support such platforms with a single binary OS image distribution model. The requirements posed by this specification represent a standard set of infrastructural capabilities, encompassing areas where divergence is typically unnecessary and where novelty is absent across implementations.

To be compliant with this specification, the server platform **MUST** support all mandatory requirements and **MUST** support the listed versions of the specifications. This standard set of capabilities **MAY** be extended by a specific implementation with additional standard or custom capabilities, including compatible later versions of listed standard specifications. Portable system software **MUST** support the specified mandatory capabilities to be compliant with this specification.

The requirements in this specification use the following format:

ID#	Requirement
CAT_NNN	<p>The <b>CAT</b> is a category prefix that logically groups the requirements and is followed by 3 digits - <b>NNN</b> - assigning a numeric ID to the requirement.</p> <p>The requirements use the key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" that are to be interpreted as described in RFC 2119 [1] when, and only when, they appear in all capitals, as shown here. When these words are not capitalized, they have their normal English meanings.</p>
<p><i>A requirement or a group of requirements may be followed by non-normative text providing context or justification for the requirement. The non-normative text may also be used to reference sources that are the origin of the requirement.</i></p>	

This specification groups the requirements in the following broad categories:

- Hardware
- Firmware
- Security

## 1.1. Glossary

Most terminology has the standard RISC-V meaning. This table captures other terms used in the document.

*Table 1. Terms and definitions*

Term	Definition
ACPI	Advanced Configuration and Power Interface <a href="#">[2]</a> .
Guest	Software in a virtual machine.
Hypervisor	Software entity that controls virtualization.
ID	Identifier.
OS	Operating System.
SoC	System on a chip, also referred as system-on-a-chip and system-on-chip.
UEFI	Unified Extensible Firmware Interface. <a href="#">[3]</a>
VM	Virtual Machine.



# Chapter 2. Server Platform Hardware Requirements

## 2.1. RISC-V SoC

A RISC-V server platform is based on a RISC-V SoC with RISC-V application processors.

ID#	Requirement
HSOC_010	The RISC-V SoC MUST comply to the Server SoC specification <a href="#">[4]</a> .
<i>The Server SoC specification is still under construction. This specification should be updated once the specification versioning info is finalized.</i>	

# Chapter 3. Server Platform Firmware Requirements

ID#	Requirement
FIRM_010	The RISC-V SoC MUST comply to the BRS-I recipe described in the Boot and Runtime Service specification <a href="#">[5]</a> .
<i>The Boot and Runtime Services specification is still under construction. This specification should be updated once the specification versioning info is finalized.</i>	

# **Chapter 4. Server Platform Security Requirements**

# Bibliography

- [1] “Key words for use in RFCs to Indicate Requirement Levels.” [Online]. Available: [datatracker.ietf.org/doc/html/rfc2119](https://datatracker.ietf.org/doc/html/rfc2119).
- [2] “Advanced Configuration and Power Interface (ACPI) Specification.” [Online]. Available: [uefi.org/specifications](https://uefi.org/specifications).
- [3] “Unified Extensible Firmware Interface.” [Online]. Available: [uefi.org/specifications](https://uefi.org/specifications).
- [4] “RISC-V Server SoC Specification.” [Online]. Available: [github.com/riscv-non-isa/server-soc](https://github.com/riscv-non-isa/server-soc).
- [5] “RISC-V Boot and Runtime Services Specification.” [Online]. Available: [github.com/riscv-non-isa/riscv-brs](https://github.com/riscv-non-isa/riscv-brs).