2nd Spring School on Theory & Applications of pHs 25th March 2022, FrauenInsel

Numerics for PH-PDEs:

the Partitioned Finite Element Method, a structure-preserving method for physics-based PDEs with boundary control.

Denis Matignon¹

¹ISAE-SUPAERO, Université de Toulouse





Outline

- 1 Introduction
 - Goal of the presentation
 - A few references
 - Main objective of PFEM
- 2 Linear Wave equations: towards PH-DAEs and PH-ODEs
 - Discretization in terms of energy and co-energy variables: PH-DAEs
 - Application: Boundary Dissipation
 - Discretization in terms of co-energy variables: PH-ODEs
 - Case of mixed boundary control: PH-DAEs again
 - Convergence of PFEM
- 3 Nonlinear wave equation: the 2D Shallow Water Equation
 - Modelling: SWE as a pHs
 - Numerics: PFEM in the polynomial case
 - Application: Boundary Dissipation

Outline

- 1 Introduction
 - Goal of the presentation
 - A few references
 - Main objective of PFEM
- 2 Linear Wave equations: towards PH-DAEs and PH-ODEs
- 3 Nonlinear wave equation: the 2D Shallow Water Equation

Goal of the presentation

- Make links with other courses given at this Spring School:
 - 1 course on infinite-dimensional PH-PDEs by Birgit Jacob and Hans Zwart,
 - 2 course on PH-DAEs by Volker Mehrmann and Arjan van der Schaft,
 - 3 course on Thermodynamics by Hans-Christian Öttinger.
- Main Goal: the underlying structure of physical systems must be preserved by numerical methods at the discrete level, i.e. from infinite dimension to finite dimension (but still in continuous time).
- The question of specific time discretization addressed in the course by Paul Kotyczka and Laurent Lefèvre, just before, will not be tackled in the sequel.

Outline

- 1 Introduction
 - Goal of the presentation
 - A few references
 - Main objective of PFEM
- 2 Linear Wave equations: towards PH-DAEs and PH-ODEs
- 3 Nonlinear wave equation: the 2D Shallow Water Equation

A recent reference on distributed port-Hamiltonian systems

Twenty years of distributed port-Hamiltonian systems: a literature review Rashad, R., Califano, F., van der Schaft, A.J. and Stramigioli, S. *IMA J. Mathematics of Control and Information*, vol.37 (4), pp. 1400–1422 (2020)

- ⇒ More than 170 up-to-date references on:
 - Theoretical Framework
 - Modeling
 - Analysis and Control
 - Discretization

and more specifically

- Numerical Methods for Distributed Parameter Port-Hamiltonian Systems Kotyczka P. TUM University Press, Munich (2019),
- Structure preserving approximation of dissipative evolution problems **Egger H.** Numerische Mathematik vol.143(1), pp. 85–106 (2019)
- A Partitioned Finite-Element Method for power-preserving discretization of open systems of conservation laws, Cardoso-Ribeiro F.L., Matignon D., Lefèvre L. IMA J. Mathematics of Control and Information, vol.38(2), pp. 493–533 (2021)
- Numerical Approximation of Port-Hamiltonian Systems for Hyperbolic or Parabolic PDEs with Boundary Control, Brugnoli A., Haine G.,
 Serhani A., Vasseur X. Journal of Applied Mathematics and Physics, vol.9, pp. 1278–1321 (2021).

Outline

- 1 Introduction
 - Goal of the presentation
 - A few references
 - Main objective of PFEM
- 2 Linear Wave equations: towards PH-DAEs and PH-ODEs
- 3 Nonlinear wave equation: the 2D Shallow Water Equation

Aim:

Simulate complex open physical systems by ensuring the conservation of the power balance for a chosen functional: the Hamiltonian.

Aim:

Simulate complex open physical systems by ensuring the conservation of the power balance for a chosen functional: the Hamiltonian.

- Finite Element Method:
 - → Complex geometries are allowed.
 - \rightarrow A wide range of **implementation** tools are available.

Aim:

Simulate complex open physical systems by ensuring the conservation of the **power balance** for a chosen functional: the **Hamiltonian**.

- Finite Element Method:
 - → Complex geometries are allowed.
 - \rightarrow A wide range of **implementation** tools are available.
- Port-Hamiltonian Systems (PHS):
 - → Model "energy" exchanges between simpler open subsystems.
 - → The power balance is *encoded* in a **Stokes-Dirac structure**.

Aim:

Simulate complex open physical systems by ensuring the conservation of the **power balance** for a chosen functional: the **Hamiltonian**.


- Finite Element Method:
 - → Complex geometries are allowed.
 - \rightarrow A wide range of **implementation** tools are available.
- Port-Hamiltonian Systems (PHS):
 - → Model **"energy" exchanges** between simpler open subsystems.
 - → The power balance is *encoded* in a **Stokes-Dirac structure**.
- Partitioned Finite Element Method (PFEM):
 - \rightarrow It approximates the Stokes-Dirac structure into a **Dirac structure**.
 - → The **discrete Hamiltonian** satisfies a "discrete" power balance.

A Partitioned Finite-Element Method for power-preserving discretization of open systems of conservation laws


Cardoso-Ribeiro F.L., Matignon D., Lefèvre L.

IMA J. Mathematics of Control and Information, vol.38(2), pp. 493–533 (2021)


Change of paradigm?



Change of paradigm?



Change of paradigm?



- The energy variables $\overrightarrow{\alpha}$ (vector field);
- The **Hamiltonian** $\mathcal{H}(\overrightarrow{\alpha}(t))$ (positive functional);

- The **energy variables** $\overrightarrow{\alpha}$ (vector field);
- The **Hamiltonian** $\mathcal{H}(\overrightarrow{\alpha}(t))$ (positive functional);
- The **co-energy variables** $\overrightarrow{e}_{\overrightarrow{\alpha}} := \delta_{\overrightarrow{\alpha}} \mathcal{H}$ (vector field), \rightarrow the variational derivative of \mathcal{H} w.r.t $\overrightarrow{\alpha}$;

- The energy variables $\overrightarrow{\alpha}$ (vector field);
- The **Hamiltonian** $\mathcal{H}(\overrightarrow{\alpha}(t))$ (positive functional);
- The **co-energy variables** $\overrightarrow{e}_{\overrightarrow{\alpha}} := \delta_{\overrightarrow{\alpha}} \mathcal{H}$ (vector field), \rightarrow the variational derivative of \mathcal{H} w.r.t $\overrightarrow{\alpha}$;
- The **structure operator** J (linear and formally skew-symmetric);
- The resistive/dissipative operator R (linear and positive);

- The **energy variables** $\overrightarrow{\alpha}$ (vector field);
- The **Hamiltonian** $\mathcal{H}(\overrightarrow{\alpha}(t))$ (positive functional);
- The **co-energy variables** $\overrightarrow{e}_{\overrightarrow{\alpha}} := \delta_{\overrightarrow{\alpha}} \mathcal{H}$ (vector field), \rightarrow the variational derivative of \mathcal{H} w.r.t $\overrightarrow{\alpha}$;
- The **structure operator** J (linear and formally skew-symmetric);
- The resistive/dissipative operator R (linear and positive);
- The control operator B (linear);
- The **input** u and the **collocated output** y (boundary fields);

- The energy variables $\overrightarrow{\alpha}$ (vector field);
- The **Hamiltonian** $\mathcal{H}(\overrightarrow{\alpha}(t))$ (positive functional);
- The **co-energy variables** $\overrightarrow{e}_{\overrightarrow{\alpha}} := \delta_{\overrightarrow{\alpha}} \mathcal{H}$ (vector field), \rightarrow the variational derivative of \mathcal{H} w.r.t $\overrightarrow{\alpha}$;
- The *structure* operator *J* (linear and *formally skew-symmetric*);
- The resistive/dissipative operator R (linear and positive);
- The **control operator** *B* (linear);
- The **input** u and the **collocated output** y (boundary fields);
- The dynamical system:

$$\left\{ \begin{array}{l} \partial_t \overrightarrow{\alpha}(t) = (J - R) \overrightarrow{e}_{\overrightarrow{\alpha}}(t) + B \mathbf{u}(t), \\ \mathbf{y}(t) = B^* \overrightarrow{e}_{\overrightarrow{\alpha}}(t). \end{array} \right.$$

- The energy variables $\overrightarrow{\alpha}$ (vector field);
- The **Hamiltonian** $\mathcal{H}(\overrightarrow{\alpha}(t))$ (positive functional);
- The **co-energy variables** $\overrightarrow{e}_{\overrightarrow{\alpha}} := \delta_{\overrightarrow{\alpha}} \mathcal{H}$ (vector field), \rightarrow the variational derivative of \mathcal{H} w.r.t $\overrightarrow{\alpha}$;
- The *structure* operator *J* (linear and *formally skew-symmetric*);
- The resistive/dissipative operator R (linear and positive);
- The **control operator** B (linear);
- The **input** u and the **collocated output** y (boundary fields);
- The dynamical system:

$$\left\{ \begin{array}{l} \partial_t \overrightarrow{\alpha}(t) = (J - R) \overrightarrow{e}_{\overrightarrow{\alpha}}(t) + B \mathbf{u}(t), \\ \mathbf{y}(t) = B^* \overrightarrow{e}_{\overrightarrow{\alpha}}(t). \end{array} \right.$$

Lossy Power Balance

$$\tfrac{\mathrm{d}}{\mathrm{d}t}\mathcal{H}(\overrightarrow{\boldsymbol{\alpha}}(t)) = -\left\langle R\overrightarrow{\boldsymbol{e}}_{\overrightarrow{\boldsymbol{\alpha}}}(t), \overrightarrow{\boldsymbol{e}}_{\overrightarrow{\boldsymbol{\alpha}}}(t)\right\rangle_{I} + \left\langle \boldsymbol{u}(t), \boldsymbol{y}(t)\right\rangle_{B} \, \leq \, \left\langle \boldsymbol{u}(t), \boldsymbol{y}(t)\right\rangle_{B}.$$

Although the underlying geometry is well-determined with the above equality, constitutive relations between $\overrightarrow{\alpha}$ and $\overrightarrow{e}_{\overrightarrow{\alpha}}$ are also needed to solve the system!

Outline

- 1 Introduction
- 2 Linear Wave equations: towards PH-DAEs and PH-ODEs
 - Discretization in terms of energy and co-energy variables: PH-DAEs
 - Application: Boundary Dissipation
 - Discretization in terms of co-energy variables: PH-ODEs
 - Case of mixed boundary control: PH-DAEs again
 - Convergence of PFEM
- 3 Nonlinear wave equation: the 2D Shallow Water Equation

Deflection w of a 2D-membrane, boundary deflection velocity as control.

$$\mathcal{H}(\overrightarrow{\boldsymbol{\alpha}}_q, \alpha_p) := \frac{1}{2} \int_{\Omega} \left(\overrightarrow{\boldsymbol{\alpha}}_q \cdot \overline{\overline{\boldsymbol{T}}} \cdot \overrightarrow{\boldsymbol{\alpha}}_q + \frac{1}{\rho} \alpha_p^2 \right).$$

$$\mathcal{H}(\overrightarrow{\boldsymbol{\alpha}}_q, \alpha_p) := \frac{1}{2} \int_{\Omega} \left(\overrightarrow{\boldsymbol{\alpha}}_q \cdot \overline{\overline{\boldsymbol{T}}} \cdot \overrightarrow{\boldsymbol{\alpha}}_q + \frac{1}{\rho} \alpha_p^2 \right).$$

- ullet ρ the mass density of the medium and \overline{T} the Young modulus tensor;
- $\mathbf{Q}_p := \mathbf{Q} \partial_t w$ the linear momentum and $\overrightarrow{\mathbf{Q}}_q := \overrightarrow{\mathbf{grad}}(w)$ the strain;

$$\mathcal{H}(\overrightarrow{\boldsymbol{\alpha}}_q, \alpha_p) := \frac{1}{2} \int_{\Omega} \left(\overrightarrow{\boldsymbol{\alpha}}_q \cdot \overline{\overline{\boldsymbol{T}}} \cdot \overrightarrow{\boldsymbol{\alpha}}_q + \frac{1}{\rho} \alpha_p^2 \right).$$

- ullet ρ the mass density of the medium and \overline{T} the Young modulus tensor;
- $lackbox{\ } \alpha_p := rac{
 ho}{
 ho} \partial_t w$ the *linear momentum* and $\overrightarrow{lpha}_q := \overrightarrow{\mathbf{grad}}(w)$ the *strain*;
- $\overrightarrow{e}_q := \delta_{\overrightarrow{\alpha}_q} \mathcal{H} = \overline{\overline{T}} \cdot \overrightarrow{\alpha}_q$ the stress;
- $lackbox{\textbf{e}}_p := \delta_{lpha_p} \mathcal{H} = rac{lpha_p}{
 ho} = \partial_t w$ the deflection velocity and $oldsymbol{u} := e_p;$

$$\mathcal{H}(\overrightarrow{\boldsymbol{\alpha}}_q, \alpha_p) := \frac{1}{2} \int_{\Omega} \left(\overrightarrow{\boldsymbol{\alpha}}_q \cdot \overline{\overline{\boldsymbol{T}}} \cdot \overrightarrow{\boldsymbol{\alpha}}_q + \frac{1}{\rho} \alpha_p^2 \right).$$

- ullet ρ the mass density of the medium and \overline{T} the Young modulus tensor;
- $lackbox{\ } \alpha_p := rac{
 ho}{
 ho} \partial_t w$ the *linear momentum* and $\overrightarrow{lpha}_q := \overrightarrow{\mathbf{grad}}(w)$ the *strain*;
- $\overrightarrow{e}_q := \delta_{\overrightarrow{\alpha}_q} \mathcal{H} = \overline{\overline{T}} \cdot \overrightarrow{\alpha}_q$ the stress;
- $\bullet e_p := \delta_{\alpha_p} \mathcal{H} = \frac{\alpha_p}{\rho} = \partial_t w$ the deflection velocity and $u := e_p$;
- $\mathbf{y} := \overrightarrow{e}_q \cdot \overrightarrow{n}$ the output *normal stress*.

$$\mathcal{H}(\overrightarrow{\boldsymbol{\alpha}}_q, \alpha_p) := \frac{1}{2} \int_{\Omega} \left(\overrightarrow{\boldsymbol{\alpha}}_q \cdot \overline{\overline{\boldsymbol{T}}} \cdot \overrightarrow{\boldsymbol{\alpha}}_q + \frac{1}{\rho} \alpha_p^2 \right).$$

- ullet ho the mass density of the medium and $\overline{\overline{T}}$ the Young modulus tensor;
- $\mathbf{a}_p := \rho \, \partial_t w$ the linear momentum and $\overrightarrow{\mathbf{a}}_q := \overrightarrow{\mathbf{grad}}(w)$ the strain;
- $\overrightarrow{e}_q := \delta_{\overrightarrow{\alpha}_q} \mathcal{H} = \overline{\overline{T}} \cdot \overrightarrow{\alpha}_q$ the stress;
- $\bullet e_p := \delta_{\alpha_p} \mathcal{H} = \frac{\alpha_p}{\rho} = \partial_t w$ the deflection velocity and $u := e_p$;
- $\mathbf{y} := \overrightarrow{e}_q \cdot \overrightarrow{n}$ the output *normal stress*.

$$\begin{cases} \rho \partial_{tt}^{2} w &= \operatorname{div} \left(\overline{\overline{T}} \cdot \overrightarrow{\mathbf{grad}} (w) \right), \\ \boldsymbol{u} &= \partial_{t} w, \\ \boldsymbol{y} &= \left(\overline{\overline{T}} \cdot \overrightarrow{\mathbf{grad}} (w) \right) \cdot \overrightarrow{\boldsymbol{n}}. \end{cases}$$

$$\mathcal{H}(\overrightarrow{\boldsymbol{\alpha}}_q, \alpha_p) := \frac{1}{2} \int_{\Omega} \left(\overrightarrow{\boldsymbol{\alpha}}_q \cdot \overline{\overline{\boldsymbol{T}}} \cdot \overrightarrow{\boldsymbol{\alpha}}_q + \frac{1}{\rho} \alpha_p^2 \right).$$

- ullet ρ the mass density of the medium and \overline{T} the Young modulus tensor;
- $\mathbf{Q}_p := \rho \, \partial_t w$ the linear momentum and $\overrightarrow{\mathbf{Q}}_q := \overrightarrow{\mathbf{grad}}(w)$ the strain;
- $\overrightarrow{e}_q := \delta_{\overrightarrow{\alpha}_q} \mathcal{H} = \overline{\overline{T}} \cdot \overrightarrow{\alpha}_q$ the stress;
- $\bullet e_p := \delta_{\alpha_p} \mathcal{H} = \frac{\alpha_p}{\rho} = \partial_t w$ the deflection velocity and $u := e_p$;
- $oldsymbol{y}:=\overrightarrow{e}_q\cdot\overrightarrow{n}$ the output *normal stress*.

$$\left\{ \begin{array}{ll} \rho \partial_{tt}^2 w &= \operatorname{div} \left(\overline{\overline{T}} \cdot \overrightarrow{\mathbf{grad}} \left(w \right) \right), \\ \boldsymbol{u} &= \partial_t w, \\ \boldsymbol{y} &= \left(\overline{\overline{T}} \cdot \overrightarrow{\mathbf{grad}} \left(w \right) \right) \cdot \overrightarrow{\boldsymbol{n}}. \end{array} \right. \Leftrightarrow \left\{ \begin{array}{ll} \partial_t \overrightarrow{\boldsymbol{\alpha}}_q &= \overrightarrow{\mathbf{grad}} \left(e_p \right), \\ \partial_t \alpha_p &= \operatorname{div} \left(\overrightarrow{e}_q \right), \end{array} \right. \& \left\{ \begin{array}{ll} \boldsymbol{u} &= e_p, \\ \boldsymbol{y} &= \overrightarrow{e}_q \cdot \overrightarrow{\boldsymbol{n}}. \end{array} \right.$$

Deflection w of a 2D-membrane, boundary deflection velocity as control. Its total energy is given by the sum of the potential & kinetic energies:

$$\mathcal{H}(\overrightarrow{\boldsymbol{\alpha}}_q,\alpha_p) := \frac{1}{2} \int_{\Omega} \left(\overrightarrow{\boldsymbol{\alpha}}_q \cdot \overline{\overline{\boldsymbol{T}}} \cdot \overrightarrow{\boldsymbol{\alpha}}_q + \frac{1}{\rho} \alpha_p^2 \right).$$

- ullet ρ the mass density of the medium and \overline{T} the Young modulus tensor;
- $lackbox{$\boldsymbol{\alpha}$}_p := rac{
 ho}{\partial_t w}$ the linear momentum and $\overrightarrow{\boldsymbol{\alpha}}_q := \overrightarrow{\mathbf{grad}}(w)$ the strain;
- $\overrightarrow{e}_q := \delta_{\overrightarrow{\alpha}_q} \mathcal{H} = \overline{\overline{T}} \cdot \overrightarrow{\alpha}_q$ the stress;
- $\bullet e_p := \delta_{\alpha_p} \mathcal{H} = \frac{\alpha_p}{\rho} = \partial_t w$ the deflection velocity and $u := e_p$;
- $oldsymbol{y}:=\overrightarrow{e}_q\cdot\overrightarrow{n}$ the output *normal stress*.

$$\begin{cases} \rho \partial_{tt}^{2} w &= \operatorname{div} \left(\overline{\overline{T}} \cdot \overrightarrow{\mathbf{grad}} (w) \right), \\ \boldsymbol{u} &= \partial_{t} w, \\ \boldsymbol{y} &= \left(\overline{\overline{T}} \cdot \overrightarrow{\mathbf{grad}} (w) \right) \cdot \overrightarrow{\boldsymbol{n}}. \end{cases} \Leftrightarrow \begin{cases} \partial_{t} \overrightarrow{\boldsymbol{\alpha}}_{q} &= \overrightarrow{\mathbf{grad}} (e_{p}), \\ \partial_{t} \alpha_{p} &= \operatorname{div} \left(\overrightarrow{\boldsymbol{e}}_{q} \right), \end{cases} & \& \begin{cases} \boldsymbol{u} &= \boldsymbol{e}_{p}, \\ \boldsymbol{y} &= \overrightarrow{\boldsymbol{e}}_{q} \cdot \overrightarrow{\boldsymbol{n}}. \end{cases}$$

Lossless Power Balance

$$\frac{\mathrm{d}}{\mathrm{d}t}\mathcal{H}(\overrightarrow{\boldsymbol{\alpha}}_q, \boldsymbol{\alpha}_p) = \langle \boldsymbol{y}, \boldsymbol{u} \rangle_{H^{-\frac{1}{2}} H^{\frac{1}{2}}}.$$

 \implies for infinite-dimensional pHs in general, see the course by Birgit Jacob and Hans Zwart on Wednesday morning.

The strategy follows:

The strategy follows:

Write the weak formulation;

The strategy follows:

- Write the weak formulation;
- \blacksquare Apply an accurate **Stokes (Green) identity** (such that u "appears");

The strategy follows:

- Write the weak formulation;
- \blacksquare Apply an accurate **Stokes (Green) identity** (such that u "appears");
- 3 Project on a finite-dimensional space thanks to **FEM**.

The strategy follows:

- Write the weak formulation;
- \blacksquare Apply an accurate **Stokes (Green) identity** (such that u "appears");
- Project on a finite-dimensional space thanks to FEM.

For all test functions $\overrightarrow{\boldsymbol{v}}_q$, v_p and v_∂ (smooth enough):

$$\left\{ \begin{array}{l} \left\langle \partial_t \overrightarrow{\boldsymbol{\alpha}}_q, \overrightarrow{\boldsymbol{v}}_q \right\rangle_{\mathbf{L}^2} = \left\langle \overrightarrow{\mathbf{grad}} \left(\boldsymbol{e}_p \right), \overrightarrow{\boldsymbol{v}}_q \right\rangle_{\mathbf{L}^2}, \\ \left\langle \partial_t \alpha_p, v_p \right\rangle_{L^2} = \left\langle \operatorname{div} \left(\overrightarrow{\boldsymbol{e}}_q \right), v_p \right\rangle_{L^2}, \\ \left\langle \mathbf{\boldsymbol{y}}, v_\partial \right\rangle_{H^{-\frac{1}{2}}, H^{\frac{1}{2}}} = \left\langle \overrightarrow{\boldsymbol{e}}_q \cdot \overrightarrow{\boldsymbol{n}}, v_\partial \right\rangle_{H^{-\frac{1}{2}}, H^{\frac{1}{2}}}. \end{array} \right.$$

The strategy follows:

- Write the weak formulation;
- \blacksquare Apply an accurate **Stokes (Green) identity** (such that u "appears");
- 3 Project on a finite-dimensional space thanks to **FEM**.

For all test functions $\overrightarrow{\boldsymbol{v}}_q$, v_p and v_∂ (smooth enough):

$$\left\{ \begin{array}{l} \left\langle \partial_t \overrightarrow{\boldsymbol{\alpha}}_q, \overrightarrow{\boldsymbol{v}}_q \right\rangle_{\mathbf{L}^2} = \left\langle \overrightarrow{\mathbf{grad}} \left(\boldsymbol{e}_p \right), \overrightarrow{\boldsymbol{v}}_q \right\rangle_{\mathbf{L}^2}, \\ \left\langle \partial_t \alpha_p, v_p \right\rangle_{L^2} = \left\langle \operatorname{div} \left(\overrightarrow{\boldsymbol{e}}_q \right), v_p \right\rangle_{L^2}, \\ \left\langle \boldsymbol{y}, v_\partial \right\rangle_{H^{-\frac{1}{2}}, H^{\frac{1}{2}}} = \left\langle \overrightarrow{\boldsymbol{e}}_q \cdot \overrightarrow{\boldsymbol{n}}, v_\partial \right\rangle_{H^{-\frac{1}{2}}, H^{\frac{1}{2}}}. \end{array} \right.$$

Applying Green's formula on the 1st line and using the definition of u:

$$\left\langle \partial_t \overrightarrow{\boldsymbol{\alpha}}_q, \overrightarrow{\boldsymbol{v}}_q \right\rangle_{\mathbf{L}^2} = -\left\langle \underline{\boldsymbol{e}}_p, \operatorname{div} \left(\overrightarrow{\boldsymbol{v}}_q \right) \right\rangle_{L^2} + \left\langle \overrightarrow{\boldsymbol{v}}_q \cdot \overrightarrow{\boldsymbol{n}}, \underline{\boldsymbol{u}} \right\rangle_{H^{-\frac{1}{2}}, H^{\frac{1}{2}}}.$$

Conservative System: PFEM strategy

The strategy follows:

- Write the weak formulation;
- **2** Apply an accurate **Stokes (Green) identity** (such that u "appears");
- 3 Project on a finite-dimensional space thanks to **FEM**.

For all test functions $\overrightarrow{\boldsymbol{v}}_q$, v_p and v_∂ (smooth enough):

$$\left\{ \begin{array}{l} \left\langle \partial_t \overrightarrow{\boldsymbol{\alpha}}_q, \overrightarrow{\boldsymbol{v}}_q \right\rangle_{\mathbf{L}^2} = \left\langle \overrightarrow{\mathbf{grad}} \left(\boldsymbol{e}_p \right), \overrightarrow{\boldsymbol{v}}_q \right\rangle_{\mathbf{L}^2}, \\ \left\langle \partial_t \alpha_p, v_p \right\rangle_{L^2} = \left\langle \operatorname{div} \left(\overrightarrow{\boldsymbol{e}}_q \right), v_p \right\rangle_{L^2}, \\ \left\langle \boldsymbol{y}, v_\partial \right\rangle_{H^{-\frac{1}{2}}, H^{\frac{1}{2}}} = \left\langle \overrightarrow{\boldsymbol{e}}_q \cdot \overrightarrow{\boldsymbol{n}}, v_\partial \right\rangle_{H^{-\frac{1}{2}}, H^{\frac{1}{2}}}. \end{array} \right.$$

Applying Green's formula on the 1st line and using the definition of u:

$$\left\langle \partial_t \overrightarrow{\boldsymbol{\alpha}}_q, \overrightarrow{\boldsymbol{v}}_q \right\rangle_{\mathbf{L}^2} = -\left\langle \boldsymbol{e}_p, \operatorname{div} \left(\overrightarrow{\boldsymbol{v}}_q \right) \right\rangle_{L^2} + \left\langle \overrightarrow{\boldsymbol{v}}_q \cdot \overrightarrow{\boldsymbol{n}}, \boldsymbol{u} \right\rangle_{H^{-\frac{1}{2}} H^{\frac{1}{2}}}.$$

Green's formula applied on the 2nd line would lead to normal stress control $u = \overrightarrow{e}_q \cdot \overrightarrow{n}$. The energy variables are **partitioned** accordingly.

The energy, co-energy, boundary and test functions of the *same* index are discretized by using the *same* bases, either scalar- or **vector**-valued:

$$\overrightarrow{\alpha}_q^{ap}(t,\overrightarrow{\boldsymbol{x}}) := \textstyle\sum_{\ell=1}^{N_q} \overrightarrow{\phi}_q^{\ell}(\overrightarrow{\boldsymbol{x}}) \alpha_q^{\ell}(t) = \overrightarrow{\boldsymbol{\Phi}}_q^{\top} \cdot \underline{\alpha}_q(t),$$

with $\overrightarrow{\boldsymbol{\Phi}}_q$ an $N_q\times 2$ matrix,

The energy, co-energy, boundary and test functions of the *same* index are discretized by using the *same* bases, either scalar- or **vector**-valued:

$$\overrightarrow{\pmb{\alpha}}_q^{ap}(t,\overrightarrow{\pmb{x}}) := \textstyle\sum_{\ell=1}^{N_q} \overrightarrow{\pmb{\phi}}_q^{\ell}(\overrightarrow{\pmb{x}}) \alpha_q^{\ell}(t) = \overrightarrow{\pmb{\Phi}}_q^{\top} \cdot \underline{\alpha}_q(t), \quad \overrightarrow{\pmb{e}}_q^{ap}(t,\overrightarrow{\pmb{x}}) = \overrightarrow{\pmb{\Phi}}_q^{\top} \cdot \underline{\underline{e}}_q(t),$$

with $\overrightarrow{\Phi}_q$ an $N_q \times 2$ matrix,

The energy, co-energy, boundary and test functions of the *same* index are discretized by using the *same* bases, either scalar- or **vector**-valued:

$$\begin{array}{l} \overrightarrow{\boldsymbol{\alpha}}_{q}^{ap}(t,\overrightarrow{\boldsymbol{x}}) := \sum_{\ell=1}^{N_q} \overrightarrow{\boldsymbol{\phi}}_{q}^{\ell}(\overrightarrow{\boldsymbol{x}}) \boldsymbol{\alpha}_{q}^{\ell}(t) = \overrightarrow{\boldsymbol{\Phi}}_{q}^{\top} \cdot \underline{\boldsymbol{\alpha}}_{q}(t), \quad \overrightarrow{\boldsymbol{e}}_{q}^{ap}(t,\overrightarrow{\boldsymbol{x}}) = \overrightarrow{\boldsymbol{\Phi}}_{q}^{\top} \cdot \underline{\boldsymbol{e}}_{q}(t), \\ \boldsymbol{\alpha}_{p}^{ap}(t,\overrightarrow{\boldsymbol{x}}) := \sum_{k=1}^{N_p} \varphi_{p}^{k}(\overrightarrow{\boldsymbol{x}}) \boldsymbol{\alpha}_{p}^{k}(t) = \boldsymbol{\phi}_{p}^{\top} \cdot \underline{\boldsymbol{\alpha}}_{p}(t), \qquad \boldsymbol{e}_{p}^{ap}(t,\overrightarrow{\boldsymbol{x}}) = \boldsymbol{\phi}_{p}^{\top} \cdot \underline{\boldsymbol{e}}_{p}(t), \end{array}$$

with $\overrightarrow{\Phi}_q$ an $N_q \times 2$ matrix, ϕ_p an $N_p \times 1$ matrix

The energy, co-energy, boundary and test functions of the *same* index are discretized by using the *same* bases, either scalar- or **vector**-valued:

$$\begin{split} \overrightarrow{\boldsymbol{\alpha}}_{q}^{ap}(t,\overrightarrow{\boldsymbol{x}}) &:= \sum_{\ell=1}^{N_{q}} \overrightarrow{\boldsymbol{\phi}}_{q}^{\ell}(\overrightarrow{\boldsymbol{x}}) \boldsymbol{\alpha}_{q}^{\ell}(t) = \overrightarrow{\boldsymbol{\Phi}}_{q}^{\top} \cdot \underline{\boldsymbol{\alpha}}_{q}(t), \quad \overrightarrow{\boldsymbol{e}}_{q}^{ap}(t,\overrightarrow{\boldsymbol{x}}) &= \overrightarrow{\boldsymbol{\Phi}}_{q}^{\top} \cdot \underline{\boldsymbol{e}}_{q}(t), \\ \boldsymbol{\alpha}_{p}^{ap}(t,\overrightarrow{\boldsymbol{x}}) &:= \sum_{k=1}^{N_{p}} \varphi_{p}^{k}(\overrightarrow{\boldsymbol{x}}) \boldsymbol{\alpha}_{p}^{k}(t) = \boldsymbol{\phi}_{p}^{\top} \cdot \underline{\boldsymbol{\alpha}}_{p}(t), \qquad \boldsymbol{e}_{p}^{ap}(t,\overrightarrow{\boldsymbol{x}}) &= \boldsymbol{\phi}_{p}^{\top} \cdot \underline{\boldsymbol{e}}_{p}(t), \\ \boldsymbol{u}^{ap}(t,\overrightarrow{\boldsymbol{s}}) &:= \sum_{m=1}^{N_{\partial}} \psi^{m}(\overrightarrow{\boldsymbol{s}}) \boldsymbol{u}^{m}(t) = \boldsymbol{\Psi}^{\top} \cdot \underline{\boldsymbol{u}}(t), \qquad \boldsymbol{y}^{ap}(t,\overrightarrow{\boldsymbol{s}}) &= \boldsymbol{\Psi}^{\top} \cdot \underline{\boldsymbol{y}}(t), \end{split}$$

with $\overrightarrow{\Phi}_q$ an $N_q \times 2$ matrix, $\pmb{\phi}_p$ an $N_p \times 1$ matrix and $\pmb{\Psi}$ an $N_\partial \times 1$ matrix.

The energy, co-energy, boundary and test functions of the *same* index are discretized by using the *same* bases, either scalar- or **vector**-valued:

$$\begin{split} \overrightarrow{\boldsymbol{\alpha}}_{q}^{ap}(t,\overrightarrow{\boldsymbol{x}}) &:= \sum_{\ell=1}^{N_q} \overrightarrow{\boldsymbol{\phi}}_{q}^{\ell}(\overrightarrow{\boldsymbol{x}}) \boldsymbol{\alpha}_{q}^{\ell}(t) = \overrightarrow{\boldsymbol{\Phi}}_{q}^{\top} \cdot \underline{\boldsymbol{\alpha}}_{q}(t), & \overrightarrow{\boldsymbol{e}}_{q}^{ap}(t,\overrightarrow{\boldsymbol{x}}) &= \overrightarrow{\boldsymbol{\Phi}}_{q}^{\top} \cdot \underline{\boldsymbol{e}}_{q}(t), \\ \boldsymbol{\alpha}_{p}^{ap}(t,\overrightarrow{\boldsymbol{x}}) &:= \sum_{k=1}^{N_p} \varphi_{p}^{k}(\overrightarrow{\boldsymbol{x}}) \boldsymbol{\alpha}_{p}^{k}(t) = \boldsymbol{\phi}_{p}^{\top} \cdot \underline{\boldsymbol{\alpha}}_{p}(t), & \boldsymbol{e}_{p}^{ap}(t,\overrightarrow{\boldsymbol{x}}) &= \boldsymbol{\phi}_{p}^{\top} \cdot \underline{\boldsymbol{e}}_{p}(t), \\ \boldsymbol{u}^{ap}(t,\overrightarrow{\boldsymbol{s}}) &:= \sum_{m=1}^{N_{\partial}} \psi^{m}(\overrightarrow{\boldsymbol{s}}) \boldsymbol{u}^{m}(t) = \boldsymbol{\Psi}^{\top} \cdot \underline{\boldsymbol{u}}(t), & \boldsymbol{y}^{ap}(t,\overrightarrow{\boldsymbol{s}}) &= \boldsymbol{\Psi}^{\top} \cdot \underline{\boldsymbol{y}}(t), \end{split}$$

with $\overrightarrow{\Phi}_q$ an $N_q \times 2$ matrix, ϕ_p an $N_p \times 1$ matrix and Ψ an $N_\partial \times 1$ matrix.

The discretized system (giving the structure) then reads:

$$\begin{cases} \overrightarrow{\boldsymbol{M}}_q \cdot \frac{\mathrm{d}}{\mathrm{d}t} \underline{\alpha}_q(t) = D \cdot \underline{\boldsymbol{e}}_p(t) + B \cdot \underline{\boldsymbol{u}}(t), \\ M_p \cdot \frac{\mathrm{d}}{\mathrm{d}t} \underline{\alpha}_p(t) = -D^\top \cdot \underline{\boldsymbol{e}}_q(t), \\ M_{\partial} \cdot \underline{\boldsymbol{y}}(t) = B^\top \cdot \underline{\boldsymbol{e}}_q(t), \end{cases}$$

The energy, co-energy, boundary and test functions of the *same* index are discretized by using the *same* bases, either scalar- or **vector**-valued:

$$\begin{split} \overrightarrow{\boldsymbol{\alpha}}_{q}^{ap}(t,\overrightarrow{\boldsymbol{x}}) &:= \sum_{\ell=1}^{N_q} \overrightarrow{\boldsymbol{\phi}}_{q}^{\ell}(\overrightarrow{\boldsymbol{x}}) \boldsymbol{\alpha}_{q}^{\ell}(t) = \overrightarrow{\boldsymbol{\Phi}}_{q}^{\top} \cdot \underline{\boldsymbol{\alpha}}_{q}(t), & \overrightarrow{\boldsymbol{e}}_{q}^{ap}(t,\overrightarrow{\boldsymbol{x}}) &= \overrightarrow{\boldsymbol{\Phi}}_{q}^{\top} \cdot \underline{\boldsymbol{e}}_{q}(t), \\ \boldsymbol{\alpha}_{p}^{ap}(t,\overrightarrow{\boldsymbol{x}}) &:= \sum_{k=1}^{N_p} \varphi_{p}^{k}(\overrightarrow{\boldsymbol{x}}) \boldsymbol{\alpha}_{p}^{k}(t) = \boldsymbol{\phi}_{p}^{\top} \cdot \underline{\boldsymbol{\alpha}}_{p}(t), & \boldsymbol{e}_{p}^{ap}(t,\overrightarrow{\boldsymbol{x}}) &= \boldsymbol{\phi}_{p}^{\top} \cdot \underline{\boldsymbol{e}}_{p}(t), \\ \boldsymbol{u}^{ap}(t,\overrightarrow{\boldsymbol{s}}) &:= \sum_{m=1}^{N_{\partial}} \psi^{m}(\overrightarrow{\boldsymbol{s}}) \boldsymbol{u}^{m}(t) = \boldsymbol{\Psi}^{\top} \cdot \underline{\boldsymbol{u}}(t), & \boldsymbol{y}^{ap}(t,\overrightarrow{\boldsymbol{s}}) &= \boldsymbol{\Psi}^{\top} \cdot \underline{\boldsymbol{y}}(t), \end{split}$$

with $\overrightarrow{\Phi}_q$ an $N_q \times 2$ matrix, ϕ_p an $N_p \times 1$ matrix and Ψ an $N_\partial \times 1$ matrix.

The discretized system (giving the structure) then reads:

$$\left\{ \begin{array}{l} \overrightarrow{\boldsymbol{M}}_q \cdot \frac{\mathrm{d}}{\mathrm{d}t} \underline{\boldsymbol{\alpha}}_q(t) = D \cdot \underline{\boldsymbol{e}}_p(t) + B \cdot \underline{\boldsymbol{u}}(t), \\ M_p \cdot \frac{\mathrm{d}}{\mathrm{d}t} \underline{\boldsymbol{\alpha}}_p(t) = -D^\top \cdot \underline{\boldsymbol{e}}_q(t), \\ M_{\partial} \cdot \boldsymbol{y}(t) = B^\top \cdot \underline{\boldsymbol{e}}_q(t), \end{array} \right.$$

where:

$$\overrightarrow{\boldsymbol{M}}_{q} := \int_{\Omega} \overrightarrow{\boldsymbol{\Phi}}_{q} \cdot \overrightarrow{\boldsymbol{\Phi}}_{q}^{\top}, \qquad M_{p} := \int_{\Omega} \boldsymbol{\phi}_{p} \cdot \boldsymbol{\phi}_{p}^{\top}, \qquad M_{\partial} := \int_{\partial \Omega} \boldsymbol{\Psi} \cdot \boldsymbol{\Psi}^{\top},$$

$$D := -\int_{\Omega} \operatorname{div} \left(\overrightarrow{\boldsymbol{\Phi}}_{q}\right) \cdot \boldsymbol{\phi}_{p}^{\top}, \qquad B := \int_{\partial \Omega} \left(\overrightarrow{\boldsymbol{\Phi}}_{q} \cdot \overrightarrow{\boldsymbol{n}}\right) \cdot \boldsymbol{\Psi}^{\top}.$$

Finite-Dimensional extended structure operator

$$\mathcal{J}_d := \begin{pmatrix} 0 & D & B \\ -D^\top & 0 & 0 \\ -B^\top & 0 & 0 \end{pmatrix}.$$

Finite-Dimensional extended structure operator

$$\mathcal{J}_d := \begin{pmatrix} 0 & D & B \\ -D^\top & 0 & 0 \\ -B^\top & 0 & 0 \end{pmatrix}.$$

The inner product on \mathbb{R}^{N_q} , \mathbb{R}^{N_p} and $\mathbb{R}^{N_{\partial}}$ has to be taken w.r.t. the mass matrices \overrightarrow{M}_q , M_p and M_{∂} : e.g. $\left\langle \overrightarrow{v}_1, \overrightarrow{v}_2 \right\rangle_{N_q} := \overrightarrow{v}_2^{\top} \cdot \overrightarrow{M}_q \cdot \overrightarrow{v}_1$.

Finite-Dimensional extended structure operator

$$\mathcal{J}_d := \begin{pmatrix} 0 & D & B \\ -D^\top & 0 & 0 \\ -B^\top & 0 & 0 \end{pmatrix}.$$

The inner product on \mathbb{R}^{N_q} , \mathbb{R}^{N_p} and $\mathbb{R}^{N_{\partial}}$ has to be taken w.r.t. the mass matrices \overrightarrow{M}_q , M_p and M_{∂} : e.g. $\left\langle \overrightarrow{v}_1, \overrightarrow{v}_2 \right\rangle_{N_o} := \overrightarrow{v}_2^{\top} \cdot \overrightarrow{M}_q \cdot \overrightarrow{v}_1$.

Discrete Hamiltonian

$$\mathcal{H}_d\left(\underline{lpha}_q,\underline{lpha}_p
ight) := \mathcal{H}\left(\overrightarrow{m{lpha}}_q^{ap}, \mathbf{lpha}_p^{ap}
ight) = rac{1}{2}\left(\underline{lpha}_q^ op \cdot \overrightarrow{m{M}}_{\overline{\overline{m{r}}}} \cdot \underline{lpha}_q + \underline{lpha}_p^ op \cdot M_{rac{1}{
ho}} \cdot \underline{lpha}_p
ight),$$

Finite-Dimensional extended structure operator

$$\mathcal{J}_d := \begin{pmatrix} 0 & D & B \\ -D^\top & 0 & 0 \\ -B^\top & 0 & 0 \end{pmatrix}.$$

The inner product on \mathbb{R}^{N_q} , \mathbb{R}^{N_p} and $\mathbb{R}^{N_{\partial}}$ has to be taken w.r.t. the mass matrices \overrightarrow{M}_q , M_p and M_{∂} : e.g. $\left\langle \overrightarrow{v}_1, \overrightarrow{v}_2 \right\rangle_{N_o} := \overrightarrow{v}_2^{\top} \cdot \overrightarrow{M}_q \cdot \overrightarrow{v}_1$.

Discrete Hamiltonian

$$\begin{aligned} \mathcal{H}_d\left(\underline{\alpha}_q,\underline{\alpha}_p\right) &:= \mathcal{H}\left(\overrightarrow{\boldsymbol{\alpha}}_q^{ap},\alpha_p^{ap}\right) = \frac{1}{2}\left(\underline{\alpha}_q^\top \cdot \overrightarrow{\boldsymbol{M}}_{\overline{\overline{\boldsymbol{T}}}} \cdot \underline{\alpha}_q + \underline{\alpha}_p^\top \cdot M_{\frac{1}{\rho}} \cdot \underline{\alpha}_p\right), \\ \overrightarrow{\boldsymbol{M}}_{\overline{\overline{\boldsymbol{T}}}} &:= \int_{\Omega} \overrightarrow{\boldsymbol{\Phi}}_q \cdot \overline{\overline{\boldsymbol{T}}} \cdot \overrightarrow{\boldsymbol{\Phi}}_q^\top & \& \quad M_{\frac{1}{\rho}} := \int_{\Omega} \frac{1}{\rho} \phi_p \cdot \phi_p^\top. \end{aligned}$$

Finite-Dimensional extended structure operator

$$\mathcal{J}_d := \begin{pmatrix} 0 & D & B \\ -D^\top & 0 & 0 \\ -B^\top & 0 & 0 \end{pmatrix}.$$

The inner product on \mathbb{R}^{N_q} , \mathbb{R}^{N_p} and $\mathbb{R}^{N_{\partial}}$ has to be taken w.r.t. the mass matrices \overrightarrow{M}_q , M_p and M_{∂} : e.g. $\left\langle \overrightarrow{v}_1, \overrightarrow{v}_2 \right\rangle_{N_a} := \overrightarrow{v}_2^{\top} \cdot \overrightarrow{M}_q \cdot \overrightarrow{v}_1$.

Discrete Hamiltonian

$$\mathcal{H}_{d}\left(\underline{\alpha}_{q},\underline{\alpha}_{p}\right) := \mathcal{H}\left(\overrightarrow{\boldsymbol{\alpha}}_{q}^{ap},\alpha_{p}^{ap}\right) = \frac{1}{2}\left(\underline{\alpha}_{q}^{\top}\cdot\overrightarrow{\boldsymbol{M}}_{\overline{\boldsymbol{T}}}^{\top}\cdot\underline{\alpha}_{q} + \underline{\alpha}_{p}^{\top}\cdot\boldsymbol{M}_{\frac{1}{\rho}}\cdot\underline{\alpha}_{p}\right),$$

$$\overrightarrow{\boldsymbol{M}}_{\overline{\boldsymbol{T}}} := \int_{\Omega}\overrightarrow{\boldsymbol{\Phi}}_{q}\cdot\overline{\overline{\boldsymbol{T}}}\cdot\overrightarrow{\boldsymbol{\Phi}}_{q}^{\top} \qquad \& \qquad \boldsymbol{M}_{\frac{1}{\rho}} := \int_{\Omega}\frac{1}{\rho}\boldsymbol{\phi}_{p}\cdot\boldsymbol{\phi}_{p}^{\top}.$$

Finite-Dimensional extended structure operator

$$\mathcal{J}_d := \begin{pmatrix} 0 & D & B \\ -D^\top & 0 & 0 \\ -B^\top & 0 & 0 \end{pmatrix}.$$

The inner product on \mathbb{R}^{N_q} , \mathbb{R}^{N_p} and $\mathbb{R}^{N_{\partial}}$ has to be taken w.r.t. the mass matrices \overrightarrow{M}_q , M_p and M_{∂} : e.g. $\left\langle \overrightarrow{v}_1, \overrightarrow{v}_2 \right\rangle_{N_a} := \overrightarrow{v}_2^{\top} \cdot \overrightarrow{M}_q \cdot \overrightarrow{v}_1$.

Discrete Hamiltonian

$$\mathcal{H}_{d}\left(\underline{\alpha}_{q},\underline{\alpha}_{p}\right) := \mathcal{H}\left(\overrightarrow{\boldsymbol{\alpha}}_{q}^{ap},\alpha_{p}^{ap}\right) = \frac{1}{2}\left(\underline{\alpha}_{q}^{\top}\cdot\overrightarrow{\boldsymbol{M}}_{\overline{\boldsymbol{T}}}\cdot\underline{\alpha}_{q} + \underline{\alpha}_{p}^{\top}\cdot\boldsymbol{M}_{\frac{1}{\rho}}\cdot\underline{\alpha}_{p}\right),$$

$$\overrightarrow{\boldsymbol{M}}_{\overline{\boldsymbol{T}}} := \int_{\Omega}\overrightarrow{\boldsymbol{\Phi}}_{q}\cdot\overline{\overline{\boldsymbol{T}}}\cdot\overrightarrow{\boldsymbol{\Phi}}_{q}^{\top} \qquad \& \qquad \boldsymbol{M}_{\frac{1}{\rho}} := \int_{\Omega}\frac{1}{\rho}\boldsymbol{\phi}_{p}\cdot\boldsymbol{\phi}_{p}^{\top}.$$

Discrete Lossless Power Balance

$$\frac{\mathrm{d}}{\mathrm{d}t} \mathcal{H}_d \left(\underline{\alpha}_q, \underline{\alpha}_p \right) = \underline{\boldsymbol{u}}^\top \cdot M_\partial \cdot \boldsymbol{y}.$$

A Proof of the Discrete Power Balance

Since by definition the discrete Hamiltonian reads:

$$\mathcal{H}_d\left(\underline{lpha}_q,\underline{lpha}_p
ight) = rac{1}{2} \left(\underline{lpha}_q^ op \cdot \overrightarrow{m{M}}_{\overline{m{r}}} \cdot \underline{lpha}_q + \underline{lpha}_p^ op \cdot M_{rac{1}{
ho}} \cdot \underline{lpha}_p
ight),$$

we can compute its time derivative along the trajectories:

$$\frac{\mathrm{d}}{\mathrm{d}t}\mathcal{H}_{d}\left(\underline{\alpha}_{q},\underline{\alpha}_{p}\right) = \left(\frac{\mathrm{d}}{\mathrm{d}t}\underline{\alpha}_{q}\right)^{\top} \cdot \overrightarrow{M}_{\overline{\mathbf{T}}} \cdot \underline{\alpha}_{q} + \left(\frac{\mathrm{d}}{\mathrm{d}t}\underline{\alpha}_{p}\right)^{\top} \cdot M_{\frac{1}{\rho}} \cdot \underline{\alpha}_{p},$$

$$= \left(\frac{\mathrm{d}}{\mathrm{d}t}\underline{\alpha}_{q}\right)^{\top} \cdot \overrightarrow{M}_{q} \cdot \underline{e}_{q} + \left(\frac{\mathrm{d}}{\mathrm{d}t}\underline{\alpha}_{p}\right)^{\top} \cdot M_{p} \cdot \underline{e}_{p},$$

$$= \left(\overrightarrow{M}_{q} \cdot \frac{\mathrm{d}}{\mathrm{d}t}\underline{\alpha}_{q}\right)^{\top} \cdot \underline{e}_{q} + \left(M_{p} \cdot \frac{\mathrm{d}}{\mathrm{d}t}\underline{\alpha}_{p}\right)^{\top} \cdot \underline{e}_{p},$$

$$= \left(D \cdot \underline{e}_{p}(t) + B \cdot \underline{u}(t)\right)^{\top} \cdot \underline{e}_{q} + \left(-D^{\top} \cdot \underline{e}_{q}(t)\right)^{\top} \cdot \underline{e}_{p},$$

$$= \underline{u}(t)^{\top} \cdot B^{\top} \cdot \underline{e}_{q}$$

$$= \underline{u}(t)^{\top} \cdot M_{\partial} \cdot \underline{y}(t). \quad \Box$$

PFEM for pHs gives rise to PH-DAEs

Summarizing the main steps: discretization of the structure and of the constitutive relations are made separately.

The discretized system is a PH-DAE:

$$\left\{ \begin{array}{l} \overrightarrow{\boldsymbol{M}}_q \cdot \frac{\mathrm{d}}{\mathrm{d}t} \underline{\boldsymbol{\alpha}}_q(t) = D \cdot \underline{\boldsymbol{e}}_p(t) + B \cdot \underline{\boldsymbol{u}}(t), \\ M_p \cdot \frac{\mathrm{d}}{\mathrm{d}t} \underline{\boldsymbol{\alpha}}_p(t) = -D^\top \cdot \underline{\boldsymbol{e}}_q(t), \\ M_{\partial} \cdot \underline{\boldsymbol{y}}(t) = B^\top \cdot \underline{\boldsymbol{e}}_q(t), \\ & \text{together with} \\ \left\{ \begin{array}{l} \overrightarrow{\boldsymbol{M}}_q \cdot \underline{\boldsymbol{e}}_q(t) = \overrightarrow{\boldsymbol{M}}_{\overline{\boldsymbol{T}}} \cdot \underline{\boldsymbol{\alpha}}_q(t), \\ M_p \cdot \underline{\boldsymbol{e}}_p(t) = M_{\frac{1}{2}} \cdot \underline{\boldsymbol{\alpha}}_p(t) \end{array} \right. \end{array} \right.$$

⇒ in general, PFEM for pHs gives rise to finite-dimensional PH-DAEs, for which efficient numerical methods can be used (see the course by Volker Mehrmann on Tuesday morning)

Outline

- 1 Introduction
- 2 Linear Wave equations: towards PH-DAEs and PH-ODEs
 - Discretization in terms of energy and co-energy variables: PH-DAEs
 - Application: Boundary Dissipation
 - Discretization in terms of co-energy variables: PH-ODEs
 - Case of mixed boundary control: PH-DAEs again
 - Convergence of PFEM
- 3 Nonlinear wave equation: the 2D Shallow Water Equation

The Impedance Boundary Condition, with $Z \geq 0$ on $\partial\Omega$, and ν as new control, is considered: $\nu = e_p + Z\overrightarrow{e}_q \cdot \overrightarrow{n} \Leftrightarrow \nu = \partial_t w + Z\left(\overline{\overline{T}} \cdot \overrightarrow{\mathbf{grad}}(w)\right) \cdot \overrightarrow{n}$.

The Impedance Boundary Condition, with $Z \geq 0$ on $\partial \Omega$, and ν as new control, is considered: $\nu = e_p + Z \overrightarrow{e}_q \cdot \overrightarrow{n} \Leftrightarrow \nu = \partial_t w + Z \left(\overline{T} \cdot \overrightarrow{\mathbf{grad}}(w) \right) \cdot \overrightarrow{n}$. This kind of dissipation does not easily fit in the "J - R framework".

The Impedance Boundary Condition, with $Z \geq 0$ on $\partial\Omega$, and ν as new control, is considered: $\nu = e_p + Z \overrightarrow{e}_q \cdot \overrightarrow{n} \Leftrightarrow \nu = \partial_t w + Z \left(\overline{T} \cdot \overrightarrow{\mathbf{grad}}(w)\right) \cdot \overrightarrow{n}$. This kind of dissipation does not *easily* fit in the "J-R framework". It can be seen as an *output feedback law* $u = -Zy + \nu$ in the previous case.

Lossy Power Balance

$$\frac{\mathrm{d}}{\mathrm{d}t}\mathcal{H}(\overrightarrow{\boldsymbol{\alpha}}_q,\alpha_p) = -\left\langle \boldsymbol{y},\boldsymbol{Z}\boldsymbol{y}\right\rangle_{H^{-\frac{1}{2}}.H^{\frac{1}{2}}} + \left\langle \boldsymbol{y},\boldsymbol{\nu}\right\rangle_{H^{-\frac{1}{2}}.H^{\frac{1}{2}}}.$$

The Impedance Boundary Condition, with $Z \geq 0$ on $\partial\Omega$, and ${\boldsymbol \nu}$ as new control, is considered: ${\boldsymbol \nu} = e_p + Z \overrightarrow{\boldsymbol e}_q \cdot \overrightarrow{\boldsymbol n} \Leftrightarrow {\boldsymbol \nu} = \partial_t w + Z \left(\overline{\overline{\boldsymbol T}} \cdot \overrightarrow{\mathbf{grad}} \left(w\right)\right) \cdot \overrightarrow{\boldsymbol n}$. This kind of dissipation does not *easily* fit in the "J-R framework". It can be seen as an *output feedback law* ${\boldsymbol u} = -Z{\boldsymbol y} + {\boldsymbol \nu}$ in the previous case.

Lossy Power Balance

$$\frac{\mathrm{d}}{\mathrm{d}t}\mathcal{H}(\overrightarrow{\boldsymbol{\alpha}}_q,\alpha_p) = -\left\langle \boldsymbol{y},\boldsymbol{Z}\boldsymbol{y}\right\rangle_{H^{-\frac{1}{2}}.H^{\frac{1}{2}}} + \left\langle \boldsymbol{y},\boldsymbol{\nu}\right\rangle_{H^{-\frac{1}{2}}.H^{\frac{1}{2}}}.$$

Add impedance ports (f_i, e_i) and dissipative constitutive relation $e_i = Zf_i$, and approximate f_i and e_i in the boundary FEM basis Ψ :

$$\begin{pmatrix} \overrightarrow{M}_q & 0 & 0 & 0 & 0 \\ 0 & M_p & 0 & 0 & 0 \\ 0 & 0 & M_p & 0 & 0 \\ 0 & 0 & 0 & M_{\partial} & 0 \\ 0 & 0 & 0 & 0 & M_{\partial} \end{pmatrix} \begin{pmatrix} \frac{\mathrm{d}}{\mathrm{d}t} \underline{\alpha}_q(t) \\ \frac{\mathrm{d}}{\mathrm{d}t} \underline{\alpha}_p(t) \\ \underline{f}_i(t) \\ -\underline{\boldsymbol{y}}(t) \end{pmatrix} = \begin{pmatrix} 0 & D & -B & B \\ -D^\top & 0 & 0 & 0 \\ B^\top & 0 & 0 & 0 \\ -B^\top & 0 & 0 & 0 \end{pmatrix} \begin{pmatrix} \underline{e}_q(t) \\ \underline{e}_p(t) \\ \underline{e}_i(t) \\ \underline{\boldsymbol{\nu}}(t) \end{pmatrix}$$

and
$$M_{\partial} \cdot \underline{e}_i = \langle \underline{Z} \rangle \cdot \underline{f}_i$$
, with $\langle \underline{Z} \rangle := \int_{\partial\Omega} \underline{Z} \Psi \cdot \Psi^{\top} \geq 0$.

The Impedance Boundary Condition, with $Z \geq 0$ on $\partial\Omega$, and $\boldsymbol{\nu}$ as new control, is considered: $\boldsymbol{\nu} = e_p + Z \overrightarrow{e}_q \cdot \overrightarrow{\boldsymbol{n}} \Leftrightarrow \boldsymbol{\nu} = \partial_t w + Z \left(\overline{T} \cdot \overrightarrow{\mathbf{grad}} \left(w \right) \right) \cdot \overrightarrow{\boldsymbol{n}}$. This kind of dissipation does not *easily* fit in the "J-R framework". It can be seen as an *output feedback law* $\boldsymbol{u} = -Z \boldsymbol{y} + \boldsymbol{\nu}$ in the previous case.

Lossy Power Balance

$$\frac{\mathrm{d}}{\mathrm{d}t}\mathcal{H}(\overrightarrow{\boldsymbol{\alpha}}_q,\alpha_p) = -\left\langle \boldsymbol{y},\boldsymbol{Z}\boldsymbol{y}\right\rangle_{H^{-\frac{1}{2}},H^{\frac{1}{2}}} + \left\langle \boldsymbol{y},\boldsymbol{\nu}\right\rangle_{H^{-\frac{1}{2}},H^{\frac{1}{2}}}.$$

Add impedance ports (f_i, e_i) and dissipative constitutive relation $e_i = Zf_i$, and approximate f_i and e_i in the boundary FEM basis Ψ :

$$\begin{pmatrix} \overrightarrow{M}_q & 0 & 0 & 0 & 0 \\ 0 & M_p & 0 & 0 & 0 \\ 0 & 0 & M_p & 0 & 0 \\ 0 & 0 & 0 & M_{\partial} & 0 \\ 0 & 0 & 0 & 0 & M_{\partial} \end{pmatrix} \begin{pmatrix} \frac{\mathrm{d}}{\mathrm{d}t}\underline{\alpha}_q(t) \\ \frac{\mathrm{d}}{\mathrm{d}t}\underline{\alpha}_p(t) \\ f(t) \\ -\underline{\boldsymbol{v}}(t) \end{pmatrix} = \begin{pmatrix} 0 & D & -B & B \\ -D^\top & 0 & 0 & 0 \\ B^\top & 0 & 0 & 0 \\ -B^\top & 0 & 0 & 0 \end{pmatrix} \begin{pmatrix} \underline{\boldsymbol{e}}_q(t) \\ \underline{\boldsymbol{e}}_p(t) \\ \underline{\boldsymbol{e}}_p(t) \\ \underline{\boldsymbol{e}}_p(t) \end{pmatrix}$$

and
$$M_{\partial} \cdot \underline{e}_i = \langle Z \rangle \cdot \underline{f}_i$$
,


with
$$\langle \mathbf{Z} \rangle := \int_{\partial \Omega} \mathbf{Z} \mathbf{\Psi} \cdot \mathbf{\Psi}^{\top} \geq 0.$$

Discrete Lossy Power Balance

$$\frac{\mathrm{d}}{\mathrm{d}t}\mathcal{H}_d\left(\underline{\alpha}_q,\underline{\alpha}_p\right) = -\boldsymbol{y}^\top\cdot\langle \boldsymbol{Z}\rangle\cdot\boldsymbol{y} + \underline{\boldsymbol{\nu}}^\top\cdot\boldsymbol{M}_\partial\cdot\boldsymbol{y}.$$

Boundary Dissipation: Simulations

- Heteregenous ($\rho \neq constant$);
- Anisotropic (tensor $\overline{\overline{T}} \not\equiv constant$);
- $\epsilon \equiv 0$;
- $\mathbb{Z} \neq 0$ for $t \geq 2$;
- Raviart-Thomas FEM for q-variables;
- Lagrange FEM for *p*-variables;
- Lagrange FEM for ∂ -variables;



Outline

- 1 Introduction
- 2 Linear Wave equations: towards PH-DAEs and PH-ODEs
 - Discretization in terms of energy and co-energy variables: PH-DAEs
 - Application: Boundary Dissipation
 - Discretization in terms of co-energy variables: PH-ODEs
 - Case of mixed boundary control: PH-DAEs again
 - Convergence of PFEM
- 3 Nonlinear wave equation: the 2D Shallow Water Equation

Discretization in terms of co-energy

In order to transform the PH-DAEs into PH-ODEs, in the linear case, the constitutive relations can be first inverted, second discretized.

$$\overrightarrow{\pmb{\alpha}}_q^{ap}(t,\overrightarrow{\pmb{x}}) = \overline{\overline{\pmb{T}}}^{-1} \cdot \overrightarrow{\pmb{e}}_q^{ap}(t,\overrightarrow{\pmb{x}}) \quad \text{and} \quad \alpha_p^{ap}(t,\overrightarrow{\pmb{x}}) = \Pr_p e_p^{ap}(t,\overrightarrow{\pmb{x}}).$$

Discretization in terms of co-energy

In order to transform the PH-DAEs into PH-ODEs, in the linear case, the constitutive relations can be first inverted, second discretized.

$$\overrightarrow{\pmb{\alpha}}_q^{ap}(t,\overrightarrow{\pmb{x}}) = \overline{\overline{\pmb{T}}}^{-1} \cdot \overrightarrow{\pmb{e}}_q^{ap}(t,\overrightarrow{\pmb{x}}) \quad \text{and} \quad \alpha_p^{ap}(t,\overrightarrow{\pmb{x}}) = \underset{\rho}{\rho} \, e_p^{ap}(t,\overrightarrow{\pmb{x}}).$$

The discretization in the same bases as previously gives:

$$\overrightarrow{M}_q \cdot \underline{\alpha}_q = \overrightarrow{M}_{\overline{\overline{\mathbf{r}}}^{-1}} \cdot \underline{e}_q \quad \text{and} \quad M_p \cdot \underline{\alpha}_p = M_{{\color{red}\rho}} \cdot \underline{e}_p,$$

where new mass matrices, or spatial averages, have been defined:

$$\overrightarrow{M}_{\overline{\overline{\mathbf{r}}}_{-1}} := \int_{\Omega} \overrightarrow{\Phi}_q \cdot \overline{\overline{\mathbf{r}}}^{-1} \cdot \overrightarrow{\Phi}_q^{\top} \qquad \& \qquad M_{\boldsymbol{\rho}} := \int_{\Omega} {\boldsymbol{\rho}} \, \boldsymbol{\phi}_p \cdot \boldsymbol{\phi}_p^{\top}.$$

Discretization in terms of co-energy

In order to transform the PH-DAEs into PH-ODEs, in the linear case, the constitutive relations can be first inverted, second discretized.

$$\overrightarrow{\pmb{\alpha}}_q^{ap}(t,\overrightarrow{\pmb{x}}) = \overline{\overline{\pmb{T}}}^{-1} \cdot \overrightarrow{\pmb{e}}_q^{ap}(t,\overrightarrow{\pmb{x}}) \quad \text{and} \quad \alpha_p^{ap}(t,\overrightarrow{\pmb{x}}) = \underset{\rho}{\rho} \, e_p^{ap}(t,\overrightarrow{\pmb{x}}).$$

The discretization in the same bases as previously gives:

$$\overrightarrow{\pmb{M}}_q \cdot \underline{\underline{\alpha}}_q = \overrightarrow{\pmb{M}}_{\overline{\overline{\pmb{q}}}-1} \cdot \underline{\underline{e}}_q \quad \text{and} \quad M_p \cdot \underline{\underline{\alpha}}_p = M_{\underline{\rho}} \cdot \underline{\underline{e}}_p,$$

where new mass matrices, or spatial averages, have been defined:

$$\overrightarrow{M}_{\overline{\overline{T}}-1} := \int_{\Omega} \overrightarrow{\Phi}_q \cdot \overline{\overline{\overline{T}}}^{-1} \cdot \overrightarrow{\Phi}_q^{\top} \qquad \& \qquad M_{\rho} := \int_{\Omega} \rho \, \phi_p \cdot \phi_p^{\top}.$$

The discretized system now is a PH-ODE:

$$\begin{cases} \overrightarrow{\boldsymbol{M}}_{\overline{\boldsymbol{T}}^{-1}} \cdot \frac{\mathrm{d}}{\mathrm{d}t} \underline{\boldsymbol{e}}_q(t) = D \cdot \underline{\boldsymbol{e}}_p(t) + B \cdot \underline{\boldsymbol{u}}(t), \\ M_{\rho} \cdot \frac{\mathrm{d}}{\mathrm{d}t} \underline{\boldsymbol{e}}_p(t) = -D^{\top} \cdot \underline{\boldsymbol{e}}_q(t), \\ M_{\partial} \cdot \underline{\boldsymbol{y}}(t) = B^{\top} \cdot \underline{\boldsymbol{e}}_q(t), \end{cases}$$

and enjoys the same conservative power balance at the discrete level.

With the same definition the discrete Hamiltonian:

$$\widetilde{\mathcal{H}}_d\left(\underline{e}_q,\underline{e}_p\right) := \mathcal{H}\left(\overrightarrow{\boldsymbol{\alpha}}_q^{ap},\alpha_p^{ap}\right) = \frac{1}{2}\left(\underline{e}_q^\top \cdot \overrightarrow{\boldsymbol{M}}_{\overline{\boldsymbol{T}}^{-1}} \cdot \underline{e}_q + \underline{e}_p^\top \cdot M_{\rho} \cdot \underline{e}_p\right),$$

we can easily compute its time derivative along the trajectories:

$$\frac{\mathrm{d}}{\mathrm{d}t}\widetilde{\mathcal{H}}_{d}\left(\underline{e}_{q},\underline{e}_{p}\right) = \left(\frac{\mathrm{d}}{\mathrm{d}t}\underline{e}_{q}\right)^{\top}\cdot\overrightarrow{M}_{\overline{\mathbf{T}}^{-1}}\cdot\underline{e}_{q} + \left(\frac{\mathrm{d}}{\mathrm{d}t}\underline{e}_{p}\right)^{\top}\cdot M_{\rho}\cdot\underline{e}_{p},$$

$$= \left(\overrightarrow{M}_{\overline{\mathbf{T}}^{-1}}\cdot\frac{\mathrm{d}}{\mathrm{d}t}\underline{e}_{q}\right)^{\top}\cdot\underline{e}_{q} + \left(M_{\rho}\cdot\frac{\mathrm{d}}{\mathrm{d}t}\underline{e}_{p}\right)^{\top}\cdot\underline{e}_{p},$$

$$= \left(D\cdot\underline{e}_{p}(t) + B\cdot\underline{u}(t)\right)^{\top}\cdot\underline{e}_{q} + \left(-D^{\top}\cdot\underline{e}_{q}(t)\right)^{\top}\cdot\underline{e}_{p},$$

$$= \underline{u}(t)^{\top}\cdot B^{\top}\cdot\underline{e}_{q}$$

$$= \underline{u}(t)^{\top}\cdot M_{\partial}\cdot\underline{y}(t). \quad \Box$$

Remark: both definitions do coincide, i.e. $\widetilde{\mathcal{H}}_d\left(\underline{e}_q,\underline{e}_p\right)=\mathcal{H}_d\left(\underline{\alpha}_q,\underline{\alpha}_p\right)$, since the discretization of the constitutive relations now provides: $\overrightarrow{M}_q\cdot\underline{\alpha}_q=\overrightarrow{M}_{\overline{\mathbf{T}}^{-1}}\cdot\underline{e}_q$ and $M_p\cdot\underline{\alpha}_p=M_\rho\cdot\underline{e}_p$ (exercise).

Outline

- 1 Introduction
- 2 Linear Wave equations: towards PH-DAEs and PH-ODEs
 - Discretization in terms of energy and co-energy variables: PH-DAEs
 - Application: Boundary Dissipation
 - Discretization in terms of co-energy variables: PH-ODEs
 - Case of mixed boundary control: PH-DAEs again
 - Convergence of PFEM
- 3 Nonlinear wave equation: the 2D Shallow Water Equation

Mixed boundary control: principle

- **1** The basic idea is: $\partial\Omega=\Gamma_D\cup\Gamma_N$ and $\int_{\partial\Omega}=\int_{\Gamma_D}+\int_{\Gamma_N}.$
- 2 Where the control is not known, a Lagrange multiplier λ is introduced instead + a constraint is added to the system, an extended skew-symmetric J_e matrix is obtained.
- \Longrightarrow a PH-DAE is readily obtained, with a Lagrange multiplier of very small dimension.
- This method is detailed in one early reference, but several other possibilities have been explored since then.

Outline

- 1 Introduction
- 2 Linear Wave equations: towards PH-DAEs and PH-ODEs
 - Discretization in terms of energy and co-energy variables: PH-DAEs
 - Application: Boundary Dissipation
 - Discretization in terms of co-energy variables: PH-ODEs
 - Case of mixed boundary control: PH-DAEs again
 - Convergence of PFEM
- 3 Nonlinear wave equation: the 2D Shallow Water Equation

Convergence rate: theory

Theorem (Haine, Matignon & Serhani, 2020)

Let $\kappa \geq \delta$ be an integer, where $\delta = 0$ if Ω is convex and 1 otherwise, and T > 0.

Let
$$\begin{pmatrix} \overrightarrow{\boldsymbol{\alpha}}_{q_0} \\ \boldsymbol{\alpha}_{p_0} \end{pmatrix} \in \mathcal{Z}_{\kappa} := \begin{pmatrix} \overline{\overline{\boldsymbol{T}}} & 0 \\ 0 & \frac{1}{\rho} \end{pmatrix}^{-1} \begin{bmatrix} \mathbf{H}_{\mathrm{div}}^{\kappa+1}(\Omega) \\ H^{\kappa+1}(\Omega) \end{bmatrix}$$
, $\boldsymbol{u} \in C^2([0,\infty); H^{\kappa+1}(\partial\Omega))$.

Let $\begin{pmatrix} \overrightarrow{\alpha}_q^{ap}(0) \\ \alpha_p^{ap}(0) \end{pmatrix}$, u^{ap} be their interpolations with $(\mathbb{P}^k)^N \times \mathbb{P}^\ell \times \mathbb{P}^m$.

Let
$$\mathbf{E}(t) := \left\| \left((\overrightarrow{\alpha}_q - \overrightarrow{\alpha}_q^{ap})(t), \quad (\alpha_p - \alpha_p^{ap})(t) \right)^\top \right\|_{\mathbf{L}^2 \times L^2}$$
,

 $\exists C_T > 0$, independent of $\begin{pmatrix} \overrightarrow{\boldsymbol{\alpha}}_{q_0} \\ \alpha_{p_0} \end{pmatrix}$, and \boldsymbol{u} : for all h and all $t \in [0,T]$

$$\mathbf{E}(t) \leq C_T h^{\min\{\ell-\delta; k; m\}} \left(\left\| \begin{pmatrix} \overrightarrow{\boldsymbol{\alpha}}_q \\ \alpha_p \end{pmatrix} \right\|_{L^{\infty}([0,T]; \mathcal{Z}_{\kappa})} + \|\boldsymbol{u}\|_{L^{\infty}([0,T]; H^{\kappa+1}(\partial\Omega))} \right).$$

The **optimal** order is $\kappa - \delta$, when $k = \kappa - \delta$, $\ell = \max{\{\kappa; 1\}}$ and $m = \kappa - \delta$.

Convergence rate: theory

Theorem (Haine, Matignon & Serhani, 2020)

Let $\kappa \geq \delta$ be an integer, where $\delta = 0$ if Ω is convex and 1 otherwise, and T > 0.

Let
$$\begin{pmatrix} \overrightarrow{\boldsymbol{\alpha}}_{q_0} \\ \boldsymbol{\alpha}_{p_0} \end{pmatrix} \in \mathcal{Z}_{\kappa} := \begin{pmatrix} \overline{\overline{\boldsymbol{T}}} & 0 \\ 0 & \frac{1}{\rho} \end{pmatrix}^{-1} \begin{bmatrix} \mathbf{H}_{\mathrm{div}}^{\kappa+1}(\Omega) \\ H^{\kappa+1}(\Omega) \end{bmatrix}$$
, $\boldsymbol{u} \in C^2([0,\infty); H^{\kappa+1}(\partial\Omega))$.

Let $\begin{pmatrix} \overrightarrow{\alpha}_q^{ap}(0) \\ \alpha_p^{ap}(0) \end{pmatrix}$, u^{ap} be their interpolations with $(\mathbb{P}^k)^N \times \mathbb{P}^\ell \times \mathbb{P}^m$.

Let
$$\mathbf{E}(t) := \left\| \left((\overrightarrow{\alpha}_q - \overrightarrow{\alpha}_q^{ap})(t), \quad (\alpha_p - \alpha_p^{ap})(t) \right)^\top \right\|_{\mathbf{L}^2 \times L^2}$$
,


 $\exists C_T > 0$, independent of $\begin{pmatrix} \overrightarrow{\boldsymbol{\alpha}}_{q_0} \\ \alpha_{p_0} \end{pmatrix}$, and \boldsymbol{u} : for all h and all $t \in [0,T]$

$$\mathbf{E}(t) \leq C_T h^{\min\{\ell-\delta; k; m\}} \left(\left\| \begin{pmatrix} \overrightarrow{\boldsymbol{\alpha}}_q \\ \alpha_p \end{pmatrix} \right\|_{L^{\infty}([0,T]; \mathcal{Z}_{\kappa})} + \|\boldsymbol{u}\|_{L^{\infty}([0,T]; H^{\kappa+1}(\partial\Omega))} \right).$$

The **optimal** order is $\kappa - \delta$, when $k = \kappa - \delta$, $\ell = \max{\{\kappa, 1\}}$ and $m = \kappa - \delta$.

$$RT_{\kappa-1-\delta}\times \mathbb{P}^{\kappa}\times \mathbb{P}^{\kappa-\delta} \qquad BDM_{\kappa-\delta}\times \mathbb{P}^{\kappa}\times \mathbb{P}^{\kappa-\delta} \qquad BDFM_{\kappa-\delta}\times \mathbb{P}^{\kappa}\times \mathbb{P}^{\kappa-\delta}$$

Convergence rate: numerics



Periodic Table of the Finite Elements



Outline

- 1 Introduction
- 2 Linear Wave equations: towards PH-DAEs and PH-ODEs
- 3 Nonlinear wave equation: the 2D Shallow Water Equation
 - Modelling: SWE as a pHs
 - Numerics: PFEM in the polynomial case
 - Application: Boundary Dissipation

The irrotational shallow water equations

* Energy variables: $lpha_h$ the fluid height, $oldsymbol{lpha}_v$ the linear momentum,

The irrotational shallow water equations

- * Energy variables: α_h the fluid height, α_v the linear momentum,
- * Non-quadratic and non-separable Hamiltonian functional:

$$H(\alpha_h, \boldsymbol{\alpha}_v) = \frac{1}{2} \int_{\Omega} \left\{ \frac{1}{\rho} \alpha_h \|\boldsymbol{\alpha}_v\|^2 + \rho g \alpha_h^2 \right\} d\Omega.$$

The irrotational shallow water equations

- * Energy variables: $lpha_h$ the fluid height, $oldsymbol{lpha}_v$ the linear momentum,
- * Non-quadratic and non-separable Hamiltonian functional:

$$H(\alpha_h, \boldsymbol{\alpha}_v) = \frac{1}{2} \int_{\Omega} \left\{ \frac{1}{\rho} \alpha_h \left\| \boldsymbol{\alpha}_v \right\|^2 + \rho g \alpha_h^2 \right\} d\Omega.$$

* Dynamical system:

$$\begin{split} \frac{\partial}{\partial t} \begin{pmatrix} \alpha_h \\ \boldsymbol{\alpha}_v \end{pmatrix} &= \begin{bmatrix} 0 & -\mathrm{div} \\ -\mathbf{grad} & \mathbf{0} \end{bmatrix} \begin{pmatrix} e_h \\ \mathbf{e}_v \end{pmatrix}, \qquad (x,y) \in \Omega = \{x^2 + y^2 \leq R\}, \\ \begin{pmatrix} e_h \\ \mathbf{e}_v \end{pmatrix} &= \begin{pmatrix} \delta_{\alpha_h} H \\ \delta_{\boldsymbol{\alpha}_v} H \end{pmatrix} = \begin{pmatrix} \frac{1}{2\rho} \left\| \boldsymbol{\alpha}_v \right\|^2 + \rho g \alpha_h \\ \frac{1}{\rho} \alpha_h \boldsymbol{\alpha}_v \end{pmatrix}, \end{split}$$

The irrotational shallow water equations

- * Energy variables: α_h the fluid height, α_v the linear momentum,
- * Non-quadratic and non-separable Hamiltonian functional:

$$H(\alpha_h, \boldsymbol{\alpha}_v) = \frac{1}{2} \int_{\Omega} \left\{ \frac{1}{\rho} \alpha_h \left\| \boldsymbol{\alpha}_v \right\|^2 + \rho g \alpha_h^2 \right\} \ \mathrm{d}\Omega.$$

* Dynamical system:

$$\begin{split} \frac{\partial}{\partial t} \begin{pmatrix} \alpha_h \\ \boldsymbol{\alpha}_v \end{pmatrix} &= \begin{bmatrix} \frac{0}{-\mathbf{grad}} & -\mathbf{div} \\ -\mathbf{grad} & \mathbf{0} \end{bmatrix} \begin{pmatrix} e_h \\ \mathbf{e}_v \end{pmatrix}, \qquad (x,y) \in \Omega = \{x^2 + y^2 \leq R\}, \\ \begin{pmatrix} e_h \\ \mathbf{e}_v \end{pmatrix} &= \begin{pmatrix} \delta_{\alpha_h} H \\ \delta_{\boldsymbol{\alpha}_v} H \end{pmatrix} = \begin{pmatrix} \frac{1}{2\rho} \left\| \boldsymbol{\alpha}_v \right\|^2 + \rho g \alpha_h \\ \frac{1}{\rho} \alpha_h \boldsymbol{\alpha}_v \end{pmatrix}, \end{split}$$

* Consider a uniform Neumann boundary control

$$u_{\partial} = -\mathbf{e}_v \cdot \mathbf{n}|_{\partial\Omega} = -\frac{1}{\rho} \alpha_h \boldsymbol{\alpha}_v \cdot \mathbf{n}|_{\partial\Omega},$$
 Volumetric inflow rate.

The corresponding output reads

$$y_{\partial} = e_h|_{\partial\Omega} = (\rho g \alpha_h + \frac{1}{2\rho} \|\boldsymbol{\alpha}_v\|^2)|_{\partial\Omega}.$$

Outline

- 1 Introduction
- 2 Linear Wave equations: towards PH-DAEs and PH-ODEs
- 3 Nonlinear wave equation: the 2D Shallow Water Equation
 - Modelling: SWE as a pHs
 - Numerics: PFEM in the polynomial case
 - Application: Boundary Dissipation

Numerics: PFEM in the polynomial case

The difficulty lies in the non-linear nature of both constitutive relations. However, since they remain polynomial, off-line Finite Element computations can be performed, and makes possible the online computation of the discrete constitutive relations at each time step.

Numerics: **PFEM** in the polynomial case

The difficulty lies in the non-linear nature of both constitutive relations. However, since they remain polynomial, off-line Finite Element computations can be performed, and makes possible the online computation of the discrete constitutive relations at each time step.

A general result

$$M_h \cdot \underline{e_h} := \nabla_{\underline{\alpha_h}} \mathcal{H}_d(\underline{\alpha_h}, \underline{\alpha_v}), \text{ and } M_v \cdot \underline{e_v} := \nabla_{\underline{\alpha_v}} \mathcal{H}_d(\underline{\alpha_h}, \underline{\alpha_v}).$$

Numerics: PFEM in the polynomial case

The difficulty lies in the non-linear nature of both constitutive relations. However, since they remain polynomial, off-line Finite Element computations can be performed, and makes possible the online computation of the discrete constitutive relations at each time step.

A general result

$$M_h \cdot \underline{e_h} := \nabla_{\underline{\alpha_h}} \mathcal{H}_d(\underline{\alpha_h}, \underline{\alpha_v}), \text{ and } M_v \cdot \underline{e_v} := \nabla_{\underline{\alpha_v}} \mathcal{H}_d(\underline{\alpha_h}, \underline{\alpha_v}).$$

Here quadratic quantities have to be computed in the integrals, namely $\underline{q_h} := \int_{\Omega} \phi_h \frac{1}{2\rho} \underline{\alpha_v}^\top \cdot \overrightarrow{\Phi}_v \cdot \overrightarrow{\Phi}_v^\top \cdot \underline{\alpha_v} \text{ and } \underline{q_v} := \int_{\Omega} \overrightarrow{\Phi}_v \frac{1}{\rho} \underline{\alpha_h}^\top \cdot \phi_h \cdot \overrightarrow{\Phi}_v^\top \cdot \underline{\alpha_v}.$ $\Rightarrow 1 \leq i \leq N_h, \quad q_h^i(t) = \underline{\alpha_v}(t)^\top \cdot \left(\int_{\Omega} \phi_h^i \frac{1}{2\rho} \overrightarrow{\Phi}_v \cdot \overrightarrow{\Phi}_v^\top \right) \cdot \underline{\alpha_v}(t),$ $\Rightarrow 1 \leq k \leq N_v, \quad q_v^k(t) = \underline{\alpha_h}(t)^\top \cdot \left(\int_{\Omega} \phi_h \frac{1}{\rho} \overrightarrow{\phi}_v^{k\top} \cdot \overrightarrow{\Phi}_v^\top \right) \cdot \underline{\alpha_v}(t).$

Remark: the sizes of the vectors and matrices do match as well (exercise). ⇒ Off-line computation proves possible!

Outline

- 1 Introduction
- 2 Linear Wave equations: towards PH-DAEs and PH-ODEs
- 3 Nonlinear wave equation: the 2D Shallow Water Equation
 - Modelling: SWE as a pHs
 - Numerics: PFEM in the polynomial case
 - Application: Boundary Dissipation

Boundary stabilization of the 2D SWE

A simple proportional control stabilizes the system around the desired point h^{des}

$$u_{\partial} = -k(y_{\partial} - y_{\partial}^{\mathsf{des}}), \qquad y_{\partial}^{\mathsf{des}} = \rho g h^{\mathsf{des}}, \quad k > 0.$$

This control law ensures that the Lyapunov functional


$$V = \frac{1}{2} \int_{\Omega} \left\{ \frac{1}{2} \rho g (\alpha_h - \alpha_h^{\mathsf{des}})^2 + \frac{1}{2\rho} \alpha_h \|\boldsymbol{\alpha}_v\|^2 \right\} d\Omega \ge 0,$$


where $\alpha_h^{\mathrm{des}} = h^{\mathrm{des}}$, has negative semi-definite time derivative

$$\dot{V} = -k \int_{\partial \Omega} \left(y_{\partial} - y_{\partial}^{\mathsf{des}} \right)^2 d\Gamma \le 0.$$



Simulation Results for the 2D SWE





■ Timoshenko beam:
$$J := \begin{pmatrix} 0 & 0 & 0 & \partial_x \\ 0 & 0 & \partial_x & 1 \\ 0 & \partial_x & 0 & 0 \\ \partial_x & -1 & 0 & 0 \end{pmatrix}$$
;

- Timoshenko beam: $J := \begin{pmatrix} 0 & 0 & 0 & \partial_x \\ 0 & 0 & \partial_x & 1 \\ 0 & \partial_x & 0 & 0 \\ \partial_x & -1 & 0 & 0 \end{pmatrix}$;
 - Euler–Bernoulli beam: $J := \begin{pmatrix} 0 & -\partial_{xx}^2 \\ \partial_{xx}^2 & 0 \end{pmatrix}$;

- Timoshenko beam: $J := \begin{pmatrix} 0 & 0 & 0 & \partial_x \\ 0 & 0 & \partial_x & 1 \\ 0 & \partial_x & 0 & 0 \\ \partial_x & -1 & 0 & 0 \end{pmatrix}$;
- $\qquad \textbf{Euler-Bernoulli beam:} \ J := \begin{pmatrix} 0 & -\partial_{xx}^2 \\ \partial_{xx}^2 & 0 \end{pmatrix} ;$
- Kirchhoff-Love plate: $J := \begin{pmatrix} 0 & -\text{div} \circ \text{Div} \\ \text{Grad} \circ \overrightarrow{\textbf{grad}} & 0 \end{pmatrix}$;

- Timoshenko beam: $J := \begin{pmatrix} 0 & 0 & 0 & \partial_x \\ 0 & 0 & \partial_x & 1 \\ 0 & \partial_x & 0 & 0 \\ \partial_x & -1 & 0 & 0 \end{pmatrix}$;
- Euler–Bernoulli beam: $J := \begin{pmatrix} 0 & -\partial_{xx}^2 \\ \partial_{xx}^2 & 0 \end{pmatrix}$;
- $\qquad \textbf{Kirchhoff-Love plate:} \ J := \begin{pmatrix} 0 & -\mathrm{div} \circ \mathrm{Div} \\ \mathrm{Grad} \circ \overrightarrow{\mathbf{grad}} & 0 \end{pmatrix} ;$
- 3D Maxwell's equation: $J := \begin{pmatrix} 0 & \overrightarrow{\mathbf{curl}} \\ -\overrightarrow{\mathbf{curl}} & 0 \end{pmatrix}$.

As soon as J is formally skew-symmetric...

- Timoshenko beam: $J := \begin{pmatrix} 0 & 0 & 0 & \partial_x \\ 0 & 0 & \partial_x & 1 \\ 0 & \partial_x & 0 & 0 \\ \partial_x & -1 & 0 & 0 \end{pmatrix}$;
- $\qquad \qquad \mathbf{Euler-Bernoulli\ beam:}\ J:=\begin{pmatrix} 0 & -\partial_{xx}^2 \\ \partial_{xx}^2 & 0 \end{pmatrix};$
- $\qquad \textbf{Kirchhoff-Love plate:} \ J := \begin{pmatrix} 0 & -\mathrm{div} \circ \mathrm{Div} \\ \mathrm{Grad} \circ \overrightarrow{\mathbf{grad}} & 0 \end{pmatrix} ;$
- 3D Maxwell's equation: $J := \begin{pmatrix} 0 & \overrightarrow{\mathbf{curl}} \\ -\overrightarrow{\mathbf{curl}} & 0 \end{pmatrix}$.

Constitutive relations are postponed!

Dissipation is not a drawback!

Available computer codes for numerical simulation

- SCRIMP project at Isae-Supaero: Python as programming language, modules FEniCS (Finite elements), PETSc (Time integration), and SCRIMP (a wrapper to speed up the coding process), as well as usual modules such as NumPy and Matplotlib.
- Supplementary material to the Open Access paper by A. BRUGNOLI, G. HAINE, A. SERHANI, AND X. VASSEUR, Numerical approximation of port-Hamiltonian systems for hyperbolic or parabolic PDEs with boundary control, (2021):

 supplementary material https://doi.org/10.5281/zenodo.3938600
 - supplementary material https://doi.org/10.5281/zenodo.3938600.
- Github and Supplementary material in MatLab associated to the IEEE CDC paper by F. L. CARDOSO-RIBEIRO, A. BRUGNOLI, D. MATIGNON, AND L. LEFÈVRE, Port-Hamiltonian modeling, discretization and feedback control of a circular water tank, supplementary material https://doi.org/10.5281/zenodo.4029598

https://github.com/flavioluiz/Circular-Tank-PFEM-CDC-supplementary-materia

References (on PFEM)

A structure-preserving Partitioned Finite Element Method for the 2D wave equation Cardoso-Ribeiro F.L., Matignon D., Lefèvre L.

IFAC-PapersOnLine, vol.51(3), pp.119-124 (2018), LHMNC 2018

Partitioned Finite Element Method for port-Hamiltonian systems with Boundary Damping: Anisotropic Heterogeneous 2D wave equations Serhani A., Matignon D., Haine G.

IFAC-PapersOnLine, vol.52(2), pp.96-101 (2019), CPDE 2019

Port-Hamiltonian modeling, discretization and feedback control of a circular water tank.

Cardoso-Ribeiro, F.L., Brugnoli, A., Matignon, Denis, Lefè vre, L.

2019 IEEE 58th Conference on Decision and Control (CDC), CDC 2019

Port-Hamiltonian formulation and symplectic discretization of plate models Part I: Mindlin model for thick plates

Brugnoli A., Alazard D., Pommier-Budinger V., Matignon D.

Applied Mathematical Modelling, vol.75, pp.940–960 (2019)

Port-Hamiltonian formulation and symplectic discretization of plate models Part II: Kirchhoff model for thin plates Brugnoli A., Alazard D., Pommier-Budinger V., Matignon D.

Applied Mathematical Modelling, vol.75, pp.961-981 (2019)

Anisotropic heterogeneous n-D heat equation with boundary control and observation: I. Modeling as port-Hamiltonian system Serhani A., Haine G., Matignon D.

IFAC-PapersOnLine, vol.52(7), pp.51-56 (2019), TFMST 2019

Anisotropic heterogeneous n-D heat equation with boundary control and observation: II. Structure-preserving discretization

Serhani A., Haine G., Matignon D.

IFAC-PapersOnLine, vol.52(7), pp.57-62 (2019), TFMST 2019

A Partitioned Finite Element Method for the Structure-Preserving Discretization of Damped Infinite-Dimensional Port-Hamiltonian Systems with Boundary Control

Serhani A., Matignon D., Haine G.

Lecture Notes in Computer Science (GSI 2019), Springer Verlag, pp.549-558

Modelling and structure-preserving discretization of Maxwell's equations as port-Hamiltonian system

Payen G., Matignon D., Haine G.

IFAC-PapersOnLine, vol.53(2), pp.7671-7676 (2020), IFAC WC 2020

A Partitioned Finite-Element Method (PFEM) for power-preserving discretization of open systems of conservation laws

Cardoso-Ribeiro F.L., Matignon D., Lefèvre L.

IMA J. Mathematics of Control and Information, vol.38(2), pp. 493–533 (2021)

References (on PFEM)

Partitioned finite element method for structured discretization with mixed boundary conditions

Brugnoli, A. and Cardoso-Ribeiro, F. L. and Haine, G. and Kotyczka, P.

IFAC-PapersOnLine, vol.53(2), pp. 7557-7562 (2020), IFAC WC 2020

Numerical approximation of port-Hamiltonian systems for hyperbolic or parabolic partial differential equations Brugnoli A., Haine G., Serhani A., Vasseur X.

Journal of Applied Mathematics and Physics, vol.09(06), pp. 1278-1321 (2021)

Incompressible Navier-Stokes Equation as port-Hamiltonian systems: velocity formulation versus vorticity formulation Haine, G. and Matignon, D.

IFAC-PapersOnLine, vol.54(19), pp. 161-166 (2021), IFAC LHMNLC 2021

Structure-Preserving Discretization of a Coupled Heat-Wave System, as Interconnected Port-Hamiltonian Systems

Haine G., Matignon D.

Lecture Notes in Computer Science (GSI 2021), Springer Verlag, pp.191-199

Long-time behavior of a coupled heat-wave system using structure-preserving finite element method

Haine G., Matignon D., Monteghetti F. Mathematical Reports, Vol. 24(74), (2022)

Numerical analysis of a structure-preserving space-discretization for an anisotropic and heterogeneous boundary controlled N-dimensional wave equation as port-Hamiltonian system

Haine G., Matignon D., Serhani A.

https://arxiv.org/abs/2006.15032

Institut Supérieur de l'Aéronautique et de l'Espace

10 avenue Édouard Belin – BP 54032 31055 Toulouse Cedex 4 – France Phone: +33 5 61 33 80 80

www.isae-supaero.fr

