

# Package ‘rpostgisLT’

October 26, 2016

**Title** Managing Animal Movement Data with 'PostGIS' and R

**Version** 0.4.0

**Date** 2016-10-26

**Description** The 'rpostgisLT' package develops the integration of R and 'PostGIS' for managing movement trajectories. The focus is on streamlining the work flow for biologists to store and process animal trajectories in 'PostGIS' and analyze them in R, thus utilizing the strengths of both software. The package relies on 'ltraj' objects from the R package 'adehabitatLT', and provides the analogous 'pgtraj' data structure in 'PostGIS', with all functions to create and manage 'pgtraj' data, and convert from and to both formats ('pgtraj' in 'PostGIS', 'ltraj' in R).

**SystemRequirements** PostgreSQL with PostGIS extension

**Depends** R (>= 3.3.0),  
DBI,  
RPostgreSQL,  
rpostgis (>= 1.0.3),  
adehabitatLT (>= 0.3.12)

**License** GPL (>= 3)

**URL** <https://github.com/mablab/rpostgisLT>

**BugReports** <https://github.com/mablab/rpostgisLT/issues>

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 5.0.1

**Imports** sp,  
testthat

**Suggests** knitr,  
rmarkdown

**VignetteBuilder** knitr

## R topics documented:

as_pgtraj . . . . .	2
ltraj2pgtraj . . . . .	4

pgtraj2ltraj . . . . .	5
pgtrajDrop . . . . .	6
pgtrajSchema . . . . .	6
pgtrajVacuum . . . . .	7
rpostgisLT . . . . .	8

<b>Index</b>	<b>9</b>
--------------	----------

---

as_pgtraj	<i>Imports location data from a database table into the pgtraj database model</i>
-----------	---

---

## Description

as\_pgtraj populates a pgtraj schema from the data provided in relocations\_table. If the provided schema doesn't exist, it will be created. On successful data input, as\_pgtraj creates two database views for each new pgtraj. These views are named parameters\_<pgtraj\_name>, step\_geometry\_<pgtraj\_name> and described in more detail in the package vignette.

The time zone of the pgtraj is set to the local time zone of the user.

## Usage

```
as_pgtraj(conn, relocations_table, schema = "traj", pgtrajs = "pgtraj",
  animals = "animal", bursts = NULL, relocations, timestamps = NULL,
  rids = "rid", srid = NULL, note = NULL, clauses = NULL,
  info_cols = NULL, info_table = NULL, info_rids = NULL)
```

## Arguments

conn	Connection object created with RPostgreSQL
relocations_table	String. Name of the schema and table that stores the relocations, e.g. c("schema","relocations")
schema	String. Name of the schema that stores or will store the pgtraj data model (Default = "traj").
pgtrajs	String. Name of the pgtraj or name of the field that stores the pgtraj names.
animals	String. Name of the animal or name of the field that stores the animal names.
bursts	String. (Optional) name of the burst or name of the field that stores the burst names. If not given, each animal will have one burst.
relocations	String. Name of the field that contains the relocations in relocations_table. Relocations can be provided either as columns names containing X,Y coordinates (e.g., c("x","y")) or a PostGIS geometry (e.g., "geom"). In both cases all relocations in relocations_table must have the same projection. If provided as coordinates in two columns, projection will be undefined unless srid is defined.
timestamps	String. Name of the field in relocations_table that contains the timestamps. If NULL, Type I trajectory is assumed.
rids	String. Name of the field in relocations_table that contains the numeric IDs of relocations. If timestamps = NULL, relocations will be sorted by the ascending numeric IDs in this field.
srid	Integer. Optional SRID (spatial reference ID) of (x,y) coordinates provided for relocations. Ignored if relocations is a geometry type.

note	String. Comment on the pgtraj. The comment is only used in the database and not transferred into the ltraj.
clauses	character, additional SQL to append to modify data selected from relocations_table. Must begin with WHERE ..., and cannot contain ORDER BY or LIMIT clauses.
info_cols	String. Optional character vector of database table column names storing additional information on relocations (replicating "infolocs" from the adehabitatLT object ltraj).
info_table	Character vector of c("schema", "table") holding the info_cols. If info_cols are in relocations_table, leave NULL.
info_rids	String. Column name of unique integer ID in info_table to join with rids from relocations_table. If info_cols are in relocations_table, leave NULL.

### Details

Opening and closing connections have to be done manually by the user. However, the function checks if the provided connection is still valid.

### Value

TRUE on success

### Author(s)

Balázs Dukai <balazs.dukai@gmail.com>

David Bucklin <dbucklin@ufl.edu>

### References

<https://CRAN.R-project.org/package=adehabitatLT/vignettes/adehabitatLT.pdf>

### See Also

Section on pgtraj data model in the package vignette.

### Examples

```
## Not run:
as_pgtraj(conn,
  relocations_table = c("example_data", "relocations_plus"),
  schema = "traj_t4",
  pgtrajs = "id",
  animals = "animal",
  bursts = "burst",
  relocations = "geom",
  timestamps = "time",
  rids = "gid",
  info_cols = c("dist_to_road", "land_cover", "error_class")
)

## End(Not run)

## Not run:
as_pgtraj(conn,
```

```

    relocations_table = c("example_data","relocations_plus"),
    schema = "traj_t4",
    pgtrajs = "id",
    animals = "animal",
    bursts = "burst",
    relocations = c("x","y"),
    timestamps = "time",
    rids = "gid")

## End(Not run)

```

---

ltraj2pgtraj

*Export ltraj object from R to a PostGIS database.*


---

### Description

ltraj2pgtraj creates exports an ltraj to the a database pgtraj, creating a new pgtraj schema if it doesn't exist. The time zone and projection information stored in the ltraj is transferred to the database.

### Usage

```

ltraj2pgtraj(conn, ltraj, schema = "traj", pgtraj = NULL, note = NULL,
  overwrite = FALSE, infolocs = TRUE)

```

### Arguments

conn	A connection object.
ltraj	An object of class ltraj.
schema	Character. Name of the schema that stores or will store the pgtraj data model.
pgtraj	Character. Name of the new pgtraj. Defaults to the name of the provided ltraj.
note	Character. A note that will be stored with the pgtraj in the database.
overwrite	Logical. Use if a pgtraj with the same name as the provided ltraj already exists in the database: If TRUE, the existing pgtraj is deleted and the provided ltraj is inserted. If FALSE, the function exits. Note that overwrite requires an exact match among the pgtraj names otherwise it is ignored.
infolocs	Logical. Whether to write infolocs to database.

### Value

TRUE on success.

### Author(s)

Balázs Dukai <balazs.dukai@gmail.com>

### See Also

[as\\_pgtraj](#) to create a pgtraj with data already stored in the database.

## Examples

```
## Not run:
# create pgtraj from ltraj "ibex" in schema "traj_t2"
ltraj2pgtraj(conn, ibex, "traj_t2")

## End(Not run)
```

---

pgtraj2ltraj	<i>Import a pgtraj into an ltraj.</i>
--------------	---------------------------------------

---

## Description

pgtraj2ltraj imports a single pgtraj from a database into an ltraj object.

## Usage

```
pgtraj2ltraj(conn, pgtraj, schema = "traj")
```

## Arguments

conn	Connection object created with RPostgreSQL
pgtraj	String. Name of the pgtraj
schema	String. Name of the schema storing the pgtraj

## Value

an ltraj object

## Author(s)

Balázs Dukai <balazs.dukai@gmail.com>

## Examples

```
## Not run:
# create ltraj from pgtraj named "ibex" in schema "traj_t2"
ibex<-pgtraj2ltraj(conn, "ibex", "traj_t2")

## End(Not run)
```

---

pgtrajDrop	<i>Delete a pgtraj from a traj schema.</i>
------------	--

---

**Description**

pgtrajDrop deletes a pgtraj from a traj schema.

**Usage**

```
pgtrajDrop(conn, pgtraj, schema = "traj", full_clean = TRUE)
```

**Arguments**

conn	Connection object created with RPostgreSQL
pgtraj	String. Name of the pgtraj
schema	String. Name of the schema storing the pgtraj
full_clean	String. Whether to delete all unused rows in all tables associated with the pgtraj (and any other previously deleted pgtrajs). Recommended, but may take a long time to run in schemas with many large pgtrajes.

**Value**

TRUE on success

**Author(s)**

Balázs Dukai <balazs.dukai@gmail.com>

**Examples**

```
## Not run:
# drop "ibex" pgtraj in schema "traj"
pgtrajDrop(conn, "ibex")

## End(Not run)
```

---

pgtrajSchema	<i>Check/create pgtraj schema.</i>
--------------	------------------------------------

---

**Description**

Checks if the provided schema is a valid pgtraj schema, and creates one if it does not exist.

**Usage**

```
pgtrajSchema(conn, schema = "traj")
```

**Arguments**

conn	Connection object created with RPostgreSQL.
schema	Character string. Name of the schema that stores or will store the pgtraj data model.

**Details**

Creates a schema to store pgtrajs in the database by calling a SQL script from `./sql/traj_schema.sql`. The schema name defaults to `traj`. If a schema with the provided name already exists in the database, it checks if it contains all the required tables. The function does not attempt to repair the schema if all pgtraj tables are not present (e.g. because some were manually deleted). In this case, a new pgtraj schema needs to be created, or the existing schema needs to be deleted and recreated. The function has its own standalone transaction control.

**Value**

TRUE if the schema exists (whether it was already available or was successfully created).

**Author(s)**

Balázs Dukai <balazs.dukai@gmail.com>

**Examples**

```
## Not run:
# Check (or create) pgtraj schema with name "traj_1"
pgtrajSchema(conn,"traj_1")

## End(Not run)
```

---

pgtrajVacuum	<i>pgtrajVacuum VACUUM a pgtraj schema.</i>
--------------	---

---

**Description**

Performs a VACUUM (garbage-collect and optionally analyze) on all the tables of a traj schema.

**Usage**

```
pgtrajVacuum(conn, schema = "traj", full = FALSE, verbose = FALSE,
  analyze = TRUE)
```

**Arguments**

conn	Connection object created with RPostgreSQL
schema	String. Name of the schema that stores or will store the pgtraj data model.
full	Logical. Whether to perform a "full" vacuum, which can reclaim more space, but takes much longer and exclusively locks the table.
verbose	Logical. Whether to print a detailed vacuum activity report for each table.
analyze	Logical. Whether to update statistics used by the planner to determine the most efficient way to execute a query (default to TRUE).

**Value**

TRUE on success.

**Author(s)**

Balázs Dukai <balazs.dukai@gmail.com>

**Examples**

```
## Not run:  
# Vacuum analyze all tables in pgtraj schema with default name "traj"  
pgtrajVacuum(conn)  
  
## End(Not run)
```

---

rpostgisLT

*Integration of ltraj (adehabitatLT) and pgtraj (PostGIS).*

---

**Description**

rpostgisLT

**Details**

The ‘rpostgisLT’ package develops the integration of R and PostGIS for managing movement trajectories. The focus is on streamlining the workflow for biologists to store and process animal trajectories in PostGIS and analyze them in R, thus utilizing the strengths of both software. The package relies on ‘ltraj’ objects from the R package ‘adehabitatLT’, and provides the analogous ‘pgtraj’ data structure in PostGIS, with all functions to create and manage ‘pgtraj’ data, and convert from and to both format (‘pgtraj’ in PostGIS, ‘ltraj’ in R). For a list of documented functions, use `library(help = "rpostgisLT")`

**Author(s)**

Balázs Dukai <balazs.dukai@gmail.com>



# Index

as\_pgtraj, [2](#), [4](#)

ltraj2pgtraj, [4](#)

pgtraj2ltraj, [5](#)

pgtrajDrop, [6](#)

pgtrajSchema, [6](#)

pgtrajVacuum, [7](#)

rpostgisLT, [8](#)

rpostgisLT-package (rpostgisLT), [8](#)