

# Naive-Bayes model using text data vectorized with TF-IDF

```
In [ ]: #import packages

import numpy as np

import pandas as pd

from sklearn.model_selection import KFold, cross_validate

from sklearn.pipeline import Pipeline

from sklearn.linear_model import LogisticRegression
from sklearn.naive_bayes import MultinomialNB
from sklearn.svm import SVC

from sklearn.metrics import accuracy_score, precision_score, recall_score, f1_score, confusion_matrix, ConfusionMatrixDisplay

import matplotlib as plt

from time import process_time
```

```
In [ ]: #import data

%store -r x_text_train_tf
%store -r x_text_test_tf
%store -r y_text_train_tf
%store -r y_text_test_tf
```

```
In [ ]: #rename variables for ease of use

x_train = x_text_train_tf
x_test = x_text_test_tf
y_train = y_text_train_tf
y_test = y_text_test_tf
```

```
In [ ]: #define model

mnf = MultinomialNB()
```

```
In [ ]: #define scoring metrics for cross validation

scorer = {'accuracy': make_scorer(accuracy_score),
          'precision': make_scorer(precision_score),
          'recall': make_scorer(recall_score),
          'f1_score': make_scorer(f1_score)}
}
```

```
In [ ]: #define KFold

k_folds = KFold(n_splits = 5, random_state=42, shuffle=True)
```

```
In [ ]: #cross validate on training set to check model stability

cv_scores_tfidf_text_mnf = cross_validate(mnf, x_train, y_train, cv = k_folds, scoring=scorer)
```

```
In [ ]: #check cross validation scores

cv_scores_tfidf_text_mnf
```

```
Out[ ]: {'fit_time': array([0.07380319, 0.06083751, 0.05784488, 0.05983973, 0.0588448 ]),
         'score_time': array([0.02194238, 0.02197242, 0.01792026, 0.0179522 , 0.0179522 ]),
         'test_accuracy': array([0.85569651, 0.8570383 , 0.85799683, 0.8559229 , 0.84518726]),
         'test_precision': array([0.84408004, 0.84      , 0.84426458, 0.84291609, 0.82107574]),
         'test_recall': array([0.8300082 , 0.83535912, 0.83310383, 0.83396843, 0.82903851]),
         'test_f1_score': array([0.83698498, 0.83767313, 0.83864708, 0.83841839, 0.82503792])}
```

```
In [ ]: #fit model on the whole training set

start = process_time()

mnf.fit(x_train, y_train)

end=process_time()
```

```
In [ ]: #test model on test set

y_pred = mnbn.predict(x_test)
```

```
In [ ]: #view classification report

print(classification_report(y_pred, y_test))
```


	precision	recall	f1-score	support
0	0.86	0.87	0.87	9704
1	0.84	0.83	0.83	7863
accuracy			0.85	17567
macro avg	0.85	0.85	0.85	17567
weighted avg	0.85	0.85	0.85	17567

```
In [ ]: #view confusion matrix

conf_matrix=confusion_matrix(y_test, y_pred)
```

```
In [ ]: cm_plot = ConfusionMatrixDisplay(conf_matrix, display_labels = ['real', 'fake'])
cm_plot.plot(values_format='')
cm_plot.ax_.set(
    title='Multinomial Naive Bayes model with Text Data (TF-IDF)',
    xlabel='Predicted',
    ylabel='Actual')
```

```
Out[ ]: [Text(0.5, 1.0, 'Multinomial Naive Bayes model with Text Data (TF-IDF)'),
Text(0.5, 0, 'Predicted'),
Text(0, 0.5, 'Actual')]
```



```
In [ ]: accuracy=accuracy_score(y_test, y_pred)
precision=precision_score(y_test, y_pred)
recall=recall_score(y_test, y_pred)
f1=f1_score(y_test, y_pred)
fit_time=end-start
```

```
In [ ]: dict = {'data type': 'text',
               'model type': 'multinomial Naive-Bayes',
               'vectorize type': 'TF-IDF',
               'accuracy': accuracy,
               'precision': precision,
               'recall': recall,
               'f1': f1,
               'fit time': fit_time
            }
```

```
In [ ]: tfidf_text_mnb=pd.DataFrame.from_dict([dict])
```

```
In [ ]: tfidf_text_mnb
```

Out[ ]:

	data type	model type	vectorize type	accuracy	precision	recall	f1	fit time
0	text	multinomial Naive-Bayes	TF-IDF	0.851768	0.829836	0.837505	0.833653	0.03125

```
In [ ]: #save results for later use

%store tfidf_text_mnb

Stored 'tfidf_text_mnb' (DataFrame)
```