

Dealroom API V1 documentation

la bus al cabi a la	_
Introduction	
GET /transactions	
GET /transactions/filters	
GET /companies/:id/similar	
GET /companies/filters	
POST /companies/filters	
GET /companies/:id/board_members	
GET /companies/:id/media	
GET /companies/:id/fundings	
GET /companies/batch	
GET /companies/:id/analytics	
GET /companies/updated	
GET /companies/:id/team	
GET /companies/:id/news	
GET /companies/:id/investors	
GET /companies/:id	
GET /companies	
POST /companies	
GET /services	
GET /services/filters	
GET /countries/:id	
GET /countries/:id/recent_fundings	
GET /countries/:id/rising_stars	
GET /countries/:id/news	
GET /countries/:id/leaders	
GET /countries/:id/active_funds	
GET /countries	
GET /composite/filters	
GET /composite	
GET /industries/:id/recent_fundings	
GET /industries/:id/rising_stars	
GET /industries/:id/news	
GET /industries/:id/leaders	36
GET /industries/:id/active_funds	
GET /industries/:id	38
GET /industries	39
GET /investors	40
POST /investors	41
GET /investors/:id	42
GET /investors/:id/similar	43
GET /investors/filters	44
POST /investors/filters	45
GET /investors/:id/board_members	46
GET /investors/:id/media	47
GET /investors/:id/fundings	48
GET /investors/batch	49
GET /investors/:id/co_investors	50
GET /investors/updated	
GET /investors/:id/team	
GET /investors/:id/news	
POST /investors/:id/investments	

#### Dealroom.co API v1

#### **Endpoint**

https://api.dealroom.co/api/v1 sandbox endpoint https://staging-api.dealroom.co/api/v1

#### Authentication

**For server-side apps** we use HTTP Auth over ssl. To sign your request you need to provide an api key received as username. Password field can be empty or any dummy value.

Example for curl:

```
curl -u '091df29088e2db05db4f76a2e53e2aaf:' https://api.dealroom.co/api/v1/companies
```

Or for php curl:

```
curl_setopt($ch, CURLOPT_HTTPAUTH, CURLAUTH_BASIC);
curl_setopt($ch, CURLOPT_USERPWD, '091df29088e2db05db4f76a2e53e2aaf:');
```

For client-side apps you need to set special header X-Dealroom-App-Id

Also you need to provide X-Requested-With header with XMLHttpRequest value

```
$http.get('https://api.dealroom.co/api/v1/companies', {
  headers: {
    'X-Dealroom-App-Id': '123123123',
    'X-Requested-With': 'XMLHttpRequest'
  }
});
```

#### HTTP status codes

- **200** OK
- **201** Created
- **400** Bad Request (invalid query data)
- 401 Not Authorized (invalid authentication data)
- 403 Forbidden (no permissions)
- 404 Not found
- 405 Not Allowed (invalid request method)
- 500 Internal Server Error
- 503 Service Temporarily Unavailable (requests limit exceeded)

#### Partial response

Use query param and comma-separated list of fields, e.g.

```
?fields=id,name,tagline
```

For sub-partials we can use brackets, e.g.

?fields=id,name,similar(id,name)

#### Results limit

?limit=10&offset=10

# Ordering

```
?sort=field // ascending
?sort=-field // descending
```

#### Error messages

When http status code >= 400 error message will be returned.

```
{
  "error": true,
  "code": 404,
  "message": "Not found"
}
```

#### **GET** /transactions

Search for transactions (filtered query)

Parameter	Description	
form_data optional string	filter's values for search <b>Example:</b> locations(Western%20Europe),industries(charity)	
optional integer	Default: 10	
offset optional integer		
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, name, text_type, path, url, tagline, images(32x32, 74x74, 100x100), address, industries, hq_locations, locations, tg_locations, traffic_summary, performance, growth_stage, total_funding, total_funding_source, investors(id, name, path), last_funding(year, month, amount, amount_source, currency, round, investors, unknown_investors)	
SORT optional string	<b>Options:</b> name, date, industries, locations, growth_stage, total_funding, last_funding	

#### **GET** /transactions/filters

Retrieve filters for transactions (filtered query).

When you make a companies search request, filter's hash key will be returned that pointed to current search request filters. You can use this hash key or form\_data formatted string. Filters, associated with a hash key stored for 5 minutes only.

Form data must be encoded according RFC 3986 standart.

Note: you can specify only one form\_data or hash. Hash has higher priority than form\_data.

Parameter	Description
hash optional string	hash string received from /investors
form_data optional string	filter's values for search <b>Example:</b> locations(Western%20Europe),industries(charity)
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> industries(name, count, active), locations, hq_locations(name, count, active), growth_stages(name, count, active), fundings(name, count, active)

# GET /companies/:id/similar

Retrieve similar companies for company

Parameter	Description	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, name, path, url, tagline, images(32x32, 74x74, 100x100), address, hq_locations, locations, growth_stage, performance, employees, industries, traffic(visitors, annual_growth, sources, top_countries), total_funding, total_funding_source, fundings(year, month, amount, amount_source, currency, round_investors_unknown_investors).	
limit optional integer	round, investors, unknown_investors), score  Default: 10	
offset optional integer		
SOFT optional string	Options: name, locations, growth_stage	

#### **GET** /companies/filters

Retrieve filters for companies (filtered query).

When you make a companies search request, filter's hash key will be returned that pointed to current search request filters. You can use this hash key or form\_data formatted string. Filters, associated with a hash key stored for 5 minutes only.

Form data must be encoded according RFC 3986 standart.

Note: you can specify only one form\_data or hash. Hash has higher priority than form\_data. **24.03.17** Now you can filter or sort companies by last updated date. Also last\_updated field added.

/companies?form\_data=last\_updated(2017-03-17 00:00:00)&sort=-last\_updated

This filter has no buckets, just key and current value.

Parameter	Description
hash optional string	hash string received from /companies
form_data optional string	filter's values for search <b>Example:</b> locations(Western%20Europe),industries(charity)
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> client_focus(name, count, active), revenues(name, count, active), performance(name, count, active), fundings(name, count, active), industries(name, count, active), achievements(name, count, active), tags(name, count, active), locations, hq_locations(name, count, active), tg_locations(name, count, active), delivery_methods(name, count, active), growth_stages(name, count, active), company_status(name, count, active), employees(name, count, active), last_updated

#### POST /companies/filters

Retrieve filters for companies (bool query).

When you make a companies search request, filter's hash key will be returned that pointed to current search request filters. You can use this hash key or form\_data formatted string. Filters, associated with a hash key stored for 5 minutes only.

Form data must be encoded according RFC 3986 standart.

Note: you can specify only one form\_data or hash. Hash has higher priority than form\_data.

**24.03.17** Now you can filter or sort companies by last updated date. Also last\_updated field added.

```
-X POST /companies
-d '{
    "form_data": {
        "must": {
            "last_updated": "2016-12-10 00:00:00"
        }
    },
    "sort": "-last_updated"
}'
```

This filter has no buckets, just key and current value.

Parameter	Description
hash optional string	hash string received from /companies
form_data	filter's values for search
optional array	<b>Example:</b> {'must': {'locations': 'Western%20Europe'}, 'should': {'industries': 'charity'}, 'must_not: {}}
fields	Comma-separated fields to return. Nested fields in brackets
optional	Example: id,name,path,images(32x32)
string	<b>Options:</b> client_focus(name, count, active), revenues(name, count, active), performance(name, count, active), fundings(name, count, active), industries(name, count, active), achievements(name, count, active), tags(name, count, active), locations, hq_locations(name, count, active), tg_locations(name, count, active), delivery_methods(name, count, active), growth_stages(name, count, active), company_status(name, count, active), employees(name, count, active), last_updated

# GET /companies/:id/board\_members

Get company board members

Parameter	Description
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> name, url, images(32x32, 74x74, 100x100)
optional integer	Default: 10
offset optional integer	

#### GET /companies/:id/media

Retrieve company media files

Media files types:

- vimeo vimeo video
- **youtube** youtube video
- **slideshare** slideshare presentation
- image image file
- ppt ppt/pptx presentation file
- **pdf** pdf file
- doc doc/docx file
- vimeo vimeo video

For video, youtube and slideshare types file field contains item ID in coincident service image, ppt, pdf and doc types file field contains link to original file. This types do not thumbs.

Parameter	Description
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> type, file, thumb, description
optional integer	Default: 10
offset optional integer	

# GET /companies/:id/fundings

Retrieve company funding rounds

Parameter	Description
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> year, month, amount, amount_source, currency, round, investors(id, name), unknown_investors
limit optional integer	Default: 10
offset optional integer	

### GET /companies/batch

Get batch companies for ids

Parameter	Description	
ids required string	comma-separated companies ids (int, not strings urls, 50 max)	
fields	Comma-separated fields to return. Nested fields in brackets	
optional	<b>Example:</b> id,name,path,images(32x32)	
string	Options: id, name, path, tagline, about, url, website_url, twitter_url, facebook_url, linkedin_url, google_url, crunchbase_url, angellist_url, playmarket_app_id, appstore_app_id, images(32x32, 74x74, 100x100), employees, twitter_followers, industries, growth_stage, traffic_summary, performance, total_growth, hq_locations, tg_locations, client_focus, revenues, tags, delivery_method, launch_year, launch_month, total_funding, total_funding_source, last_funding, last_funding_source, company_status, facebook_likes_chart, alexa_rank_chart, twitter_tweets_chart, twitter_followers_chart, twitter_favorites_chart, growth_index_chart, app_downloads_chart, kpi_valuation, kpi_revenues, kpi_currency, achievements, team(name, title, images), board_members(name), investors(id, name, images, exited, path), fundings(year, month, amount, amount_source, currency, round, investors, unknown_investors), media(type, file, thumb, description), traffic(visitors, annual_growth, sources, top_countries), similar(id, name, path)	

#### GET /companies/:id/analytics

Get company analytics data

Parameter	Description
fields	Comma-separated fields to return. Nested fields in brackets
optional	<b>Example:</b> id,name,path,images(32x32)
twitter_tweets_chart, twitter_followers_chart, tw growth_index_chart, similarweb_chart, app_dow growth_stage, performance, momentum_rank, k users, paying_customers, volume, avg_price, ek revenues_predictive, revenues_source, valuatio gross_margin, operating_margin, source, curren target, total_ev, ev_ltm_sales, ev_ltm_ebidta), t company_name, company_path, company_type	<b>Options:</b> alexa_rank_chart, alexa_visitors_chart, facebook_likes_chart, twitter_tweets_chart, twitter_followers_chart, twitter_favorites_chart, growth_index_chart, similarweb_chart, app_downloads_chart, traffic, growth_stage, performance, momentum_rank, kpi_summary(id, last_update_date, users, paying_customers, volume, avg_price, ebidta, revenues, revenues_predictive, revenues_source, valuation, users_growth, yoy_growth, gross_margin, operating_margin, source, currency), exits(id, date, acquirors, target, total_ev, ev_ltm_sales, ev_ltm_ebidta), trading_multiples(id, categories, company_name, company_path, company_type, company_id, market_equity, market_firm, revenue 2015, revenue 2016, ebitda 2015, ebitda 2016)

#### GET /companies/updated

Retrieve companies list that was updated since any date

Parameter	Description
timestamp required integer	any date in past in Y-m-d H:i:s format <b>Default:</b> none
optional integer	Default: 10
offset optional integer	

# GET /companies/:id/team

Retrieve company team members

Parameter	Description
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> name, url, images(32x32, 74x74, 100x100), title
optional integer	Default: 10
offset optional integer	

# GET /companies/:id/news

#### Company newsfeed

Parameter	Description
optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, title, pub_date, summary, content, link, image, feed, author, categories(id, name), related_companies(id, name, path, type)

# GET /companies/:id/investors

#### Retrieve company investors

Parameter	Description
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, name, path, url, images(32x32, 74x74, 100x100), exited
optional integer	Default: 10
offset optional integer	

### GET /companies/:id

Retrieve single company profile

name, path)

Parameter	Description
fields	Comma-separated fields to return. Nested fields in brackets
optional	Example: id,name,path,images(32x32)
string	Default: return all fields by default
	Options: id, name, path, tagline, about, url, website_url, twitter_url, facebook_url, linkedin_url, google_url, crunchbase_url, angellist_url, playmarket_app_id, appstore_app_id, images(32x32, 74x74, 100x100), address, employees, twitter_followers, industries, growth_stage, traffic_summary, performance, total_growth, hq_locations, locations, tg_locations, client_focus, revenues, tags, delivery_method, launch_year, launch_month, total_funding, total_funding_source, last_funding, last_funding_source, company_status, facebook_likes_chart, alexa_rank_chart, twitter_tweets_chart, twitter_followers_chart, twitter_favorites_chart, growth_index_chart, app_downloads_chart, last_updated, kpi_valuation, kpi_revenues, kpi_currency, achievements, team(name, title, images), board_members(name), investors(id, name, images, exited, path), fundings(year, month, amount, amount_source, currency, round, investors, unknown_investors), media(type, file, thumb, description), traffic(visitors, annual_growth, sources, top_countries), similar(id,

# GET /companies

Search for companies (filtered query)

**24.03.17** Now you can filter or sort companies by last updated date. Also last\_updated field added.

 $/companies? form\_data = last\_updated (2017-03-17~00:00:00) \& sort = -last\_updated$ 

Parameter	Description
keyword optional string	keyword to search
form_data optional string	filter's values for search <b>Example:</b> locations(Western%20Europe),industries(charity)
limit optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id, name, path, images(32x32) <b>Default:</b> id, name, path, images(32x32, 74x74, 100x100), tagline, hq_locations, growth_stage, employees, performance, traffic_summary, total_funding, last_updated <b>Options:</b> id, name, path, tagline, url, website_url, twitter_url, facebook_url, linkedin_url, google_url, crunchbase_url, angellist_url, playmarket_app_id, appstore_app_id, images(32x32, 74x74, 100x100), address, employees, twitter_followers, industries, growth_stage, traffic_summary, performance, total_growth, hq_locations, locations, tg_locations, client_focus, revenues, tags, delivery_method, launch_year, launch_month, total_funding, total_funding_source, last_funding, last_funding_source, company_status, last_updated, kpi_valuation, kpi_revenues, kpi_currency, achievements, team(name, title, images), board_members(name), investors(id, name, path, exited, images), fundings(year, month, amount, amount_source, currency, round, investors, unknown_investors), media(type, file, thumb, description), traffic(visitors, annual_growth, sources, top_countries), similar(id, name, path)
SORT optional string	<b>Options:</b> name, industries, growth_stage, performance, locations, tg_locations, total_funding, achievements, tags, traffic_summary, last_funding_date, last_updated

#### POST /companies

Search for companies (bool query)

**24.03.17** Now you can filter or sort companies by last updated date. Also last\_updated field added.

```
-X POST /companies
-d '{
    "form_data": {
        "must": {
            "last_updated": "2016-12-10 00:00:00"
        }
    },
    "sort": "-last_updated"
}'
```

Parameter	Description
keyword optional string	keyword to search
form_data optional array	filter's values for search <b>Example:</b> {'must': {'locations': 'Western%20Europe'}, 'should': {'industries': 'charity'}, 'must_not: {}}
limit optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets  Example: id,name,path,images(32x32)  Default: id, name, path, images(32x32, 74x74, 100x100), tagline, hq_locations, growth_stage, employees, performance, traffic_summary, total_funding, last_updated  Options: id, name, path, tagline, url, website_url, twitter_url, facebook_url, linkedin_url, google_url, crunchbase_url, angellist_url, playmarket_app_id, appstore_app_id, images(32x32, 74x74, 100x100), address, employees, twitter_followers, industries, growth_stage, traffic_summary, performance, total_growth, hq_locations, locations, tg_locations, client_focus, revenues, tags, delivery_method, launch_year, launch_month, total_funding, total_funding_source, last_funding, last_funding_source, company_status, last_updated, kpi_valuation, kpi_revenues, kpi_currency, achievements, team(name, title, images), board_members(name), investors(id, name, path, exited, images), fundings(year, month, amount, amount_source, currency, round, investors, unknown_investors), media(type, file, thumb, description), traffic(visitors, annual_growth, sources, top_countries), similar(id, name, path)
SORT optional string	<b>Options:</b> name, industries, growth_stage, performance, locations, tg_locations, total_funding, achievements, tags, traffic_summary, last_funding_date, last_updated

#### **GET** /services

Retrieve mix of companies with "co-working" industry and funds-accelerators (filtered query).

Parameter	Description
form_data optional string	filter's values for search <b>Example:</b> locations(Western%20Europe),industries(charity)
optional integer	Default: 10
offset optional integer	
fields	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32)
string	<b>Options:</b> id, name, text_type, path, tagline, images(32x32, 74x74, 100x100), url, website_url, hq_locations, locations, address(full_address, country, city, street, street_number, zip, lat, lon)
SORT optional string	Options: name, locations

#### **GET** /services/filters

Retrieve filters for services (filtered query).

When you make a companies search request, filter's hash key will be returned that pointed to current search request filters. You can use this hash key or form\_data formatted string. Filters, associated with a hash key stored for 5 minutes only.

Form data must be encoded according RFC 3986 standart.

Note: you can specify only one form\_data or hash. Hash has higher priority than form\_data.

Parameter	Description
hash optional string	hash string received from /investors
form_data optional string	filter's values for search <b>Example:</b> locations(Western%20Europe),industries(charity)
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> hq_locations(name, count, active), locations, type(name, active)

# GET /countries/:id

#### Get country data

Parameter	Description
fields	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32)
string	<b>Options:</b> id, name, total_recent_fundings, total_recent_fundings_source, one_month_fundings, one_month_fundings_source, companies_count, fundings_count, leaders(id, name, url, images, path), rising_stars(id, name, url, images, path), active_funds(id, name, url, images, path), recent_fundings(year, month, amount, amount_source, currency, round, investors, unknown_investors), news

# GET /countries/:id/recent\_fundings

Retrieve country last funding rounds

Parameter	Description
limit optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> company(id, name, tagline, images, industries, growth_stage, hq_locations, locations, tg_locations, traffic_summary, performance, total_funding, total_funding_source), year, month, amount, amount_source, currency, round, investors(id, name, path), unknown_investors
SORT optional string	<b>Options:</b> name, total_funding, recent_funding, performance, date, traffic_summary

# GET /countries/:id/rising\_stars

Retrieve country rising stars

Parameter	Description
optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, name, path, url, tagline, industries, images(32x32, 74x74, 100x100), hq_locations, locations, tg_locations, growth_stage, performance, traffic_summary, total_funding, total_funding_source
SORT optional string	Options: name, total_funding, performance, traffic_summary

# GET /countries/:id/news

#### Retrieve country news

Parameter	Description
optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, title, pub_date, link, feed, related_companies(id, name, path)

# GET /countries/:id/leaders

Retrieve country leader companies

Parameter	Description
optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, name, path, url, tagline, industries, images(32x32, 74x74, 100x100), hq_locations, locations, tg_locations, growth_stage, performance, total_funding, total_funding_source, traffic_summary
SORT optional string	<b>Options:</b> name, total_funding, performance, traffic_summary

# GET /countries/:id/active\_funds

Retrieve country most active funds

Parameter	Description
optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, name, path, url, images(32x32, 74x74, 100x100), tagline, locations, hq_locations, deal_size, investment_stages, recent_funding, recent_funding_source, total_funding, total_funding_source, investments(id, name, path)
SORT optional string	Options: name, total_funding, recent_funding, investments

# **GET** /countries

Retrieve countries list with common data

Parameter	Description
limit optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, name, total_recent_fundings, total_recent_fundings_source, one_month_fundings, one_month_fundings_source, companies_count, fundings_count, leaders(id, name, path), active_funds(id, name, path), rising_stars(id, name, path)
SORT optional string	<b>Options:</b> name, total_recent_fundings, one_month_fundings

#### **GET** /composite/filters

Retrieve filters for composite search endpoint (filtered query).

When you make a composite search request, filter's hash key will be returned that pointed to current search request filters. You can use this hash key or form\_data formatted string. Filters, associated with a hash key stored for 5 minutes only.

Form data must be encoded according RFC 3986 standart.

Note: you can specify only one form\_data or hash. Hash has higher priority than form\_data.

Parameter	Description
hash optional string	hash string received from /composite
form_data optional string	filter's values for search <b>Example:</b> locations(Western%20Europe),industries(charity)
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> object_type(name, count, active), industries(name, count, active), growth_stages(name, count, active), locations, hq_locations(name, count, active), performance(name, count, active), fundings(name, count, active)

#### **GET** /composite

Retrieve composite search for different object types, such as companies or funds for example. You can use object\_type filter field to get required object type and it will work, but when you will use any other filters results for companies will be returned. Counters for object\_type are always null.

Parameter	Description
keyword optional string	keyword to search
form_data optional string	filter's values for search <b>Example:</b> locations(Western%20Europe),industries(charity)
limit optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, object_type, name, path, tagline, url, website_url, twitter_url, facebook_url, linkedin_url, google_url, crunchbase_url, angellist_url, playmarket_app_id, appstore_app_id, images(32x32, 74x74, 100x100), address, employees, twitter_followers, industries, growth_stage, traffic_summary, performance, hq_locations, locations, tg_locations, client_focus, revenues, tags, delivery_method, launch_year, launch_month, total_funding, total_funding_source, last_funding, last_funding_source, achievements, team(name, title, images), board_members(name), investors(id, name, images, exited, path), fundings(year, month, amount, amount_source, currency, round, investors, unknown_investors), media(type, file, thumb, description), traffic(visitors, annual_growth, sources, top_countries), similar(id, name, path)
SORT optional string	Options: name

# GET /industries/:id/recent\_fundings

Retrieve country last funding rounds

Parameter	Description
limit optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> company(id, name, tagline, images, industries, growth_stage, hq_locations, locations, tg_locations, traffic_summary, performance, total_funding, total_funding_source), year, month, amount, amount_source, currency, round, investors(id, name), unknown_investors
SORT optional string	<b>Options:</b> name, total_funding, recent_funding, performance, date, traffic_summary

# GET /industries/:id/rising\_stars

Retrieve industry rising stars

Parameter	Description
optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, name, path, url, tagline, industries, images(32x32, 74x74, 100x100), hq_locations, locations, tg_locations, growth_stage, performance, traffic_summary, total_funding, total_funding_source
SORT optional string	<b>Options:</b> name, total_funding, performance, traffic_summary

# GET /industries/:id/news

#### Retrieve industry news

Parameter	Description
optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, title, pub_date, link, feed, related_companies(id, name, path)

# GET /industries/:id/leaders

Retrieve industry leader companies

Parameter	Description
optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, name, path, url, tagline, industries, images(32x32, 74x74, 100x100), hq_locations, locations, tg_locations, growth_stage, performance, total_funding, total_funding_source, traffic_summary
SORT optional string	<b>Options:</b> name, total_funding, performance, traffic_summary

# GET /industries/:id/active\_funds

Retrieve industry most active funds

Parameter	Description
optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, name, path, url, images(32x32, 74x74, 100x100), tagline, hq_locations, locations, deal_size, investment_stages, recent_funding, recent_funding_source, total_funding, total_funding_source, investments(id, name, path)
SORT optional string	Options: name, total_funding, recent_funding, investments

## **GET** /industries/:id

#### Retrieve industry data

Parameter	Description
fields	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32)
string	<b>Options:</b> id, name, total_recent_fundings, total_recent_fundings_source, one_month_fundings, one_month_fundings_source, companies_count, dutch_companies_count, fundings_count, leaders(id, name, url, images, path), rising_stars(id, name, url, images, path), active_funds(id, name, url, images, path), recent_fundings(year, month, amount, amount_source, currency, round, investors, unknown_investors), news

## **GET** /industries

Retrieve industries list with common data

Parameter	Description
limit optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, name, total_recent_fundings, total_recent_fundings_source, one_month_fundings, one_month_fundings_source, companies_count, dutch_companies_count, fundings_count, leaders(id, name, path), active_funds(id, name, path), rising_stars(id, name, path)
SORT optional string	Options: name, total_recent_fundings, one_month_fundings

### **GET** /investors

Search for investors (filtered query)

**24.03.17** Now you can filter or sort investors by last updated date. Also last\_updated field added.

 $/investors? form\_data = last\_updated (2017-03-17~00:00:00) \& sort = -last\_updated (2017-03-17~00:00) \& sort = -l$ 

Parameter	Description
keyword optional string	keyword to search
form_data optional string	filter's values for search <b>Example:</b> locations(Western%20Europe),industries(charity)
limit optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets  Example: id,name,path,images(32x32)  Default: id, name, path, images(32x32, 74x74, 100x100), tagline, hq_locations, investment_stages, employees, total_funding, last_updated  Options: id, name, path, tagline, investor_type, url, website_url, twitter_url, facebook_url, linkedin_url, google_url, crunchbase_url, angellist_url, playmarket_app_id, appstore_app_id, images(32x32, 74x74, 100x100), address, investment_stages, employees, tg_industries, hq_locations, locations, tg_locations, deal_size, industry_experience, country_experience, client_focus, tags, tg_revenues, deal_structure, total_funding, total_funding_source, recent_funding, recent_funding_source, last_funding, last_funding_source, investments_num, top_investments_num, dutch_investments_num, investor_activity_rank, investor_performance_rank, last_updated, team(name, title), board_members(name), media(type, file, thumb, description), fundings(company, year, month, amount, amount_source, currency, round, investors, unknown_investors), investments(id, name, path), co_investors(id, name, path), similar(id, name, path)
SORT optional string	<b>Options:</b> name, investment_stages, tg_industries, locations, tg_locations, industry_experience, client_focus, tags, tg_revenues, total_funding, recent_funding, last_updated

### POST /investors

Search for investors (bool query)

**24.03.17** Now you can filter or sort investors by last updated date. Also last\_updated field added.

```
-X POST /investors
-d '{
    "form_data": {
        "must": {
            "last_updated": "2016-12-10 00:00:00"
        }
    },
    "sort": "-last_updated"
}'
```

Parameter	Description
keyword optional string	keyword to search
form_data optional array	filter's values for search <b>Example:</b> {'must': {'locations': 'Western%20Europe'}, 'should': {'industries': 'charity'}, 'must_not: {}}
limit optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets  Example: id, name, path, images(32x32)  Default: id, name, path, images(32x32, 74x74, 100x100), tagline, hq_locations, investment_stages, employees, total_funding, last_updated  Options: id, name, path, tagline, investor_type, url, website_url, twitter_url, facebook_url, linkedin_url, google_url, crunchbase_url, angellist_url, playmarket_app_id, appstore_app_id, images(32x32, 74x74, 100x100), address, investment_stages, employees, tg_industries, hq_locations, locations, tg_locations, deal_size, industry_experience, country_experience, client_focus, tags, tg_revenues, deal_structure, total_funding, total_funding_source, recent_funding, recent_funding_source, last_funding, last_funding_source, investments_num, top_investments_num, dutch_investments_num, investor_activity_rank, investor_performance_rank, last_updated, team(name, title), board_members(name), media(type, file, thumb, description), fundings(company, year, month, amount, amount_source, currency, round, investors, unknown_investors), investments(id, name, path), co_investors(id, name, path), similar(id, name, path)
SORT optional string	<b>Options:</b> name, investment_stages, tg_industries, locations, tg_locations, industry_experience, client_focus, tags, tg_revenues, total_funding, recent_funding, last_updated

### **GET** /investors/:id

Retrieve single company profile

Parameter	Description
fields optional string	Comma-separated fields to return. Nested fields in brackets  Example: id,name,path,images(32x32)  Default: return all fields by default  Options: id, name, path, tagline, about, investor_type, url, website_url, twitter_url, facebook_url, linkedin_url, google_url, crunchbase_url, angellist_url, playmarket_app_id, appstore_app_id, images(32x32, 74x74, 100x100), address, investment_stages, employees, tg_industries, hq_locations, locations, tg_locations, deal_size, industry_experience, country_experience, client_focus, tags, tg_revenues, deal_structure, total_funding, total_funding_source, recent_funding, recent_funding_source, last_funding, last_funding_source, investments_num, top_investments_num, dutch_investments_num, investor_activity_rank, investor_performance_rank, last_updated, team(name, title, images), board_members(name), media(type, file, thumb, description), fundings(company, year, month, amount, amount_source, currency, round, investors, unknown_investors), investments(id, name, path), co_investors(id,
	name, path), similar(id, name, path)

## GET /investors/:id/similar

Retrieve similar investors for investor

Parameter	Description
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, name, path, url, images(32x32, 74x74, 100x100), address, tagline, hq_locations, locations, deal_size, investment_stages, tg_locations, score
optional integer	Default: 10
offset optional integer	
string	Options: name, locations

### **GET** /investors/filters

Retrieve filters for investors (filtered query).

When you make a companies search request, filter's hash key will be returned that pointed to current search request filters. You can use this hash key or form\_data formatted string. Filters, associated with a hash key stored for 5 minutes only.

Form data must be encoded according RFC 3986 standart.

Note: you can specify only one form\_data or hash. Hash has higher priority than form\_data. **24.03.17** Now you can filter or sort investors by last updated date. Also last\_updated field added.

/companies?form\_data=last\_updated(2017-03-17 00:00:00)&sort=-last\_updated

This filter has no buckets, just key and current value.

Parameter	Description
hash optional string	hash string received from /investors
form_data	filter's values for search
optional string	<b>Example:</b> locations(Western%20Europe),industries(charity)
fields	Comma-separated fields to return. Nested fields in brackets
optional	Example: id,name,path,images(32x32)
string	<b>Options:</b> deal_structure(name, count, active), industry_experience(name, count, active), country_experience(name, count, active), tg_revenues(name, count, active), investor_type(name, count, active), tg_industries(name, count, active), achievements(name, count, active), tg_tags(name, count, active), locations, hq_locations(name, count, active), tg_locations(name, count, active), investment_stages(name, count, active), investments_num(name, count, active), investor_activity_rank(name, count, active), investor_performance_rank(name, count, active), last_updated

### POST /investors/filters

Retrieve filters for investors (bool query).

When you make a companies search request, filter's hash key will be returned that pointed to current search request filters. You can use this hash key or form data formatted string. Filters, associated with a hash key stored for 5 minutes only.

Form data must be encoded according RFC 3986 standart.

Note: you can specify only one form\_data or hash. Hash has higher priority than form\_data.

**24.03.17** Now you can filter or sort investors by last updated date. Also last\_updated field added.

```
-X POST /investors
-d '{
    "form_data": {
        "must": {
            "last_updated": "2016-12-10 00:00:00"
    },
    "sort": "-last_updated"
}'
```

This filter has no buckets, just key and current value.

Parameter	Description
hash optional string	hash string received from /investors
form_data optional array	filter's values for search <b>Example:</b> {'must': {'locations': 'Western%20Europe'}, 'should': {'industries': 'charity'}, 'must_not: {}}
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> deal_structure(name, count, active), industry_experience(name, count, active), country_experience(name, count, active), tg_revenues(name, count, active), investor_type(name, count, active), tg_industries(name, count, active), achievements(name, count, active), tg_tags(name, count, active), locations, hq_locations(name, count, active), tg_locations(name, count, active), investment_stages(name, count, active), investor_activity_rank(name, count, active), investor_performance_rank(name, count, active), last_updated

## GET /investors/:id/board\_members

#### Get investor board members

Parameter	Description
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> name, url, images(32x32, 74x74, 100x100)
optional integer	Default: 10
offset optional integer	

### GET /investors/:id/media

Retrieve investor media files

Media files types:

- vimeo vimeo video
- youtube youtube video
- slideshare slideshare presentation
- image image file
- ppt ppt/pptx presentation file
- pdf pdf file
- doc doc/docx file
- vimeo vimeo video

For video, youtube and slideshare types file field contains item ID in coincident service image, ppt, pdf and doc types file field contains link to original file. This types do not thumbs.

Parameter	Description
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> type, file, thumb, description
optional integer	Default: 10
offset optional integer	

## GET /investors/:id/fundings

Retrieve investor funding rounds

Parameter	Description
fields optional	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32)  Options: company(id_name), year, month, amount, amount, source, surronsy
string	<b>Options:</b> company(id, name), year, month, amount, amount_source, currency, round, investors(id, name), unknown_investors
limit	Default: 10
optional integer	
offset	
optional integer	

### GET /investors/batch

Get batch investors by ids

Parameter	Description
required string	comma-separated companies ids (int, not strings urls, 50 max)
fields	Comma-separated fields to return. Nested fields in brackets
optional string	Example: id,name,path,images(32x32)
	<b>Options:</b> id, name, path, tagline, about, investor_type, url, website_url, twitter_url, facebook_url, linkedin_url, google_url, crunchbase_url, angellist_url, playmarket_app_id, appstore_app_id, images(32x32, 74x74, 100x100), investment_stages, employees, tg_industries, hq_locations, tg_locations, deal_size, industry_experience, country_experience, client_focus, tags, tg_revenues, deal_structure, total_funding, total_funding_source, recent_funding, recent_funding_source, last_funding, last_funding_source, investments_num, top_investments_num, dutch_investments_num, investor_activity_rank, investor_performance_rank, team(name, title, images), board_members(name), media(type, file, thumb, description), fundings(company, year, month, amount, amount_source, currency, round, investors, unknown_investors), investments(id, name, path), co_investors(id, name, path), similar(id, name, path)

## GET /investors/:id/co\_investors

#### Get investor co-investors

Parameter	Description
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, name, path, tagline, url, images(32x32, 74x74, 100x100), co_investments(id, name), investment_stages, locations
limit optional integer	Default: 10
offset optional integer	

### **GET** /investors/updated

Retrieve companies list that was updated since any date

Parameter	Description
timestamp required integer	any date in past in Y-m-d H:i:s format <b>Default:</b> none
optional integer	Default: 10
offset optional integer	

## GET /investors/:id/team

Retrieve company team members

Parameter	Description
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> name, url, images(32x32, 74x74, 100x100), title
limit optional integer	Default: 10
offset optional integer	

## GET /investors/:id/news

#### Investor newsfeed

Parameter	Description
optional integer	Default: 10
offset optional integer	
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, title, pub_date, summary, content, link, image, feed, author, categories(id, name), related_companies(id, name, path, type)

### POST /investors/:id/investments

#### Retrieve investor investments

Parameter	Description
fields optional string	Comma-separated fields to return. Nested fields in brackets <b>Example:</b> id,name,path,images(32x32) <b>Options:</b> id, name, path, url, images(32x32, 74x74, 100x100), tagline, hq_locations, locations, traffic_summary, traffic(visitors, annual_growth, sources, top_countries), performance, total_funding, total_funding_source, exited, industries, growth_stage
optional integer	Default: 10
offset optional integer	