

R documentation

of ‘man/MSOpt.Rd’

October 1, 2021

MSOpt

MSOpt

Description

The MSOpt function creates a list object containing the main information on the experiment settings (e.g. number of factors, factor levels, number of runs, units per stratum) and the optimization criteria to be considered (number and names). According to the declared criteria, it also provides the basic matrices for their implementation. MSOpt returns input objects of the [Score](#) and [MSSearch](#) functions of the multiDoE package.

Usage

```
MSOpt(facts, units, levels, etas, criteria, model)
```

Arguments

facts	A list of vectors representing the distribution of factors across strata. Each item in the list represents a stratum and the first item is the highest stratum of the multi-stratum structure of the experiment. Within the vectors, experimental factors are indicated by progressive integer from 1 to the total number of experimental factors, starting from the highest strata. Blocking factors are denoted by empty vectors.
units	A list containing the number of units in each stratum (e.g. in a split-plot experiment with <i>h</i> whole plots and <i>k</i> subplots per whole plot: <code>units = list(h,k)</code>). It follows that <code>length(units)</code> must be equal to <code>length(facts)</code> .
levels	A vector or an integer. If the number of levels differs from factor to factor, levels is a vector containing the number of available levels for each experimental factor (blocking factors are excluded). If all the experimental factors share the number of levels, one integer is sufficient.
etas	A list specifying the ratios of error variance between subsequent strata. It follows that <code>length(etas)</code> must be equal to <code>length(facts) - 1</code> .
criteria	A list containing the criteria to be optimized. It can contain any combination of: <ul style="list-style-type: none">• "I" : I-optimality• "Id" : Id-optimality

- "D" : D-optimality
- "Ds" : Ds-optimality
- "A" : A-optimality
- "As" : As-optimality

See the **Details** section for more detailed information on the available criteria. The details of model specification are given under 'Details'.

`model` A string which indicates the type of model, among "main", "interaction" and "quadratic".

Value

MSOpt returns a list containing the following components:

<code>facts</code>	The argument facts.
<code>nfacts</code>	An integer, the number of experimental factors.
<code>nstrat</code>	An integer, the number of strata.
<code>units</code>	The argument units.
<code>runs</code>	An integer, the number of runs.
<code>etas</code>	The argument etas.
<code>avlev</code>	A list showing the available levels for each experimental factor.
<code>levs</code>	A vector showing the number of levels for each experimental factor.
<code>Vinv</code>	The inverse of the variance-covariance matrix of the responses.
<code>model</code>	The argument model.
<code>crit</code>	The argument criteria.
<code>ncrit</code>	An integer, the number of criteria.
<code>M</code>	The matrix of moments of the cube. Only with <i>I-optimality</i> criteria.
<code>M0</code>	The matrix of moments of the cube. Only with <i>Id-optimality</i> criteria.
<code>W</code>	The diagonal matrix of weights. Only with <i>As-optimality</i> criteria.

Index

MSOpt, [1](#)
MSSearch, [1](#)
Score, [1](#)