

compute_graph.py

```
import ast
from typing import List, Dict, Set

import networkx as nx

import helper
from base_node_class import BaseOperationNodeClass
from compute_graph_nodes import Name, Num, Binop, Call, Output, Subscript, Ternary, Compare, UnaryOp

class ComputeGraph:
    """
    The ComputeGraph class manages the inner data flow of a single computation respectively a single kernel
    including its properties e.g. latency, internal buffer sizes and field accesses.

    Notes:
    - Creation of a proper graph representation for the computation data flow graph.
    - Credits for node-visitor: https://stackoverflow.com/questions/33029168/how-to-calculate-an-equation-in-a-string-python
    - More info: https://networkx.github.io/

    Note about ast structure:
    tree.body[i] : i-th expression
    tree.body[i] = Assign: of type: x = Expr
    tree.body[i].targets      ->
    tree.body[i].value = {BinOp, Name, Call}
    tree.body[i] = Expr:
    tree.body[i].value = BinOp    -> subtree: .left, .right, .op {Add, Mult, Name, Call}
    tree.body[i].value = Name     -> subtree: .id (name)
    tree.body[i].value = Call     -> subtree: .func.id (function), .args[i] (i-th argument)
    tree.body[i].value = Subscript -> subtree: .slice.value.elts[i]: i-th parameter in [i, j, k, ...]
    """

    def __init__(self,
                 verbose: bool = False) -> None:
        """
        Create new ComputeGraph with given initialization parameters.
        :param verbose: flag for console output logging
        """
        # set parameter variables
        self.verbose = verbose
        # read static parameters from config file
        self.config: Dict[str, int] = helper.parse_json("compute_graph.config")
        # initialize internal data structures
        self.graph: nx.DiGraph = nx.DiGraph() # networkx (library) compute graph with compute_graph_nodes as nodes
        self.tree: type(ast) = None # abstract syntax tree (python) data structure
        self.max_latency: int = -1 # (non-valid) initial value for the maximum latency (critical path) of the
        # computational tree
        self.inputs: Set[BaseOperationNodeClass] = set() # link to all nodes that feed input into this computation
```

compute_graph.py

```
self.outputs: Set[BaseOperationNodeClass] = set() # link to all nodes this computation feeds data to
self.min_index: Dict[str, List] = dict() # per input array the last access index of the stencil
self.max_index: Dict[str, List] = dict() # per input array the furthest access index of the stencil
self.buffer_size: Dict[str, List] = dict() # size (dimensional) from the last to the first access (determines
# the internal buffer size)
self.accesses: Dict[str, List[List]] = dict() # dictionary containing all field accesses for a specific
# resource e.g. {"A":{[0,0,0],[0,1,0]}} for the stencil "res = A[i,j,k] + A[i,j+1,k]"

@staticmethod
def create_operation_node(node: ast,
                          number: int) -> BaseOperationNodeClass:
    """
    Create operation node of the correct type.
    :param node: abstract syntax tree node
    :param number: tree numbering
    :return: corresponding operation node
    """
    if isinstance(node, ast.Name): # variables or array access
        return Name(node, number)
    elif isinstance(node, ast.Num): # static value
        return Num(node, number)
    elif isinstance(node, ast.BinOp): # binary operation
        return Binop(node, number)
    elif isinstance(node, ast.Call): # function (e.g. sin, cos,..)
        return Call(node, number)
    elif isinstance(node, ast.Assign): # assign operator (var = expr;)
        return Output(node, number)
    elif isinstance(node, ast.Subscript): # array access (form: arr[i,j,k])
        return Subscript(node, number)
    elif isinstance(node, ast.IfExp): # if/else clause of ternary operation
        return Ternary(node, number)
    elif isinstance(node, ast.Compare): # comparison of ternary operation
        return Compare(node, number)
    elif isinstance(node, ast.UnaryOp): # negation of value ('-' sign)
        return UnaryOp(node, number)
    else:
        raise Exception("Unknown AST type {}".format(type(node)))

def setup_internal_buffers(self,
                           relative_to_center=True) -> None:
    """
    Set up minimum/maximum index and accesses for the internal data structures.
    :param relative_to_center: if true, the center of the stencil is at position [0,0,0] respectively 0, if false,
    the furthest element is at position [0,0,0] and all other accesses on the same input field are relative to that
    (i.e. negative)
    """
    # init dicts
    self.min_index = dict() # min_index["buffer_name"] = [i_min, j_min, k_min]
    self.max_index = dict()
```

compute_graph.py

```
self.buffer_size = dict() # buffer_size["buffer_name"] = size
# find min and max index
for inp in self.inputs:
    if isinstance(inp, Subscript): # subscript nodes only
        if inp.name in self.min_index:
            if inp.index < self.min_index[inp.name]: # check min
                self.min_index[inp.name] = inp.index
            if inp.index >= self.max_index[inp.name]: # check max
                self.max_index[inp.name] = inp.index
        else: # first entry
            self.min_index[inp.name] = inp.index
            self.max_index[inp.name] = inp.index
        if inp.name not in self.accesses: # create initial list
            self.accesses[inp.name] = list()
        self.accesses[inp.name].append(inp.index) # add entry
# set buffer_size = max_index - min_index
for buffer_name in self.min_index:
    self.buffer_size[buffer_name] = [abs(a_i - b_i) for a_i, b_i in zip(self.max_index[buffer_name],
                                                                    self.min_index[buffer_name])]

# update access to have [0,0,0] for the max_index (subtract it from all)
if not relative_to_center:
    for field in self.accesses:
        updated_entries = list()
        for entry in self.accesses[field]:
            updated_entries.append(helper.list_subtract_cwise(entry, self.max_index[field]))
        self.accesses[field] = updated_entries

def determine_inputs_outputs(self) -> None:
    """
    Fill up internal input and output data structures with the corresponding nodes.
    """
    # create empty sets
    self.inputs = set()
    self.outputs = set()
    # idea: do a tree-walk: all nodes with cardinality(predecessor)=0 are inputs, all nodes with cardinality(
    # successor)=0 are outputs
    for node in self.graph.nodes:
        if len(self.graph.pred[node]) == 0:
            self.inputs.add(node)
        if len(self.graph.succ[node]) == 0:
            self.outputs.add(node)

def contract_edge(self,
                  u: BaseOperationNodeClass,
                  v: BaseOperationNodeClass) -> None:
    """
    Contract node v into node u.
    :param u: contractor node
    :param v: contracted node
```

compute_graph.py

```
"""
# add edges of node v to node u
for edge in self.graph.succ[v]:
    self.graph.add_edge(u, edge)
for edge in self.graph.pred[v]:
    self.graph.add_edge(edge, u)
# remove node v
self.graph.remove_node(v)

def generate_graph(self,
                    computation_string: str) -> nx.DiGraph:
    """
    Create networkx graph of the mathematical computation given in the computation_string.
    :param computation_string:
    :return networkx (library) graph of the computation with nodes from compute_graph_nodes
    """
    # generate abstract syntax tree
    self.tree = ast.parse(computation_string)
    # iterate over all equations (e.g. res=a+b;b=c+d; ...)
    for equation in self.tree.body:
        # check if base node is of type Expr or Assign
        if isinstance(equation, ast.Assign):
            lhs = self.create_operation_node(equation, 0) # left hand side equation
            rhs = self.ast_tree_walk(equation.value, 1) # right hand side of equation
            self.graph.add_edge(rhs, lhs)
    # merge ambiguous variables in tree (implies: merge of ast.Assign trees into a single tree)
    outp_nodes = list(self.graph.nodes)
    for outp in outp_nodes:
        if isinstance(outp, Name):
            inp_nodes = list(self.graph.nodes)
            for inp in inp_nodes:
                if isinstance(outp, Subscript) and outp is not inp and outp.name == inp.name and \
                    outp.index == inp.index:
                    # only contract if the indices and the names match
                    self.contract_edge(outp, inp)
                elif isinstance(outp, Name) and outp is not inp and outp.name == inp.name:
                    # contract nodes if the names match
                    self.contract_edge(outp, inp)
    # test if graph is now a single component (for directed graph: each non-output must have at least one successor)
    for node in self.graph.nodes:
        if not isinstance(node, Output) and len(self.graph.succ[node]) == 0:
            raise RuntimeError("Kernel-internal data flow is not single component (must be connected in the sense "
                               "of a DAG).")

    return self.graph

def ast_tree_walk(self,
                  node: ast,
                  number: int) -> BaseOperationNodeClass:
    """
```

Recursively walk through the abstract syntax tree structure.

```

:param node: current node
:param number: tree numbering
:return: reference of current node
"""
# create node
new_node = self.create_operation_node(node, number)
# add node to graph
self.graph.add_node(new_node)
# node type specific implementation of the tree walk
if isinstance(node, ast.BinOp):
    # do tree-walk recursively and get references to children (to create the edges to them)
    lhs = self.ast_tree_walk(node.left, ComputeGraph.child_left_number(number)) # left hand side
    rhs = self.ast_tree_walk(node.right, ComputeGraph.child_right_number(number)) # right hand side
    # add edges from parent to children
    self.graph.add_edge(lhs, new_node)
    self.graph.add_edge(rhs, new_node)
elif isinstance(node, ast.Call):
    # do tree-walk for all arguments
    if len(node.args) > 2:
        raise NotImplementedError("Current implementation does not support more than two arguments due"
                                   " to the binary tree numbering convention")

    # process first argument
    first = self.ast_tree_walk(node.args[0], ComputeGraph.child_left_number(number))
    self.graph.add_edge(first, new_node)
    # check if second argument exist
    if len(node.args) >= 2:
        second = self.ast_tree_walk(node.args[1], ComputeGraph.child_right_number(number))
        self.graph.add_edge(second, new_node)
elif isinstance(node, ast.Name):
    # nothing to do
    pass
elif isinstance(node, ast.Num):
    # nothing to do
    pass
elif isinstance(node, ast.Compare):
    # do tree-walk recursively and get references to children (to create the edges to them)
    lhs = self.ast_tree_walk(node.left, ComputeGraph.child_left_number(number)) # left hand side
    rhs = self.ast_tree_walk(node.comparators[0], ComputeGraph.child_right_number(number)) # right hand side
    # add edges from parent to children
    self.graph.add_edge(lhs, new_node)
    self.graph.add_edge(rhs, new_node)
elif isinstance(node, ast.IfExp):
    # do tree-walk recursively and get references to children (to create the edges to them)
    test = self.ast_tree_walk(node.test, 0) # test clause
    true_path = self.ast_tree_walk(node.body, ComputeGraph.child_left_number(number))
    false_path = self.ast_tree_walk(node.orelse, ComputeGraph.child_right_number(number))
    # add edges from parent to children
    self.graph.add_edge(true_path, new_node)

```

compute_graph.py

```
        self.graph.add_edge(false_path, new_node)
        self.graph.add_edge(test, new_node)
    elif isinstance(node, ast.UnaryOp):
        # do tree-walk recursively and get references to child
        operand = self.ast_tree_walk(node.operand, ComputeGraph.child_right_number(number))
        # add edges form parent to child
        self.graph.add_edge(operand, new_node)
    return new_node

@staticmethod
def child_left_number(n: int) -> int:
    """
    Default tree numbering (number from root right to left downward per level).
    :param n: parent number
    :return: left child number
    """
    return 2 * n + 1

@staticmethod
def child_right_number(n: int) -> int:
    """
    Default tree numbering (number from root right to left downward per level).
    :param n: parent number
    :return: right child number
    """
    return 2 * n

def plot_graph(self,
               save_path: str = None) -> None:
    """
    Plot the compute graph graphically.
    :param save_path: filename of the output image, if none: do not save to file
    """
    # create drawing area
    import matplotlib.pyplot as plt # import matplotlib only if graph plotting is set to true
    plt.figure(figsize=(20, 20)) # define drawing size. NOTE: must probably be a function of the number of nodes at
    # some point (for large graphs)
    plt.axis('off')
    # generate positions
    positions = nx.nx_pydot.graphviz_layout(self.graph, prog='dot')
    # divide nodes into different lists for colouring purpose
    nums = list()
    names = list()
    ops = list()
    outs = list()
    comp = list()
    for node in self.graph.nodes:
        if isinstance(node, Num): # numerals
            nums.append(node)
```

compute_graph.py

```
elif isinstance(node, Name) or isinstance(node, Subscript): # variables
    names.append(node)
elif isinstance(node, Binop) or isinstance(node, Call) or isinstance(node, UnaryOp): # operations
    ops.append(node)
elif isinstance(node, Output): # outputs
    outs.append(node)
elif isinstance(node, Ternary) or isinstance(node, Compare): # comparison
    comp.append(node)
# create dictionary of the labels and add all of them
labels = dict()
for node in self.graph.nodes:
    labels[node] = node.generate_label()
# add nodes and edges
# name nodes
nx.draw_networkx_nodes(G=self.graph,
                       pos=positions,
                       nodelist=names,
                       node_color='orange',
                       node_size=3000,
                       node_shape='s', # square
                       edge_color='black')

# output nodes
nx.draw_networkx_nodes(G=self.graph,
                       pos=positions,
                       nodelist=outs,
                       node_color='green',
                       node_size=3000,
                       node_shape='s')

# numeral nodes
nx.draw_networkx_nodes(G=self.graph,
                       pos=positions,
                       nodelist=nums,
                       node_color='#007acc',
                       node_size=3000,
                       node_shape='s')

# ternary operator nodes
nx.draw_networkx_nodes(G=self.graph,
                       pos=positions,
                       nodelist=comp,
                       node_color='#009999',
                       node_size=3000,
                       node_shape='o') # circle

# operation nodes and edges between all nodes
nx.draw_networkx(G=self.graph,
                 pos=positions,
                 nodelist=ops,
                 node_color='red',
                 node_size=3000,
                 node_shape='o',
```

compute_graph.py

```
        font_weight='bold',
        font_size=16,
        edge_color='black',
        arrows=True,
        arrowsize=36,
        arrowstyle='->',
        width=6,
        linewidths=1,
        with_labels=False)

# add labels
nx.draw_networkx_labels(G=self.graph,
                        pos=positions,
                        labels=labels,
                        font_weight='bold',
                        font_size=16)

# save plot to file if save_path has been specified
if save_path is not None:
    plt.savefig(save_path)
# plot it
plt.show()

def try_set_max_latency(self,
                        new_val: int) -> bool:
    """
    Update the maximum latency of the compute graph.
    :param new_val: new maximum latency candidate
    :return: whether or not the candidate is the new maximum
    """
    if self.max_latency <= new_val:
        self.max_latency = new_val
        return True
    else:
        return False

def calculate_latency(self) -> None:
    """
    Find critical path in the computation tree.
    """
    # idea: do a longest-path tree-walk (since the graph is a DAG (directed acyclic graph) we can do that
    for node in self.graph.nodes:
        if isinstance(node, Output): # start at the output nodes and walk the tree up to the input nodes
            node.latency = 1
            self.try_set_max_latency(node.latency)
            self.latency_tree_walk(node)

def latency_tree_walk(self,
                      node: BaseOperationNodeClass) -> None:
    """
    Computation tree walk for latency calculation.
```


compute_graph.py

```
:param node: current node
"""
# check node type
if isinstance(node, Name) or isinstance(node, Num) or isinstance(node, Subscript): # variable or numeral:
    # no additional latency
    # copy parent latency to children
    for child in self.graph.pred[node]:
        child.latency = node.latency
        self.latency_tree_walk(child)
elif isinstance(node, Binop) or isinstance(node, Call): # function calls: additional latency of the function
    # added
    # get op latency from config
    op_latency = self.config["op_latency"][node.name]
    # add latency to children
    for child in self.graph.pred[node]:
        child.latency = max(child.latency, node.latency + op_latency)
        self.latency_tree_walk(child)
elif isinstance(node, Output): # output: no additional latency
    # copy parent latency to children
    for child in self.graph.pred[node]:
        child.latency = node.latency
        self.latency_tree_walk(child)
elif isinstance(node, Ternary): # function calls: additional latency of the conditional operator added
    # get op latency from config
    op_latency = self.config["op_latency"]["conditional"]
    # add latency to children
    for child in self.graph.pred[node]:
        child.latency = max(child.latency, node.latency + op_latency)
        self.latency_tree_walk(child)
elif isinstance(node, Compare): # comparison: additional latency of the comparison operator added
    # get op latency from config
    op_latency = self.config["op_latency"]["comparison"]
    # add latency to children
    for child in self.graph.pred[node]:
        child.latency = max(child.latency, node.latency + op_latency)
        self.latency_tree_walk(child)
elif isinstance(node, UnaryOp): # unary operator
    # get op latency from config
    op_latency = self.config["op_latency"][node.name]
    # add latency to children
    for child in self.graph.pred[node]:
        child.latency = max(child.latency, node.latency + op_latency)
        self.latency_tree_walk(child)
else:
    raise NotImplementedError("Node type {} has not been implemented yet.".format(type(node)))
self.try_set_max_latency(node.latency)
```

```
if __name__ == "__main__":
```

compute_graph.py

```
"""
    simple debugging example
"""
computation = "res = -a if (a+1 > b-c) else b; b = d + e"
graph = ComputeGraph()
graph.generate_graph(computation)
graph.calculate_latency()
# graph.plot_graph("compute_graph_example.png") # write graph to file
graph.plot_graph()
```