



Main Office, R&D and Logistics

Avenida do Polo 3, nº159,
4590-137 Carvalhosa
Paços de Ferreira - Portugal
Tlm . +351 917 851 019

Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9
2820-690 Charneca da Caparica - Portugal
Tel . +351 212 964 100
Fax . +351 212 964 101
E-mail . info@vicoustic.com

Vicoustic USA

5701 Sixth Avenue South, Suite 229
Seattle, WA 98108
Tel . (206) 767-2020
E-mail . info@vicousticusa.com

www.vicousticusa.com

An addition to Vicoustic's Flexi Panel A family, the Flexi Panel A40 is truly effective when applied in any type of space. A scientific combination of material, absorption surface and cavity thickness means that the panel's absorption performance is extremely efficient in the treatment of first reflections.

Flexi Panel A40 offers you the best performance on medium and high frequencies, this panel represents an adaptation to the industrial sector, providing one of the best acoustic solutions on the market, at an attractive price. It also has a unique characteristic - when placed in a sequence, the panel junctions become undetectable, allowing you to place a continuous pattern on large surfaces.

Flexi A40 Tech Premium - (Vicoustic Tech Premium) :

Made of Basotect® foam, it's long-term resistance to high temperatures and excellent fire characteristics are based on the use of melamine resin. The high nitrogen content of the resin is responsible for the extremely flame-resistant property of the foam without the need for fire retardants, making it particularly suitable for applications with high fire safety requirements..

Features:

- Innovative design
- Easy to install
- Unique Vicoustic technology
- 4 cm Thickness

Available in two different foams (Vicoustic Foam and Vicoustic Tech Foam) and in 8 different colored fabric (Brown, White, Blue, Orange, Beige, Bordeaux, Grey and Black).

Applications

Conference and Teleconference Rooms, Lecture Halls, Distance Learning Rooms, Public Spaces, Auditoriums, Performance Spaces, etc.

Please notice that the dimensions of this panel have a tolerance margin of ± 3 mm

Main Info

Ref: B00636
EAN13: 5600301846991
HS-Code: 39211310
Dimensions: 595.0 x 595.0 x 40.0 mm
Scratch Resistance: No
Washable: No

Technical File

Performance	Functionality: Absorption
	Absorption Frequency: High
	alpha with Shape Indicators: 0.75 (H)
	NRC: 0.750
	Fire Class European (EN): Euroclass E
Shipping	Fire Class Germany (DIN): B1
	Fire Class France (NF P): M1
	Units Per Box: 12 boxes
	Box Dimensions: 620.0 x 620.0 x 495.0 mm
Row Materials	Material: Fabric, Foam
	Foam Type: Tech
Design	Fabric Color: Natural White
	Edges: Angled
Installation	Place: Wall, Ceiling
	Fixing Type: Adhesive