



Main Office, R&D and Logistics

Avenida do Polo 3, nº159,
4590-137 Carvalhosa
Paços de Ferreira - Portugal
Tlm . +351 917 851 019

Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9
2820-690 Charneca da Caparica - Portugal
Tel . +351 212 964 100
Fax . +351 212 964 101
E-mail . info@vicoustic.com

Vicoustic USA

5701 Sixth Avenue South, Suite 229
Seattle, WA 98108
Tel . (206) 767-2020
E-mail . info@vicousticusa.com

www.vicousticusa.com

The ISO Underfloor is a highly efficient solution in the treatment of structural noise at floor level. It ensures a high level of isolation by diminishing the sound emitted from joins between the floor and the rest of the construction.

The ISO Underfloor is an affordable, high performance product which is indispensable in modern construction projects.

Color: Grey Applications Home Theatres, Listening Rooms, Recording and Broadcast Studios, Post Production Studios, Lecture Halls, Distance Learning Rooms, etc.

Main Info

Ref: U00061
EAN13: 5600217588367
HS-Code: 68069000
Dimensions: 26000 x 1500 x 5 mm
Weight: 6.00 kg

Performance

RW: 27.00 dB
RW-CTR: 26.90 dB

Shipping

Units Per Box: 1 roll
Box Dimensions: 1500.0 x 0.0 x 0.0 mm

Technical File