



Main Office, R&D and Logistics

Avenida do Polo 3, nº159,
4590-137 Carvalhosa
Paços de Ferreira - Portugal
Tlm . +351 917 851 019

Office 2

Rua Quinta do Bom Retiro nº16, Armazém 9
2820-690 Charneca da Caparica - Portugal
Tel . +351 212 964 100
Fax . +351 212 964 101
E-mail . info@vicoustic.com

Vicoustic USA

5701 Sixth Avenue South, Suite 229
Seattle, WA 98108
Tel . (206) 767-2020
E-mail . info@vicousticusa.com

www.vicousticusa.com

Flexi Wood A75 is a panel dedicated to the control of medium and medium-low frequencies. It acts simultaneously as an absorber and a reflector, controlling excess energy in a room without compromising its ambience. This helps to create listening spaces with a natural, bright sound.

The panel's revolutionary design is further enhanced by the addition of a wood surface. Long known for its excellent acoustic properties, the wood also adds elegance and modernity to the panel, making it suitable for use in any type of space.

The Flexi Wood panel is available in two different thicknesses for use in different frequency ranges. Flexi Wood A75 acts as a Helmholtz resonator performing between 200Hz and 2000Hz.

Main Info

Ref: B00050
EAN13: 5600217588145
HS-Code: 39211310
Dimensions: 600.0 x 600.0 x 77.0 mm
Scratch Resistance: No
Washable: No

Performance

Functionality: Absorption
Absorption Frequency: Medium
alpha with Shape Indicators: 0.65
NRC: 0.700
Fire Class European (EN): Euroclass F
Fire Class France (NF P): M1

Shipping

Units Per Box: 6 boxes
Box Dimensions: 620.0 x 620.0 x 495.0 mm
Box Weight: 9.4 kg

Row Materials

Material: Wood, Foam

Technical File

Flexi Wood A75 Cherry



Wood Type: Mdf Painted
Foam Type: M1

Design

Wood Color: Cherry
Edges: Angled

Installation

Place: Wall, Ceiling
Fixing Type: Glued

Technical File